

Presentación:

Nombre:

Algelis Severino

Tema:

Introducción a la Programación y Diagrama de flujo.

Tecnico:

Ciberseguridad Semipresencial

Facilitador:

Kevin Feliz Henriquez

Centro:

Diapiato Pro salud

Descripción:

En este documento .pdf adjunto capturas del reto 6 de 30 days of code de HackerRank.

Link GitHub:

<https://github.com/SeverinoCyber/30-days-of-code/tree/main/Hackerrank/day6>

Python 3:

Submissions

Leaderboard

Discussions

Editorial

Tutorial

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 6: Let's Review

ooo-indexed characters.

Sample Input

2
Hacker
Rank

Sample Output

Hce akr
Rn ak

Explanation

Test Case 0: $S = \text{"Hacker"}$
 $S[0] = \text{"H"}$
 $S[1] = \text{"a"}$
 $S[2] = \text{"c"}$
 $S[3] = \text{"k"}$
 $S[4] = \text{"e"}$
 $S[5] = \text{"r"}$
The even indices are 0, 2, and 4, and the odd indices are 1, 3, and 5. We then print a single line of 2 space-separated strings: the first string contains the ordered characters from S 's even indices (Hce), and the second string contains the ordered characters from S 's odd indices (akr).
Test Case 1: $S = \text{"Rank"}$
 $S[0] = \text{"R"}$
 $S[1] = \text{"a"}$
 $S[2] = \text{"n"}$
 $S[3] = \text{"k"}$
The even indices are 0 and 2, and the odd indices are 1 and 3. We then print a single line of 2 space-separated strings: the first string contains the ordered characters from S 's even indices (Rn), and the second string contains the ordered characters from S 's odd indices (ak).

Change Theme

Language Python 3

Exit Full Screen View

```
1 # Enter your code here. Read input from STDIN. Print output to STDOUT
2 T = int(input())
3
4
5 for i in range(T):
6     S = input()
7     par = ""
8     impar = ""
9
10    for indice in range(len(S)):
11        if indice % 2 == 0:
12            par += S[indice]
13        else:
14            impar += S[indice]
15
16    print(par + " " + impar)
17
```

Line: 17 Col: 1

Upload Code as File Test against custom input Run Code Submit Code

Submissions

Leaderboard

Discussions

Editorial

Tutorial

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 6: Let's Review

Each line i of the T subsequent lines contain a string, S .

Constraints

- $1 \leq T \leq 10$
- $2 \leq \text{length of } S \leq 10000$

Output Format

For each String S_j (where $0 \leq j \leq T - 1$), print S_j 's even-indexed characters, followed by a space, followed by S_j 's odd-indexed characters.

Sample Input

2
Hacker
Rank

Sample Output

Hce akr
Rn ak

Explanation

Test Case 0: $S = \text{"Hacker"}$
 $S[0] = \text{"H"}$
 $S[1] = \text{"a"}$
 $S[2] = \text{"c"}$
 $S[3] = \text{"k"}$
 $S[4] = \text{"e"}$
 $S[5] = \text{"r"}$
The even indices are 0, 2, and 4, and the odd indices are 1, 3, and 5. We then print a single line of 2 space-separated strings: the first string contains the ordered characters from S 's even indices (Hce), and the second string contains the ordered characters from S 's odd indices (akr).
Test Case 1: $S = \text{"Rank"}$
 $S[0] = \text{"R"}$

Upload Code as File Test against custom input Run Code Submit Code

30

Days of code

You have earned 30.00 points!
You are now 8 challenges away from the 3rd star for your 30 days of code badge.

0% 7/15

Congratulations

You solved this challenge. Would you like to challenge your friends?

Next Challenge

Test case 0

Test case 1

Test case 2

Test case 3

Test case 4

Test case 5

Test case 6

Compiler Message

Success

Input (stdin)

2
Hacker
Rank

Expected Output

Hce akr
Rn ak

JavaScript(Node js):

2

Hacker

Rank

Hce akr

Rn ak

Test Case 0: $S = \text{"Hacker"}$

$S[0] = \text{"H"}$
 $S[1] = \text{"a"}$
 $S[2] = \text{"c"}$
 $S[3] = \text{"k"}$
 $S[4] = \text{"e"}$
 $S[5] = \text{"r"}$

The even indices are 0, 2, and 4, and the odd indices are 1, 3, and 5. We then print a single line of 2 space-separated strings: the first string contains the ordered characters from S 's even indices (Hce), and the second string contains the ordered characters from S 's odd indices (akr).

Test Case 1: $S = \text{"Rank"}$

$S[0] = \text{"R"}$
 $S[1] = \text{"a"}$
 $S[2] = \text{"n"}$
 $S[3] = \text{"k"}$

The even indices are 0 and 2, and the odd indices are 1 and 3. We then print a single line of 2 space-separated strings: the first string contains the ordered characters from S 's even indices (Rn), and the second string contains the ordered characters from S 's odd indices (ak).

function processData(input) {
 //Enter your code here
 let lines = input.trim().split('\n');
 let T = parseInt(lines[0]);
 for (let i = 1; i <= T; i++) {
 let S = lines[i].trim();
 let par = "";
 let impar = "";

 for (let indice = 0; indice < S.length; indice++) {
 if(indice % 2 === 0){
 par += S[indice];
 } else {
 impar += S[indice];
 }
 }
 console.log(par+" "+impar)
 }
}

process.stdin.resume();
process.stdin.setEncoding("ascii");
let input = "";
process.stdin.on("data", function (input) {
 input += input;
});
process.stdin.on("end", function () {
 processData(input);
});

Line: 18 Col: 3

Upload Codes as File Test against custom input Run Code Submit Code

2

Hacker

Rank

Hce akr

Rn ak

Test Case 0: $S = \text{"Hacker"}$

$S[0] = \text{"H"}$
 $S[1] = \text{"a"}$
 $S[2] = \text{"c"}$
 $S[3] = \text{"k"}$
 $S[4] = \text{"e"}$
 $S[5] = \text{"r"}$

The even indices are 0, 2, and 4, and the odd indices are 1, 3, and 5. We then print a single line of 2 space-separated strings: the first string contains the ordered characters from S 's even indices (Hce), and the second string contains the ordered characters from S 's odd indices (akr).

Test Case 1: $S = \text{"Rank"}$

$S[0] = \text{"R"}$
 $S[1] = \text{"a"}$
 $S[2] = \text{"n"}$
 $S[3] = \text{"k"}$

The even indices are 0 and 2, and the odd indices are 1 and 3. We then print a single line of 2 space-separated strings: the first string contains the ordered characters from S 's even indices (Rn), and the second string contains the ordered characters from S 's odd indices (ak).

Line: 18 Col: 3

Upload Codes as File Test against custom input Run Code Submit Code

Congratulations

You solved this challenge. Would you like to challenge your friends? [f](#) [t](#) [in](#)

Next Challenge

Test case 0

Test case 1

Test case 2

Test case 3

Test case 4

Test case 5

Test case 6

Compiler Message

Success

Input (stdin)
2
Hacker
Rank

Expected Output
Hce akr
Rn ak

C++:

HackerRank

[Prepare](#) |
 [Tutorials](#) |
 [30 Days of Code](#) |
 Day 6: Let's Review

odd-indexed characters.

Sample Input

```
2
Hacker
Rank
```

Sample Output

```
Hce akr
Rn ak
```

Explanation

Test Case 0: $S = \text{"Hacker"}$

$S[0] = \text{"H"}$
 $S[1] = \text{"a"}$
 $S[2] = \text{"c"}$
 $S[3] = \text{"k"}$
 $S[4] = \text{"e"}$
 $S[5] = \text{"r"}$

The even indices are 0, 2, and 4, and the odd indices are 1, 3, and 5. We then print a single line of 2 space-separated strings: the first string contains the ordered characters from S 's even indices (**Hce**), and the second string contains the ordered characters from S 's odd indices (**akr**).

Test Case 1: $S = \text{"Rank"}$

$S[0] = \text{"R"}$
 $S[1] = \text{"a"}$
 $S[2] = \text{"n"}$
 $S[3] = \text{"k"}$

The even indices are 0 and 2, and the odd indices are 1 and 3. We then print a single line of 2 space-separated strings: the first string contains the ordered characters from S 's even indices (**Ran**), and the second string contains the ordered characters from S 's odd indices (**ak**).

Change Theme Language C++11
⌕ ⋮

```

1  #include <cmath>
2  #include <cstdio>
3  #include <vector>
4  #include <iostream>
5  #include <algorithm>
6  #include <string>
7  using namespace std;
8
9
10 int main() {
11     /* Enter your code here. Read input from STDIN. Print output to STDOUT */
12
13     int T;
14     cin >> T;
15     cin.ignore();
16     for(int i = 1; i <= T; i++){
17         string cadena;
18         getline(cin, cadena);
19         string par = "";
20         string impar = "";
21
22         for(int l = 0; l < cadena.length(); l++){
23             if(l % 2 == 0){
24                 par += cadena[l];
25             }else{
26                 impar += cadena[l];
27             }
28         }
29         cout << par << " " << impar << endl;
30     }
31     return 0;
32 }
```

Line: 14 Col: 18

Upload Code as File
Test against custom input

Run Code
Submit Code

HackerRank
Prepare > Tutorials > 30 Days of Code > Day 6: Let's Review

ooo-indexed characters.

Sample Input

```
2
Hacker
Rank
```

Sample Output

```
Hce akr
Rn ak
```

Explanation

Test Case 0: S = "Hacker"

S[0] = "H"
S[1] = "a"
S[2] = "c"
S[3] = "k"
S[4] = "e"
S[5] = "r"

The even indices are 0, 2, 4, and the odd indices are 1, 3, and 5. We then print a single line of 2 space-separated strings: the first string contains the ordered characters from S's even indices (Hce), and the second string contains the ordered characters from S's odd indices (akr).

Test Case 1: S = "Rank"

S[0] = "R"
S[1] = "a"
S[2] = "n"
S[3] = "k"

The even indices are 0 and 2, and the odd indices are 1 and 3. We then print a single line of 2 space-separated strings: the first string contains the ordered characters from S's even indices (Rn), and the second string contains the ordered characters from S's odd indices (ak).

Submissions
Leaderboard
Discussions
Tutorial

Line: 14 Col: 18

☐ Test against custom input

Congratulations

You solved this challenge. Would you like to challenge your friends?

Next Challenge

- ✔ Test case 0
- ✔ Test case 1 ↗
- ✔ Test case 2 ↗
- ✔ Test case 3 ↗
- ✔ Test case 4 ↗
- ✔ Test case 5 ↗
- ✔ Test case 6 ↗

Compiler Message

Success

Input (stdin)

```
1 2
2 Hacker
3 Rank
```

[Download](#)

Expected Output

```
1 Hce akr
2 Rn ak
```

[Download](#)

Java7:

000-indexed characters.

Sample Input

2
Hacker
Rank

Sample Output

Hce akr
Rn ak

Explanation

Test Case 0: S = "Hacker"
S[0] = "H"
S[1] = "a"
S[2] = "c"
S[3] = "k"
S[4] = "e"
S[5] = "r"
The even indices are 0, 2, and 4, and the odd indices are 1, 3, and 5. We then print a single line of 2 space-separated strings; the first string contains the ordered characters from S's even indices (Hce), and the second string contains the ordered characters from S's odd indices (akr).

Test Case 1: S = "Rank"
S[0] = "R"
S[1] = "a"
S[2] = "n"
S[3] = "k"
The even indices are 0 and 2, and the odd indices are 1 and 3. We then print a single line of 2 space-separated strings; the first string contains the ordered characters from S's even indices (Rn), and the second string contains the ordered characters from S's odd indices (ak).

Submissions

Leaderboard

Discussions

Editorial

Tutorial

Change Theme Language Java 7

```
1 import java.io.*;
2 import java.util.*;
3 import java.text.*;
4 import java.math.*;
5 import java.util.regex.*;
6 import java.util.Scanner;
7
8 public class Solution {
9
10
11     /* Enter your code here. Read input from STDIN. Print output to STDOUT. Your class should be named Solution. */
12     Scanner scanner = new Scanner(System.in);
13     int T = scanner.nextInt();
14     scanner.nextLine();
15
16     for(int i = 1; i <= T; i++){
17         String S = scanner.nextLine();
18         String par = "";
19         String impar = "";
20
21         for(int l = 0; l < S.length(); l++){
22             if(l % 2 == 0){
23                 par += S.charAt(l);
24             }
25             else{
26                 impar += S.charAt(l);
27             }
28         }
29         System.out.println(par+" "+impar);
30     }
31     scanner.close();
32 }
33
34 }
```

Line: 16 Col: 27

Upload Code as File

Test against custom input

Run Code

Submit Code

000-indexed characters.

Sample Input

2
Hacker
Rank

Sample Output

Hce akr
Rn ak

Explanation

Test Case 0: S = "Hacker"
S[0] = "H"
S[1] = "a"
S[2] = "c"
S[3] = "k"
S[4] = "e"
S[5] = "r"
The even indices are 0, 2, and 4, and the odd indices are 1, 3, and 5. We then print a single line of 2 space-separated strings; the first string contains the ordered characters from S's even indices (Hce), and the second string contains the ordered characters from S's odd indices (akr).

Test Case 1: S = "Rank"
S[0] = "R"
S[1] = "a"
S[2] = "n"
S[3] = "k"
The even indices are 0 and 2, and the odd indices are 1 and 3. We then print a single line of 2 space-separated strings; the first string contains the ordered characters from S's even indices (Rn), and the second string contains the ordered characters from S's odd indices (ak).

Submissions

Leaderboard

Discussions

Editorial

Tutorial

Line: 16 Col: 27

Upload Code as File

Test against custom input

Run Code

Submit Code

Congratulations

You solved this challenge. Would you like to challenge your friends? [f](#) [t](#) [in](#)

Next Challenge

Test case 0

Test case 1

Test case 2

Test case 3

Test case 4

Test case 5

Test case 6

Compiler Message

Success

Input (stdin)

Download

2
Hacker
Rank

Expected Output

Download

Hce akr
Rn ak

C#:

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 6: Let's Review

odd-indexed characters.

Sample Input

2
Hacker
Rank

Sample Output

Hce akr
Rn ak

Explanation

Test Case 0: $S = \text{"Hacker"}$
 $S[0] = \text{"H"}$
 $S[1] = \text{"a"}$
 $S[2] = \text{"c"}$
 $S[3] = \text{"k"}$
 $S[4] = \text{"e"}$
 $S[5] = \text{"r"}$
The even indices are 0, 2, and 4, and the odd indices are 1, 3, and 5. We then print a single line of 2 space-separated strings; the first string contains the ordered characters from S 's even indices (Hce), and the second string contains the ordered characters from S 's odd indices (akr).

Test Case 1: $S = \text{"Rank"}$
 $S[0] = \text{"R"}$
 $S[1] = \text{"a"}$
 $S[2] = \text{"n"}$
 $S[3] = \text{"k"}$
The even indices are 0 and 2, and the odd indices are 1 and 3. We then print a single line of 2 space-separated strings; the first string contains the ordered characters from S 's even indices (Rn), and the second string contains the ordered characters from S 's odd indices (ak).

Exit Full Screen View

Change Theme Language C#

```
1 using System;
2 using System.Collections.Generic;
3 using System.IO;
4 class Solution {
5     static void Main(String[] args) {
6         /* Enter your code here. Read input from STDIN. Print output to STDOUT. Your class should be named
7         Solution */
8         int T = Convert.ToInt32(Console.ReadLine());
9         for(int i = 1; i <= T; i++){
10             string S = Console.ReadLine();
11             string par = "";
12             string impar = "";
13
14             for(int l = 0; l < S.Length; l++){
15                 if(l % 2 == 0){
16                     par += S[l];
17                 }
18                 else{
19                     impar += S[l];
20                 }
21             }
22             Console.WriteLine(par+" "+impar);
23         }
24     }
25 }
```

Line: 20 Col: 46

Upload Codes as File

Test against custom input

Run Code

Submit Code

The image displays two side-by-side screenshots of a web application interface, likely a coding platform like HackerRank.

Left Window:

- Header:** Shows the HackerRank logo and navigation links: "Prepare > Tutorials > 30 Days of Code > Day 6: Let's Review".
- Submissions:** A sidebar on the left lists "Submissions", "Leaderboard", "Discussions", "Editorial", and "Tutorial".
- Main Content Area:**
 - Sample Input:** A code editor containing:

```
2  
Hacker  
Rank
```
 - Sample Output:** A code editor containing:

```
Hce akr  
Rn ak
```
 - Explanation:**

The first test case: $S = \text{"Hacker"}$

$S[0] = \text{"H"}$
 $S[1] = \text{"a"}$
 $S[2] = \text{"c"}$
 $S[3] = \text{"k"}$
 $S[4] = \text{"e"}$
 $S[5] = \text{"r"}$

The even indices are 0, 2, and 4, and the odd indices are 1, 3, and 5. We then print a single line of 2 space-separated strings; the first string contains the ordered characters from S's even indices (Hce), and the second string contains the ordered characters from S's odd indices (akr).

The second test case: $S = \text{"Rank"}$

$S[0] = \text{"R"}$
 $S[1] = \text{"a"}$
 $S[2] = \text{"n"}$
 $S[3] = \text{"k"}$

The even indices are 0 and 2, and the odd indices are 1 and 3. We then print a single line of 2 space-separated strings; the first string contains the ordered characters from S's even indices (Rn), and the second string contains the ordered characters from S's odd indices (ak).

Right Window:

- Header:** Shows "Exit Full Screen View" and "Line: 20 Col: 46".
- Main Content Area:**
 - A button labeled "Upload Codes as File" and a checkbox labeled "Test against custom input".
 - Buttons labeled "Run Code" and "Submit Code".
 - A large green banner with the text "Congratulations" and "You solved this challenge. Would you like to challenge your friends?" followed by social media icons (Facebook, Twitter, LinkedIn). A button labeled "Next Challenge" is also present.
 - A vertical scroll bar on the left indicates the position of the current view.
 - Compiler Message:** A section titled "Success" with a "Download" link.
 - Input (stdin):** A code editor containing:

```
2  
Hacker  
Rank
```
 - Expected Output:** A code editor containing:

```
Hce akr  
Rn ak
```