

Presentación:

Nombre:

Algelis Severino

Tema:

Introducción a la programación y diagrama de flujo.

Tecnico:

Ciberseguridad Semipresencial

Facilitador:

Kevin Feliz Henriquez

Centro:

Diapiato Pro salud

Descripción:

En este documento .pdf adjunto capturas del reto 1 de 30-days-of-codes de HackerRank.

Link GitHub:

<https://github.com/SeverinoCyber/30-days-of-code/tree/main/Hackerrank/day1>

TypeScript:

HackerRank
Prepare > Tutorials > 30 Days of Code > Day 1: Data Types
Exit Full Screen View

Note: If you are using a language that doesn't support using + for string concatenation (e.g., C), you can just print one variable immediately following the other on the same line. The string provided in your editor must be printed first, immediately followed by the string you read as input.

Input Format

The first line contains an integer that you must sum with i.
 The second line contains a double that you must sum with d.
 The third line contains a string that you must concatenate with s.

Output Format

Print the sum of both integers on the first line, the sum of both doubles (scaled to 1 decimal place) on the second line, and then the two concatenated strings on the third line.

Sample Input

```
12
4.0
Is the best place to learn and practice coding!
```

Sample Output

```
16
8.0
HackerRank Is the best place to learn and practice coding!
```

Explanation

When we sum the integers 4 and 12, we get the integer 16.
 When we sum the floating-point numbers 4.0 and 4.0, we get 8.0.
 When we concatenate HackerRank with Is the best place to learn and practice coding!, we get HackerRank Is the best place to learn and practice coding!.

You will not pass this challenge if you attempt to assign the Sample Case values to your variables instead of following the instructions above and reading input from stdin.

```

1 let inputLines: string[] = [];
2 let currentLine: number = 0;
3 process.stdin.on('data', function(inputStdin: string): void {
4     inputString += inputStdin;
5 });
6
7 process.stdin.on('end', function(): void {
8     inputLines = inputString.split('\n');
9     inputString = '';
10    main();
11 });
12
13 function readline(): string {
14     return inputLines[currentLine++];
15 }
16
17 function main() {
18     // Enter your code here
19     var i = 4;
20     var d = 4.0;
21     var s = "HackerRank ";
22
23     var entero
24     var flotante
25     var cadena
26
27     entero = Number(readline());
28     flotante = Number(readline());
29     cadena = readline();
30
31     console.log(entero + i);
32     var result = flotante + d
33     console.log(result.toFixed(1))
34     console.log(s + cadena)
35 }
        
```

Line: 38 Col: 33

Upload Code as File
Test against custom input
Run Code
Submit Code

HackerRank

[Prepare > Tutorials > 30 Days of Code > Day 1: Data Types](#)

Submissions

Leaderboard

Discussions

Editorial

Tutorial

Note: If you are using a language that doesn't support using + for string concatenation (e.g.: C), you can just print one variable immediately following the other on the same line. The string provided in your editor must be printed first, immediately followed by the string you read as input.

Input Format

The first line contains an integer that you must sum with i.
The second line contains a double that you must sum with d.
The third line contains a string that you must concatenate with s.

Output Format

Print the sum of both integers on the first line, the sum of both doubles (scaled to 1 decimal place) on the second line, and then the two concatenated strings on the third line.

Sample Input

```
12  
4.0  
Is the best place to learn and practice coding!
```

Sample Output

```
16  
8.0  
HackerRank is the best place to learn and practice coding!
```

Explanation

When we sum the integers 4 and 12, we get the integer 16.
When we sum the floating-point numbers 4.0 and 4.0, we get 8.0.
When we concatenate HackerRank with Is the best place to learn and practice coding!, we get HackerRank Is the best place to learn and practice coding!.

You will not pass this challenge if you attempt to assign the Sample Case values to your variables instead of following the instructions above and reading input from stdin.

Exit Full Screen View

Line: 38 Col: 33

Upload Code as File Test against custom input Run Code Submit Code

Congratulations

You solved this challenge. Would you like to challenge your friends? f t in
The next challenge in the tutorial will unlock in 13:39:21

Go to Dashboard Try a Random Challenge

Test case 0 Compiler Message Success

Test case 1 Download

Expected Output Download

Perl:

Submissions

Leaderboard

Discussions

Editorial

Tutorial

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 1: Data Types

Note:

If you are using a language that doesn't support using + for string concatenation (e.g.: C), you can just print one variable immediately following the other on the same line. The string provided in your editor must be printed first, immediately followed by the string you read as input.

Input Format

The first line contains an integer that you must sum with i.
The second line contains a double that you must sum with d.
The third line contains a string that you must concatenate with s.

Output Format

Print the sum of both integers on the first line, the sum of both doubles (scaled to 1 decimal place) on the second line, and then the two concatenated strings on the third line.

Sample Input

12
4.0
is the best place to learn and practice coding!

Sample Output

16
8.0
HackerRank is the best place to learn and practice coding!

Explanation

When we sum the integers 4 and 12, we get the integer 16.
When we sum the floating-point numbers 4.0 and 4.0, we get 8.0.
When we concatenate HackerRank with is the best place to learn and practice coding!, we get HackerRank is the best place to learn and practice coding!.

You will not pass this challenge if you attempt to assign the Sample Case values to your variables instead of following the instructions above and reading input from stdin.

Change Theme

Language Perl

Exit Full Screen View

```
1 > $i = 4; ---
4 # Declare second integer, double, and String variables.
5 my $entero = <STDIN>;
6 my $flotante = <STDIN>;
7 my $cadena = <STDIN>;
8 # Read and save an integer, double, and String to your variables.
9
10 # Print the sum of both integer variables on a new line.
11 my $result = $entero + $i;
12 print "$result\n";
13 # Print the sum of the double variables on a new line.
14 my $result1 = $flotante + $d;
15 printf ("%1f\n", $result1);
16 # Concatenate and print the String variables on a new line
17 # The 's' variable above should be printed first.
18 my $result2 = $s . $cadena;
19 print $result2;
20
```

Line: 20 Col: 1

Upload Code as File

Test against custom input

Run Code

Submit Code

Submissions

Leaderboard

Discussions

Editorial

Tutorial

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 1: Data Types

Note:

If you are using a language that doesn't support using + for string concatenation (e.g.: C), you can just print one variable immediately following the other on the same line. The string provided in your editor must be printed first, immediately followed by the string you read as input.

Input Format

The first line contains an integer that you must sum with i.
The second line contains a double that you must sum with d.
The third line contains a string that you must concatenate with s.

Output Format

Print the sum of both integers on the first line, the sum of both doubles (scaled to 1 decimal place) on the second line, and then the two concatenated strings on the third line.

Sample Input

12
4.0
is the best place to learn and practice coding!

Sample Output

16
8.0
HackerRank is the best place to learn and practice coding!

Explanation

When we sum the integers 4 and 12, we get the integer 16.
When we sum the floating-point numbers 4.0 and 4.0, we get 8.0.
When we concatenate HackerRank with is the best place to learn and practice coding!, we get HackerRank is the best place to learn and practice coding!.

You will not pass this challenge if you attempt to assign the Sample Case values to your variables instead of following the instructions above and reading input from stdin.

Line: 20 Col: 1

Upload Code as File

Test against custom input

Run Code

Submit Code

Congratulations

You solved this challenge. Would you like to challenge your friends? [f](#) [t](#) [i](#) [n](#)

The next challenge in this tutorial will unlock in 13:38:40

Go to Dashboard

Try a Random Challenge

Test case 0

Compiler Message

Success

Test case 1

Input (stdin)

Download

1 12
2 4.0
3 is the best place to learn and practice coding!

Expected Output

Download

1 16
2 8.0
3 HackerRank is the best place to learn and practice coding!

C++:

Submissions

Leaderboard

Discussions

Editorial

Tutorial

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 1: Data Types

For more information on what this string you must use input and print the values left to right.

Note: If you are using a language that doesn't support using + for string concatenation (e.g., C), you can just print one variable immediately following the other on the same line. The string provided in your editor must be printed first, immediately followed by the string you read as input.

Input Format

The first line contains an integer that you must sum with i.
The second line contains a double that you must sum with d.
The third line contains a string that you must concatenate with s.

Output Format

Print the sum of both integers on the first line, the sum of both doubles (scaled to 1 decimal place) on the second line, and then the two concatenated strings on the third line.

Sample Input

12
4.0
Is the best place to learn and practice coding!

Sample Output

16
8.0
HackerRank is the best place to learn and practice coding!

Explanation

When we sum the integers 4 and 12, we get the integer 16.
When we sum the floating-point numbers 4.0 and 4.0, we get 8.0.
When we concatenate HackerRank with Is the best place to learn and practice coding!, we get HackerRank is the best place to learn and practice coding!.

You will not pass this challenge if you attempt to assign the Sample Case values to your variables instead of following the instructions above and reading input from stdin.

Change Theme Language C++11

1 #include <iostream>
2 #include <iomanip>
3 #include <iomanip>
4
5 using namespace std;
6
7 int main() {
8 int i = 4;
9 double d = 4.0;
10 string s = "HackerRank ";
11
12
13 // Declare second integer, double, and String variables.
14 int entero;
15 double flotante;
16 string cadena;
17 // Read and save an integer, double, and String to your variables.
18 // Note: If you have trouble reading the entire string, please go back and review the Tutorial closely!
19 cin >> entero;
20 cin >> flotante;
21 cin.ignore();
22 getline(cin, cadena);
23 // Print the sum of both integer variables on a new line.
24 int result = entero + i;
25 cout << result << endl;
26 // Print the sum of the double variables on a new line.
27 double result1 = flotante + d;
28 cout << fixed << setprecision(1) << result1 << endl;
29 // Concatenate and print the String variables on a new line
30 // The 's' variable above should be printed first.
31 string result2 = s + cadena;
32 cout << result2 << endl;
33
34 return 0; //

Line: 21 Col: 18

Upload Codes File Test against custom input Run Code Submit Code

Submissions

Leaderboard

Discussions

Editorial

Tutorial

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 1: Data Types

For more information on what this string you must use input and print the values left to right.

Note: If you are using a language that doesn't support using + for string concatenation (e.g., C), you can just print one variable immediately following the other on the same line. The string provided in your editor must be printed first, immediately followed by the string you read as input.

Input Format

The first line contains an integer that you must sum with i.
The second line contains a double that you must sum with d.
The third line contains a string that you must concatenate with s.

Output Format

Print the sum of both integers on the first line, the sum of both doubles (scaled to 1 decimal place) on the second line, and then the two concatenated strings on the third line.

Sample Input

12
4.0
Is the best place to learn and practice coding!

Sample Output

16
8.0
HackerRank is the best place to learn and practice coding!

Explanation

When we sum the integers 4 and 12, we get the integer 16.
When we sum the floating-point numbers 4.0 and 4.0, we get 8.0.
When we concatenate HackerRank with Is the best place to learn and practice coding!, we get HackerRank is the best place to learn and practice coding!.

You will not pass this challenge if you attempt to assign the Sample Case values to your variables instead of following the instructions above and reading input from stdin.

Line: 21 Col: 18

Upload Codes File Test against custom input Run Code Submit Code

Congratulations

You solved this challenge. Would you like to challenge your friends? [f](#) [t](#) [in](#)

The next challenge in this tutorial will unlock in 13:35:13

Go to Dashboard Try a Random Challenge

Test case 0

Compiler Message

Success

Input (stdin)

1 12
2 4.0
3 Is the best place to learn and practice coding!

Expected Output

1 16
2 8.0
3 HackerRank is the best place to learn and practice coding!

C#:

Submissions

Leaderboard

Discussions

Editorial

Tutorial

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 1: Data Types

for, and concatenation (+) is used to string your code and output, so that you can get the results, sent to your editor.

Note: If you are using a language that doesn't support using + for string concatenation (e.g.: C), you can just print one variable immediately following the other on the same line. The string provided in your editor must be printed first, immediately followed by the string you read as input.

Input Format

The first line contains an integer that you must sum with i .

The second line contains a double that you must sum with d .

The third line contains a string that you must concatenate with s .

Output Format

Print the sum of both integers on the first line, the sum of both doubles (scaled to 1 decimal place) on the second line, and then the two concatenated strings on the third line.

Sample Input

12
4.0
is the best place to learn and practice coding!

Sample Output

16
8.0
HackerRank is the best place to learn and practice coding!

Explanation

When we sum the integers 4 and 12, we get the integer 16.

When we sum the floating-point numbers 4.0 and 4.0, we get 8.0.

When we concatenate HackerRank with is the best place to learn and practice coding!, we get HackerRank is the best place to learn and practice coding!.

You will not pass this challenge if you attempt to assign the Sample Case values to your variables instead of following the instructions above and reading input from stdin.

Change Theme

Language C#

Exit Full Screen View

```
1 using System;
2 using System.Collections.Generic;
3 using System.IO;
4
5 class Solution {
6     static void Main(String[] args) {
7         int i = 4;
8         double d = 4.0;
9         string s = "HackerRank ";
10
11
12         // Declare second integer, double, and String variables.
13         int entero;
14         double flotante;
15         string cadena;
16         // Read and save an integer, double, and String to your variables.
17         entero = int.Parse(Console.ReadLine());
18         flotante = double.Parse(Console.ReadLine());
19         cadena = Console.ReadLine();
20         // Print the sum of both integer variables on a new line.
21         Console.WriteLine(entero + i);
22         // Print the sum of the double variables on a new line.
23         double result1 = flotante + d;
24         Console.WriteLine($"{result1:F1}");
25         // Concatenate and print the String variables on a new line
26         // The 's' variable above should be printed first.
27         string result = $"{s}{cadena}";
28         Console.WriteLine(result);
29     }
30 }
```

Line: 24 Col: 40

Upload Code as File

Test against custom input

Run Code

Submit Code

Submissions

Leaderboard

Discussions

Editorial

Tutorial

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 1: Data Types

for, and concatenation (+) is used to string your code and output, so that you can get the results, sent to your editor.

Note: If you are using a language that doesn't support using + for string concatenation (e.g.: C), you can just print one variable immediately following the other on the same line. The string provided in your editor must be printed first, immediately followed by the string you read as input.

Input Format

The first line contains an integer that you must sum with i .

The second line contains a double that you must sum with d .

The third line contains a string that you must concatenate with s .

Output Format

Print the sum of both integers on the first line, the sum of both doubles (scaled to 1 decimal place) on the second line, and then the two concatenated strings on the third line.

Sample Input

12
4.0
is the best place to learn and practice coding!

Sample Output

16
8.0
HackerRank is the best place to learn and practice coding!

Explanation

When we sum the integers 4 and 12, we get the integer 16.

When we sum the floating-point numbers 4.0 and 4.0, we get 8.0.

When we concatenate HackerRank with is the best place to learn and practice coding!, we get HackerRank is the best place to learn and practice coding!.

You will not pass this challenge if you attempt to assign the Sample Case values to your variables instead of following the instructions above and reading input from stdin.

Line: 24 Col: 40

Upload Code as File

Test against custom input

Run Code

Submit Code

Congratulations

You solved this challenge. Would you like to challenge your friends?

[f](#) [t](#) [in](#)

The next challenge in this tutorial will unlock in 13:23:59

Go to Dashboard

Try a Random Challenge

Test case 0

Test case 1

Compiler Message

Success

Input (stdin)

Download

1 12
2 4.0
3 is the best place to learn and practice coding!

Expected Output

Download

1 16
2 8.0
3 HackerRank is the best place to learn and practice coding!

Java 7:

</

Javascript (node js):

Submissions

Leaderboard

Discussions

Editorial

Tutorial

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 1: Data Types

Get your solution history or report an issue with your code. Please don't forget to check the feedback left by other users.

Note: If you are using a language that doesn't support using `+` for string concatenation (e.g.: C), you can just print one variable immediately following the other on the same line. The string provided in your editor must be printed first, immediately followed by the string you read as input.

Input Format

The first line contains an integer that you must sum with `i`.

The second line contains a double that you must sum with `d`.

The third line contains a string that you must concatenate with `s`.

Output Format

Print the sum of both integers on the first line, the sum of both doubles (scaled to 1 decimal place) on the second line, and then the two concatenated strings on the third line.

Sample Input

```
12
4.0
is the best place to learn and practice coding!
```

Sample Output

```
16
8.0
HackerRank is the best place to learn and practice coding!
```

Explanation

When we sum the integers 4 and 12, we get the integer 16.

When we sum the floating-point numbers 4.0 and 4.0, we get 8.0.

When we concatenate HackerRank with is the best place to learn and practice coding!, we get HackerRank is the best place to learn and practice coding!.

You will not pass this challenge if you attempt to assign the Sample Case values to your variables instead of following the instructions above and reading input from stdin.

Change Theme

Language JavaScript (Node.js)

Exit Full Screen View

```
8 process.stdin.on('data', function (data) {
9     input_stdin += data;
10 });
11
12 process.stdin.on('end', function () {
13     input_stdin_array = input_stdin.split("\n");
14     main();
15 });
16
17 // Reads complete line from STDIN
18 function readLine() {
19     return input_stdin_array[input_currentline++];
20 }
21
22 function main() {
23     var i = 4;
24     var d = 4.0;
25     var s = "HackerRank ";
26     // Declare second integer, double, and String variables.
27     var entero
28     var flotante
29     var cadena
30
31     // Read and save an integer, double, and String to your variables.
32     entero = Number(readLine())
33     flotante = Number(readLine())
34     cadena = readLine()
35
36     // Print the sum of both integer variables on a new line.
37     console.log(entero + i)
38
39     // Print the sum of the double variables on a new line.
40     var result = flotante + d
41     console.log(result.toFixed(1))
42
43     // Concatenate and print the String variables on a new line
```

Line: 41 Col: 33

Upload Codes as File

Test against custom input

Run Code

Submit Code

Submissions

Leaderboard

Discussions

Editorial

Tutorial

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 1: Data Types

Get your solution history or report an issue with your code. Please don't forget to check the feedback left by other users.

Note: If you are using a language that doesn't support using `+` for string concatenation (e.g.: C), you can just print one variable immediately following the other on the same line. The string provided in your editor must be printed first, immediately followed by the string you read as input.

Input Format

The first line contains an integer that you must sum with `i`.

The second line contains a double that you must sum with `d`.

The third line contains a string that you must concatenate with `s`.

Output Format

Print the sum of both integers on the first line, the sum of both doubles (scaled to 1 decimal place) on the second line, and then the two concatenated strings on the third line.

Sample Input

```
12
4.0
is the best place to learn and practice coding!
```

Sample Output

```
16
8.0
HackerRank is the best place to learn and practice coding!
```

Explanation

When we sum the integers 4 and 12, we get the integer 16.

When we sum the floating-point numbers 4.0 and 4.0, we get 8.0.

When we concatenate HackerRank with is the best place to learn and practice coding!, we get HackerRank is the best place to learn and practice coding!.

You will not pass this challenge if you attempt to assign the Sample Case values to your variables instead of following the instructions above and reading input from stdin.

Line: 41 Col: 33

Upload Codes as File

Test against custom input

Run Code

Submit Code

Congratulations

You solved this challenge. Would you like to challenge your friends? [f](#) [t](#) [in](#)

The next challenge in this tutorial will unlock in 13:15:15

Go to Dashboard

Try a Random Challenge

Test case 0

Test case 1

Compiler Message

Success

Input (stdin)

Download

```
1 12
2 4.0
3 is the best place to learn and practice coding!
```

Expected Output

Download

```
1 16
2 8.0
3 HackerRank is the best place to learn and practice coding!
```

Python3:

Submissions

Understand

Discussions

Editorial

Tutorial

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 1: Data Types

You can use the editor to write the code, or you can copy and paste the code from the editor into your IDE.

Note: If you are using a language that doesn't support using `+` for string concatenation (e.g., C), you can just print one variable immediately following the other on the same line. The string provided in your editor must be printed first, immediately followed by the string you read as input.

Input Format
The first line contains an integer that you must sum with `i`.
The second line contains a double that you must sum with `d`.
The third line contains a string that you must concatenate with `s`.

Output Format
Print the sum of both integers on the first line, the sum of both doubles (scaled to 1 decimal place) on the second line, and then the two concatenated strings on the third line.

Sample Input

```
12
4.0
is the best place to learn and practice coding!
```

Sample Output

```
16
8.0
HackerRank is the best place to learn and practice coding!
```

Explanation
When we sum the integers 4 and 12, we get the integer 16.
When we sum the floating-point numbers 4.0 and 4.0, we get 8.0.
When we concatenate HackerRank with is the best place to learn and practice coding!, we get HackerRank is the best place to learn and practice coding!.

You will not pass this challenge if you attempt to assign the Sample Case values to your variables instead of following the instructions above and reading input from stdin.

Change Theme Language Pypy 3

```
1 > i = 4...
4 # Declare second integer, double, and String variables.
5
6 # Read and save an integer, double, and String to your variables.
7 entero = int(input())
8 flotante = float(input())
9 cadena = input()
10 # Print the sum of both integer variables on a new line.
11 print(entero + i)
12 # Print the sum of the double variables on a new line.
13 print(flotante + d)
14 # Concatenate and print the String variables on a new line
15 # The 's' variable above should be printed first.
16 print(f'{s}|{cadena}')
```

Line: 16 Col: 19

Upload Code as File

Test against custom input

Run Code

Submit Code

Submissions

Understand

Discussions

Editorial

Tutorial

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 1: Data Types

You can use the editor to write the code, or you can copy and paste the code from the editor into your IDE.

Note: If you are using a language that doesn't support using `+` for string concatenation (e.g., C), you can just print one variable immediately following the other on the same line. The string provided in your editor must be printed first, immediately followed by the string you read as input.

Input Format
The first line contains an integer that you must sum with `i`.
The second line contains a double that you must sum with `d`.
The third line contains a string that you must concatenate with `s`.

Output Format
Print the sum of both integers on the first line, the sum of both doubles (scaled to 1 decimal place) on the second line, and then the two concatenated strings on the third line.

Sample Input

```
12
4.0
is the best place to learn and practice coding!
```

Sample Output

```
16
8.0
HackerRank is the best place to learn and practice coding!
```

Explanation
When we sum the integers 4 and 12, we get the integer 16.
When we sum the floating-point numbers 4.0 and 4.0, we get 8.0.
When we concatenate HackerRank with is the best place to learn and practice coding!, we get HackerRank is the best place to learn and practice coding!.

You will not pass this challenge if you attempt to assign the Sample Case values to your variables instead of following the instructions above and reading input from stdin.

Line: 16 Col: 22

Upload Code as File

Test against custom input

Run Code

Submit Code

Congratulations
You solved this challenge. Would you like to challenge your friends? [f](#) [t](#) [i](#) [n](#)
The next challenge in this tutorial will unlock in 12:59:59

Go to Dashboard

Try a Random Challenge

Test case 0

Test case 1

Compiler Message

Success

Input (stdin)

Download

```
1 12
2 4.0
3 is the best place to learn and practice coding!
```

Expected Output

Download

```
1 16
2 8.0
3 HackerRank is the best place to learn and practice coding!
```

<https://www.hackerrank.com/challenge>