

Presentación:

Nombre:

Algelis Severino

Tema:

Introducción a la Programación y Diagrama De Flujo

Técnico:

Ciberseguridad Semipresencial

Facilitador:

Kevin Feliz Henríquez

Centro:

Diapiato Pro salud

Descripción:

En este documento .pdf adjunto capturas de mi primer reto en HackerRank de 30 days of code.

C#

Submissions

Leaderboard

Discussions

Editorial

Tutorial

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 0: Hello, World.

Exit Full Screen View

support submissions in many popular languages. You can switch languages using the drop-down menu above your editor, and the *inputString* variable may be written differently depending on the best-practice conventions of your submission language.

Input Format

A single line of text denoting *inputString* (the variable whose contents must be printed).

Output Format

Print Hello, World. on the first line, and the contents of *inputString* on the second line.

Sample Input

```
Welcome to 30 Days of Code!
```

Sample Output

```
Hello, World.
Welcome to 30 Days of Code!
```

Explanation

On the first line, we print the string literal Hello, World.. On the second line, we print the contents of the *inputString* variable which, for this sample case, happens to be Welcome to 30 Days of Code!. If you do not print the variable's contents to stdout, you will not pass the hidden test case.

Change Theme

Language C#

↺ ↻ ⋮

```
1 > using System;...
4
5 class Solution {
6     static void Main(String[] args) {
7         // Declare a variable named
7         // 'inputString' to hold our input.
8         String inputString = "Welcome to 30
8         Days of Code!";
9
10        // Read a full line of input from
10        // stdin (cin) and save it to our
10        // variable, input_string.
11        inputString = Console.ReadLine();
12
13        // Print a string literal saying
13        // "Hello, World." to stdout using cout.
13        Console.WriteLine("Hello, World.");
14
15        // TODO: Write a line of code here
15        // that prints the contents of
15        // input_string to stdout.
16        Console.WriteLine(inputString);
17
18    }
19 }
20 }
```

Line: 11 Col: 40

Upload Code as File

Run Code

Submit Code

Submissions

Leaderboard

Discussions

Editorial

Tutorial

support submissions in many popular languages. You can switch languages using the drop-down menu above your editor, and the `inputString` variable may be written differently depending on the best-practice conventions of your submission language.

Input Format

A single line of text denoting `inputString` (the variable whose contents must be printed).

Output Format

Print `Hello, World.` on the first line, and the contents of `inputString` on the second line.

Sample Input


```
Welcome to 30 Days of Code!
```

Sample Output

```
Hello, World.
Welcome to 30 Days of Code!
```

Explanation

On the first line, we print the string literal `Hello, World.` On the second line, we print the contents of the `inputString` variable which, for this sample case, happens to be `Welcome to 30 Days of Code!`. If you do not print the variable's contents to stdout, you will not pass the hidden test case.

☐ Test against custom input

You have earned 30.00 points!

You are now 1 challenge away from the 1st star for your 30 days of code badge.

50%

1/2

Congratulations

You solved this challenge. Would you like to challenge your friends?



The next challenge in this tutorial will unlock in 13:08:13

[Go to Dashboard](#)[Try a Random Challenge](#)☒ Test case 0☒ Test case 1

Compiler Message

Success

Input (stdin)

[Download](#)

```
1 Welcome to 30 Days of Code!
```

Expected Output

[Download](#)

```
1 Hello, World.
2 Welcome to 30 Days of Code!
```

C++

HackerRank

[Prepare](#) > [Tutorials](#) > [30 Days of Code](#) > [Day 0: Hello, World.](#)

Exit Full Screen View

Submissions

Leaderboard

Discussions

Editorial

Tutorial

support submissions in many popular languages. You can switch languages using the drop-down menu above your editor, and the *inputString* variable may be written differently depending on the best-practice conventions of your submission language.

Input Format

A single line of text denoting *inputString* (the variable whose contents must be printed).

Output Format

Print `Hello, World.` on the first line, and the contents of *inputString* on the second line.

Sample Input

```
Welcome to 30 Days of Code!
```

Sample Output

```
Hello, World.
Welcome to 30 Days of Code!
```

Explanation

On the first line, we print the string literal `Hello, World.`. On the second line, we print the contents of the *inputString* variable which, for this sample case, happens to be `Welcome to 30 Days of Code!`. If you do not print the variable's contents to stdout, you will not pass the hidden test case.

Change Theme

Language C++11

↺ ⋮

```
1 > #include <cmath>...
7 int main() {
8     // Declare a variable named
9     // 'input_string' to hold our input.
10    string input_string = "Welcome to 30 Days
11    of Code!";
12
13    // Read a full line of input from stdin
14    // (cin) and save it to our variable,
15    // input_string.
16    getline(cin, input_string);
17
18    // Print a string literal saying "Hello,
19    // World." to stdout using cout.
20    cout << "Hello, World." << endl;
21    cout << input_string << endl;
22
23    // TODO: Write a line of code here that
24    // prints the contents of input_string to
25    // stdout.
26
27    return 0;
28 }
```

Line: 22 Col: 1

⬇ Upload Code as File

Run Code

Submit Code

Submissions

Leaderboard

Discussions

Editorial

Tutorial

support submissions in many popular languages. You can switch languages using the drop-down menu above your editor, and the `inputString` variable may be written differently depending on the best-practice conventions of your submission language.

Input Format

A single line of text denoting `inputString` (the variable whose contents must be printed).

Output Format

Print `Hello, World.` on the first line, and the contents of `inputString` on the second line.

Sample Input

```
Welcome to 30 Days of Code!
```

Sample Output

```
Hello, World.
Welcome to 30 Days of Code!
```

Explanation

On the first line, we print the string literal `Hello, World.`. On the second line, we print the contents of the `inputString` variable which, for this sample case, happens to be `Welcome to 30 Days of Code!`. If you do not print the variable's contents to stdout, you will not pass the hidden test case.



You have earned 30.00 points!

You are now 1 challenge away from the 1st star for your 30 days of code badge. 50% 1/2

Congratulations

You solved this challenge. Would you like to challenge your friends?



The next challenge in this tutorial will unlock in 13:07:43

[Go to Dashboard](#)[Try a Random Challenge](#)

✓ Test case 0

✓ Test case 1

Compiler Message

Success

Input (stdin)

[Download](#)

```
1 Welcome to 30 Days of Code!
```

Expected Output

[Download](#)

```
1 Hello, World.
2 Welcome to 30 Days of Code!
```

Python3

HackerRank

[Prepare](#) > [Tutorials](#) > [30 Days of Code](#) > [Day 0: Hello, World.](#)

Exit Full Screen View

Submissions

Leaderboard

Discussions

Editorial

Tutorial

support submissions in many popular languages. You can switch languages using the drop-down menu above your editor, and the *inputString* variable may be written differently depending on the best-practice conventions of your submission language.

Input Format

A single line of text denoting *inputString* (the variable whose contents must be printed).

Output Format

Print `Hello, World.` on the first line, and the contents of *inputString* on the second line.

Sample Input

```
Welcome to 30 Days of Code!
```

Sample Output

```
Hello, World.
Welcome to 30 Days of Code!
```

Explanation

On the first line, we print the string literal `Hello, World.`. On the second line, we print the contents of the *inputString* variable which, for this sample case, happens to be `Welcome to 30 Days of Code!`. If you do not print the variable's contents to stdout, you will not pass the hidden test case.

Change Theme

Language Python 3

↺ ⋮

```
1 # Read a full line of input from stdin and
  # save it to our dynamically typed variable,
  # input_string.
2 input_string = input()
3
4 # Print a string literal saying "Hello, World."
  # to stdout.
5 print('Hello, World.')
6
7 # TODO: Write a line of code here that prints
  # the contents of input_string to stdout.
8 print(input_string)
```

Line: 8 Col: 19

⬆ Upload Code as File

Run Code

Submit Code

Submissions

Leaderboard

Discussions

Editorial

Tutorial

support submissions in many popular languages. You can switch languages using the drop-down menu above your editor, and the `inputString` variable may be written differently depending on the best-practice conventions of your submission language.

Input Format

A single line of text denoting `inputString` (the variable whose contents must be printed).

Output Format

Print `Hello, World.` on the first line, and the contents of `inputString` on the second line.

Sample Input

```
Welcome to 30 Days of Code!
```

Sample Output

```
Hello, World.  
Welcome to 30 Days of Code!
```

Explanation

On the first line, we print the string literal `Hello, World.`. On the second line, we print the contents of the `inputString` variable which, for this sample case, happens to be `Welcome to 30 Days of Code!`. If you do not print the variable's contents to stdout, you will not pass the hidden test case.

☐ Test against custom input

You have earned 30.00 points!

You are now 1 challenge away from the 1st star for your 30 days of code badge.

50%

1/2

Congratulations

You solved this challenge. Would you like to challenge your friends?



The next challenge in this tutorial will unlock in 13:00:37

[Go to Dashboard](#)[Try a Random Challenge](#)☒ Test case 0☒ Test case 1

Compiler Message

Success

Input (stdin)

[Download](#)

```
1 Welcome to 30 Days of Code!
```

Expected Output

[Download](#)

```
1 Hello, World.  
2 Welcome to 30 Days of Code!
```

C

Submissions

Leaderboard

Discussions

Editorial

Tutorial

support submissions in many popular languages. You can switch languages using the drop-down menu above your editor, and the *inputString* variable may be written differently depending on the best-practice conventions of your submission language.

Input Format
A single line of text denoting *inputString* (the variable whose contents must be printed).

Output Format
Print Hello, World. on the first line, and the contents of *inputString* on the second line.

Sample Input
Welcome to 30 Days of Code!

Sample Output
Hello, World.
Welcome to 30 Days of Code!

Explanation
On the first line, we print the string literal Hello, World.. On the second line, we print the contents of the *inputString* variable which, for this sample case, happens to be Welcome to 30 Days of Code!. If you do not print the variable's contents to stdout, you will not pass the hidden test case.

Change Theme

Language C

Exit Full Screen View

```
1 >#include <stdio.h>...
5
6 int main() {
7     // Declare a variable named
8     // 'input_string' to hold our input.
9     char input_string[105];
10
11    // Read a full line of input from stdin
12    // and save it to our variable, input_string.
13    scanf("%[^\n]", input_string);
14
15    // Print a string literal saying "Hello,
16    // World." to stdout using printf.
17    printf("Hello, World.\n");
18
19    // TODO: Write a line of code here that
20    // prints the contents of input_string to
21    // stdout.
22    printf(input_string);
23    return 0;
24 }
```

Line: 17 Col: 26

Upload Code as File

Run Code

Submit Code

support submissions in many popular languages. You can switch languages using the drop-down menu above your editor, and the `inputString` variable may be written differently depending on the best-practice conventions of your submission language.

Input Format

A single line of text denoting `inputString` (the variable whose contents must be printed).

Output Format

Print `Hello, World.` on the first line, and the contents of `inputString` on the second line.

Sample Input

```
Welcome to 30 Days of Code!
```

Sample Output

```
Hello, World.
Welcome to 30 Days of Code!
```

Explanation

On the first line, we print the string literal `Hello, World.`. On the second line, we print the contents of the `inputString` variable which, for this sample case, happens to be `Welcome to 30 Days of Code!`. If you do not print the variable's contents to stdout, you will not pass the hidden test case.



30

Days of Code

You have earned 30.00 points!

You are now 1 challenge away from the 1st star for your 30 days of code badge.



50%

1/2

Congratulations

You solved this challenge. Would you like to challenge your friends?



The next challenge in this tutorial will unlock in 12:59:17

[Go to Dashboard](#)[Try a Random Challenge](#) **Test case 0** **Test case 1**

Compiler Message

Success

Input (stdin)

[Download](#)

```
1 Welcome to 30 Days of Code!
```

Expected Output

[Download](#)

```
1 Hello, World.
2 Welcome to 30 Days of Code!
```

Java 7

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 0: Hello, World.

Exit Full Screen View

Problem

Submissions

Leaderboard

Discussions

Editorial

Objective

In this challenge, we review some basic concepts that will get you started with this series. You will need to use the same (or similar) syntax to read input and write output in challenges throughout HackerRank. Check out the [Tutorial](#) tab for learning materials and an instructional video!

Task

To complete this challenge, you must save a line of input from stdin to a variable, print `Hello, World.` on a single line, and finally print the value of your variable on a second line.

You've got this!

Note: The instructions are Java-based, but we support submissions in many popular languages. You can switch languages using the drop-down menu above your editor, and the `inputString` variable may be written differently depending on the best-practice conventions of your submission language.

Input Format

A single line of text denoting `inputString` (the variable whose contents must be printed).

Output Format

Print `Hello, World.` on the first line, and the contents of `inputString` on the second line.

Sample Input

Change Theme

Language

Java 7

```
1 > import java.io.*;...
6 public class Solution {
7     public static void main(String[] args) {
8         // Create a Scanner object to read
9         // input from stdin.
10        Scanner scan = new Scanner(System.
11            in);
12
13        // Read a full line of input from
14        // stdin and save it to our variable,
15        // inputString.
16        String inputString = scan.nextLine();
17
18        // Close the scanner object, because
19        // we've finished reading
20        // all of the input from stdin needed
21        // for this challenge.
22        scan.close();
23
24        // Print a string literal saying
25        // "Hello, World." to stdout.
26        System.out.println("Hello, World.");
27
28        // TODO: Write a line of code here
29        // that prints the contents of
30        // inputString to stdout.
31        System.out.println(inputString);
32    }
33 }
```

Line: 23 Col: 3

Upload Code as File

Run Code

Submit Code

Problem

Objective

In this challenge, we review some basic concepts that will get you started with this series. You will need to use the same (or similar) syntax to read input and write output in challenges throughout HackerRank. Check out the [Tutorial](#) tab for learning materials and an instructional video!

Task

To complete this challenge, you must save a line of input from stdin to a variable, print `Hello, World.` on a single line, and finally print the value of your variable on a second line.

You've got this!

Note: The instructions are Java-based, but we support submissions in many popular languages. You can switch languages using the drop-down menu above your editor, and the `inputString` variable may be written differently depending on the best-practice conventions of your submission language.

Input Format

A single line of text denoting `inputString` (the variable whose contents must be printed).

Output Format

Print `Hello, World.` on the first line, and the contents of `inputString` on the second line.

Sample Input

```
Welcome to 30 Days of Code!
```

Submissions

Leaderboard

Discussions

Editorial

Congratulations

You solved this challenge. Would you like to challenge your friends?



The next challenge in this tutorial will unlock in 12:30:05

[Go to Dashboard](#)[Try a Random Challenge](#)

✓ Test case 0

✓ Test case 1

Compiler Message

Success

Input (stdin)

[Download](#)

```
1 Welcome to 30 Days of Code!
```

Expected Output

[Download](#)

```
1 Hello, World.
2 Welcome to 30 Days of Code!
```

JavaScript (Node.js)

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 0: Hello, World.

Exit Full Screen View

Problem

Submissions

Leaderboard

Discussions

Editorial

Objective

In this challenge, we review some basic concepts that will get you started with this series. You will need to use the same (or similar) syntax to read input and write output in challenges throughout HackerRank. Check out the [Tutorial](#) tab for learning materials and an instructional video!

Task

To complete this challenge, you must save a line of input from stdin to a variable, print `Hello, World.` on a single line, and finally print the value of your variable on a second line.

You've got this!

Note: The instructions are Java-based, but we support submissions in many popular languages. You can switch languages using the drop-down menu above your editor, and the `inputString` variable may be written differently depending on the best-practice conventions of your submission language.

Input Format

A single line of text denoting `inputString` (the variable whose contents must be printed).

Output Format

Print `Hello, World.` on the first line, and the contents of `inputString` on the second line.

Sample Input

Welcome to 30 Days of Code!

Change Theme

Language JavaScript (Node.js)

↺ ⋮

```
1 function processData(inputString) {
2     // This line of code prints the first
3     // line of output
4     console.log("Hello, World.");
5
6     // Write the second line of output that
7     // prints the contents of 'inputString' here.
8     console.log(inputString)
9 }
10 > ...
```

Line: 9 Col: 1

⬆ Upload Code as File

Run Code

Submit Code

Problem

Objective

In this challenge, we review some basic concepts that will get you started with this series. You will need to use the same (or similar) syntax to read input and write output in challenges throughout HackerRank. Check out the [Tutorial](#) tab for learning materials and an instructional video!

Task

To complete this challenge, you must save a line of input from `stdin` to a variable, print `Hello, World.` on a single line, and finally print the value of your variable on a second line.

You've got this!

Note: The instructions are Java-based, but we support submissions in many popular languages. You can switch languages using the drop-down menu above your editor, and the `inputString` variable may be written differently depending on the best-practice conventions of your submission language.

Input Format

A single line of text denoting `inputString` (the variable whose contents must be printed).

Output Format

Print `Hello, World.` on the first line, and the contents of `inputString` on the second line.

Sample Input

```
Welcome to 30 Days of Code!
```

Submissions

Leaderboard

Discussions

Editorial

Congratulations

You solved this challenge. Would you like to challenge your friends?



The next challenge in this tutorial will unlock in 12:16:53

[Go to Dashboard](#)[Try a Random Challenge](#)

✓ Test case 0

Compiler Message

✓ Test case 1 Hidden test case

Input (stdin)

[Download](#)

1

```
Welcome to 30 Days of Code!
```

Expected Output

[Download](#)

1

```
Hello, World.
```

2

```
Welcome to 30 Days of Code!
```

COBOL:

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 0: Hello, World.

Exit Full Screen View

Submissions

Leaderboard

Discussions

Editorial

Tutorial

support submissions in many popular languages. You can switch languages using the drop-down menu above your editor, and the *inputString* variable may be written differently depending on the best-practice conventions of your submission language.

Input Format

A single line of text denoting *inputString* (the variable whose contents must be printed).

Output Format

Print `Hello, World.` on the first line, and the contents of *inputString* on the second line.

Sample Input

```
Welcome to 30 Days of Code!
```

Sample Output

```
Hello, World.
Welcome to 30 Days of Code!
```

Explanation

On the first line, we print the string literal `Hello, World.`. On the second line, we print the contents of the *inputString* variable which, for this sample case, happens to be `Welcome to 30 Days of Code!`. If you do not print the variable's contents to stdout, you will not pass the hidden test case.

Change Theme

Language COBOL

↺ ⋮

```
1 IDENTIFICATION DIVISION.
2 PROGRAM-ID. SOLUTION.
3 ENVIRONMENT DIVISION.
4 INPUT-OUTPUT SECTION.
5 FILE-CONTROL.
6 SELECT SYSIN ASSIGN TO KEYBOARD ORGANIZATION
  LINE SEQUENTIAL.
7
8 DATA DIVISION.
9 FILE SECTION.
10 FD SYSIN.
11 01 INPUT-STRING PIC X(255). *> This
   variable will hold a line of input from
   stdin.
12 88 EOF VALUE HIGH-VALUES.
13
14 PROCEDURE DIVISION.
15 OPEN INPUT SYSIN
16 READ SYSIN
17 AT END SET EOF TO TRUE
18 END-READ
19 DISPLAY "Hello, World.".
20
21 *> Write your code here to print the
   contents of the variable to stdout.
22 DISPLAY INPUT-STRING.
23 CLOSE SYSIN.
24
25 STOP RUN.
```

Line: 22 Col: 26

⬆ Upload Code as File

Run Code

Submit Code

support submissions in many popular languages. You can switch languages using the drop-down menu above your editor, and the `inputString` variable may be written differently depending on the best-practice conventions of your submission language.

Input Format

A single line of text denoting `inputString` (the variable whose contents must be printed).

Output Format

Print `Hello, World.` on the first line, and the contents of `inputString` on the second line.

Sample Input

```
Welcome to 30 Days of Code!
```

Sample Output

```
Hello, World.
Welcome to 30 Days of Code!
```

Explanation

On the first line, we print the string literal `Hello, World.`. On the second line, we print the contents of the `inputString` variable which, for this sample case, happens to be `Welcome to 30 Days of Code!`. If you do not print the variable's contents to `stdout`, you will not pass the hidden test case.

[Upload Code as File](#)[Run Code](#)[Submit Code](#)☐ Test against custom input

Congratulations

You solved this challenge. Would you like to challenge your friends?



The next challenge in this tutorial will unlock in 11:48:37

[Go to Dashboard](#)[Try a Random Challenge](#)

✓ Test case 0

✓ Test case 1

Compiler Message

Success

Input (stdin)

[Download](#)

```
1 Welcome to 30 Days of Code!
```

Expected Output

[Download](#)

```
1 Hello, World.
2 Welcome to 30 Days of Code!
```

Scala:

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 0: Hello, World.

Exit Full Screen View

Submissions

Leaderboard

Discussions

Editorial

Tutorial

support submissions in many popular languages. You can switch languages using the drop-down menu above your editor, and the *inputString* variable may be written differently depending on the best-practice conventions of your submission language.

Input Format

A single line of text denoting *inputString* (the variable whose contents must be printed).

Output Format

Print `Hello, World.` on the first line, and the contents of *inputString* on the second line.

Sample Input

```
Welcome to 30 Days of Code!
```

Sample Output

```
Hello, World.
Welcome to 30 Days of Code!
```

Explanation

On the first line, we print the string literal `Hello, World.`. On the second line, we print the contents of the *inputString* variable which, for this sample case, happens to be `Welcome to 30 Days of Code!`. If you do not print the variable's contents to stdout, you will not pass the hidden test case.

Change Theme

Language Scala

↺ ⋮

```
1 object Solution {
2   def main(args: Array[String]) {
3     // Print "Hello, World."
4     println("Hello, World.")
5
6     // Read a string variable
7     val s = scala.io.StdIn.readLine()
8
9     // Print the value of the string
10    variable
11    println(s)
12  }
13 }
```

Line: 10 Col: 18

Upload Code as File

Run Code

Submit Code

support submissions in many popular languages. You can switch languages using the drop-down menu above your editor, and the `inputString` variable may be written differently depending on the best-practice conventions of your submission language.

Input Format

A single line of text denoting `inputString` (the variable whose contents must be printed).

Output Format

Print `Hello, World.` on the first line, and the contents of `inputString` on the second line.

Sample Input

```
Welcome to 30 Days of Code!
```

Sample Output

```
Hello, World.
Welcome to 30 Days of Code!
```

Explanation

On the first line, we print the string literal `Hello, World.`. On the second line, we print the contents of the `inputString` variable which, for this sample case, happens to be `Welcome to 30 Days of Code!`. If you do not print the variable's contents to `stdout`, you will not pass the hidden test case.

[Upload Code as File](#)[Run Code](#)[Submit Code](#)☐ Test against custom input

Congratulations

You solved this challenge. Would you like to challenge your friends?



The next challenge in this tutorial will unlock in 11:42:01

[Go to Dashboard](#)[Try a Random Challenge](#)

✓ Test case 0

✓ Test case 1

Compiler Message

Success

Input (stdin)

[Download](#)

```
1 Welcome to 30 Days of Code!
```

Expected Output

[Download](#)

```
1 Hello, World.
2 Welcome to 30 Days of Code!
```

BASH:

Submissions

Leaderboard

Discussions

Editorial

Tutorial

HackerRank

[Prepare](#) > [Tutorials](#) > [30 Days of Code](#) > [Day 0: Hello, World.](#)

Exit Full Screen View

support submissions in many popular languages. You can switch languages using the drop-down menu above your editor, and the *inputString* variable may be written differently depending on the best-practice conventions of your submission language.

Input Format

A single line of text denoting *inputString* (the variable whose contents must be printed).

Output Format

Print `Hello, World.` on the first line, and the contents of *inputString* on the second line.

Sample Input

```
Welcome to 30 Days of Code!
```

Sample Output

```
Hello, World.
Welcome to 30 Days of Code!
```

Explanation

On the first line, we print the string literal `Hello, World.`. On the second line, we print the contents of the *inputString* variable which, for this sample case, happens to be `Welcome to 30 Days of Code!`. If you do not print the variable's contents to stdout, you will not pass the hidden test case.

Change Theme

Language

BASH





```
1 read inputString # get a line of input from
2   stdin and save it to our variable
3
4 # Your first line of output goes here
5 echo 'Hello, World.'
6
7 # Write the second line of output
8 echo $inputString
```

Line: 7 Col: 18

Upload Code as File

Run Code

Submit Code

support submissions in many popular languages. You can switch languages using the drop-down menu above your editor, and the *inputString* variable may be written differently depending on the best-practice conventions of your submission language.

Input Format

A single line of text denoting *inputString* (the variable whose contents must be printed).

Output Format

Print `Hello, World.` on the first line, and the contents of *inputString* on the second line.

Sample Input

```
Welcome to 30 Days of Code!
```

Sample Output

```
Hello, World.  
Welcome to 30 Days of Code!
```

Explanation

On the first line, we print the string literal `Hello, World.`. On the second line, we print the contents of the *inputString* variable which, for this sample case, happens to be `Welcome to 30 Days of Code!`. If you do not print the variable's contents to stdout, you will not pass the hidden test case.

[Upload Code as File](#)[Run Code](#)[Submit Code](#)☐ Test against custom input

Congratulations

You solved this challenge. Would you like to challenge your friends?



The next challenge in this tutorial will unlock in 11:38:54

[Go to Dashboard](#)[Try a Random Challenge](#)

✓ Test case 0

✓ Test case 1

Compiler Message

Success

Input (stdin)

[Download](#)

```
1 Welcome to 30 Days of Code!
```

Expected Output

[Download](#)

```
1 Hello, World.  
2 Welcome to 30 Days of Code!
```

Perl:

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 0: Hello, World.

Exit Full Screen View

Submissions

Leaderboard

Discussions

Editorial

Tutorial

support submissions in many popular languages. You can switch languages using the drop-down menu above your editor, and the *inputString* variable may be written differently depending on the best-practice conventions of your submission language.

Input Format

A single line of text denoting *inputString* (the variable whose contents must be printed).

Output Format

Print `Hello, World.` on the first line, and the contents of *inputString* on the second line.

Sample Input

```
Welcome to 30 Days of Code!
```

Sample Output

```
Hello, World.
Welcome to 30 Days of Code!
```

Explanation

On the first line, we print the string literal `Hello, World.` On the second line, we print the contents of the *inputString* variable which, for this sample case, happens to be `Welcome to 30 Days of Code!`. If you do not print the variable's contents to stdout, you will not pass the hidden test case.

Change Theme

Language Perl

⌂

⋮

```
1 my $inputString = <STDIN>; # get a line of
2   input from stdin and save it to our variable
3
4 # Your first line of output goes here
5   print "Hello, World.\n";
6
7 # Write the second line of output
8   print $inputString;
```

Line: 7 Col: 20

⬇ Upload Code as File

Run Code

Submit Code

support submissions in many popular languages. You can switch languages using the drop-down menu above your editor, and the `inputString` variable may be written differently depending on the best-practice conventions of your submission language.

Input Format

A single line of text denoting `inputString` (the variable whose contents must be printed).

Output Format

Print `Hello, World.` on the first line, and the contents of `inputString` on the second line.

Sample Input

```
Welcome to 30 Days of Code!
```

Sample Output

```
Hello, World.
Welcome to 30 Days of Code!
```

Explanation

On the first line, we print the string literal `Hello, World.` On the second line, we print the contents of the `inputString` variable which, for this sample case, happens to be `Welcome to 30 Days of Code!`. If you do not print the variable's contents to stdout, you will not pass the hidden test case.

Line: 7 Col: 20

[Upload Code as File](#)[Run Code](#)[Submit Code](#)☐ Test against custom input

Congratulations

You solved this challenge. Would you like to challenge your friends?



The next challenge in this tutorial will unlock in 11:37:48

[Go to Dashboard](#)[Try a Random Challenge](#) **Test case 0** **Test case 1**

Compiler Message

Success

Input (stdin)

[Download](#)

```
1 Welcome to 30 Days of Code!
```

Expected Output

[Download](#)

```
1 Hello, World.
2 Welcome to 30 Days of Code!
```