

Presentación:

Nombre:

Algelis Severino

Tema:

Introducción a la Programación y Diagrama de flujo.

Tecnico:

Ciberseguridad Semipresencial

Facilitador:

Kevin Feliz Henriquez

Centro:

Diapiato Pro salud

Descripción:

En este documento .pdf adjunto capturas del reto 11 de 30 days of code de HackerRank.

Link GitHub:

<https://github.com/SeverinoCyber/30-days-of-code/tree/main/Hackerrank/day14>

Python3:

Problem

Submissions

Leaderboard

Discussions

Editorial

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 14: Scope

Objective

Today we're discussing scope. Check out the [Tutorial](#) tab for learning materials and an instructional video!

The absolute difference between two integers, a and b , is written as $|a - b|$. The maximum absolute difference between two integers in a set of positive integers, *elements*, is the largest absolute difference between any two integers in *__elements*.

The Difference class is started for you in the editor. It has a private integer array (*elements*) for storing N non-negative integers, and a public integer (*maximumDifference*) for storing the maximum absolute difference.

Task

Complete the Difference class by writing the following:

- A class constructor that takes an array of integers as a parameter and saves it to the *__elements* instance variable.
- A *computeDifference* method that finds the maximum absolute difference between any 2 numbers in *__elements* and stores it in the *maximumDifference* instance variable.

Input Format

You are not responsible for reading any input from stdin. The locked Solution class in the editor reads in 2 lines of input. The first line contains N , the size of the elements array. The second line has N space-separated integers that describe the *__elements* array.

Constraints

- $1 \leq N \leq 10$
- $1 \leq \text{__elements}[i] \leq 100$, where $0 \leq i \leq N - 1$

Output Format

You are not responsible for printing any output; the Solution class will print the value of the *maximumDifference* instance variable.

Sample Input

STDIN	Function
3	<i>__elements</i> [] size N = 3
1 2 5	<i>__elements</i> = [1, 2, 5]

Change Theme

Language Python 3

Exit Full Screen View

```
1 > class Difference:
2
3     # Add your code here
4     def computeDifference(self):
5         self.maximumDifference = max(self.__elements) - min(self.__elements)
6
7
8
9
10
11 > # End of Difference class
```

Line: 11 Col: 26

Upload Code as File

Test against custom input

Run Code

Submit Code

Problem

Submissions

Leaderboard

Discussions

Editorial

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 14: Scope

Objective

Today we're discussing scope. Check out the [Tutorial](#) tab for learning materials and an instructional video!

The absolute difference between two integers, a and b , is written as $|a - b|$. The maximum absolute difference between two integers in a set of positive integers, *elements*, is the largest absolute difference between any two integers in *__elements*.

The Difference class is started for you in the editor. It has a private integer array (*elements*) for storing N non-negative integers, and a public integer (*maximumDifference*) for storing the maximum absolute difference.

Task

Complete the Difference class by writing the following:

- A class constructor that takes an array of integers as a parameter and saves it to the *__elements* instance variable.
- A *computeDifference* method that finds the maximum absolute difference between any 2 numbers in *__elements* and stores it in the *maximumDifference* instance variable.

Input Format

You are not responsible for reading any input from stdin. The locked Solution class in the editor reads in 2 lines of input. The first line contains N , the size of the elements array. The second line has N space-separated integers that describe the *__elements* array.

Constraints

- $1 \leq N \leq 10$
- $1 \leq \text{__elements}[i] \leq 100$, where $0 \leq i \leq N - 1$

Output Format

You are not responsible for printing any output; the Solution class will print the value of the *maximumDifference* instance variable.

Sample Input

STDIN	Function
3	<i>__elements</i> [] size N = 3
1 2 5	<i>__elements</i> = [1, 2, 5]

Exit Full Screen View

Line: 11 Col: 26

Upload Code as File

Test against custom input

Run Code

Submit Code

Test case 0

Compiler Message

Success

Test case 1

Input (stdin)

Download

1 3

2 1 2 5

Test case 2

Expected Output

Download

1 4

Test case 3

Test case 4

Test case 5

Test case 6

C#:

Problem

Submissions

Leaderboard

Discussions

Editorial

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 14: Scope

Objective

Today we're discussing scope. Check out the [Tutorial](#) tab for learning materials and an instructional video!

The absolute difference between two integers, a and b , is written as $|a - b|$. The maximum absolute difference between two integers in a set of positive integers, *elements*, is the largest absolute difference between any two integers in *__elements*.

The Difference class is started for you in the editor. It has a private integer array (*elements*) for storing N non-negative integers, and a public integer (*maximumDifference*) for storing the maximum absolute difference.

Task

Complete the Difference class by writing the following:

- A class constructor that takes an array of integers as a parameter and saves it to the *__elements* instance variable.
- A computeDifference method that finds the maximum absolute difference between any 2 numbers in *__elements* and stores it in the *maximumDifference* instance variable.

Input Format

You are not responsible for reading any input from stdin. The locked Solution class in the editor reads in 2 lines of input. The first line contains N , the size of the elements array. The second line has N space-separated integers that describe the *__elements* array.

Constraints

- $1 \leq N \leq 10$
- $1 \leq \text{__elements}[i] \leq 100$, where $0 \leq i \leq N - 1$

Output Format

You are not responsible for printing any output; the Solution class will print the value of the *maximumDifference* instance variable.

Sample Input

STDIN	Function
3	__elements[] size N = 3
1 2 5	__elements = [1, 2, 5]

Change Theme

Language C#

Exit Full Screen View

```
1 > using System;
2
3 // Add your code here
4 public Difference(int[] elements)
5 {
6     this.elements = elements;
7 }
8
9 public void computeDifference() {
10     int min = elements[0];
11     int max = elements[0];
12
13     foreach (int num in elements)
14     {
15         if (num < min) min = num;
16         if (num > max) max = num;
17     }
18
19     maximumDifference = Math.Abs(max - min);
20 }
21
22 // End of Difference Class
```

Line: 28 Col: 29

Upload Codes File

Test against custom input

Run Code

Submit Code

Problem

Submissions

Leaderboard

Discussions

Editorial

HackerRank

Prepare > Tutorials > 30 Days of Code > Day 14: Scope

Objective

Today we're discussing scope. Check out the [Tutorial](#) tab for learning materials and an instructional video!

The absolute difference between two integers, a and b , is written as $|a - b|$. The maximum absolute difference between two integers in a set of positive integers, *elements*, is the largest absolute difference between any two integers in *__elements*.

The Difference class is started for you in the editor. It has a private integer array (*elements*) for storing N non-negative integers, and a public integer (*maximumDifference*) for storing the maximum absolute difference.

Task

Complete the Difference class by writing the following:

- A class constructor that takes an array of integers as a parameter and saves it to the *__elements* instance variable.
- A computeDifference method that finds the maximum absolute difference between any 2 numbers in *__elements* and stores it in the *maximumDifference* instance variable.

Input Format

You are not responsible for reading any input from stdin. The locked Solution class in the editor reads in 2 lines of input. The first line contains N , the size of the elements array. The second line has N space-separated integers that describe the *__elements* array.

Constraints

- $1 \leq N \leq 10$
- $1 \leq \text{__elements}[i] \leq 100$, where $0 \leq i \leq N - 1$

Output Format

You are not responsible for printing any output; the Solution class will print the value of the *maximumDifference* instance variable.

Sample Input

STDIN	Function
3	__elements[] size N = 3
1 2 5	__elements = [1, 2, 5]

Upload Codes File

Test against custom input

Run Code

Submit Code

Congratulations

You solved this challenge. Would you like to challenge your friends? [f](#) [t](#) [in](#)

The next challenge in this tutorial will unlock in 09:08:20

Go to Dashboard

Try a Random Challenge

Test case 0

Test case 1

Test case 2

Test case 3

Test case 4

Test case 5

Test case 6

Compiler Message

Success

Input (stdin)

Download

1 3

2 1 2 5

Expected Output

Download

1 4

