



Operations with `for` Loop



Operations with the **for** Loop_(review)

- ▶ In the following example, you'll get a **number** from the user and *print a sentence* the *number of times* we take from the user :

```
1 times = int(input("How many times should I say 'I love you'"))
2
3 for i in range(times):
4     print('I love you')
5
```



Operations with the for Loop_(review)

- ▶ In the following example, you'll get a number from the user and print a sentence the number of times we receive from the user :

```
1 times = int(input("How many times should I say 'I love you'"))  
2  
3 for i in range(times):  
4     print('I love you')  
5
```

Let's say the user enters **3**.

```
1 I love you  
2 I love you  
3 I love you  
4
```



Operations with the for Loop

- ▶ **Task :** This time, write a code block that asks the user a number between 1 and 10 then puts that number into the multiplication table.
- ▶ For example, the output for 5 should be as follows :

```
5x0 = 0
5x1 = 5
5x2 = 10
5x3 = 15
5x4 = 20
5x5 = 25
5x6 = 30
5x7 = 35
5x8 = 40
5x9 = 45
5x10 = 50
```



Working with the Iterators

- **The output can be like :**

```
1  nmbr = int(input('enter a number between 1-10'))
2
3  for i in range(11):
4      print('{}x{} = {}'.format(nmbr, i), nmbr * i)
5
```



Operations with the for Loop_(review)

- ▶ Let's take a close look at the `range()` function.
 - ▷ As we stated before, the formula syntax of the `range()` function is:

```
range(start, stop, step)
```



parameters



Operations with the for Loop_(review)



► (... continued)

► Consider this example :

```
1 b = list(range(11))
2
3 print(b)
4
```



Operations with the for Loop_(review)

- ▶ Let's take a close look at the `range()` function.
 - ▷ It creates an iterable sequence of numbers. And it can be simply converted into the `list`, `set`, and `tuple`.
 - ▷ Consider this example :

```
1 b = list(range(11))
2
3 print(b)
4
```

```
1 [0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10]
2
```




Operations with the for Loop_(review)



- ▶ (... continued)
 - ▷ Here's the other examples :

```
1 a = set(range(0,10))  
2  
3 print(a)  
4
```



Operations with the for Loop_(review)



- ▶ (... continued)
 - ▷ Here's the other examples :

```
1 a = set(range(0,10))  
2  
3 print(a)  
4
```

```
1 {0, 1, 2, 3, 4, 5, 6, 7, 8, 9}  
2
```



Operations with the for Loop_(review)



- ▶ (... continued)
 - ▷ Here's the other examples :

```
1 a = set(range(0,10))
2
3 print(a)
4
```

```
1 {0, 1, 2, 3, 4, 5, 6, 7, 8, 9}
2
```

```
1 c = tuple(range(11))
2
3 print(c)
4
```



Operations with the for Loop_(review)



- ▶ (... continued)
 - ▷ Here's the other examples :

```
1 a = set(range(0,10))  
2  
3 print(a)  
4
```

```
1 {0, 1, 2, 3, 4, 5, 6, 7, 8, 9}  
2
```

```
1 c = tuple(range(11))  
2  
3 print(c)  
4
```

```
1 (0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10)  
2
```



Operations with the for Loop_(review)



- ▶ An asterisk 📎 * separates the elements of the iterables.
 - ▷ Let's take a look at an example of the `range()` function with starred 📎 * expression :


```
1 print(range(5)) # it will not print the numbers in sequence
2
3 print(*range(5)) # '*' separates its elements
4
```

What is the output? Try to figure out in your mind...



Operations with the for Loop_(review)



- ▶ (... continued)
 - ▷ Let's take a look at an example of the `range()` function with starred  `*` expression :

```
1 print(range(5)) # it will not print the numbers in sequence
2
3 print(*range(5)) # '*' separates its elements
4
```

```
1 range(0, 5)
2 0 1 2 3 4
3
```



Operations with the for Loop_(review)



- ▶ (... continued)
 - ▷ Here's another example of the `range()` function with starred 📎 `*` expression :

```
1 print(*range(5,25,2))  
2
```

What is the output? Try to figure out in your mind...



Operations with the for Loop_(review)



- ▶ (... continued)
 - ▷ Here's another example of the `range()` function with starred 📎 `*` expression :

```
1 print(*range(5,25,2))  
2
```

```
1 5 7 9 11 13 15 17 19 21 23  
2
```




Operations with the for Loop_(review)



- ▶ (... continued)
 - ▷ Starred 📌 * expression can also be used to separate the other iterable objects. Such as **str**:

```
1 print(*('separate'))  
2
```



Operations with the for Loop_(review)



- ▶ (... continued)
 - ▷ Starred 📎 * expression can also be used to separate the other iterable objects. Such as **str**:

```
1 print(*('separate'))  
2
```

```
1 s e p a r a t e  
2
```



Operations with the for Loop_(review)

- ▶ (... continued)
 - ▷ You can create reverse sequence numbers using a negative **step**.

```
1 print(*range(10,0,-2))  
2
```

What is the output? Try to figure out in your mind...



Operations with the for Loop_(review)



- ▶ (... continued)
 - ▷ You can create reverse sequence numbers using a negative **step**.

```
1 print(*range(10,0,-2))  
2
```

```
1 10 8 6 4 2  
2
```



Operations with the `for` Loop_(review)



- ▶ Multiple variables in `for` loop.
 - ▷ Examine this example carefully :

```
zip(iterator1, iterator2, ...)
```

```
1 text = ['one', 'two', 'three', 'four', 'five']
2 numbers = [1, 2, 3, 4, 5]
3 for x, y in zip(text, numbers):
4     print(x, ': ', y)
5
```

Use your IDEs

Operations with the for Loop (review)




💡 Tips :

- `zip()` function make an iterator that aggregates elements from each of the iterables.

```
1 text = ['one', 'two', 'three', 'four', 'five']
2 numbers = [1, 2, 3, 4, 5]
3 for x, y in zip(text, numbers):
4     print(x, ': ', y)
5
```

```
1 one : 1
2 two : 2
3 three : 3
4 four : 4
5 five : 5
6
```





Operations with the for Loop



- ▶ **Task : Python Program to collect the odd and even numbers in two different lists.**
 - ▷ Write a program to choose and collect the even and odd numbers (1 to 10) in two different **list**.
 - ▷ Print the result such as :

```
evens: [0, 2, 4, 6, 8]
```

```
odds : [1, 3, 5, 7, 9]
```



Operations with the for Loop

- The code might be like :

```
1 evens = []
2 odds = []
3
4 for n in range(10):
5     if n % 2 == 0:
6         evens.append(n)
7     else:
8         odds.append(n)
9
10 print(evens)
11 print(odds)
```

Output

```
[0, 2, 4, 6, 8]
[1, 3, 5, 7, 9]
```




Operations with the for Loop



- ▶ **Task : Python Program to sum the amount of odd and even numbers in a tuple/list.**
 - ▷ Write a code that counts the odd and even numbers in a given **list** or **tuple**.
 - ▷ Print the result such as :

```
example list: [11, 2, 24, 61, 48, 33, 3]
```

```
example output : The number of even numbers : 3
```

```
                  The number of odd numbers : 4
```



Operations with the for Loop

- The code might be like :

```
1 numbers = (11, 36, 33, 66, 89, 21, 32, 16, 10)
2 odds = 0
3 evens = 0
4 for i in numbers:
5     if not i % 2:
6         evens+=1
7     else:
8         odds+=1
9 print("The number of even numbers :", evens)
10 print("The number of odd numbers :", odds)
11
```

Output

```
The number of even numbers : 5
The number of odd numbers  : 4
```



Operations with the for Loop

- ▶ **Task : Python Program to print out the numbers.**
 - ▶ Using the **for** loop, print the numbers from **1** to **9** as many as it is and get the following output.

```
1
22
333
4444
55555
666666
7777777
88888888
999999999
```



Operations with the for Loop

- ▶ **The code might be like :**

```
1 for i in range(1, 10):  
2     print(str(i) * i)  
3
```



Operations with the for Loop



- ▶ **Task** : Python Program to sum of the numbers from **1** to **74**
 - ▶ Get the output of **2775** as a sum of the numbers between **1** - **74** (including).
 - ▶ Use **for** loop to make this calculation.



Operations with the for Loop

- The code might be like :

```
1 sum_num=0
2
3 for i in range(1, 75):
4     sum_num += i
5
6 print(sum_num)
7
```



Nested **for** Loop



▶ Nested for Loop (review)

- ▶ Simple structure of the nested `for` loops look like :

```
for variable1 in iterable1:  
    for variable2 in iterable2:  
        body
```




▶ Nested for Loop (review)

- ▶ Consider this example of the nested for loop :

```
1 who = ['I am ', 'You are ']  
2 mood = ['happy', 'confident']  
3 for i in who:  
4     for ii in mood:  
5         print(i + ii)  
6
```



Nested for Loop

- Consider this example of the nested for loop :

```
1 who = ['I am ', 'You are ']  
2 mood = ['happy', 'confident']  
3 for i in who:  
4     for ii in mood:  
5         print(i + ii)  
6
```


First *outer* **then**
inner loop runs.

```
1 I am happy  
2 I am confident  
3 You are happy  
4 You are confident  
5
```



Nested for Loop (review)

- ▶ You can follow the animated diagram of this nested `for` loop for a better understanding.





Nested for Loop

- ▶ **Task** : Concatenation string elements from two separate lists.
 - ▷ Write a code that takes string elements one by one and prints a sentence using nested **for** loops :
 - ▷ The given lists and sample outputs are :

```
names = ["susan", "tom", "edward"]  
mood = ["happy", "sad"]  
example output : susan is happy  
                  susan is sad  
                  tom is happy  
                  .  
                  .
```



Nested for Loop

- ▶ The code might be like :

```
1 names = ["susan", "tom", "edward"]
2 mood = ["happy", "sad"]
3
4 for i in names:
5     for ii in mood:
6         print(i + " is " + ii)
7
```

Output

```
susan is happy
susan is sad
tom is happy
tom is sad
edward is happy
edward is sad
```