

Minicourse on *information, complexity and organisation in
multidimensional symbolic dynamics*

On the limit between the computable and the uncomputable


Silvere Gangloff

April 16, 2021

sgangloff@agh.edu.pl ; silvere.gangloff@gmx.com


Multidimensional SFT: a computational 'transition':

Reminder (third lecture):




Uncomputability in quantum physics:

Energy states:




Uncomputability in quantum physics:

Energy states:




Uncomputability in quantum physics:

Energy states:



Uncomputability in quantum physics:


Energy states:



Cubitt, Perez-Garcia, Wolf(2015): *The spectral gap problem is undecidable.*

Uncomputability in quantum physics:

Energy states:




Cubitt, Perez-Garcia, Wolf(2015): *The spectral gap problem is undecidable.*

Kreinovich(2017): *Why Some Physicists Are Excited About the Undecidability of the Spectral Gap Problem and Why Should We*


Uncomputability in quantum physics: Exactly solvable models

Square ice model [Pauling(1935)]:



Uncomputability in quantum physics: Exactly solvable models


Square ice model [Pauling(1935)]:



Lieb(1967): The entropy of square ice is $\frac{3}{2} \log(4/3)$ (incomplete proof).

Uncomputability in quantum physics: Exactly solvable models

Square ice model [Pauling(1935)]:




Lieb(1967): The entropy of square ice is $\frac{3}{2} \log(4/3)$ (incomplete proof).

!! Bidimensional SFT have uncomputable entropy in general!

Uncomputability in quantum physics: Exactly solvable models

Square ice model [Pauling(1935)]:




Lieb(1967): The entropy of square ice is $\frac{3}{2} \log(4/3)$ (incomplete proof).

!! Bidimensional SFT have uncomputable entropy in general!

Uncomputability in quantum physics: Exactly solvable models

Square ice model [Pauling(1935)]:



Lieb(1967): The entropy of square ice is $\frac{3}{2} \log(4/3)$ (incomplete proof).

!! Bidimensional SFT have uncomputable entropy in general!

Questions:

1. When does uncomputability phenomena appear in the classes of models considered ?

Questions:

1. When does uncomputability phenomena appear in the classes of models considered ?
2. How does 'organisation' emerge from simple interactions between elements of matter ?



Questions:

1. When does uncomputability phenomena appear in the classes of models considered ?
2. How does 'organisation' emerge from simple interactions between elements of matter ?
3. Are the models for which uncomputability occur physically significant ? Can we formulate a restriction which ensures computability ?

Computability of (topological) entropy:

Milnor (2002): is the *entropy* of a dynamical system effectively computable ?

Computable




[Jeandel 2014]

Expansive


[D'amico Manzini Margara 2003]



Uncomputable



[Koiran 2001]




[Delvenne Blondel 2004]

Non constraint

[Hurd Kari Culik 1992]

Computability of (topological) entropy:

Milnor (2002): is the *entropy* of a dynamical system effectively computable ?



Reminders:

Alphabet \mathcal{A} finite. **Patterns:** $(d=1)$ elements of $\mathcal{A}^{\mathbb{U}}$, $\mathbb{U} \subset \mathbb{Z}$.

Subshifts $(d=1)$: set of patterns \mathcal{F} .

$$X_{\mathcal{F}} = \{x \in \mathcal{A}^{\mathbb{Z}} : \forall \mathbb{U} \subset \mathbb{Z}, x|_{\mathbb{U}} \notin \mathcal{F}\}.$$

For every subshift X on alphabet \mathcal{A} there exists \mathcal{F} s.t. $X = X_{\mathcal{F}}$.

When \mathcal{F} finite : of finite type; when \mathcal{F} recursively enumerable (set of outputs of a computing machine): effective.

Reminders:

Language: $\mathcal{L}(X)$: set of patterns which appear in some $x \in X$.

Entropy(d=1): $N_n(X)$: number of words $w \in \mathcal{L}(X)$, $|w| = n$.


$$h(X) = \lim_{n \rightarrow +\infty} \frac{\log_2(N_n(X))}{n} = \inf_{\text{Th}} \lim_{n \rightarrow +\infty} \frac{\log_2(N_n(X))}{n}$$

Π_1 -computable: $x \in \mathbb{R}$: exists an algorithm $n \mapsto r_n$ with $r_n \downarrow x$.

Lemma: when X is effective, $h(X)$ is Π_1 -computable.

Reminders:

f -block gluing:



When $d = 1$: square patterns \rightarrow words.

Decidable subshifts: characterization of a threshold

Decidable:


Decidable subshifts: characterization of a threshold

Decidable:

Algorithm


Decidable subshifts: characterization of a threshold

Decidable:




Decidable subshifts: characterization of a threshold

Decidable:




Decidable subshifts: characterization of a threshold

Decidable:




Decidable subshifts: characterization of a threshold

Decidable:



Decidable subshifts: characterization of a threshold


Decidable:



Assume $\Sigma(f) \stackrel{\text{Def}}{=} \sum_n \frac{f(k)}{k^2}$ computable.

Decidable subshifts: characterization of a threshold

Decidable:




Assume $\Sigma(f) \stackrel{\text{Def}}{=} \sum_n \frac{f(k)}{k^2}$ computable.

Theorem[G., Hellouin (2018)]:


Decidable subshifts: characterization of a threshold

Decidable:




Assume $\Sigma(f) \stackrel{\text{Def}}{=} \sum_n \frac{f(k)}{k^2}$ computable.

Theorem[G., Hellouin (2018)]:



Decidable subshifts: characterization of a threshold

Decidable:




Assume $\Sigma(f) \stackrel{\text{Def}}{=} \sum_n \frac{f(k)}{k^2}$ computable.

Theorem[G., Hellouin (2018)]:

$$\Sigma(f) < +\infty \quad \begin{array}{c} \log(k) \qquad k(\log(k))^{-\alpha} \\ \text{---} \bullet \text{---} \bullet \text{---} \bullet \text{---} | \text{---} \bullet \text{---} \bullet \text{---} \\ K \qquad k^\beta \log(k) \qquad k \end{array}$$

Decidable subshifts: characterization of a threshold

Decidable:




Assume $\Sigma(f) \stackrel{\text{Def}}{=} \sum_n \frac{f(k)}{k^2}$ computable.

Theorem[G., Hellouin (2018)]:

$$\Sigma(f) < +\infty \quad \text{---} \quad \begin{array}{c} \log(k) \\ \bullet \\ K \end{array} \quad \begin{array}{c} \bullet \\ k^\beta \log(k) \end{array} \quad \begin{array}{c} \bullet \\ k(\log(k))^{-\alpha} \end{array} \quad \begin{array}{c} \bullet \\ k \end{array} \quad \text{---} \quad \Sigma(f) = +\infty$$


Decidable subshifts: characterization of a threshold

Decidable:




Assume $\Sigma(f) \stackrel{\text{Def}}{=} \sum_n \frac{f(k)}{k^2}$ computable.

Theorem[G., Hellouin (2018)]:




Set of entropies, f -block
gluing decidable subshifts




Decidable subshifts: characterization of a threshold

Decidable:




Assume $\Sigma(f) \stackrel{\text{Def}}{=} \sum_n \frac{f(k)}{k^2}$ computable.

Theorem[G., Hellouin (2018)]:




Set of entropies, f -block
gluing decidable subshifts




Decidable subshifts: characterization of a threshold

Decidable:




Assume $\Sigma(f) \stackrel{\text{Def}}{=} \sum_n \frac{f(k)}{k^2}$ computable.

Theorem[G., Hellouin (2018)]:




Set of entropies, f -block
gluing decidable subshifts



Π_1


Below the threshold : $\Sigma(f) < +\infty \Rightarrow h$ computable

f -block gluing: $N_k(X)^2 \leq N_{2k+f(k)}(X) \leq |\mathcal{A}|^{f(k)} \cdot N_{2k}(X)$




Below the threshold : $\Sigma(f) < +\infty \Rightarrow h$ computable

f -block gluing: $N_k(X)^2 \leq N_{2k+f(k)}(X) \leq |\mathcal{A}|^{f(k)} \cdot N_{2k}(X)$




Below the threshold : $\Sigma(f) < +\infty \Rightarrow h$ computable

f -block gluing: $N_k(X)^2 \leq N_{2k+f(k)}(X) \leq |\mathcal{A}|^{f(k)} \cdot N_{2k}(X)$




Below the threshold : $\Sigma(f) < +\infty \Rightarrow h$ computable

f -block gluing: $N_k(X)^2 \leq N_{2k+f(k)}(X) \leq |\mathcal{A}|^{f(k)} \cdot N_{2k}(X)$




Below the threshold : $\Sigma(f) < +\infty \Rightarrow h$ computable

f -block gluing: $N_k(X)^2 \leq N_{2k+f(k)}(X) \leq |\mathcal{A}|^{f(k)} \cdot N_{2k}(X)$




Below the threshold : $\Sigma(f) < +\infty \Rightarrow h$ computable

f -block gluing: $N_k(X)^2 \leq N_{2k+f(k)}(X) \leq |\mathcal{A}|^{f(k)} \cdot N_{2k}(X)$



Below the threshold : $\Sigma(f) < +\infty \Rightarrow h$ computable


f -block gluing: $N_k(X)^2 \leq N_{2k+f(k)}(X) \leq |\mathcal{A}|^{f(k)} \cdot N_{2k}(X)$



$$\frac{\log(N_k(X))}{k} - |\mathcal{A}| \cdot \sum_k^{+\infty} \frac{f(2^l)}{2^l} \leq h \leq \frac{\log(N_k(X))}{k}$$

Below the threshold : $\Sigma(f) < +\infty \Rightarrow h$ computable

f -block gluing: $N_k(X)^2 \leq N_{2k+f(k)}(X) \leq |\mathcal{A}|^{f(k)} \cdot N_{2k}(X)$



$$\frac{\log(N_k(X))}{k} - |\mathcal{A}| \cdot \sum_k^{+\infty} \frac{f(2^l)}{2^l} \leq h \leq \frac{\log(N_k(X))}{k}$$

Since X is decidable, $k \mapsto N_k(X)$ is computable, hence h is computable.

Above the threshold I. Objects: $\Sigma(f) = +\infty$

Known: obstruction \rightarrow let us prove realization

Above the threshold I. Objects: $\Sigma(f) = +\infty$

Known: obstruction \rightarrow let us prove realization

Bounded density shifts.

Above the threshold I. Objects: $\Sigma(f) = +\infty$

Known: obstruction \rightarrow let us prove realization

Bounded density shifts. Consider $(p_k)_k \in \mathbb{N}^{\mathbb{N}}$ non-decreasing and computable.

Above the threshold I. Objects: $\Sigma(f) = +\infty$


Known: obstruction \rightarrow let us prove realization

Bounded density shifts. Consider $(p_k)_k \in \mathbb{N}^{\mathbb{N}}$ non-decreasing and computable. Define \mathcal{F} as set of:

Above the threshold I. Objects: $\Sigma(f) = +\infty$

Known: obstruction \rightarrow let us prove realization


Bounded density shifts. Consider $(p_k)_k \in \mathbb{N}^{\mathbb{N}}$ non-decreasing and computable. Define \mathcal{F} as set of:



Above the threshold I. Objects: $\Sigma(f) = +\infty$

Known: obstruction \rightarrow let us prove realization

Bounded density shifts. Consider $(p_k)_k \in \mathbb{N}^{\mathbb{N}}$ non-decreasing and computable. Define \mathcal{F} as set of:



Above the threshold I. Objects: $\Sigma(f) = +\infty$

Known: obstruction \rightarrow let us prove realization

Bounded density shifts. Consider $(p_k)_k \in \mathbb{N}^{\mathbb{N}}$ non-decreasing and computable. Define \mathcal{F} as set of:

$$\begin{array}{c} \overleftarrow{\hspace{1.5cm}} \overrightarrow{\hspace{1.5cm}} \\ k = 8 \\ \boxed{0 \mid 1 \mid 0 \mid 1 \mid 1 \mid 0 \mid 0 \mid 1} \\ > p_8 = 3 \end{array}$$

Above the threshold I. Objects: $\Sigma(f) = +\infty$

Known: obstruction \rightarrow let us prove realization

Bounded density shifts. Consider $(p_k)_k \in \mathbb{N}^{\mathbb{N}}$ non-decreasing and computable. Define \mathcal{F} as set of:

$$\begin{array}{c} \overleftarrow{\hspace{1.5cm}} \overrightarrow{\hspace{1.5cm}} \\ k = 8 \\ \boxed{0 \mid 1 \mid 0 \mid 1 \mid 1 \mid 0 \mid 0 \mid 1} \\ > p_8 = 3 \end{array}$$

Since (p_k) is computable, $X_{\mathcal{F}}$ is decidable:

Above the threshold I. Objects: $\Sigma(f) = +\infty$

Known: obstruction \rightarrow let us prove realization

Bounded density shifts. Consider $(p_k)_k \in \mathbb{N}^{\mathbb{N}}$ non-decreasing and computable. Define \mathcal{F} as set of:

$$\begin{array}{c} \overleftarrow{\hspace{1.5cm}} \overrightarrow{\hspace{1.5cm}} \\ k = 8 \\ \boxed{0 \mid 1 \mid 0 \mid 1 \mid 1 \mid 0 \mid 0 \mid 1} \\ > p_8 = 3 \end{array}$$

Since (p_k) is computable, $X_{\mathcal{F}}$ is decidable:

$$\boxed{1 \mid 1 \mid 0 \mid 1 \mid 0 \mid 1}$$

Above the threshold I. Objects: $\Sigma(f) = +\infty$

Known: obstruction \rightarrow let us prove realization

Bounded density shifts. Consider $(p_k)_k \in \mathbb{N}^{\mathbb{N}}$ non-decreasing and computable. Define \mathcal{F} as set of:

$$\begin{array}{c} \overleftarrow{\hspace{1.5cm}} \overrightarrow{\hspace{1.5cm}} \\ k = 8 \\ \boxed{0} \boxed{1} \boxed{0} \boxed{1} \boxed{1} \boxed{0} \boxed{0} \boxed{1} \\ > p_8 = 3 \end{array}$$

Since (p_k) is computable, $X_{\mathcal{F}}$ is decidable:

$$\boxed{1} \boxed{1} \boxed{0} \boxed{1} \boxed{0} \boxed{1} \quad \text{Computed: } p_1, p_2, p_3, p_4, p_5, p_6.$$

Above the threshold I. Objects: $\Sigma(f) = +\infty$

Known: obstruction \rightarrow let us prove realization

Bounded density shifts. Consider $(p_k)_k \in \mathbb{N}^{\mathbb{N}}$ non-decreasing and computable. Define \mathcal{F} as set of:

$$\begin{array}{c} \longleftrightarrow k=8 \longrightarrow \\ \boxed{0} \boxed{1} \boxed{0} \boxed{1} \boxed{1} \boxed{0} \boxed{0} \boxed{1} \\ > p_8 = 3 \end{array}$$

Since (p_k) is computable, $X_{\mathcal{F}}$ is decidable:

$$\boxed{1} \boxed{1} \boxed{0} \boxed{1} \boxed{0} \boxed{1} \quad \text{Computed: } p_1, p_2, p_3, p_4, p_5, p_6.$$

Above the threshold I. Objects: $\Sigma(f) = +\infty$

Known: obstruction \rightarrow let us prove realization

Bounded density shifts. Consider $(p_k)_k \in \mathbb{N}^{\mathbb{N}}$ non-decreasing and computable. Define \mathcal{F} as set of:

$$\begin{array}{c} \longleftrightarrow k=8 \longrightarrow \\ \boxed{0} \boxed{1} \boxed{0} \boxed{1} \boxed{1} \boxed{0} \boxed{0} \boxed{1} \\ > p_8 = 3 \end{array}$$

Since (p_k) is computable, $X_{\mathcal{F}}$ is decidable:

$$\begin{array}{c} \boxed{1} \boxed{1} \boxed{0} \boxed{1} \boxed{0} \boxed{1} \\ \swarrow \end{array} \quad \text{Computed: } p_1, p_2, p_3, p_4, p_5, p_6.$$

Above the threshold I. Objects: $\Sigma(f) = +\infty$

Known: obstruction \rightarrow let us prove realization

Bounded density shifts. Consider $(p_k)_k \in \mathbb{N}^{\mathbb{N}}$ non-decreasing and computable. Define \mathcal{F} as set of:

$$\begin{array}{c} \longleftrightarrow k=8 \longrightarrow \\ \boxed{0} \boxed{1} \boxed{0} \boxed{1} \boxed{1} \boxed{0} \boxed{0} \boxed{1} \\ > p_8 = 3 \end{array}$$

Since (p_k) is computable, $X_{\mathcal{F}}$ is decidable:

$\boxed{1} \boxed{1} \boxed{0} \boxed{1} \boxed{0} \boxed{1}$ Computed: $p_1, p_2, p_3, p_4, p_5, p_6$.

\swarrow

$\notin \mathcal{L}(X_{\mathcal{F}})$

Above the threshold I. Objects: $\Sigma(f) = +\infty$

Known: obstruction \rightarrow let us prove realization

Bounded density shifts. Consider $(p_k)_k \in \mathbb{N}^{\mathbb{N}}$ non-decreasing and computable. Define \mathcal{F} as set of:

$$\begin{array}{c} \overleftarrow{\hspace{1.5cm}} \overrightarrow{\hspace{1.5cm}} \\ k = 8 \\ \boxed{0} \boxed{1} \boxed{0} \boxed{1} \boxed{1} \boxed{0} \boxed{0} \boxed{1} \\ > p_8 = 3 \end{array}$$

Since (p_k) is computable, $X_{\mathcal{F}}$ is decidable:

$$0 \boxed{1} \boxed{1} \boxed{0} \boxed{1} \boxed{0} \boxed{1} 0$$

Above the threshold I. Objects: $\Sigma(f) = +\infty$

Known: obstruction \rightarrow let us prove realization

Bounded density shifts. Consider $(p_k)_k \in \mathbb{N}^{\mathbb{N}}$ non-decreasing and computable. Define \mathcal{F} as set of:

$$\begin{array}{c} \overleftarrow{\hspace{1.5cm}} \overrightarrow{\hspace{1.5cm}} \\ k = 8 \\ \boxed{0} \boxed{1} \boxed{0} \boxed{1} \boxed{1} \boxed{0} \boxed{0} \boxed{1} \\ > p_8 = 3 \end{array}$$

Since (p_k) is computable, $X_{\mathcal{F}}$ is decidable:

$$0 \ 0 \boxed{1} \boxed{1} \boxed{0} \boxed{1} \boxed{0} \boxed{1} \ 0 \ 0$$

Above the threshold I. Objects: $\Sigma(f) = +\infty$

Known: obstruction \rightarrow let us prove realization

Bounded density shifts. Consider $(p_k)_k \in \mathbb{N}^{\mathbb{N}}$ non-decreasing and computable. Define \mathcal{F} as set of:

$$\begin{array}{c} \overleftarrow{\hspace{1.5cm}} \overrightarrow{\hspace{1.5cm}} \\ k = 8 \\ \boxed{0 \mid 1 \mid 0 \mid 1 \mid 1 \mid 0 \mid 0 \mid 1} \\ > p_8 = 3 \end{array}$$

Since (p_k) is computable, $X_{\mathcal{F}}$ is decidable:

$$0 \ 0 \ 0 \ \boxed{1 \mid 1 \mid 0 \mid 1 \mid 0 \mid 1} \ 0 \ 0 \ 0$$

Above the threshold I. Objects: $\Sigma(f) = +\infty$

Known: obstruction \rightarrow let us prove realization

Bounded density shifts. Consider $(p_k)_k \in \mathbb{N}^{\mathbb{N}}$ non-decreasing and computable. Define \mathcal{F} as set of:

$$\begin{array}{c} \overleftarrow{\hspace{1.5cm}} \overrightarrow{\hspace{1.5cm}} \\ k=8 \\ \boxed{0 \mid 1 \mid 0 \mid 1 \mid 1 \mid 0 \mid 0 \mid 1} \\ > p_8 = 3 \end{array}$$

Since (p_k) is computable, $X_{\mathcal{F}}$ is decidable:

$$0 \ 0 \ 0 \ 0 \ \boxed{1 \ 1 \ 0 \ 1 \ 0 \ 1} \ 0 \ 0 \ 0 \ 0$$

Above the threshold I. Objects: $\Sigma(f) = +\infty$

Known: obstruction \rightarrow let us prove realization

Bounded density shifts. Consider $(p_k)_k \in \mathbb{N}^{\mathbb{N}}$ non-decreasing and computable. Define \mathcal{F} as set of:

$$\begin{array}{c} \longleftrightarrow k=8 \longrightarrow \\ \boxed{0 \mid 1 \mid 0 \mid 1 \mid 1 \mid 0 \mid 0 \mid 1} \\ > p_8 = 3 \end{array}$$

Since (p_k) is computable, $X_{\mathcal{F}}$ is decidable:

$$0 \ 0 \ 0 \ 0 \ \boxed{1 \ 1 \ 0 \ 1 \ 0 \ 1} \ 0 \ 0 \ 0 \ 0$$


\searrow
 $\in \mathcal{L}(X_{\mathcal{F}})$

Above the threshold I. Objects: $\Sigma(f) = +\infty$

Let $F(k) \underset{Def}{=} 2k + f(k)$;


Above the threshold I. Objects: $\Sigma(f) = +\infty$

Let $F(k) \stackrel{\text{Def}}{=} 2k + f(k)$; (p_k) is taken as discretised of:



Above the threshold I. Objects: $\Sigma(f) = +\infty$

Let $F(k) \stackrel{\text{Def}}{=} 2k + f(k)$; (p_k) is taken as discretised of:



f -block gluing $\Leftrightarrow \forall n, p_{F(n)} \geq 2p_n + 4$

Above the threshold II. Strategy: $\Sigma(f) = +\infty$

Let $\alpha \in \Pi_1$, $\alpha_k \downarrow \alpha$.

Above the threshold II. Strategy: $\Sigma(f) = +\infty$

Let $\alpha \in \Pi_1$, $\alpha_k \downarrow \alpha$.

Start from $k \mapsto p_k = k$ and change successively the slope on the k th interval to **minimal slope** s.t.:

Above the threshold II. Strategy: $\Sigma(f) = +\infty$

Let $\alpha \in \Pi_1$, $\alpha_k \downarrow \alpha$.

Start from $k \mapsto p_k = k$ and change successively the slope on the k th interval to **minimal slope** s.t.:


1. $\forall l \leq F^k(1), p_{F(l)} \geq 2p_l + 4$ (f -block gluing)
2. entropy after change : $> \alpha_k + 2^{-k} \geq \alpha$.

Above the threshold II. Strategy: $\Sigma(f) = +\infty$

Let $\alpha \in \Pi_1$, $\alpha_k \downarrow \alpha$.

Start from $k \mapsto p_k = k$ and change successively the slope on the k th interval to **minimal slope** s.t.:

1. $\forall l \leq F^k(1)$, $p_{F(l)} \geq 2p_l + 4$ (f -block gluing)
2. entropy after change : $> \alpha_k + 2^{-k} \geq \alpha$.



Current entropy:


$$h > \alpha_1 + 2^{-1}$$

Above the threshold II. Strategy: $\Sigma(f) = +\infty$

Let $\alpha \in \Pi_1$, $\alpha_k \downarrow \alpha$.

Start from $k \mapsto p_k = k$ and change successively the slope on the k th interval to **minimal slope** s.t.:

1. $\forall l \leq F^k(1)$, $p_{F(l)} \geq 2p_l + 4$ (f -block gluing)
2. entropy after change : $> \alpha_k + 2^{-k} \geq \alpha$.



Current entropy:


$$h > \alpha_1 + 2^{-1}$$

Above the threshold II. Strategy: $\Sigma(f) = +\infty$

Let $\alpha \in \Pi_1$, $\alpha_k \downarrow \alpha$.

Start from $k \mapsto p_k = k$ and change successively the slope on the k th interval to **minimal slope** s.t.:

1. $\forall l \leq F^k(1)$, $p_{F(l)} \geq 2p_l + 4$ (f -block gluing)
2. entropy after change : $> \alpha_k + 2^{-k} \geq \alpha$.




Current entropy:
 $h > \alpha_1 + 2^{-1}$

Above the threshold II. Strategy: $\Sigma(f) = +\infty$

Let $\alpha \in \Pi_1$, $\alpha_k \downarrow \alpha$.

Start from $k \mapsto p_k = k$ and change successively the slope on the k th interval to **minimal slope** s.t.:

1. $\forall l \leq F^k(1)$, $p_{F(l)} \geq 2p_l + 4$ (f -block gluing)
2. entropy after change : $> \alpha_k + 2^{-k} \geq \alpha$.




Current entropy:
 $h > \alpha_1 + 2^{-1}$

Above the threshold II. Strategy: $\Sigma(f) = +\infty$

Let $\alpha \in \Pi_1$, $\alpha_k \downarrow \alpha$.

Start from $k \mapsto p_k = k$ and change successively the slope on the k th interval to **minimal slope** s.t.:

1. $\forall l \leq F^k(1)$, $p_{F(l)} \geq 2p_l + 4$ (f -block gluing)
2. entropy after change : $> \alpha_k + 2^{-k} \geq \alpha$.




Current entropy:
 $h > \alpha_1 + 2^{-1}$

Above the threshold II. Strategy: $\Sigma(f) = +\infty$

Let $\alpha \in \Pi_1$, $\alpha_k \downarrow \alpha$.

Start from $k \mapsto p_k = k$ and change successively the slope on the k th interval to **minimal slope** s.t.:

1. $\forall l \leq F^k(1)$, $p_{F(l)} \geq 2p_l + 4$ (f -block gluing)
2. entropy after change : $> \alpha_k + 2^{-k} \geq \alpha$.




Current entropy:
 $h < \alpha_1 + 2^{-1}$

Above the threshold II. Strategy: $\Sigma(f) = +\infty$

Let $\alpha \in \Pi_1$, $\alpha_k \downarrow \alpha$.

Start from $k \mapsto p_k = k$ and change successively the slope on the k th interval to **minimal slope** s.t.:

1. $\forall l \leq F^k(1)$, $p_{F(l)} \geq 2p_l + 4$ (f -block gluing)
2. entropy after change : $> \alpha_k + 2^{-k} \geq \alpha$.




Current entropy:
 $h > \alpha_2 + 2^{-2}$

Above the threshold II. Strategy: $\Sigma(f) = +\infty$

Let $\alpha \in \Pi_1$, $\alpha_k \downarrow \alpha$.

Start from $k \mapsto p_k = k$ and change successively the slope on the k th interval to **minimal slope** s.t.:

1. $\forall l \leq F^k(1)$, $p_{F(l)} \geq 2p_l + 4$ (f -block gluing)
2. entropy after change : $> \alpha_k + 2^{-k} \geq \alpha$.




Current entropy:
 $h > \alpha_2 + 2^{-2}$

Above the threshold II. Strategy: $\Sigma(f) = +\infty$

Let $\alpha \in \Pi_1$, $\alpha_k \downarrow \alpha$.

Start from $k \mapsto p_k = k$ and change successively the slope on the k th interval to **minimal slope** s.t.:

1. $\forall l \leq F^k(1)$, $p_{F(l)} \geq 2p_l + 4$ (f -block gluing)
2. entropy after change : $> \alpha_k + 2^{-k} \geq \alpha$.




Current entropy:
 $h > \alpha_2 + 2^{-2}$

Above the threshold II. Strategy: $\Sigma(f) = +\infty$

Let $\alpha \in \Pi_1$, $\alpha_k \downarrow \alpha$.

Start from $k \mapsto p_k = k$ and change successively the slope on the k th interval to **minimal slope** s.t.:

1. $\forall l \leq F^k(1)$, $p_{F(l)} \geq 2p_l + 4$ (f -block gluing)
2. entropy after change : $> \alpha_k + 2^{-k} \geq \alpha$.




Current entropy:
 $h > \alpha_2 + 2^{-2}$

Above the threshold II. Strategy: $\Sigma(f) = +\infty$

Let $\alpha \in \Pi_1$, $\alpha_k \downarrow \alpha$.

Start from $k \mapsto p_k = k$ and change successively the slope on the k th interval to **minimal slope** s.t.:

1. $\forall l \leq F^k(1)$, $p_{F(l)} \geq 2p_l + 4$ (f -block gluing)
2. entropy after change : $> \alpha_k + 2^{-k} \geq \alpha$.




Current entropy:
 $h < \alpha_2 + 2^{-2}$

Above the threshold II. Strategy: $\Sigma(f) = +\infty$

Let $\alpha \in \Pi_1$, $\alpha_k \downarrow \alpha$.

Start from $k \mapsto p_k = k$ and change successively the slope on the k th interval to **minimal slope** s.t.:


1. $\forall l \leq F^k(1)$, $p_{F(l)} \geq 2p_l + 4$ (f -block gluing)
2. entropy after change : $> \alpha_k + 2^{-k} \geq \alpha$.



Current entropy:
 $h > \alpha_3 + 2^{-3}$

Above the threshold III. Tracking tool: $\Sigma(f) = +\infty$

Entropy change: $\beta = (\beta_1, \beta_2, \dots)$ slopes:



$$\beta, 0 \geq \Delta h \geq -H(1/F^N(1))$$

$$H(\epsilon) = \epsilon \log(\epsilon) + (1 - \epsilon) \log(1 - \epsilon)$$


(by bounding preimages of a transformation)

Above the threshold III. Tracking: $\Sigma(f) = +\infty$

Let us assume that $h_\infty < \alpha$.


Above the threshold III. Tracking: $\Sigma(f) = +\infty$

Let us assume that $h_\infty < \alpha$.




Above the threshold III. Tracking: $\Sigma(f) = +\infty$

Let us assume that $h_\infty < \alpha$.




Above the threshold III. Tracking: $\Sigma(f) = +\infty$

Let us assume that $h_\infty < \alpha$.




Above the threshold III. Tracking: $\Sigma(f) = +\infty$

Let us assume that $h_\infty > \alpha$.




Above the threshold III. Tracking: $\Sigma(f) = +\infty$

Let us assume that $h_\infty > \alpha$.




Above the threshold III. Tracking: $\Sigma(f) = +\infty$

Let us assume that $h_\infty > \alpha$.



Above the threshold III. Tracking: $\Sigma(f) = +\infty$


Let us assume that $h_\infty > \alpha$.



Block gluing condition is minimal:

Above the threshold III. Tracking: $\Sigma(f) = +\infty$


Let us assume that $h_\infty > \alpha$.



Block gluing condition is minimal: $\forall l \geq k, p_{F(l)} = 2p_l + 4$.

Above the threshold III. Tracking: $\Sigma(f) = +\infty$

Let us assume that $h_\infty > \alpha$.




Block gluing condition is minimal: $\forall l \geq k, p_{F(l)} = 2p_l + 4$.

Repeat + limit:

Above the threshold III. Tracking: $\Sigma(f) = +\infty$

Let us assume that $h_\infty > \alpha$.




Block gluing condition is minimal: $\forall l \geq k, p_{F(l)} = 2p_l + 4$.

Repeat + limit: $\inf \frac{p_l}{l} \cdot \Sigma(f) < +\infty$.

Above the threshold III. Tracking: $\Sigma(f) = +\infty$

Let us assume that $h_\infty > \alpha$.




Block gluing condition is minimal: $\forall l \geq k, p_{F(l)} = 2p_l + 4$.

Repeat + limit: $\inf \frac{p_l}{l} \cdot \Sigma(f) < +\infty$.

$\Sigma(f) = +\infty$:

Above the threshold III. Tracking: $\Sigma(f) = +\infty$

Let us assume that $h_\infty > \alpha$.




Block gluing condition is minimal: $\forall l \geq k, p_{F(l)} = 2p_l + 4$.

Repeat + limit: $\inf \frac{p_l}{l} \cdot \Sigma(f) < +\infty$.

$\Sigma(f) = +\infty$: $\inf \frac{p_l}{l} = h_\infty = 0$

Above the threshold III. Tracking: $\Sigma(f) = +\infty$

Let us assume that $h_\infty > \alpha$.



Block gluing condition is minimal: $\forall l \geq k, p_{F(l)} = 2p_l + 4$.

Repeat + limit: $\inf \frac{p_l}{l} \cdot \Sigma(f) < +\infty$.

$\Sigma(f) = +\infty$: $\inf \frac{p_l}{l} = h_\infty = 0 \rightarrow \text{contradiction}$.

Questions:

1. What happens when $\Sigma(f)$ is not computable ?

Questions:


1. What happens when $\Sigma(f)$ is not computable ?
2. Computational threshold for the spectral gap ?

Questions:

1. What happens when $\Sigma(f)$ is not computable ?
2. Computational threshold for the spectral gap ?
3. For other classes of dynamical systems ? [\rightarrow better understanding of the threshold phenomenon]

Computability in general:


X.Zheng, K.Weihrauch: The arithmetical hierarchy of real numbers.



For all m , $\Delta_m = \Sigma_m \cap \Pi_m$.

Computability in general:

X.Zheng, K.Weihrauch: The arithmetical hierarchy of real numbers.



For all m , $\Delta_m = \Sigma_m \cap \Pi_m$.

Theorem: for all m , $\Sigma_m \subsetneq \Delta_{m+1}$, $\Pi_m \subsetneq \Delta_{m+1}$, $\Delta_m \subsetneq \Sigma_m$, $\Delta_m \subsetneq \Pi_m$.

General metric dynamics:

Question: Classification of classes of dynamical systems according to possible values of entropy ?

General metric dynamics:

Question: Classification of classes of dynamical systems according to possible values of entropy ?

Theorem[[G., Herrera, Rojas, Sablik\(2019\)](#)]: the entropy of a topological **computable** dynamical system (X, f) is Σ_2 -computable.

General metric dynamics:

Question: Classification of classes of dynamical systems according to possible values of entropy ?

Theorem[[G., Herrera, Rojas, Sablik\(2019\)](#)]: the entropy of a topological **computable** dynamical system (X, f) is Σ_2 -computable.

If in the arithmetical hierarchy, possible classes are: $\Delta_1, \Sigma_1, \Pi_1, \Delta_2, \Sigma_2$.

Definition of computable dynamical system

A topological dynamical system is some (X, f) , where X is 'computable' and f is 'computable'.

Definition of computable dynamical system

A topological dynamical system is some (X, f) , where X is 'computable' and f is 'computable'.

Computable metric space: (X, d, \mathcal{S}) with (X, d) metric space, $\mathcal{S} = \{s_i : i \geq 0\}$ a countable dense subset of X (**ideal points**), s.t. exists an algorithm which on input (i, j, n) outputs $r \in \mathbb{Q}$ s.t.:

$$|d(s_i, s_j) - r| \leq 2^{-n}.$$

Definition of computable dynamical system

A topological dynamical system is some (X, f) , where X is 'computable' and f is 'computable'.

Computable metric space: (X, d, \mathcal{S}) with (X, d) metric space, $\mathcal{S} = \{s_i : i \geq 0\}$ a countable dense subset of X (**ideal points**), s.t. exists an algorithm which on input (i, j, n) outputs $r \in \mathbb{Q}$ s.t.:

$$|d(s_i, s_j) - r| \leq 2^{-n}.$$

Examples:

Definition of computable dynamical system

A topological dynamical system is some (X, f) , where X is 'computable' and f is 'computable'.

Computable metric space: (X, d, \mathcal{S}) with (X, d) metric space, $\mathcal{S} = \{s_i : i \geq 0\}$ a countable dense subset of X (**ideal points**), s.t. exists an algorithm which on input (i, j, n) outputs $r \in \mathbb{Q}$ s.t.:

$$|d(s_i, s_j) - r| \leq 2^{-n}.$$

Examples:

1. $X = [0, 1]$, $\mathcal{S} = \mathbb{Q} \cap [0, 1]$, $d(x, y) = |x - y|$;

Definition of computable dynamical system

A topological dynamical system is some (X, f) , where X is 'computable' and f is 'computable'.

Computable metric space: (X, d, \mathcal{S}) with (X, d) metric space, $\mathcal{S} = \{s_i : i \geq 0\}$ a countable dense subset of X (**ideal points**), s.t. exists an algorithm which on input (i, j, n) outputs $r \in \mathbb{Q}$ s.t.:

$$|d(s_i, s_j) - r| \leq 2^{-n}.$$

Examples:

1. $X = [0, 1]$, $\mathcal{S} = \mathbb{Q} \cap [0, 1]$, $d(x, y) = |x - y|$;
2. $\mathcal{A}^{\mathbb{N}}$, $\# \in \mathcal{A}$, $\mathcal{S} = \{w \cdot \#^{\infty} : |w| < +\infty\}$,

$$d(x, y) = 2^{-\min(\{n \in \mathbb{N} : x_n \neq y_n\})}.$$

Definition of computable functions

Set $(B_n)_n$ is an enumeration of ideal balls $B(s, r)$, $s \in \mathcal{S}$, $r \in \mathbb{Q}$.

Definition of computable functions

Set $(B_n)_n$ is an enumeration of ideal balls $B(s, r)$, $s \in \mathcal{S}$, $r \in \mathbb{Q}$.

Definition: A function $f : X \rightarrow X$ is **computable** when there exists an algorithm which on input m enumerates $I_m \subset \mathbb{N}$ such that

$$f^{-1}(B_m) = \bigcup_{n \in I_m} B_n,$$

Characterization of computable functions on Cantor sets

Lemma: a function $\mathcal{A}^{\mathbb{N}} \rightarrow \mathcal{A}^{\mathbb{N}}$ is computable when there exists a non-decreasing computable function $\varphi : \mathbb{N} \rightarrow \mathbb{N}$ and an algorithm which provided as input the $\varphi(n)$ first elements of some $x \in \mathcal{A}^{\mathbb{N}}$ outputs the n first elements of $f(x)$.

Characterization of computable functions on Cantor sets

Lemma: a function $\mathcal{A}^{\mathbb{N}} \rightarrow \mathcal{A}^{\mathbb{N}}$ is computable when there exists a non-decreasing computable function $\varphi : \mathbb{N} \rightarrow \mathbb{N}$ and an algorithm which provided as input the $\varphi(n)$ first elements of some $x \in \mathcal{A}^{\mathbb{N}}$ outputs the n first elements of $f(x)$.

Examples: shift map, cellular automata.

Characterization of computable functions on Cantor sets

Lemma: a function $\mathcal{A}^{\mathbb{N}} \rightarrow \mathcal{A}^{\mathbb{N}}$ is computable when there exists a non-decreasing computable function $\varphi : \mathbb{N} \rightarrow \mathbb{N}$ and an algorithm which provided as input the $\varphi(n)$ first elements of some $x \in \mathcal{A}^{\mathbb{N}}$ outputs the n first elements of $f(x)$.

Examples: shift map, cellular automata.




Characterization of computable functions on Cantor sets

Lemma: a function $\mathcal{A}^{\mathbb{N}} \rightarrow \mathcal{A}^{\mathbb{N}}$ is computable when there exists a non-decreasing computable function $\varphi : \mathbb{N} \rightarrow \mathbb{N}$ and an algorithm which provided as input the $\varphi(n)$ first elements of some $x \in \mathcal{A}^{\mathbb{N}}$ outputs the n first elements of $f(x)$.

Examples: shift map, cellular automata.


x  ...

$f(x)$  ...

Characterization of computable functions on Cantor sets

Lemma: a function $\mathcal{A}^{\mathbb{N}} \rightarrow \mathcal{A}^{\mathbb{N}}$ is computable when there exists a non-decreasing computable function $\varphi : \mathbb{N} \rightarrow \mathbb{N}$ and an algorithm which provided as input the $\varphi(n)$ first elements of some $x \in \mathcal{A}^{\mathbb{N}}$ outputs the n first elements of $f(x)$.


Examples: shift map, cellular automata.



Characterization of computable functions on Cantor sets

Lemma: a function $\mathcal{A}^{\mathbb{N}} \rightarrow \mathcal{A}^{\mathbb{N}}$ is computable when there exists a non-decreasing computable function $\varphi : \mathbb{N} \rightarrow \mathbb{N}$ and an algorithm which provided as input the $\varphi(n)$ first elements of some $x \in \mathcal{A}^{\mathbb{N}}$ outputs the n first elements of $f(x)$.


Examples: shift map, cellular automata.



Characterization of computable functions on Cantor sets

Lemma: a function $\mathcal{A}^{\mathbb{N}} \rightarrow \mathcal{A}^{\mathbb{N}}$ is computable when there exists a non-decreasing computable function $\varphi : \mathbb{N} \rightarrow \mathbb{N}$ and an algorithm which provided as input the $\varphi(n)$ first elements of some $x \in \mathcal{A}^{\mathbb{N}}$ outputs the n first elements of $f(x)$.


Examples: shift map, cellular automata.



Characterization of computable functions on Cantor sets

Lemma: a function $\mathcal{A}^{\mathbb{N}} \rightarrow \mathcal{A}^{\mathbb{N}}$ is computable when there exists a non-decreasing computable function $\varphi : \mathbb{N} \rightarrow \mathbb{N}$ and an algorithm which provided as input the $\varphi(n)$ first elements of some $x \in \mathcal{A}^{\mathbb{N}}$ outputs the n first elements of $f(x)$.


Examples: shift map, cellular automata.



Characterization of computable functions on Cantor sets

Lemma: a function $\mathcal{A}^{\mathbb{N}} \rightarrow \mathcal{A}^{\mathbb{N}}$ is computable when there exists a non-decreasing computable function $\varphi : \mathbb{N} \rightarrow \mathbb{N}$ and an algorithm which provided as input the $\varphi(n)$ first elements of some $x \in \mathcal{A}^{\mathbb{N}}$ outputs the n first elements of $f(x)$.


Examples: shift map, cellular automata.



Characterization of computable functions on Cantor sets

Lemma: a function $\mathcal{A}^{\mathbb{N}} \rightarrow \mathcal{A}^{\mathbb{N}}$ is computable when there exists a non-decreasing computable function $\varphi : \mathbb{N} \rightarrow \mathbb{N}$ and an algorithm which provided as input the $\varphi(n)$ first elements of some $x \in \mathcal{A}^{\mathbb{N}}$ outputs the n first elements of $f(x)$.


Examples: shift map, cellular automata.



Characterization of computable functions on Cantor sets

Lemma: a function $\mathcal{A}^{\mathbb{N}} \rightarrow \mathcal{A}^{\mathbb{N}}$ is computable when there exists a non-decreasing computable function $\varphi : \mathbb{N} \rightarrow \mathbb{N}$ and an algorithm which provided as input the $\varphi(n)$ first elements of some $x \in \mathcal{A}^{\mathbb{N}}$ outputs the n first elements of $f(x)$.

Examples: shift map, cellular automata.



Cantor maps: a case with no jump

Theorem[G.,Herrera,Rojas,Sablik(2019)]: the possible values for entropy for effective surjective dynamical systems on $\{0,1\}^{\mathbb{N}}$ are the non-negative Σ_2 -computable real numbers.

Cantor maps: a case with no jump

Theorem[G.,Herrera,Rojas,Sablik(2019)]: the possible values for entropy for effective surjective dynamical systems on $\{0,1\}^{\mathbb{N}}$ are the non-negative Σ_2 -computable real numbers.

Proof(Schema):

Cantor maps: a case with no jump

Theorem[G.,Herrera,Rojas,Sablik(2019)]: the possible values for entropy for effective surjective dynamical systems on $\{0,1\}^{\mathbb{N}}$ are the non-negative Σ_2 -computable real numbers.

Proof(Schema):

1. $h \in \Sigma_2$: $h = \sup_n h_n$, $h_n \in \Pi_1$.

Cantor maps: a case with no jump

Theorem[G.,Herrera,Rojas,Sablik(2019)]: the possible values for entropy for effective surjective dynamical systems on $\{0,1\}^{\mathbb{N}}$ are the non-negative Σ_2 -computable real numbers.

Proof(Schema):

1. $h \in \Sigma_2$: $h = \sup_n h_n$, $h_n \in \Pi_1$.
2. X_n some *id*-block gluing decidable subshift, $h(X_n) = h_n$

Cantor maps: a case with no jump

Theorem[G.,Herrera,Rojas,Sablik(2019)]: the possible values for entropy for effective surjective dynamical systems on $\{0,1\}^{\mathbb{N}}$ are the non-negative Σ_2 -computable real numbers.

Proof(Schema):

1. $h \in \Sigma_2$: $h = \sup_n h_n$, $h_n \in \Pi_1$.
2. X_n some *id*-block gluing decidable subshift, $h(X_n) = h_n$: $\sigma|_{X_n}$ surjective.

Cantor maps: a case with no jump

Theorem[G.,Herrera,Rojas,Sablik(2019)]: the possible values for entropy for effective surjective dynamical systems on $\{0,1\}^{\mathbb{N}}$ are the non-negative Σ_2 -computable real numbers.

Proof(Schema):

1. $h \in \Sigma_2$: $h = \sup_n h_n$, $h_n \in \Pi_1$.
2. X_n some *id*-block gluing decidable subshift, $h(X_n) = h_n$: $\sigma|_{X_n}$ surjective.
3. $X_n \sim \{0,1\}^{\mathbb{N}} \rightarrow$

Cantor maps: a case with no jump

Theorem[G.,Herrera,Rojas,Sablik(2019)]: the possible values for entropy for effective surjective dynamical systems on $\{0,1\}^{\mathbb{N}}$ are the non-negative Σ_2 -computable real numbers.

Proof(Schema):

1. $h \in \Sigma_2$: $h = \sup_n h_n$, $h_n \in \Pi_1$.
2. X_n some *id*-block gluing decidable subshift, $h(X_n) = h_n$: $\sigma|_{X_n}$ surjective.
3. $X_n \sim \{0,1\}^{\mathbb{N}} \rightarrow$: $\sigma|_{X_n} \sim f_n$ on $\{0,1\}^{\mathbb{N}}$.

Cantor maps: a case with no jump

Theorem[G.,Herrera,Rojas,Sablik(2019)]: the possible values for entropy for effective surjective dynamical systems on $\{0,1\}^{\mathbb{N}}$ are the non-negative Σ_2 -computable real numbers.

Proof(Schema):

1. $h \in \Sigma_2$: $h = \sup_n h_n$, $h_n \in \Pi_1$.
2. X_n some *id*-block gluing decidable subshift, $h(X_n) = h_n$: $\sigma|_{X_n}$ surjective.
3. $X_n \sim \{0,1\}^{\mathbb{N}} \rightarrow$: $\sigma|_{X_n} \sim f_n$ on $\{0,1\}^{\mathbb{N}}$.
4. Definition of f on $\{0,1\}^{\mathbb{N}}$:


$$\begin{array}{ccc} f_1 \circlearrowleft & f_2 \circlearrowleft & f_3 \circlearrowleft \\ \hline & & \dots \end{array}$$

Cantor maps: a case with no jump

Theorem[G.,Herrera,Rojas,Sablik(2019)]: the possible values for entropy for effective surjective dynamical systems on $\{0,1\}^{\mathbb{N}}$ are the non-negative Σ_2 -computable real numbers.

Proof(Schema):

1. $h \in \Sigma_2$: $h = \sup_n h_n$, $h_n \in \Pi_1$.
2. X_n some *id*-block gluing decidable subshift, $h(X_n) = h_n$: $\sigma|_{X_n}$ surjective.
3. $X_n \sim \{0,1\}^{\mathbb{N}} \rightarrow$: $\sigma|_{X_n} \sim f_n$ on $\{0,1\}^{\mathbb{N}}$.
4. Definition of f on $\{0,1\}^{\mathbb{N}}$:



5. f surjective with entropy $\sup_n h_n$.

Interval maps: a case of jump

Theorem[G.,Herrera,Rojas,Sablik(2019)]: the possible values for entropy for effective interval maps are the non-negative Σ_1 -computable real numbers.

Interval maps: a case of jump

Theorem[G.,Herrera,Rojas,Sablik(2019)]: the possible values for entropy for effective interval maps are the non-negative Σ_1 -computable real numbers.

Definition:((p, n)-Horseshoe): for $f : [0, 1] \rightarrow [0, 1]$, a sequence I_1, \dots, I_p of disjoint intervals such that

$$\cup I_i \subset \cap f^n(I_i).$$

Interval maps: a case of jump

Theorem[G.,Herrera,Rojas,Sablik(2019)]: the possible values for entropy for effective interval maps are the non-negative Σ_1 -computable real numbers.

Definition:((p, n)-Horseshoe): for $f : [0, 1] \rightarrow [0, 1]$, a sequence I_1, \dots, I_p of disjoint intervals such that

$$\cup I_i \subset \cap f^n(I_i).$$

Theorem[M.Misiurewicz,J.Llibre]: For all $f : [0, 1] \rightarrow [0, 1]$, the entropy of $([0, 1], f)$ is equal to $\sup_{(p,n) \in \Delta} \frac{\log_2(p)}{n}$, where Δ is the set of (p, n) for which f has a (p, n) horseshoe.

Interval maps: a case of jump

Theorem[G.,Herrera,Rojas,Sablik(2019)]: the possible values for entropy for effective interval maps are the non-negative Σ_1 -computable real numbers.

Definition:((p, n)-Horseshoe): for $f : [0, 1] \rightarrow [0, 1]$, a sequence I_1, \dots, I_p of disjoint intervals such that

$$\cup I_i \subset \cap f^n(I_i).$$

Theorem[M.Misiurewicz,J.Llibre]: For all $f : [0, 1] \rightarrow [0, 1]$, the entropy of $([0, 1], f)$ is equal to $\sup_{(p,n) \in \Delta} \frac{\log_2(p)}{n}$, where Δ is the set of (p, n) for which f has a (p, n) horseshoe.

With a bit of work(detecting horseshoes algorithmically):

Interval maps: a case of jump

Theorem[G.,Herrera,Rojas,Sablik(2019)]: the possible values for entropy for effective interval maps are the non-negative Σ_1 -computable real numbers.

Definition:((p, n)-Horseshoe): for $f : [0, 1] \rightarrow [0, 1]$, a sequence I_1, \dots, I_p of disjoint intervals such that


$$\cup I_i \subset \cap f^n(I_i).$$

Theorem[M.Misiurewicz,J.Llibre]: For all $f : [0, 1] \rightarrow [0, 1]$, the entropy of $([0, 1], f)$ is equal to $\sup_{(p,n) \in \Delta} \frac{\log_2(p)}{n}$, where Δ is the set of (p, n) for which f has a (p, n) horseshoe.

With a bit of work(detecting horseshoes algorithmically): the entropy of an effective map is Σ_1 .


Interval maps: realization

$f_s, s \in \mathbb{Q}$:



Interval maps: realization


$f_s, s \in \mathbb{Q}$:



Theorem[A.Katok]: if $f : [0, 1] \rightarrow [0, 1]$ is piecewise linear with slopes $\pm\lambda$, $\lambda > 0$, then entropy of $([0, 1], f)$ is λ .

Interval maps: realization

$f_s, s \in \mathbb{Q}$:




Theorem[A.Katok]: if $f : [0, 1] \rightarrow [0, 1]$ is piecewise linear with slopes $\pm\lambda$, $\lambda > 0$, then entropy of $([0, 1], f)$ is λ .


Thus for all $s \in \mathbb{Q}$, the entropy of $([0, 1], f_s)$ is s .

For $s \in \Sigma_1$: $s = \sup_n s_n$:


For $s \in \Sigma_1$: $s = \sup_n s_n$:




For $s \in \Sigma_1$: $s = \sup_n s_n$:



For $s \in \Sigma_1$: $s = \sup_n s_n$:



For $s \in \Sigma_1$: $s = \sup_n s_n$:



Computable map, entropy s .

Further questions:

Questions:

1. 'explain' jumps in computability ?

Further questions:

Questions:

1. 'explain' jumps in computability ?
2. possible values of entropy for subshifts which 'can be seen' as interval maps without loss of entropy ? $\Sigma_1 \cap \Pi_1 = \Delta_1$?

Further questions:

Questions:

1. 'explain' jumps in computability ?
2. possible values of entropy for subshifts which 'can be seen' as interval maps without loss of entropy ? $\Sigma_1 \cap \Pi_1 = \Delta_1$?
3. Do you have other ideas of classes of systems and dynamical constraints ?