BASICS OF INFORMATION SYSTEM SECURITY






Video Summary

- A Drawback of Packet Filtering Firewall
- Stateful Packet Inspection Firewall
- Example Network
- Connection State Table

What if we moved the firewall from computer 1.1.1.12 to Ra
Aim: Stop everyone except 1.1.1.12 from browsing to servers on 3.3.3.0/24



TCP/Webserver

Browsing using TCP request/response sequence cti ent

What if we moved the firewall from computer 1.1.1.12 to Ra Aim: Stop everyone except 1.1.1.12 from browsing to servers on 3.3.3.0/24

Is 1.1.1.12 able to communicate with the server successfully?



How we can resolve this issue?

| | SrcIP | DstIP 7.7.70/24 | SrcPort | DstPort | Protocol | Action |
|-------|----------|-----------------|---------|---------|-------------------|--------|
| £23.3 | 3.3.0/24 | .12 | 86 | * | 6 | Allow |
| 3. | 3.3.36 | , 2 | 80 | 40981 | 6 | Allow |
| | | | 000 | | 0 0 11 11 10 10 1 | |

What other problem we have here? Can an attacker reach 1.1.1.12? What about using 3.3.3.36 to send attack 1.1.1.12?

Yes

How to stop that?

???

Stateful Packet in Specton Firewall.

Stateful Packet Inspection


- Traditional packet filtering firewall makes decisions based on individual packets; don't consider past packets (stateless)
- Many applications establish a connection between client/server; group of packets belong to a connection
- Often easier to define rules for connections, rather than individual packets
- Need to store information about past behaviour (stateful)
- Stateful Packet Inspection (SPI) is extension of traditional packet filtering firewalls
- Issues: extra overhead required for maintaining state information

3-ulor hundshake

Stateful Packet Inspection

- For connections accepted by packet filtering firewall, record connection information
 - src/dest IP address, src/dest port, sequence numbers, connection state (e.g. Established, Closing)

 Packets arriving that belong to existing connections can be accepted without processing by firewall rules



What if we moved the firewall from computer 1.1.1.12 to Ra Aim: Stop everyone except 1.1.1.12 from browsing to servers on 3.3.3.36

Dst 3.3.36; 80 Protocol 6 Action A 1150 **FW Table** Src 1.1.1) : 40981 SPI Table Src Dst Protocol State 17:48981 136488 .12 .11 3.3.3.0/24 1.1.1.0/24 TCP SrcIP: 36 SrcP: 8 0 SrcIP: 12 SrcP: 40 18 Dst: 12 DstP: 40981 Dst: - 36 DstP: 80 Flag: Port: Port: 6

Example Stateful Firewall Connection State Table

| Source Address | Source Port | Destination Address | Destination Port | Connection State |
|----------------|-------------|------------------------|-------------------------|---------------------|
| 192.168.1.100 | 1030 | 210.9.88.29 | 80 | Established ** |
| 192.168.1.102 | 1031 | 216.32.42.123 | 80 | Established |
| 192.168.1.101 | 1033 | 173.66.32.122 | 25 | Established |
| 192.168.1.106 | 1035 | 177.231.32.12 | 79 | Established |
| 223.43.21.231 | 1990 | 192.168.1.6 | 80 | Established |
| 219.22.123.32 | 2112 | 192.168.1.6 | 80 | Established |
| 210.99.212.18 | 3321 | 192.168.1.6 | 80 | Established |
| 24.102.32.23 | 1025 | 192.168.1.6 | 80 | Established |
| 223.21.22.12 | 1046 | 192.168.1.6 | 80 | Established |

Video Summary

- A Drawback of Packet Filtering Firewall
- Stateful Packet Inspection Firewall
- Example Network
- Connection State Table