

Automated Planning

Outline

I. Planning domain definition language (PPDL)

II. Example domains

III. Algorithms for classical planning

I. Classical Planning

The task of finding *a sequence of actions* to accomplish a goal in a discrete, deterministic, static, fully observable environment.

I. Classical Planning

The task of finding *a sequence of actions* to accomplish a goal in a discrete, deterministic, static, fully observable environment.

Planning approaches learned so far :

- Problem solving via informed search
- Propositional logical agent (for the wumpus world)

I. Classical Planning

The task of finding *a sequence of actions* to accomplish a goal in a discrete, deterministic, static, fully observable environment.

Planning approaches learned so far :

- Problem solving via informed search
- Propositional logical agent (for the wumpus world)

Their limitations:

- ♠ Requirement of ad hoc heuristics for a new domain
- ♠ Explicit representation of an exponentially large state space

Planning Domain Definition Language (PDDL)

- ◆ **State**: a conjunction of **ground** atomic **fluents**

no variables	single predicate	time varying aspect

Planning Domain Definition Language (PDDL)

- ◆ **State**: a conjunction of **ground atomic fluents**

no variables

single
predicate

time varying aspect

$At(Truck_1, Melbourne) \wedge At(Truck_2, Sydney)$ // a state in package delivery

Planning Domain Definition Language (PDDL)

- ◆ **State**: a conjunction of **ground atomic fluents**

no variables

single
predicate

time varying aspect

$At(Truck_1, Melbourne) \wedge At(Truck_2, Sydney)$ // a state in package delivery

Planning Domain Definition Language (PDDL)

- ◆ **State**: a conjunction of **ground** atomic **fluents**

no variables	single predicate	time varying aspect

`At(Truck1, Melbourne) ∧ At(Truck2, Sydney)` // a state in package delivery

- ◆ **Database semantics**: any unmentioned fluents are false.

Planning Domain Definition Language (PDDL)

- ◆ **State**: a conjunction of **ground** atomic **fluents**

no variables	single predicate	time varying aspect

`At(Truck1, Melbourne) ∧ At(Truck2, Sydney)` // a state in package delivery

- ◆ **Database semantics**: any unmentioned fluents are false.
- ◆ **Action schema**: a family of ground actions

Planning Domain Definition Language (PDDL)

- ◆ **State**: a conjunction of **ground** atomic **fluents**

no variables	single predicate	time varying aspect

At(Truck₁, Melbourne) ∧ At(Truck₂, Sydney) // a state in package delivery

- ◆ **Database semantics**: any unmentioned fluents are false.
- ◆ **Action schema**: a family of ground actions

Action(Fly(P₁, SFO, JFK),
PRECOND: *At(P₁, SFO) ∧ Plane(P₁) ∧ Airport(SFO) ∧ Airport(JFK)*
POSTCOND: *¬At(P₁, SFO) ∧ At(P₁, JFK)*

Planning Domain Definition Language (PDDL)

- ◆ **State**: a conjunction of **ground** atomic **fluents**

| | |
no variables single time varying aspect
 predicate

At(Truck₁, Melbourne) ∧ At(Truck₂, Sydney) // a state in package delivery

- ◆ **Database semantics**: any unmentioned fluents are false.
- ◆ **Action schema**: a family of ground actions

*Action(Fly(P_1 , SFO, JFK),
PRECOND: $At(P_1, SFO) \wedge Plane(P_1) \wedge Airport(SFO) \wedge Airport(JFK)$
POSTCOND: $\neg At(P_1, SFO) \wedge At(P_1, JFK)$*

An action a is **applicable** in state s if s entails the precondition of a .

Initial State and Goal

- ◆ Result of a in s
- | | | |
|--|-------------|----------|
| | delete list | add list |
| | | |
- $$\text{RESULT}(s, a) = (s - \text{DEL}(a)) \cup \text{ADD}(a)$$
- Remove the negative literals in the action's effects.
 - Add the positive literals in the action's effects.

Initial State and Goal

- ◆ **Result** of a in s
- | | delete list | add list |
|--|-------------|----------|
| | | |
| $\text{RESULT}(s, a) = (s - \text{DEL}(a)) \cup \text{ADD}(a)$ | | |
- Remove the negative literals in the action's effects.
 - Add the positive literals in the action's effects.

Action(Fly(P_1 , SFO, JFK),

PRECOND: $At(P_1, SFO) \wedge Plane(P_1) \wedge Airport(SFO) \wedge Airport(JFK)$

POSTCOND: $\neg At(P_1, SFO) \wedge At(P_1, JFK)$

Initial State and Goal

- ◆ **Result** of a in s
- delete list
|

add list
|
- $$\text{RESULT}(s, a) = (s - \text{DEL}(a)) \cup \text{ADD}(a)$$
- Remove the negative literals in the action's effects.
 - Add the positive literals in the action's effects.

Action(Fly(P_1 , SFO, JFK),

PRECOND: $At(P_1, SFO) \wedge Plane(P_1) \wedge Airport(SFO) \wedge Airport(JFK)$

POSTCOND: $\neg At(P_1, SFO) \wedge At(P_1, JFK)$



Remove $At(P_1, SFO)$ and add $At(P_1, JFK)$.

Initial State and Goal

- ◆ **Result** of a in s
- delete list
|

add list
|
- $$\text{RESULT}(s, a) = (s - \text{DEL}(a)) \cup \text{ADD}(a)$$
- Remove the negative literals in the action's effects.
 - Add the positive literals in the action's effects.

Action(Fly(P_1 , SFO, JFK),

PRECOND: $At(P_1, SFO) \wedge Plane(P_1) \wedge Airport(SFO) \wedge Airport(JFK)$

POSTCOND: $\neg At(P_1, SFO) \wedge At(P_1, JFK)$



Remove $At(P_1, SFO)$ and add $At(P_1, JFK)$.

- ◆ **Initial state**: conjunction of ground fluents

Initial State and Goal

- ◆ **Result** of a in s
- | | delete list | add list |
|--|-------------|----------|
| | | |
| $\text{RESULT}(s, a) = (s - \text{DEL}(a)) \cup \text{ADD}(a)$ | | |
| <ul style="list-style-type: none">• Remove the negative literals in the action's effects.• Add the positive literals in the action's effects. | | |

Action(Fly(P_1 , SFO, JFK),

PRECOND: $At(P_1, SFO) \wedge Plane(P_1) \wedge Airport(SFO) \wedge Airport(JFK)$

POSTCOND: $\neg At(P_1, SFO) \wedge At(P_1, JFK)$



Remove $At(P_1, SFO)$ and add $At(P_1, JFK)$.

- ◆ **Initial state**: conjunction of ground fluents
- ◆ **Goal**: conjunction of literals (positive or negative) possibly with variables

$At(C_1, JFK) \wedge \neg At(C_2, SFO) \wedge At(p, JFK)$

II. Example 1: Air Cargo Transport

- Three actions: *Load*, *Unload*, and *Fly*.
- Predicate $In(c, p)$: cargo c is inside plane p .
- Predicate $At(x, a)$: object x (either plane or cargo) is at airport a .

II. Example 1: Air Cargo Transport

- Three actions: *Load*, *Unload*, and *Fly*.
- Predicate $In(c, p)$: cargo c is inside plane p .
- Predicate $At(x, a)$: object x (either plane or cargo) is at airport a .

PPDL:

$Init(At(C_1, SFO) \wedge At(C_2, JFK) \wedge At(P_1, SFO) \wedge At(P_2, JFK)$
 $\wedge Cargo(C_1) \wedge Cargo(C_2) \wedge Plane(P_1) \wedge Plane(P_2)$
 $\wedge Airport(JFK) \wedge Airport(SFO))$
 $Goal(At(C_1, JFK) \wedge At(C_2, SFO))$
 $Action(Load(c, p, a),$
 PRECOND: $At(c, a) \wedge At(p, a) \wedge Cargo(c) \wedge Plane(p) \wedge Airport(a)$
 EFFECT: $\neg At(c, a) \wedge In(c, p)$)
 $Action(Unload(c, p, a),$
 PRECOND: $In(c, p) \wedge At(p, a) \wedge Cargo(c) \wedge Plane(p) \wedge Airport(a)$
 EFFECT: $At(c, a) \wedge \neg In(c, p)$)
 $Action(Fly(p, from, to),$
 PRECOND: $At(p, from) \wedge Plane(p) \wedge Airport(from) \wedge Airport(to)$
 EFFECT: $\neg At(p, from) \wedge At(p, to)$)

Example 1 (cont'd)

- ♣ When a plane flies from one airport to another, all the cargo inside the plane goes with it.
 - ◆ PDDL does not have \forall , instead we say that a piece of cargo ceases to be *At* anywhere when it is *In* a plane.
 - ◆ Namely, the cargo only becomes *At* the new airport when it is unloaded.

Example 1 (cont'd)

- ♣ When a plane flies from one airport to another, all the cargo inside the plane goes with it.
 - ◆ PDDL does not have \forall , instead we say that a piece of cargo ceases to be *At* anywhere when it is *In* a plane.
 - ◆ Namely, the cargo only becomes *At* the new airport when it is unloaded.

Plan:

[*Load*(C_1, P_1, SFO), *Fly*(P_1, SFO, JFK), *Unload*(C_1, P_1, JFK),
Load(C_2, P_2, JFK), *Fly*(P_2, JFK, SFO), *Unload*(C_2, P_2, SFO)]

Example 2: The Spare Tire Problem

- Goal: mount a good spare tire properly onto the car's axle.
- Initial state: a flat tire on the axle and a good tire in the trunk.

Example 2: The Spare Tire Problem

- Goal: mount a good spare tire properly onto the car's axle.
- Initial state: a flat tire on the axle and a good tire in the trunk.
- Four actions:
 - ♦ removing the spare tire from the trunk.
 - ♦ removing the flat tire from the axle.
 - ♦ putting the spare tire on the axle.
 - ♦ leaving the car unattended overnight.

Example 2 (cont'd)

Init(*Tire*(*Flat*) \wedge *Tire*(*Spare*) \wedge *At*(*Flat*, *Axle*) \wedge *At*(*Spare*, *Trunk*))

Goal(*At*(*Spare*, *Axle*))

Action(*Remove*(*obj*, *loc*),

 PRECOND: *At*(*obj*, *loc*)

 EFFECT: \neg *At*(*obj*, *loc*) \wedge *At*(*obj*, *Ground*))

Action(*PutOn*(*t*, *Axle*),

 PRECOND: *Tire*(*t*) \wedge *At*(*t*, *Ground*) \wedge \neg *At*(*Flat*, *Axle*) \wedge \neg *At*(*Spare*, *Axle*)

 EFFECT: \neg *At*(*t*, *Ground*) \wedge *At*(*t*, *Axle*))

Action(*LeaveOvernight*,

 PRECOND:


 EFFECT: \neg *At*(*Spare*, *Ground*) \wedge \neg *At*(*Spare*, *Axle*) \wedge \neg *At*(*Spare*, *Trunk*)
 \wedge \neg *At*(*Flat*, *Ground*) \wedge \neg *At*(*Flat*, *Axle*) \wedge \neg *At*(*Flat*, *Trunk*))

// Tires will disappear because the car is parked in a bad


// neighborhood.

Example 3: The Blocks World

- Identical cube-shaped blocks sit on a table.
- Blocks can be stacked one on top of another.
- A robotic arm can pick up a block one at a time (thus it cannot pick up a block with another one on top of it.)
- The robotic arm can place the block either on the table or on top of another block.




Start State



Goal State


Building a Three-Block Tower

$Init(On(A, Table) \wedge On(B, Table) \wedge On(C, A)$
 $\wedge Block(A) \wedge Block(B) \wedge Block(C) \wedge Clear(B) \wedge Clear(C) \wedge Clear(Table))$
 $Goal(On(A, B) \wedge On(B, C))$
 $Action(Move(b, x, y),$
 PRECOND: $On(b, x) \wedge Clear(b) \wedge Clear(y) \wedge Block(b) \wedge Block(y) \wedge$
 $(b \neq x) \wedge (b \neq y) \wedge (x \neq y),$
 EFFECT: $On(b, y) \wedge Clear(x) \wedge \neg On(b, x) \wedge \neg Clear(y))$
 $Action(MoveToTable(b, x),$
 PRECOND: $On(b, x) \wedge Clear(b) \wedge Block(b) \wedge Block(x),$
 EFFECT: $On(b, Table) \wedge Clear(x) \wedge \neg On(b, x))$




Building a Three-Block Tower

$Init(On(A, Table) \wedge On(B, Table) \wedge On(C, A)$
 $\wedge Block(A) \wedge Block(B) \wedge Block(C) \wedge Clear(B) \wedge Clear(C) \wedge Clear(Table))$
 $Goal(On(A, B) \wedge On(B, C))$
 $Action(Move(b, x, y),$ // move block b from the top of x to the top of y .
PRECOND: $On(b, x) \wedge Clear(b) \wedge Clear(y) \wedge Block(b) \wedge Block(y) \wedge$
 $(b \neq x) \wedge (b \neq y) \wedge (x \neq y),$
EFFECT: $On(b, y) \wedge Clear(x) \wedge \neg On(b, x) \wedge \neg Clear(y))$
 $Action(MoveToTable(b, x),$
PRECOND: $On(b, x) \wedge Clear(b) \wedge Block(b) \wedge Block(x),$
EFFECT: $On(b, Table) \wedge Clear(x) \wedge \neg On(b, x))$




Building a Three-Block Tower

$Init(On(A, Table) \wedge On(B, Table) \wedge On(C, A)$
 $\wedge Block(A) \wedge Block(B) \wedge Block(C) \wedge Clear(B) \wedge Clear(C) \wedge Clear(Table))$
 $Goal(On(A, B) \wedge On(B, C))$
 $Action(Move(b, x, y),$ // move block b from the top of x to the top of y .
PRECOND: $On(b, x) \wedge Clear(b) \wedge Clear(y) \wedge Block(b) \wedge Block(y) \wedge$
 $(b \neq x) \wedge (b \neq y) \wedge (x \neq y),$ // neither x nor y can be the table (which does not need
EFFECT: $On(b, y) \wedge Clear(x) \wedge \neg On(b, x) \wedge \neg Clear(y))$ // to be clear before or after
 $Action(MoveToTable(b, x),$ // the move).
PRECOND: $On(b, x) \wedge Clear(b) \wedge Block(b) \wedge Block(x),$
EFFECT: $On(b, Table) \wedge Clear(x) \wedge \neg On(b, x))$



Building a Three-Block Tower

$Init(On(A, Table) \wedge On(B, Table) \wedge On(C, A)$
 $\wedge Block(A) \wedge Block(B) \wedge Block(C) \wedge Clear(B) \wedge Clear(C) \wedge Clear(Table))$
 $Goal(On(A, B) \wedge On(B, C))$
 $Action(Move(b, x, y),$ // move block b from the top of x to the top of y .
PRECOND: $On(b, x) \wedge Clear(b) \wedge Clear(y) \wedge Block(b) \wedge Block(y) \wedge$
 $(b \neq x) \wedge (b \neq y) \wedge (x \neq y),$ // neither x nor y can be the table (which does not need
EFFECT: $On(b, y) \wedge Clear(x) \wedge \neg On(b, x) \wedge \neg Clear(y))$ // to be clear before or after
 $Action(MoveToTable(b, x),$ // the move).
PRECOND: $On(b, x) \wedge Clear(b) \wedge Block(b) \wedge Block(x),$
EFFECT: $On(b, Table) \wedge Clear(x) \wedge \neg On(b, x))$



Planning: Forward State-Space Search

Any of the heuristic search algorithms is applicable.

Planning: Forward State-Space Search

Any of the heuristic search algorithms is applicable.

- ◆ $\text{Actions}(s)$, applicable actions in a state s , are grounded instantiations of the *action schemas* from replacing variables with constant values.

Planning: Forward State-Space Search

Any of the heuristic search algorithms is applicable.

- ◆ Actions(s), applicable actions in a state s , are grounded instantiations of the *action schemas* from replacing variables with constant values.

$At(obj, loc)$

variables

Planning: Forward State-Space Search

Any of the heuristic search algorithms is applicable.

- ◆ $\text{Actions}(s)$, applicable actions in a state s , are grounded instantiations of the *action schemas* from replacing variables with constant values.

$At(obj, loc)$

variables

- Unify the current state with the preconditions of every action schema.



Apply the substitution θ to yield a ground action.

Planning: Forward State-Space Search

Any of the heuristic search algorithms is applicable.

- ◆ Actions(s), applicable actions in a state s , are grounded instantiations of the *action schemas* from replacing variables with constant values.

$At(obj, loc)$

variables

- Unify the current state with the preconditions of every action schema.



Apply the substitution θ to yield a ground action.

- Each schema may unify in multiple ways.

$At(obj, loc)$

$At(Flat, Axle)$

$At(Spare, Trunk)$

Planning: Forward State-Space Search

Any of the heuristic search algorithms is applicable.

- ◆ Actions(s), applicable actions in a state s , are grounded instantiations of the *action schemas* from replacing variables with constant values.

$At(obj, loc)$

variables

- Unify the current state with the preconditions of every action schema.



Apply the substitution θ to yield a ground action.

- Each schema may unify in multiple ways.

$At(obj, loc)$

$At(Flat, Axle)$

$At(Spare, Trunk)$

$\theta = \{obj/Flat, loc/Axle\}$

Planning: Forward State-Space Search

Any of the heuristic search algorithms is applicable.

- ◆ Actions(s), applicable actions in a state s , are grounded instantiations of the *action schemas* from replacing variables with constant values.

$At(obj, loc)$

variables

- Unify the current state with the preconditions of every action schema.



Apply the substitution θ to yield a ground action.

- Each schema may unify in multiple ways.

$At(obj, loc)$

$At(Flat, Axle)$

$At(Spare, Trunk)$

$\theta = \{obj/Flat, loc/Axle\}$

$\theta = \{obj/Spare, loc/Trunk\}$


Combinatorial Explosion

State space can get too big if we match a state with every action in every possible way!

Combinatorial Explosion

State space can get too big if we match a state with every action in every possible way!


Airport cargo problem



Combinatorial Explosion

State space can get too big if we match a state with every action in every possible way!

Airport cargo problem




- 10 airports, 5 planes and 20 pieces of cargo per airport initially.
- Goal: move all the cargos at airport A to airport B .

Combinatorial Explosion

State space can get too big if we match a state with every action in every possible way!

Airport cargo problem



- 10 airports, 5 planes and 20 pieces of cargo per airport initially.
- Goal: move all the cargos at airport A to airport B .
- Huge average branching factor.
 - ♣ Each of the 50 planes can fly to 9 other airports.
 - ♣ Each of the 200 pieces of cargo can be either unloaded from or loaded into any plane at its airport.

Backward (Regression) Search


Consider *relevant* not just applicable actions.

|
unifying with one of the goal literals,
but not negating any part of the goal.

Backward (Regression) Search

Consider *relevant* not just applicable actions.


unifying with one of the goal literals,
but not negating any part of the goal.



Backward (Regression) Search

Consider *relevant* not just applicable actions.

unifying with one of the goal literals,
but not negating any part of the goal.



Given a goal g and an action a , regression from g over a yields a state g' :


positive
literals

$$\text{Pos}(g') = (\text{Pos}(g) - \text{Add}(a)) \cup \text{Pos}(\text{Precond}(a))$$

Backward (Regression) Search

Consider *relevant* not just applicable actions.

unifying with one of the goal literals,
but not negating any part of the goal.



Given a goal g and an action a , regression from g over a yields a state g' :

positive
literals

$$\text{POS}(g') = (\text{POS}(g) - \text{ADD}(a)) \cup \text{POS}(\text{Precond}(a))$$

negative
literals

$$\text{NEG}(g') = (\text{NEG}(g) + \text{DEL}(a)) \cup \text{NEG}(\text{Precond}(a))$$

Example

Goal: $g = At(C_2, SFO)$

Action(Unload(c, p, a),

PRECOND: $In(c, p) \wedge At(p, a) \wedge Cargo(c) \wedge Plane(p) \wedge Airport(a)$

EFFECT: $At(c, a) \wedge \neg In(c, p)$)

Example

Goal: $g = At(C_2, SFO)$

Action(Unload(c, p, a),

PRECOND: $In(c, p) \wedge At(p, a) \wedge Cargo(c) \wedge Plane(p) \wedge Airport(a)$

EFFECT: $At(c, a) \wedge \neg In(c, p)$


Example

Goal: $g = At(C_2, SFO)$

Action(Unload(c, p, a),

PRECOND: $In(c, p) \wedge At(p, a) \wedge Cargo(c) \wedge Plane(p) \wedge Airport(a)$

EFFECT: $At(c, a) \wedge \neg In(c, p)$




Example

Goal: $g = At(C_2, SFO)$

Action(Unload(c, p, a),

PRECOND: $In(c, p) \wedge At(p, a) \wedge Cargo(c) \wedge Plane(p) \wedge Airport(a)$

EFFECT: $At(c, a) \wedge \neg In(c, p)$



Unification under θ yields a new goal:

$g' = In(C_2, p') \wedge At(p', SFO) \wedge Cargo(C_2) \wedge Plane(p') \wedge Airport(SFO)$

name standardization
not to conflict p


Example

Goal: $g = At(C_2, SFO)$

Action(Unload(c, p, a),

PRECOND: $In(c, p) \wedge At(p, a) \wedge Cargo(c) \wedge Plane(p) \wedge Airport(a)$

EFFECT: $At(c, a) \wedge \neg In(c, p)$



Unification under θ yields a new goal:

$g' = In(C_2, p') \wedge At(p', SFO) \wedge Cargo(C_2) \wedge Plane(p') \wedge Airport(SFO)$

name standardization
not to conflict p