

Using First-Order Logic

Outline

I. Assertions and queries

II. Numbers and sets in FOL

III. The wumpus world in FOL

I. Knowledge Engineering

A field of AI dedicated to representing information about the world in a form that can be utilized by a computer to solve complex tasks such as:

- medical diagnosis
 - dialog in a natural language
 - etc.
-
- ♦ Knowledge representation (logical rules, semantic nets, frames, etc.)
 - ♦ Automated reasoning (inference engines, theorem provers, etc.)

I. Knowledge Engineering

A field of AI dedicated to representing information about the world in a form that can be utilized by a computer to solve complex tasks such as:

- medical diagnosis
 - dialog in a natural language
 - etc.
-
- ♦ Knowledge representation (logical rules, semantic nets, frames, etc.)
 - ♦ Automated reasoning (inference engines, theorem provers, etc.)

A *domain* is some part of the world about which we wish to express some knowledge.

Assertions and Queries in FOL

- ♣ Add sentences, called *assertions*, to a KB using TELL.

TELL(*KB*, *Likes*(John, *Icecream*))

TELL(*KB*, *Father*(Zeus, Athena))

TELL(*KB*, $\forall x \exists y \text{ Brother}(x, y) \Rightarrow \text{Sibling}(x, y)$)

Assertions and Queries in FOL

- ♣ Add sentences, called *assertions*, to a KB using TELL.

TELL(*KB*, *Likes*(John, *Icecream*))

TELL(*KB*, *Father*(Zeus, Athena))

TELL(*KB*, $\forall x \exists y \text{ Brother}(x, y) \Rightarrow \text{Sibiling}(x, y)$)

- ♣ Ask the KB questions using ASK.

ASK(*KB*, *Likes*(John, *Icecream*))

Assertions and Queries in FOL

- ♣ Add sentences, called *assertions*, to a KB using TELL.

TELL(*KB*, *Likes*(John, *Icecream*))

TELL(*KB*, *Father*(Zeus, Athena))

TELL(*KB*, $\forall x \exists y \text{ Brother}(x, y) \Rightarrow \text{Sibiling}(x, y)$)

- ♣ Ask the KB questions using ASK.

ASK(*KB*, *Likes*(John, *Icecream*))



Query: question asked

Assertions and Queries in FOL

- ♣ Add sentences, called *assertions*, to a KB using TELL.

TELL(*KB*, *Likes*(John, *Icecream*))

TELL(*KB*, *Father*(Zeus, Athena))

TELL(*KB*, $\forall x \exists y \text{ Brother}(x, y) \Rightarrow \text{Sibiling}(x, y)$)

- ♣ Ask the KB questions using ASK.

ASK(*KB*, *Likes*(John, *Icecream*))



Query: question asked

Any query is entailed by the KB should be answered affirmatively.

Substitution

Suppose another KB has the following predicates:

Bird(Swan), *Bird*(Crane), *Bird*(Parrot),

- Quantified query

$\text{Ask}(KB, \exists x \text{ Bird}(x))$

Substitution

Suppose another KB has the following predicates:

Bird(Swan), *Bird*(Crane), *Bird*(Parrot),

- Quantified query

Ask(*KB*, $\exists x$ *Bird*(*x*)) returns *true*

Substitution

Suppose another KB has the following predicates:

Bird(Swan), *Bird*(Crane), *Bird*(Parrot),

- Quantified query

ASK(*KB*, $\exists x$ *Bird*(*x*)) returns *true*

- To know what values of *x* make the sentence true

ASKVARS(*KB*, *Bird*(*x*))

Substitution

Suppose another KB has the following predicates:

Bird(Swan), *Bird*(Crane), *Bird*(Parrot),

- Quantified query

$\text{ASK}(\text{KB}, \exists x \text{ Bird}(x))$ returns *true*

- To know what values of x make the sentence true

$\text{ASKVARS}(\text{KB}, \text{Bird}(x))$

The query returns

$\{x / \text{Swan}\}, \{x / \text{Crane}\}, \text{ and } \{x / \text{Parrot}\}$

Substitution

Suppose another KB has the following predicates:

Bird(Swan), *Bird*(Crane), *Bird*(Parrot),

- Quantified query

$\text{ASK}(\text{KB}, \exists x \text{ Bird}(x))$ returns *true*

- To know what values of x make the sentence true

$\text{ASKVARS}(\text{KB}, \text{Bird}(x))$

The query returns

$\{x / \text{Swan}\}, \{x / \text{Crane}\}, \text{ and } \{x / \text{Parrot}\}$



substitution or *binding list*

The Kinship Domain

Kinship relations are represented by binary predicates.

// One's mother is the person's female parent.

$\forall m, c \text{ Mother}(c) = m \Leftrightarrow \text{Female}(m) \wedge \text{Parent}(m, c)$

The Kinship Domain

Kinship relations are represented by binary predicates.

// One's mother is the person's female parent.

$\forall m, c \text{ Mother}(c) = m \Leftrightarrow \text{Female}(m) \wedge \text{Parent}(m, c)$

// One's husband is the person's male spouse.

$\forall w, h \text{ Husband}(h, w) \Leftrightarrow \text{Male}(h) \wedge \text{Spouse}(h, w)$

The Kinship Domain

Kinship relations are represented by binary predicates.

// One's mother is the person's female parent.

$\forall m, c \text{ Mother}(c) = m \Leftrightarrow \text{Female}(m) \wedge \text{Parent}(m, c)$

// One's husband is the person's male spouse.

$\forall w, h \text{ Husband}(h, w) \Leftrightarrow \text{Male}(h) \wedge \text{Spouse}(h, w)$

// Parent and child are inverse relations.

$\forall p, c \text{ Parent}(p, c) \Leftrightarrow \text{Child}(c, p)$

The Kinship Domain

Kinship relations are represented by binary predicates.

// One's mother is the person's female parent.

$\forall m, c \text{ Mother}(c) = m \Leftrightarrow \text{Female}(m) \wedge \text{Parent}(m, c)$

// One's husband is the person's male spouse.

$\forall w, h \text{ Husband}(h, w) \Leftrightarrow \text{Male}(h) \wedge \text{Spouse}(h, w)$

// Parent and child are inverse relations.

$\forall p, c \text{ Parent}(p, c) \Leftrightarrow \text{Child}(c, p)$

// A grand parent is a parent of one's parent

$\forall g, c \text{ GrandParent}(g, c) \Leftrightarrow \exists p (\text{Parent}(g, p) \wedge \text{Parent}(p, c))$

The Kinship Domain

Kinship relations are represented by binary predicates.

// One's mother is the person's female parent.

$\forall m, c \text{ Mother}(c) = m \Leftrightarrow \text{Female}(m) \wedge \text{Parent}(m, c)$

// One's husband is the person's male spouse.

$\forall w, h \text{ Husband}(h, w) \Leftrightarrow \text{Male}(h) \wedge \text{Spouse}(h, w)$

// Parent and child are inverse relations.

$\forall p, c \text{ Parent}(p, c) \Leftrightarrow \text{Child}(c, p)$

// A grand parent is a parent of one's parent

$\forall g, c \text{ GrandParent}(g, c) \Leftrightarrow \exists p (\text{Parent}(g, p) \wedge \text{Parent}(p, c))$

// A sibling is another child of one's parent

$\forall x, s \text{ Sibling}(x, s) \Leftrightarrow x \neq s \wedge \exists p (\text{Parent}(p, x) \wedge \text{Parent}(p, s))$

The Kinship Domain

Kinship relations are represented by binary predicates.

Axioms

// One's mother is the person's female parent.

$\forall m, c \text{ Mother}(c) = m \Leftrightarrow \text{Female}(m) \wedge \text{Parent}(m, c)$

// One's husband is the person's male spouse.

$\forall w, h \text{ Husband}(h, w) \Leftrightarrow \text{Male}(h) \wedge \text{Spouse}(h, w)$

// Parent and child are inverse relations.

$\forall p, c \text{ Parent}(p, c) \Leftrightarrow \text{Child}(c, p)$

// A grand parent is a parent of one's parent

$\forall g, c \text{ GrandParent}(g, c) \Leftrightarrow \exists p (\text{Parent}(g, p) \wedge \text{Parent}(p, c))$

// A sibling is another child of one's parent

$\forall x, s \text{ Sibling}(x, s) \Leftrightarrow x \neq s \wedge \exists p (\text{Parent}(p, x) \wedge \text{Parent}(p, s))$

The Kinship Domain

Kinship relations are represented by binary predicates.

Axioms

// One's mother is the person's female parent.

$\forall m, c \text{ Mother}(c) = m \Leftrightarrow \text{Female}(m) \wedge \text{Parent}(m, c)$

// One's husband is the person's male spouse.

$\forall w, h \text{ Husband}(h, w) \Leftrightarrow \text{Male}(h) \wedge \text{Spouse}(h, w)$

// Parent and child are inverse relations.

$\forall p, c \text{ Parent}(p, c) \Leftrightarrow \text{Child}(c, p)$

// A grand parent is a parent of one's parent

$\forall g, c \text{ GrandParent}(g, c) \Leftrightarrow \exists p (\text{Parent}(g, p) \wedge \text{Parent}(p, c))$

// A sibling is another child of one's parent

$\forall x, s \text{ Sibling}(x, s) \Leftrightarrow x \neq s \wedge \exists p (\text{Parent}(p, x) \wedge \text{Parent}(p, s))$

These are *definitions* in the form of $\forall x, y P(x, y) \Leftrightarrow \dots$ and built upon a basic set of predicates *Child*, *Male*, *Female*, etc.

Axioms and Theorems

♠ *Axioms* in a domain are logical sentences that are taken to be true without being derived.

♠ *Theorems* are logical sentences entailed by axioms.

Axioms and Theorems

♠ *Axioms* in a domain are logical sentences that are taken to be true without being derived.

♠ *Theorems* are logical sentences entailed by axioms.

$\forall x, y \text{ Sibling}(x, y) \Leftrightarrow \text{Sibling}(y, x)$

// entailed by

// $\forall x, s \text{ Sibling}(x, s) \Leftrightarrow x \neq s \wedge \exists p (\text{Parent}(p, x) \wedge \text{Parent}(p, s))$

Axioms and Theorems

♠ *Axioms* in a domain are logical sentences that are taken to be true without being derived.

♠ *Theorems* are logical sentences entailed by axioms.

$\forall x, y \text{ Sibling}(x, y) \Leftrightarrow \text{Sibling}(y, x)$

// entailed by

// $\forall x, s \text{ Sibling}(x, s) \Leftrightarrow x \neq s \wedge \exists p (\text{Parent}(p, x) \wedge \text{Parent}(p, s))$

ASK(*KB*, $\forall x, y \text{ Sibling}(x, y) \Leftrightarrow \text{Sibling}(y, x)$) should return *true*.

Axioms and Theorems

♠ *Axioms* in a domain are logical sentences that are taken to be true without being derived.

♠ *Theorems* are logical sentences entailed by axioms.

$\forall x, y \text{ Sibling}(x, y) \Leftrightarrow \text{Sibling}(y, x)$

// entailed by

// $\forall x, s \text{ Sibling}(x, s) \Leftrightarrow x \neq s \wedge \exists p (\text{Parent}(p, x) \wedge \text{Parent}(p, s))$

$\text{Ask}(\text{KB}, \forall x, y \text{ Sibling}(x, y) \Leftrightarrow \text{Sibling}(y, x))$ should return *true*.

♠ Some axioms are not definitions.

$\forall x \text{ Person}(x) \Leftrightarrow \dots$

// no clear way to define

Axioms and Theorems

♠ *Axioms* in a domain are logical sentences that are taken to be true without being derived.

♠ *Theorems* are logical sentences entailed by axioms.

$\forall x, y \text{ Sibling}(x, y) \Leftrightarrow \text{Sibling}(y, x)$

// entailed by

// $\forall x, s \text{ Sibling}(x, s) \Leftrightarrow x \neq s \wedge \exists p (\text{Parent}(p, x) \wedge \text{Parent}(p, s))$

ASK(*KB*, $\forall x, y \text{ Sibling}(x, y) \Leftrightarrow \text{Sibling}(y, x)$) should return *true*.

♠ Some axioms are not definitions.

$\forall x \text{ Person}(x) \Leftrightarrow \dots$

// no clear way to define

♠ Some predicates have no complete definitions.

Axioms and Theorems

♠ *Axioms* in a domain are logical sentences that are taken to be true without being derived.

♠ *Theorems* are logical sentences entailed by axioms.

$\forall x, y \text{ Sibling}(x, y) \Leftrightarrow \text{Sibling}(y, x)$

// entailed by

// $\forall x, s \text{ Sibling}(x, s) \Leftrightarrow x \neq s \wedge \exists p (\text{Parent}(p, x) \wedge \text{Parent}(p, s))$

$\text{Ask}(\text{KB}, \forall x, y \text{ Sibling}(x, y) \Leftrightarrow \text{Sibling}(y, x))$ should return *true*.

♠ Some axioms are not definitions.

$\forall x \text{ Person}(x) \Leftrightarrow \dots$

// no clear way to define

♠ Some predicates have no complete definitions.

$\forall x \text{ Person}(x) \Rightarrow \dots$

// partial specification of

$\forall x \dots \Rightarrow \text{Person}(x)$

// properties

II. Domain of Natural Numbers

Describe the theory of natural numbers using merely:

- one constant symbol, 0
- one function symbol, S (successor)
- one predicate, $NatNum$

II. Domain of Natural Numbers

Describe the theory of natural numbers using merely:

- one constant symbol, 0
- one function symbol, S (successor)
- one predicate, $NatNum$

♦ Recursive definition:

$$NatNum(0)$$

$$\forall n \, NatNum(n) \Rightarrow NatNum(S(n))$$

II. Domain of Natural Numbers

Describe the theory of natural numbers using merely:

- one constant symbol, 0
- one function symbol, S (successor)
- one predicate, $NatNum$

♦ Recursive definition:

$$NatNum(0)$$

$$\forall n \text{ } NatNum(n) \Rightarrow NatNum(S(n))$$

♦ Axioms to constrain the successor function:

$$\forall n \text{ } 0 \neq S(n)$$

$$\forall m, n \text{ } m \neq n \Rightarrow S(m) \neq S(n)$$

Defining Addition

$$\forall m \text{ NatNum}(m) \Rightarrow +(0, m) = m$$

Defining Addition

$$\forall m \text{ NatNum}(m) \Rightarrow \underbrace{+(0, m)}_{\text{prefix notation}} = m$$


prefix notation

Defining Addition

$$\forall m \text{ NatNum}(m) \Rightarrow +(0, m) = m$$

prefix notation

$$\forall m \text{ NatNum}(m) \Rightarrow 0 + m = m$$



Use infix notation
for readability.


Defining Addition

$$\forall m \text{ NatNum}(m) \Rightarrow +(0, m) = m$$

prefix notation

$$\forall m \text{ NatNum}(m) \Rightarrow 0 + m = m$$

infix notation



Use infix notation
for readability.

Defining Addition

$$\forall m \text{ NatNum}(m) \Rightarrow +(0, m) = m$$

prefix notation

$$\forall m \text{ NatNum}(m) \Rightarrow 0 + m = m$$

infix notation

Use infix notation
for readability.

$$\forall m, n \text{ NatNum}(m) \wedge \text{NatNum}(n) \Rightarrow +(S(m), n) = S(+ (m, n))$$

Defining Addition

$$\forall m \text{ NatNum}(m) \Rightarrow +(0, m) = m$$

prefix notation

$$\forall m \text{ NatNum}(m) \Rightarrow 0 + m = m$$

infix notation

Use infix notation
for readability.

$$\forall m, n \text{ NatNum}(m) \wedge \text{NatNum}(n) \Rightarrow +(S(m), n) = S(+(m, n))$$

Write $S(n)$
as $n + 1$.

$$\forall m, n \text{ NatNum}(m) \wedge \text{NatNum}(n) \Rightarrow (m + 1) + n = (m + n) + 1$$

Defining Addition

$$\forall m \text{ NatNum}(m) \Rightarrow +(0, m) = m$$

prefix notation

$$\forall m \text{ NatNum}(m) \Rightarrow 0 + m = m$$

infix notation

Use infix notation
for readability.

Syntactic sugar:
an extension to the
standard syntax that
does not change
the semantics but
improves readability.

$$\forall m, n \text{ NatNum}(m) \wedge \text{NatNum}(n) \Rightarrow +(S(m), n) = S(+(m, n))$$

Write $S(n)$
as $n + 1$.

$$\forall m, n \text{ NatNum}(m) \wedge \text{NatNum}(n) \Rightarrow (m + 1) + n = (m + n) + 1$$

Defining Addition

$$\forall m \text{ NatNum}(m) \Rightarrow +(0, m) = m$$

prefix notation

$$\forall m \text{ NatNum}(m) \Rightarrow 0 + m = m$$

infix notation

$$\forall m, n \text{ NatNum}(m) \wedge \text{NatNum}(n) \Rightarrow +(S(m), n) = S(+(m, n))$$

$$\boxed{\forall m, n \text{ NatNum}(m) \wedge \text{NatNum}(n) \Rightarrow (m + 1) + n = (m + n) + 1}$$

Use infix notation
for readability.

Syntactic sugar:
an extension to the
standard syntax that
does not change
the semantics but
improves readability.

Write $S(n)$
as $n + 1$.

Syntactic sugar: $\forall m \forall n$
according to syntax

Defining Addition

$$\forall m \text{ NatNum}(m) \Rightarrow +(0, m) = m$$

prefix notation

$$\forall m \text{ NatNum}(m) \Rightarrow 0 + m = m$$

infix notation

$$\forall m, n \text{ NatNum}(m) \wedge \text{NatNum}(n) \Rightarrow +(S(m), n) = S(+(m, n))$$

$$\boxed{\forall m, n \text{ NatNum}(m) \wedge \text{NatNum}(n) \Rightarrow (m + 1) + n = (m + n) + 1}$$

Use infix notation
for readability.

Syntactic sugar:
an extension to the
standard syntax that
does not change
the semantics but
improves readability.

Write $S(n)$
as $n + 1$.

Syntactic sugar: $\forall m \forall n$
according to syntax

Domain of Sets

Syntactic sugar:

- $\{\}$ for the empty set
- One unary predicate, *Set*

Domain of Sets

Syntactic sugar:

- $\{\}$ for the empty set
- One unary predicate, *Set*
- Binary predicate, \in

e.g., $x \in s$ (x is a member of set s)

Domain of Sets

Syntactic sugar:

- $\{\}$ for the empty set
- One unary predicate, *Set*
- Binary predicate, \in

e.g., $x \in s$ (x is a member of set s)

- Binary predicate, \subseteq

e.g., $s_1 \subseteq s_2$ (set s_1 is a subset of set s_2)

Domain of Sets

Syntactic sugar:

- $\{\}$ for the empty set
- One unary predicate, *Set*
- Binary predicate, \in
e.g., $x \in s$ (x is a member of set s)
- Binary predicate, \subseteq
e.g., $s_1 \subseteq s_2$ (set s_1 is a subset of set s_2)
- Binary functions, \cap (intersection), \cup (union), *Add*
 $s_1 \cap s_2$

Domain of Sets

Syntactic sugar:

- $\{\}$ for the empty set
- One unary predicate, *Set*
- Binary predicate, \in
e.g., $x \in s$ (x is a member of set s)
- Binary predicate, \subseteq
e.g., $s_1 \subseteq s_2$ (set s_1 is a subset of set s_2)
- Binary functions, \cap (intersection), \cup (union), *Add*
 $s_1 \cap s_2$ $s_1 \cup s_2$

Domain of Sets

Syntactic sugar:

- $\{\}$ for the empty set
- One unary predicate, *Set*
- Binary predicate, \in

e.g., $x \in s$ (x is a member of set s)

- Binary predicate, \subseteq

e.g., $s_1 \subseteq s_2$ (set s_1 is a subset of set s_2)

- Binary functions, \cap (intersection), \cup (union), *Add*

$s_1 \cap s_2$ $s_1 \cup s_2$ *Add*(x, s)

|

the set resulting from add
element x to set s

Eight Axioms for Sets

- ♦ A set is either an empty set or made by adding something to a set.

$$\forall s \text{ Set}(s) \Leftrightarrow (s = \{\}) \vee (\exists x, s_0 \text{ Set}(s_0) \wedge s = \text{Add}(x, s_0))$$

Eight Axioms for Sets

- ♦ A set is either an empty set or made by adding something to a set.

$$\forall s \text{ Set}(s) \Leftrightarrow (s = \{\}) \vee (\exists x, s_0 \text{ Set}(s_0) \wedge s = \text{Add}(x, s_0))$$

- ♦ The empty set has no elements added to it.

$$\neg \exists x, s \text{ Add}(x, s) = \{\}$$

// equivalently, no way to decompose $\{\}$
// into a smaller set and an element

Eight Axioms for Sets

- ♦ A set is either an empty set or made by adding something to a set.

$$\forall s \text{ Set}(s) \Leftrightarrow (s = \{\}) \vee (\exists x, s_0 \text{ Set}(s_0) \wedge s = \text{Add}(x, s_0))$$

- ♦ The empty set has no elements added to it.

$$\neg \exists x, s \text{ Add}(x, s) = \{\}$$

// equivalently, no way to decompose $\{\}$
// into a smaller set and an element

- ♦ Adding an element already in the set has no effect.

$$\forall x, s \quad x \in s \Leftrightarrow s = \text{Add}(x, s)$$

Eight Axioms for Sets

- ◆ A set is either an empty set or made by adding something to a set.

$$\forall s \text{ Set}(s) \Leftrightarrow (s = \{\}) \vee (\exists x, s_0 \text{ Set}(s_0) \wedge s = \text{Add}(x, s_0))$$

- ◆ The empty set has no elements added to it.

$$\neg \exists x, s \text{ Add}(x, s) = \{\}$$

// equivalently, no way to decompose $\{\}$
// into a smaller set and an element

- ◆ Adding an element already in the set has no effect.

$$\forall x, s \quad x \in s \Leftrightarrow s = \text{Add}(x, s)$$

- ◆ The only members of set are the added elements.

Eight Axioms for Sets

- ◆ A set is either an empty set or made by adding something to a set.

$$\forall s \text{ Set}(s) \Leftrightarrow (s = \{\}) \vee (\exists x, s_0 \text{ Set}(s_0) \wedge s = \text{Add}(x, s_0))$$

- ◆ The empty set has no elements added to it.

$$\neg \exists x, s \text{ Add}(x, s) = \{\}$$

// equivalently, no way to decompose $\{\}$
// into a smaller set and an element

- ◆ Adding an element already in the set has no effect.

$$\forall x, s \quad x \in s \Leftrightarrow s = \text{Add}(x, s)$$

- ◆ The only members of set are the added elements.

$$\forall x, s \quad x \in s \Leftrightarrow \exists y, s_2 \quad (s = \text{Add}(y, s_2) \wedge (x = y \vee x \in s_2))$$

// expressed recursively

Eight Axioms for Sets

- ◆ A set is either an empty set or made by adding something to a set.

$$\forall s \text{ Set}(s) \Leftrightarrow (s = \{\}) \vee (\exists x, s_0 \text{ Set}(s_0) \wedge s = \text{Add}(x, s_0))$$

- ◆ The empty set has no elements added to it.

$$\neg \exists x, s \text{ Add}(x, s) = \{\}$$

// equivalently, no way to decompose $\{\}$
// into a smaller set and an element

- ◆ Adding an element already in the set has no effect.

$$\forall x, s \quad x \in s \Leftrightarrow s = \text{Add}(x, s)$$

- ◆ The only members of set are the added elements.

$$\forall x, s \quad x \in s \Leftrightarrow \exists y, s_2 \quad (s = \text{Add}(y, s_2) \wedge (x = y \vee x \in s_2))$$

// expressed recursively

must be true at some recursion level

Set Axioms (cont'd)

- ◆ Subset relationship

$$\forall s_1, s_2 \quad s_1 \subseteq s_2 \Leftrightarrow (\forall x \ x \in s_1 \Rightarrow x \in s_2)$$

Set Axioms (cont'd)

- ◆ Subset relationship

$$\forall s_1, s_2 \quad s_1 \subseteq s_2 \Leftrightarrow (\forall x \ x \in s_1 \Rightarrow x \in s_2)$$

- ◆ Set equality

$$\forall s_1, s_2 \quad s_1 = s_2 \Leftrightarrow (s_1 \subseteq s_2 \wedge s_2 \subseteq s_1)$$

Set Axioms (cont'd)

◆ Subset relationship

$$\forall s_1, s_2 \quad s_1 \subseteq s_2 \Leftrightarrow (\forall x \ x \in s_1 \Rightarrow x \in s_2)$$

◆ Set equality

$$\forall s_1, s_2 \quad s_1 = s_2 \Leftrightarrow (s_1 \subseteq s_2 \wedge s_2 \subseteq s_1)$$

◆ Intersection

$$\forall x, s_1, s_2 \quad x \in s_1 \cap s_2 \Leftrightarrow (x \in s_1 \wedge x \in s_2)$$

Set Axioms (cont'd)

◆ Subset relationship

$$\forall s_1, s_2 \quad s_1 \subseteq s_2 \Leftrightarrow (\forall x \ x \in s_1 \Rightarrow x \in s_2)$$

◆ Set equality

$$\forall s_1, s_2 \quad s_1 = s_2 \Leftrightarrow (s_1 \subseteq s_2 \wedge s_2 \subseteq s_1)$$

◆ Intersection

$$\forall x, s_1, s_2 \quad x \in s_1 \cap s_2 \Leftrightarrow (x \in s_1 \wedge x \in s_2)$$

◆ Union

$$\forall x, s_1, s_2 \quad x \in s_1 \cup s_2 \Leftrightarrow (x \in s_1 \vee x \in s_2)$$

III. The Wumpus World in FOL

First-order logic axioms are much more concise than propositional axioms.

III. The Wumpus World in FOL

First-order logic axioms are much more concise than propositional axioms.

- Predicate for percept

Percept([Stench, Breeze, Glitter, None, None], 5)

III. The Wumpus World in FOL

First-order logic axioms are much more concise than propositional axioms.

- Predicate for percept

Percept(*[Stench, Breeze, Glitter, None, None]*, 5)

sensor reading

III. The Wumpus World in FOL

First-order logic axioms are much more concise than propositional axioms.

- Predicate for percept

Percept(*[Stench, Breeze, Glitter, None, None]*, 5)

sensor reading

time

III. The Wumpus World in FOL

First-order logic axioms are much more concise than propositional axioms.

- Predicate for percept

Percept([*Stench*, *Breeze*, *Glitter*, *None*, *None*], 5)

sensor reading

time

- Actions

Turn(*Right*), *Turn*(*Left*), *Forward*, *Shoot*, *Grab*, *Climb*

III. The Wumpus World in FOL

First-order logic axioms are much more concise than propositional axioms.

- Predicate for percept

Percept([Stench, Breeze, Glitter, None, None], 5)

└──────────────────────────────────┘
sensor reading time

- Actions

Turn(Right), Turn(Left), Forward, Shoot, Grab, Climb

- Querying the KB for best action

*ASKVARS(KB, BestAction(*a*, 5))*

A binding list, e.g., $\{a/Grab\}$, is returned.

Input/Output Rules

No need for the use of fluents (e.g., $Forward^t$, $Bump^{t+1}$)!

$\forall t, s, g, w, c \text{ Percept}([s, Breeze, g, w, c], t) \Rightarrow Breeze(t)$

$\forall t, s, g, w, c \text{ Percept}([s, None, g, w, c], t) \Rightarrow \neg Breeze(t)$

$\forall t, s, b, w, c \text{ Percept}([s, b, Glitter, w, c], t) \Rightarrow Glitter(t)$

$\forall t, s, b, w, c \text{ Percept}([s, b, None, w, c], t) \Rightarrow \neg Glitter(t)$

\vdots

Input/Output Rules

No need for the use of fluents (e.g., $Forward^t$, $Bump^{t+1}$)!

$\forall t, s, g, w, c \text{ Percept}([s, \text{Breeze}, g, w, c], t) \Rightarrow \text{Breeze}(t)$

$\forall t, s, g, w, c \text{ Percept}([s, \text{None}, g, w, c], t) \Rightarrow \neg \text{Breeze}(t)$

$\forall t, s, b, w, c \text{ Percept}([s, b, \text{Glitter}, w, c], t) \Rightarrow \text{Glitter}(t)$

$\forall t, s, b, w, c \text{ Percept}([s, b, \text{None}, w, c], t) \Rightarrow \neg \text{Glitter}(t)$

\vdots

$\forall t \text{ Glitter}(t) \Rightarrow \text{BestAction}(\text{Grab}, t)$

// simple “reflex” behavior

Rules for the Environment

- Adjacency of two squares

$$\forall x, y, a, b \text{ Adjacent}([x, y], [a, b]) \Leftrightarrow \\ (x = a \wedge (y = b - 1 \vee y = b + 1)) \vee (y = b \wedge (x = a - 1 \vee x = a + 1))$$

// if using propositional logic, we would have to name every square, say, $\text{Square}_{i,j}$,
// for $1 \leq i, j \leq 4$, and would need one such fact for 120 different pairs of squares!

Rules for the Environment

- Adjacency of two squares

square at row x and column y

$$\forall x, y, a, b \text{ Adjacent}([x, y], [a, b]) \Leftrightarrow \\ (x = a \wedge (y = b - 1 \vee y = b + 1)) \vee (y = b \wedge (x = a - 1 \vee x = a + 1))$$

// if using propositional logic, we would have to name every square, say, $\text{Square}_{i,j}$,
// for $1 \leq i, j \leq 4$, and would need one such fact for 120 different pairs of squares!

Rules for the Environment

- Adjacency of two squares

square at row x and column y

$$\forall x, y, a, b \text{ Adjacent}([x, y], [a, b]) \Leftrightarrow (x = a \wedge (y = b - 1 \vee y = b + 1)) \vee (y = b \wedge (x = a - 1 \vee x = a + 1))$$

// if using propositional logic, we would have to name every square, say, $\text{Square}_{i,j}$,
// for $1 \leq i, j \leq 4$, and would need one such fact for 120 different pairs of squares!

- Unary predicate *Pit* (no reason to distinguish among pits).

Rules for the Environment

- Adjacency of two squares

square at row x and column y

$$\forall x, y, a, b \text{ Adjacent}([x, y], [a, b]) \Leftrightarrow (x = a \wedge (y = b - 1 \vee y = b + 1)) \vee (y = b \wedge (x = a - 1 \vee x = a + 1))$$

// if using propositional logic, we would have to name every square, say, $\text{Square}_{i,j}$,
// for $1 \leq i, j \leq 4$, and would need one such fact for 120 different pairs of squares!

- Unary predicate *Pit* (no reason to distinguish among pits).

$Pit([x, y]) \equiv \text{true}$ if and only if the square $[x, y]$ contains a pit.

Rules for the Environment

- Adjacency of two squares

square at row x and column y

$$\forall x, y, a, b \quad \text{Adjacent}([x, y], [a, b]) \Leftrightarrow (x = a \wedge (y = b - 1 \vee y = b + 1)) \vee (y = b \wedge (x = a - 1 \vee x = a + 1))$$

// if using propositional logic, we would have to name every square, say, $\text{Square}_{i,j}$,
// for $1 \leq i, j \leq 4$, and would need one such fact for 120 different pairs of squares!

- Unary predicate *Pit* (no reason to distinguish among pits).

$\text{Pit}([x, y]) \equiv \text{true}$ if and only if the square $[x, y]$ contains a pit.

- Constants *Agent*, *Wumpus*

Rules for the Environment

- Adjacency of two squares

square at row x and column y

$$\forall x, y, a, b \text{ Adjacent}([x, y], [a, b]) \Leftrightarrow (x = a \wedge (y = b - 1 \vee y = b + 1)) \vee (y = b \wedge (x = a - 1 \vee x = a + 1))$$

// if using propositional logic, we would have to name every square, say, $\text{Square}_{i,j}$,
// for $1 \leq i, j \leq 4$, and would need one such fact for 120 different pairs of squares!

- Unary predicate Pit (no reason to distinguish among pits).

$Pit([x, y]) \equiv \text{true}$ if and only if the square $[x, y]$ contains a pit.

- Constants $Agent$, $Wumpus$

- Ternary predicate At to represent changing or non-changing locations

$\forall t \text{ At}(Wumpus, [1, 3], t)$

// fixed location for the wumpus

Rules for the Environment

- Adjacency of two squares

square at row x and column y

$$\forall x, y, a, b \text{ Adjacent}([x, y], [a, b]) \Leftrightarrow (x = a \wedge (y = b - 1 \vee y = b + 1)) \vee (y = b \wedge (x = a - 1 \vee x = a + 1))$$

// if using propositional logic, we would have to name every square, say, $\text{Square}_{i,j}$,
// for $1 \leq i, j \leq 4$, and would need one such fact for 120 different pairs of squares!

- Unary predicate Pit (no reason to distinguish among pits).

$Pit([x, y]) \equiv \text{true}$ if and only if the square $[x, y]$ contains a pit.

- Constants $Agent$, $Wumpus$
- Ternary predicate At to represent changing or non-changing locations

$\forall t \text{ At}(Wumpus, [1, 3], t)$ // fixed location for the wumpus

$\forall x, s_1, s_2, t \text{ At}(x, s_1, t) \wedge \text{At}(x, s_2, t) \Rightarrow s_1 = s_2$ // only one location at a time

Rules for Percepts, Actions and Inferences

- Percepts of breeze, stench, etc.

$$\forall s, t \text{ } At(Agent, s, t) \wedge Breeze(t) \Rightarrow Breezy(s)$$

Rules for Percepts, Actions and Inferences

- Percepts of breeze, stench, etc.

$$\forall s, t \text{ } At(Agent, s, t) \wedge Breeze(t) \Rightarrow Breezy(s)$$

- *Diagnostic* (inferring cause from effect)

$$\forall s \text{ } Breezy(s) \Leftrightarrow \exists r \text{ } Adjacent(r, s) \wedge Pit(r)$$

// if using propositional logic, we would need a separate axiom for every square.

Rules for Percepts, Actions and Inferences

- Percepts of breeze, stench, etc.

$$\forall s, t \text{ At}(\text{Agent}, s, t) \wedge \text{Breeze}(t) \Rightarrow \text{Breezy}(s)$$

- *Diagnostic* (inferring cause from effect)

$$\forall s \text{ Breezy}(s) \Leftrightarrow \exists r \text{ Adjacent}(r, s) \wedge \text{Pit}(r)$$

// if using propositional logic, we would need a separate axiom for every square.

- *Causal* (inferring effect from cause)

$$\forall s (\forall r \text{ Adjacent}(r, s) \Rightarrow \neg \text{Pit}(r)) \Rightarrow \neg \text{Breezy}(s)$$

Rules for Percepts, Actions and Inferences

- Percepts of breeze, stench, etc.

$$\forall s, t \text{ At}(\text{Agent}, s, t) \wedge \text{Breeze}(t) \Rightarrow \text{Breezy}(s)$$

- *Diagnostic* (inferring cause from effect)

$$\forall s \text{ Breezy}(s) \Leftrightarrow \exists r \text{ Adjacent}(r, s) \wedge \text{Pit}(r)$$

// if using propositional logic, we would need a separate axiom for every square.

- *Causal* (inferring effect from cause)

$$\forall s (\forall r \text{ Adjacent}(r, s) \Rightarrow \neg \text{Pit}(r)) \Rightarrow \neg \text{Breezy}(s)$$

- Quantification over time

$$\forall t \text{ HaveArrow}(t + 1) \Leftrightarrow \text{HaveArrow}(t) \wedge \neg \text{Action}(\text{Shoot}, t)$$

Rules for Percepts, Actions and Inferences

- Percepts of breeze, stench, etc.

$$\forall s, t \text{ At}(\text{Agent}, s, t) \wedge \text{Breeze}(t) \Rightarrow \text{Breezy}(s)$$

- *Diagnostic* (inferring cause from effect)

$$\forall s \text{ Breezy}(s) \Leftrightarrow \exists r \text{ Adjacent}(r, s) \wedge \text{Pit}(r)$$

// if using propositional logic, we would need a separate axiom for every square.

- *Causal* (inferring effect from cause)

$$\forall s (\forall r \text{ Adjacent}(r, s) \Rightarrow \neg \text{Pit}(r)) \Rightarrow \neg \text{Breezy}(s)$$

- Quantification over time

$$\forall t \text{ HaveArrow}(t + 1) \Leftrightarrow \text{HaveArrow}(t) \wedge \neg \text{Action}(\text{Shoot}, t)$$

The first-order logic formulation is no less concise than the English description.

Rules for Percepts, Actions and Inferences

- Percepts of breeze, stench, etc.

$$\forall s, t \text{ At}(\text{Agent}, s, t) \wedge \text{Breeze}(t) \Rightarrow \text{Breezy}(s)$$

- *Diagnostic* (inferring cause from effect)

$$\forall s \text{ Breezy}(s) \Leftrightarrow \exists r \text{ Adjacent}(r, s) \wedge \text{Pit}(r)$$

// if using propositional logic, we would need a separate axiom for every square.

- *Causal* (inferring effect from cause)

$$\forall s (\forall r \text{ Adjacent}(r, s) \Rightarrow \neg \text{Pit}(r)) \Rightarrow \neg \text{Breezy}(s)$$

- Quantification over time

$$\forall t \text{ HaveArrow}(t + 1) \Leftrightarrow \text{HaveArrow}(t) \wedge \neg \text{Action}(\text{Shoot}, t)$$

The first-order logic formulation is no less concise than the English description.