

# Data Warehousing and On-line Analytical Processing

---

☐ Data Warehouse: Basic Concepts



☐ Data Warehouse Modeling: Data Cube and OLAP

☐ Data Warehouse Implementation

☐ Summary

# What is a Data Warehouse?

---

- ❑ Defined in many different ways, but not rigorously
  - ❑ Support decision
  - ❑ Maintained Separately
  - ❑ Information processing
- ❑ “A data warehouse is a subject-oriented, integrated, time-variant, and nonvolatile collection of data in support of management’s decision-making process.” —W. H. Inmon
- ❑ Data warehousing:
  - ❑ The process of constructing and using data warehouses

# Data Warehouse—Subject-Oriented

---

- ❑ Help make decisions
  - ❑ A **simple** and **concise** view (modeling and analysis)
  - ❑ Not details (transaction processing)
  - ❑ Organizing around major subjects, such as **customer, product, sales**
  - ❑ Excluding data that are not useful in the decision support process

# Data Warehouse—Integrated

---

- ❑ Integrating Multiple, heterogeneous sources
  - ❑ Ex. relational databases, flat files, on-line transaction records
- ❑ Consistency
  - ❑ Data cleaning and data integration techniques are applied.
  - ❑ Ex. Hotel price: differences on currency, tax, breakfast covered, and parking
  - ❑ When data is moved to the warehouse, it is converted

# Data Warehouse—Time Variant

---

Data Warehouse	Operational Database
Long time horizon (e.g., past 5-10 years)	current value data
Contains an element of time, explicitly or implicitly	data may or may not contain “time element”

# Data Warehouse—Nonvolatile

---

- ❑ Independence – A physically separate store
- ❑ Static – No data management (updates, transaction processing, recovery, and concurrency control mechanisms)
- ❑ Requires only two operations in data accessing:
  - ❑ *initial loading of data* and *access of data*

# Why a Separate Data Warehouse?

---

- ❑ Different functions and different data:
  - ❑ [missing data](#): Decision support requires historical data which operational DBs do not typically maintain
  - ❑ [data consolidation](#): DS requires consolidation (aggregation, summarization) of data from heterogeneous sources
  - ❑ [data quality](#): different sources typically use inconsistent data representations, codes and formats which have to be reconciled
- ❑ Note: There are more and more systems which perform OLAP (online analytical processing) analysis directly on relational databases

# OLTP vs. OLAP

❑ OLTP: Online transactional processing

❑ DBMS operations

❑ Query and transactional processing

❑ OLAP: Online analytical processing

❑ Data warehouse operations


❑ Drilling, slicing, dicing, etc.

	OLTP	OLAP
<b>users</b>	clerk, IT professional	knowledge worker
<b>function</b>	day to day operations	decision support
<b>DB design</b>	application-oriented	subject-oriented
<b>data</b>	current, up-to-date detailed, flat relational isolated	historical, summarized, multidimensional integrated, consolidated
<b>usage</b>	repetitive	ad-hoc
<b>access</b>	read/write index/hash on prim. key	lots of scans
<b>unit of work</b>	short, simple transaction	complex query
<b># records accessed</b>	tens	millions
<b>#users</b>	thousands	hundreds
<b>DB size</b>	100MB-GB	100GB-TB
<b>metric</b>	transaction throughput	query throughput, response



# Data Warehouse: A Multi-Tiered Architecture

- ❑ Top Tier: Front-End Tools
- ❑ Middle Tier: OLAP Server
- ❑ Bottom Tier: Data Warehouse Server
- ❑ Data



# Extraction, Transformation, and Loading (ETL)

---

- ❑ **Data extraction**

- ❑ get data from multiple, heterogeneous, and external sources

- ❑ **Data cleaning**

- ❑ detect errors in the data and rectify them when possible

- ❑ **Data transformation**

- ❑ convert data from legacy or host format to warehouse format

- ❑ **Load**

- ❑ sort, summarize, consolidate, compute views, check integrity, and build indices and partitions

- ❑ **Refresh**

- ❑ propagate the updates from the data sources to the warehouse

# Chapter 4: Data Warehousing and On-line Analytical Processing

---

- ❑ Data Warehouse: Basic Concepts
- ❑ Data Warehouse Modeling: Data Cube and OLAP
- ❑ Data Warehouse Implementation
- ❑ Summary





# From Tables and Spreadsheets to Data Cubes

---

- ❑ A **data warehouse** is based on a multidimensional data model which views data in the form of a data cube
- ❑ Main function is to provide summarizations of the data
  - ❑ E.g., summarize the units or dollars sold at a particular store over a particular time period
- ❑ Can compute summarizations online (as they are requested)
  - ❑ Can be very slow
- ❑ Better to pre-calculate some summarizations


# A Sample Data Cube







# Design of Data Warehouses

- ❑ **Dimension tables**, such as item (item\_name, brand, type), or time(day, week, month, quarter, year)
- ❑ **Fact table** contains **measures** (such as dollars\_sold) and keys to each of the related dimension tables
- ❑ Different schema exist
  - ❑ Star
  - ❑ Snowflake
  - ❑ Fact constellation



# Star Schema: An Example


A fact table in the middle connected to a set of dimension tables






# Snowflake Schema: An Example

A refinement of star schema where some dimensional hierarchy is normalized into a set of smaller dimension tables, forming a shape similar to snowflake




# Fact Constellation: An Example

Multiple fact tables share dimension tables, viewed as a collection of stars, therefore called **galaxy schema** or **fact constellation**





# A Concept Hierarchy for a Dimension (location)




# Roll up & Drill down

**Roll up (drill-up):** summarize data  
*by climbing up hierarchy or by dimension  
reduction*




**Drill down (roll down):** reverse of roll-up  
*from higher level summary to lower level  
summary or detailed data, or introducing  
new dimensions*

# Dice and Slice



# Chapter 4: Data Warehousing and On-line Analytical Processing

---


- ❑ Data Warehouse: Basic Concepts
- ❑ Data Warehouse Modeling: Data Cube and OLAP
- ❑ Data Warehouse Implementation 
- ❑ Summary

# Efficient Data Cube Computation

- ❑ If I have  $n$  dimensions, each with  $L_i$  levels, how many cuboids are needed to preprocess all?
- ❑ Calculating **all** cuboids is costly in computation and time.
- ❑ How to decide which cuboid be pre-calculated (**Materialization**)?
  - ❑ Based on size of data, sharing, access frequency, etc.
  - ❑ Example: I know my users always search by Quarter, so that cuboid should be pre-calculated.
  - ❑ Example: If I pre-calculate days, I can use days as input to Months (30 or 31 days), or weeks (7 days), etc.

Why this formula?

$$T = \prod_{i=1}^n (L_i + 1)$$



# The “Compute Cube” Operator

- ❑ Cube definition and computation in DMQL(Data Mining Query Language)  
`define cube sales [item, city, year]: sum (sales_in_dollars)`  
`compute cube sales`
- ❑ Transform it into a SQL-like language (with a new operator `cube by`, introduced by Gray et al.'96)

```
SELECT item, city, year, SUM (amount)  
FROM SALES
```

```
CUBE BY item, city, year
```


- ❑ Need compute the following Group-Bys ( $2^3$ )

3D Cuboid → (date, product, customer),

2D Cuboid → (date, product), (date, customer), (product, customer),

1D Cuboid → (date), (product), (customer)

0D (Apex) Cuboid → ()





# Indexing OLAP Data

---

## □ Indexing

- Main purpose of indexing is to make the calculation faster/efficient

## □ Common Warehouse Index: Bitmap Index

### □ Benefits in Warehousing:

- Reduced response time for large classes of ad hoc queries.
- Reduced storage requirements compared to other indexing techniques.
- Dramatic performance gains even on hardware with a relatively small number of CPUs or a small amount of memory.

<https://docs.oracle.com/database/121/DWHSG/schemas.htm#DWHSG9041>

# Indexing OLAP Data: Bitmap Index

- Index on a particular column
  - Each value in the column has a bit vector: bit-op is fast
  - The length of the bit vector: # of records in the base table
  - The  $i$ -th bit is set if the  $i$ -th row of the base table has the value for the indexed column
  - Not suitable for high cardinality domains. (WHY? )
- A recent bit compression technique, Word-Aligned Hybrid (WAH), makes it work for high cardinality domain as well [Wu, et al. TODS'06]

**Base table**

Cust	Region	Type
C1	Asia	Retail
C2	Europe	Dealer
C3	Asia	Dealer
C4	America	Retail
C5	Europe	Dealer

**Index on Region**

RecID	Asia	Europe	America
1	1	0	0
2	0	1	0
3	1	0	0
4	0	0	1
5	0	1	0

**Index on Type**

RecID	Retail	Dealer
1	1	0
2	0	1
3	0	1
4	1	0
5	0	1

# Efficient Processing OLAP Queries

---

- ❑ **Determine which operations** should be performed on the available cuboids
  - ❑ Transform drill, roll, etc. into corresponding SQL and/or OLAP operations, e.g.,  
dice = selection + projection
- ❑ **Determine which materialized cuboid(s)** should be selected for OLAP op.
  - ❑ Let the query to be processed be on  $\{brand, province\_or\_state\}$  with the condition “ $year = 2004$ ”, and there are 4 materialized cuboids available:
    - 1)  $\{year, item\_name, city\}$
    - 2)  $\{year, brand, country\}$
    - 3)  $\{year, brand, province\_or\_state\}$
    - 4)  $\{item\_name, province\_or\_state\}$  where  $year = 2004$Which should be selected to process the query?

# OLAP Server Architectures

---

## ☐ Relational OLAP (ROLAP)

- ☐ Data is stored in a relational database.
- ☐ Greater scalability

## ☐ Multidimensional OLAP (MOLAP)


- ☐ Everything is in multi-dimensional storage (see page 13 for an example)
- ☐ Fast indexing to pre-computed summarized data

## ☐ Hybrid OLAP (HOLAP)

- ☐ Used by : Microsoft SQLServer
- ☐ Combines both ROLAP & MOLAP
- ☐ Theoretically provides best performance

# Chapter 4: Data Warehousing and On-line Analytical Processing

---

- ❑ Data Warehouse: Basic Concepts
- ❑ Data Warehouse Modeling: Data Cube and OLAP
- ❑ Data Warehouse Implementation
- ❑ Summary 

# Summary

---

- ❑ Data warehousing: A multi-dimensional model of a data warehouse
  - ❑ A data cube consists of *dimensions* & *measures*
  - ❑ Star schema, snowflake schema, fact constellations
  - ❑ OLAP operations: drilling, rolling, slicing, dicing and pivoting
- ❑ Data Warehouse Architecture, Design, and Usage
  - ❑ Multi-tiered architecture
  - ❑ Business analysis design framework
  - ❑ Information processing, analytical processing, data mining
- ❑ Implementation: Efficient computation of data cubes
  - ❑ Partial vs. full vs. no materialization
  - ❑ Indexing OALP data: Bitmap index and join index
  - ❑ OLAP query processing
  - ❑ OLAP servers: ROLAP, MOLAP, HOLAP

# References (I)

---

- ❑ S. Agarwal, R. Agrawal, P. M. Deshpande, A. Gupta, J. F. Naughton, R. Ramakrishnan, and S. Sarawagi. On the computation of multidimensional aggregates. VLDB'96
- ❑ D. Agrawal, A. E. Abbadi, A. Singh, and T. Yurek. Efficient view maintenance in data warehouses. SIGMOD'97
- ❑ R. Agrawal, A. Gupta, and S. Sarawagi. Modeling multidimensional databases. ICDE'97
- ❑ S. Chaudhuri and U. Dayal. An overview of data warehousing and OLAP technology. ACM SIGMOD Record, 26:65-74, 1997
- ❑ J. Gray, et al. Data cube: A relational aggregation operator generalizing group-by, cross-tab and sub-totals. Data Mining and Knowledge Discovery, 1:29-54, 1997.
- ❑ A. Gupta and I. S. Mumick. Materialized Views: Techniques, Implementations, and Applications. MIT Press, 1999
- ❑ J. Han. Towards on-line analytical mining in large databases. *SIGMOD Record*, 1998
- ❑ V. Harinarayan, A. Rajaraman, and J. D. Ullman. Implementing data cubes efficiently. SIGMOD'96

# References (II)

---

- ❑ C. Imhoff, N. Gallemmo, and J. G. Geiger. Mastering Data Warehouse Design: Relational and Dimensional Techniques. John Wiley, 2003
- ❑ W. H. Inmon. Building the Data Warehouse. John Wiley, 1996
- ❑ R. Kimball and M. Ross. The Data Warehouse Toolkit: The Complete Guide to Dimensional Modeling. 2ed. John Wiley, 2002
- ❑ P. O'Neil and D. Quass. Improved query performance with variant indexes. SIGMOD'97
- ❑ S. Sarawagi and M. Stonebraker. Efficient organization of large multidimensional arrays. ICDE'94
- ❑ P. Valduriez. Join indices. ACM Trans. Database Systems, 12:218-246, 1987.
- ❑ J. Widom. Research problems in data warehousing. CIKM'95.
- ❑ K. Wu, E. Otoo, and A. Shoshani, Optimal Bitmap Indices with Efficient Compression, ACM Trans. on Database Systems (TODS), 31(1), 2006, pp. 1-38.