Outline

- I. Most likely explanation
- II. Simplified matrix algorithms
- III. HMM application to robot localization

^{*} Figures/images are from the <u>textbook site</u>.

Umbrella sequence on the guard's first five days: [true, true, false, true, true]

Question What weather sequence is most likely?

Umbrella sequence on the guard's first five days: [true, true, false, true, true]

Question What weather sequence is most likely?

♣ 2⁵ possible weather sequences to pick from.

Umbrella sequence on the guard's first five days: [true, true, false, true, true]


Question What weather sequence is most likely?

- ♣ 2⁵ possible weather sequences to pick from.
- ♠ Use smoothing to find posterior distribution for weather at each time step, and select at the step the weather that scores the highest.
 - Posterior distribution by smoothing are distributed over single time steps.
 - Joint probabilities over all the time steps must be considered to find the most likely sequence.

Umbrella sequence on the guard's first five days: [true, true, false, true, true]

Question What weather sequence is most likely?


- 2⁵ possible weather sequences to pick from.
- ♠ Use smoothing to find posterior distribution for weather at each time step, and select at the step the weather that scores the highest.
 - Posterior distribution by smoothing are distributed over single time steps.
 - Joint probabilities over all the time steps must be considered to find the most likely sequence.
- View each sequence as a path through a graph whose nodes are the possible states at each time step.



Umbrella sequence on the guard's first five days: [true, true, false, true, true]

Question What weather sequence is most likely?

- $^{\bullet}$ 2⁵ possible weather sequences to pick from.
- ♠ Use smoothing to find posterior distribution for weather at each time step, and select at the step the weather that scores the highest.
 - Posterior distribution by smoothing are distributed over single time steps.
 - Joint probabilities over all the time steps must be considered to find the most likely sequence.
- View each sequence as a path through a graph whose nodes are the possible states at each time step.



Find the most likely path.


Likelihood of a path is the product of

- the transition probabilities along the path,
- and the probabilities of the given observations at each state.

Likelihood of a path is the product of

- the transition probabilities along the path,
- and the probabilities of the given observations at each state.


Consider paths that reach the state $Rain_5 = true$



Likelihood of a path is the product of

- the transition probabilities along the path,
- and the probabilities of the given observations at each state.

Consider paths that reach the state $Rain_5 = true$




• The most likely path to $Rain_5 = true$ consists of the most likely path to some state at time 4 (optimal substructure) followed by a transition.

Likelihood of a path is the product of

- the transition probabilities along the path,
- and the probabilities of the given observations at each state.

Consider paths that reach the state $Rain_5 = true$



- The most likely path to $Rain_5 = true$ consists of the most likely path to some state at time 4 (optimal substructure) followed by a transition.
- The state at time 4 that gets chosen maximizes the likelihood of the path to $Rain_5 = true$.

Define

$$m_{1:k} = \max_{x_{1:k-1}} P(x_{1:k-1}, X_k, e_{1:k})$$

Define

$$m_{1:k} = \max_{x_{1:k-1}} P(x_{1:k-1}, X_k, e_{1:k})$$

$$m_{1:k+1} = \max_{x_{1:k}} P(x_{1:k}, X_{k+1}, e_{1:k+1})$$

Define

$$m_{1:k} = \max_{x_{1:k-1}} P(x_{1:k-1}, X_k, e_{1:k})$$

$$m_{1:k+1} = \max_{x_{1:k}} P(x_{1:k}, X_{k+1}, e_{1:k+1})$$

= $\max_{x_{1:k}} P(x_{1:k}, X_{k+1}, e_{1:k}, e_{k+1})$

Define

$$m_{1:k} = \max_{x_{1:k-1}} P(x_{1:k-1}, X_k, e_{1:k})$$

$$m_{1:k+1} = \max_{x_{1:k}} P(x_{1:k}, X_{k+1}, e_{1:k+1})$$

$$= \max_{x_{1:k}} P(x_{1:k}, X_{k+1}, e_{1:k}, e_{k+1})$$

$$= \max_{x_{1:k}} P(e_{k+1} \mid x_{1:k}, X_{k+1}, e_{1:k}) P(x_{1:k}, X_{k+1}, e_{1:k})$$

Define

$$m_{1:k} = \max_{x_{1:k-1}} P(x_{1:k-1}, X_k, e_{1:k})$$

$$m_{1:k+1} = \max_{x_{1:k}} P(x_{1:k}, X_{k+1}, e_{1:k+1})$$

$$= \max_{x_{1:k}} P(x_{1:k}, X_{k+1}, e_{1:k}, e_{k+1})$$

$$= \max_{x_{1:k}} P(e_{k+1} | x_{1:k}, X_{k+1}, e_{1:k}) P(x_{1:k}, X_{k+1}, e_{1:k})$$

$$= P(e_{k+1} | X_{k+1}) \max_{x_{1:k}} P(X_{k+1} | x_k) P(x_{1:k}, e_{1:k})$$

Define

$$m_{1:k} = \max_{x_{1:k-1}} P(x_{1:k-1}, X_k, e_{1:k})$$

$$m_{1:k+1} = \max_{x_{1:k}} P(x_{1:k}, X_{k+1}, e_{1:k+1})$$

$$= \max_{x_{1:k}} P(x_{1:k}, X_{k+1}, e_{1:k}, e_{k+1})$$

$$= \max_{x_{1:k}} P(e_{k+1} \mid x_{1:k}, X_{k+1}, e_{1:k}) P(x_{1:k}, X_{k+1}, e_{1:k})$$

$$= P(e_{k+1} \mid X_{k+1}) \max_{x_{1:k}} P(X_{k+1} \mid x_k) P(x_{1:k}, e_{1:k})$$

$$= P(e_{k+1} \mid X_{k+1}) \max_{x_k} P(X_{k+1} \mid x_k) \max_{x_{1:k-1}} P(x_{1:k-1}, x_k, e_{1:k})$$

Define

$$m_{1:k} = \max_{x_{1:k-1}} P(x_{1:k-1}, X_k, e_{1:k})$$
 Entry for $X_k = x_k$

$$m_{1:k+1} = \max_{x_{1:k}} P(x_{1:k}, X_{k+1}, e_{1:k+1})$$

$$= \max_{x_{1:k}} P(x_{1:k}, X_{k+1}, e_{1:k}, e_{k+1})$$


$$= \max_{x_{1:k}} P(e_{k+1} \mid x_{1:k}, X_{k+1}, e_{1:k}) P(x_{1:k}, X_{k+1}, e_{1:k})$$

$$= P(e_{k+1} \mid X_{k+1}) \max_{x_{1:k}} P(X_{k+1} \mid x_k) P(x_{1:k}, e_{1:k})$$

$$= P(e_{k+1} \mid X_{k+1}) \max_{x_k} P(X_{k+1} \mid x_k) \max_{x_{1:k-1}} P(x_{1:k-1}, x_k, e_{1:k})$$


$$m_{1:k} = \max_{x_{1:k-1}} P(x_{1:k-1}, X_k, e_{1:k})$$

- $\bullet \ m_{1:0} = P(X_0) \to m_{1:1} \to \cdots \to m_{1:t}$
- ◆ To identify the actual sequence, record, for each state, the best state (i.e., predecessor) that leads to it.




$$m_{1:k} = \max_{x_{1:k-1}} P(x_{1:k-1}, X_k, e_{1:k})$$

- ◆ To identify the actual sequence, record, for each state, the best state (i.e., predecessor) that leads to it.



$$m_{1:k} = \max_{x_{1:k-1}} P(x_{1:k-1}, X_k, e_{1:k})$$


- $\bullet \ m_{1:0} = P(X_0) \to m_{1:1} \to \cdots \to m_{1:t}$
- ◆ To identify the actual sequence, record, for each state, the best state (i.e., predecessor) that leads to it.



0.00811 is the maximum joint probability of any rain scenario on the first four days, rain on day 5, and the umbrella sequence [true, true, false, true, true] on the first five days. It is achieved by the weather sequence [true, true, false, true, true].

$$m_{1:k} = \max_{x_{1:k-1}} P(x_{1:k-1}, X_k, e_{1:k})$$

- ◆ To identify the actual sequence, record, for each state, the best state (i.e., predecessor) that leads to it.



0.00811 is the maximum joint probability of any rain scenario on the first four days, rain on day 5, and the umbrella sequence [true, true, false, true, true] on the first five days. It is achieved by the weather sequence [true, true, false, true, true].

0.000933 is the maximum joint probability of any rain scenario on the first four days, no rain on day 5, and the umbrella sequence [true, true, false, true, true] on the first five days. It is achieved by the weather sequence [true, true, false, false, false].

- lacktriangle The state is described by a single, discrete random variable X_t .
- Its values are the possible states of the world.
- ◆ There can be many evidence variables, both discrete and continuous.

- lacktriangle The state is described by a single, discrete random variable X_t .
- Its values are the possible states of the world.
- ◆ There can be many evidence variables, both discrete and continuous.

Denote the values of X_t by 1, ..., S.

- lacktriangle The state is described by a single, discrete random variable X_t .
- Its values are the possible states of the world.
- ◆ There can be many evidence variables, both discrete and continuous.

Denote the values of X_t by 1, ..., S.

Transition model:

$$\boldsymbol{T} = \begin{pmatrix} T_{11} & \cdots & T_{1S} \\ \vdots & \ddots & \vdots \\ T_{S1} & \cdots & T_{SS} \end{pmatrix}$$

- lacktriangle The state is described by a single, discrete random variable X_t .
- Its values are the possible states of the world.
- ◆ There can be many evidence variables, both discrete and continuous.

Denote the values of X_t by 1, ..., S.

Transition model:

$$T = \begin{pmatrix} T_{11} & \cdots & T_{1S} \\ \vdots & \ddots & \vdots \\ T_{S1} & \cdots & T_{SS} \end{pmatrix}$$
 where $T_{ij} = P(X_t = j \mid X_{t-1} = i)$ probability of transition

from state *i* to state *j*

- lacktriangle The state is described by a single, discrete random variable X_t .
- Its values are the possible states of the world.
- There can be many evidence variables, both discrete and continuous.

Denote the values of X_t by $1, \dots, S$.


Transition model:

$$m{T} = egin{pmatrix} T_{11} & \cdots & T_{1S} \ dots & \ddots & dots \ T_{S1} & \cdots & T_{SS} \end{pmatrix}$$

$$T = \begin{pmatrix} T_{11} & \cdots & T_{1S} \\ \vdots & \ddots & \vdots \\ T_{S1} & \cdots & T_{SS} \end{pmatrix} \quad \text{where } T_{ij} = P(X_t = j \mid X_{t-1} = i)$$

probability of transition from state *i* to state *j*

For the umbrella world, we denote the states Rain = true and Rain = false by 1 and 2, respectively.



- lacktriangle The state is described by a single, discrete random variable X_t .
- Its values are the possible states of the world.
- There can be many evidence variables, both discrete and continuous.

Denote the values of X_t by $1, \dots, S$.

Transition model:


$$m{T} = egin{pmatrix} T_{11} & \cdots & T_{1S} \ dots & \ddots & dots \ T_{S1} & \cdots & T_{SS} \end{pmatrix}$$

 $T = \begin{pmatrix} T_{11} & \cdots & I_{1S} \\ \vdots & \ddots & \vdots \\ T_{C1} & \cdots & T_{CC} \end{pmatrix} \quad \text{where } T_{ij} = P(X_t = j \mid X_{t-1} = i)$

probability of transition from state *i* to state *j*

For the umbrella world, we denote the states Rain = true and Rain = false by 1 and 2, respectively.

$$T = P(X_t \mid X_{t-1}) = \begin{pmatrix} 0.7 & 0.3 \\ 0.3 & 0.7 \end{pmatrix}$$



The value e_t of the evidence variable E_t is known at time t.

Specify, for each state i = 1, ..., S, the likelihood that it causes e_t to appear.

$$P(e_t \mid X_t = i)$$

The value e_t of the evidence variable E_t is known at time t.

Specify, for each state $i=1,\ldots,S$, the likelihood that it causes e_t to appear.

$$P(e_t \mid X_t = i)$$

Observation matrix
$$O_t = \begin{pmatrix} P(e_t \mid X_t = 1) & \mathbf{0} \\ \mathbf{0} & \ddots & \\ P(e_t \mid X_t = S) \end{pmatrix}$$


The value e_t of the evidence variable E_t is known at time t.

Specify, for each state i = 1, ..., S, the likelihood that it causes e_t to appear.

$$P(e_t \mid X_t = i)$$

Observation matrix
$$O_t = \begin{pmatrix} P(e_t \mid X_t = 1) & & & & \\ & & \ddots & & \\ & & & & P(e_t \mid X_t = S) \end{pmatrix}$$

Suppose that $U_1 = true$ and $U_2 = false$.



The value e_t of the evidence variable E_t is known at time t.


Specify, for each state i = 1, ..., S, the likelihood that it causes e_t to appear.

$$P(e_t \mid X_t = i)$$

Observation matrix
$$O_t = \begin{pmatrix} P(e_t \mid X_t = 1) & & & & \\ & & \ddots & & \\ & & & & P(e_t \mid X_t = S) \end{pmatrix}$$

Suppose that $U_1 = true$ and $U_2 = false$.

$$O_1 = \begin{pmatrix} 0.9 & 0 \\ 0 & 0.2 \end{pmatrix} \qquad O_3 = \begin{pmatrix} 0.1 & 0 \\ 0 & 0.8 \end{pmatrix}$$



```
Forward message used in filtering: f_{1:t} \equiv P(X_t \mid e_{1:t})

S \times 1 matrix
```

Forward message used in filtering: $f_{1:t} \equiv P(X_t \mid e_{1:t})$ $S \times 1 \text{ matrix}$

$$f_{1:t+1} \equiv P(X_{t+1} \mid e_{1:t+1}) = \alpha P(e_{t+1} \mid X_{t+1}) \sum_{x_t} P(X_{t+1} \mid x_t) P(x_t \mid e_{1:t})$$

Forward message used in filtering: $f_{1:t} \equiv P(X_t \mid e_{1:t})$ $S \times 1 \text{ matrix}$

$$f_{1:t+1} \equiv P(X_{t+1} \mid e_{1:t+1}) = \alpha P(e_{t+1} \mid X_{t+1}) \sum_{x_t} P(X_{t+1} \mid x_t) P(x_t \mid e_{1:t})$$
Powrite pointwise products

Rewrite pointwise products as matrix products.

$$\boldsymbol{f}_{1:t+1} = \alpha \boldsymbol{O}_{t+1} \boldsymbol{T}^T \boldsymbol{f}_{1:t}$$
 (filtering)

Forward message used in filtering:
$$f_{1:t} \equiv P(X_t \mid e_{1:t})$$

 $S \times 1 \text{ matrix}$

$$f_{1:t+1} \equiv P(X_{t+1} \mid e_{1:t+1}) = \alpha P(e_{t+1} \mid X_{t+1}) \sum_{x_t} P(X_{t+1} \mid x_t) P(x_t \mid e_{1:t})$$
Rewrite pointwise products as matrix products.

$$\boldsymbol{f}_{1:t+1} = \alpha \boldsymbol{O}_{t+1} \boldsymbol{T}^T \boldsymbol{f}_{1:t}$$
 (filtering)

Backward message used in smoothing: $b_{k+1:t} \equiv P(e_{k+1:t} \mid X_k)$

Forward message used in filtering: $f_{1:t} \equiv P(X_t \mid e_{1:t})$ $S \times 1 \text{ matrix}$

$$f_{1:t+1} \equiv P(X_{t+1} \mid e_{1:t+1}) = \alpha P(e_{t+1} \mid X_{t+1}) \sum_{x_t} P(X_{t+1} \mid x_t) P(x_t \mid e_{1:t})$$
Rewrite pointwise products as matrix products.

$$\boldsymbol{f}_{1:t+1} = \alpha \boldsymbol{O}_{t+1} \boldsymbol{T}^T \boldsymbol{f}_{1:t}$$
 (filtering)

Backward message used in smoothing: $b_{k+1:t} \equiv P(e_{k+1:t} \mid X_k)$

$$P(e_{k+1:t} | X_k) = \sum_{x_{k+1}} P(e_{k+1} | x_{k+1}) P(e_{k+2:t} | x_{k+1}) P(x_{k+1} | X_k)$$

Matrix Formulations of Filtering and Smoothing

Forward message used in filtering: $f_{1:t} \equiv P(X_t \mid e_{1:t})$ $S \times 1 \text{ matrix}$

$$f_{1:t+1} \equiv P(X_{t+1} \mid e_{1:t+1}) = \alpha P(e_{t+1} \mid X_{t+1}) \sum_{x_t} P(X_{t+1} \mid x_t) P(x_t \mid e_{1:t})$$

Rewrite pointwise products as matrix products.

$$\boldsymbol{f}_{1:t+1} = \alpha \boldsymbol{O}_{t+1} \boldsymbol{T}^T \boldsymbol{f}_{1:t}$$
 (filtering)

Backward message used in smoothing: $b_{k+1:t} \equiv P(e_{k+1:t} \mid X_k)$

$$P(e_{k+1:t} | X_k) = \sum_{x_{k+1}} P(e_{k+1} | x_{k+1}) P(e_{k+2:t} | x_{k+1}) P(x_{k+1} | X_k)$$

$$\boldsymbol{b}_{k+1:t} = \boldsymbol{TO}_{k+1} \, \boldsymbol{b}_{k+2:t} \qquad \text{(smoothing)}$$

$$\boldsymbol{f}_{1:t+1} = \alpha \boldsymbol{O}_{t+1} \boldsymbol{T}^T \boldsymbol{f}_{1:t}$$

$$\boldsymbol{b}_{k+1:t} = \boldsymbol{TO}_{k+1} \, \boldsymbol{b}_{k+2:t}$$

$$f_{1:t+1} = \alpha \boldsymbol{O}_{t+1} \boldsymbol{T}^T \boldsymbol{f}_{1:t}$$

 $\boldsymbol{b}_{k+1:t} = \boldsymbol{T} \boldsymbol{O}_{k+1} \boldsymbol{b}_{k+2:t}$

Time complexity: $O(S^2t)$ // t steps, each requiring two rounds of $O(S^2)$ time // multiplication of an $S \times S$ matrix by an S-vector.

$$f_{1:t+1} = \alpha O_{t+1} T^T f_{1:t}$$

$$b_{k+1:t} = TO_{k+1} b_{k+2:t}$$

```
Time complexity: O(S^2t) // t steps, each requiring two rounds of O(S^2) time // multiplication of an S \times S matrix by an S-vector.
```

Space complexity: O(St) // t > S. The forward pass stores t vectors of size S.

$$f_{1:t+1} = \alpha O_{t+1} T^T f_{1:t}$$

$$b_{k+1:t} = T O_{k+1} b_{k+2:t}$$

```
Time complexity: O(S^2t) // t steps, each requiring two rounds of O(S^2) time // multiplication of an S \times S matrix by an S-vector.
```

Space complexity: O(St) // t > S. The forward pass stores t vectors of size S.

Improvements:

◆ Allows smoothing to be carried out in constant space, independent of the lengths of the sequence.

$$f_{1:t+1} = \alpha O_{t+1} T^T f_{1:t}$$

$$b_{k+1:t} = T O_{k+1} b_{k+2:t}$$

```
Time complexity: O(S^2t) // t steps, each requiring two rounds of O(S^2) time // multiplication of an S \times S matrix by an S-vector.
```

Space complexity: O(St) // t > S. The forward pass stores t vectors of size S.


Improvements:

- ◆ Allows smoothing to be carried out in constant space, independent of the lengths of the sequence.
- Leads to an algorithm whose time complexity is independent of the length d of the lag.

Smoothing at time t - d, where the current time is t.

Revisiting the Localization Task


The robot had a single action Move and a perfect sensor to report whether obstacles are immediately to the north, east, south, and west.




Possible locations of robot after $E_1 = 1011$ (obstacles in the north, south, and west, but not east). NESW

Revisiting the Localization Task

The robot had a single action Move and a perfect sensor to report whether obstacles are immediately to the north, east, south, and west.



Possible locations of robot after $E_1=1011$ (obstacles in the north, south, and west, but not east). NESW



Possible locations after $E_1 = 1011$, $E_2 = 1010$.

HMM Formulation

We now make the problem more realistic:

- Allow noise in sensing whether or not obstacles are immediately to the north, east, south, and west.
- The robot is equally likely to move to any adjacent square.

HMM Formulation


We now make the problem more realistic:

- Allow noise in sensing whether or not obstacles are immediately to the north, east, south, and west.
- The robot is equally likely to move to any adjacent square.

- State *X_t*: robot location
- $\{1, ..., S\}$: set of empty squares (labelled by integers)
- NEIGHBORS(i): set of empty squares that are adjacent to i
- N(i): size of Neighbors(i)

Transition Model

$$P(X_{t+1} = j \mid X_t = i) = \boldsymbol{T}_{ij} = \begin{cases} 1/N(i) & \text{if } j \in \mathsf{NEIGHBORS}(i) \\ 0 & \text{otherwise} \end{cases}$$




$$S = 42$$

Matrix
$$T = (T_{ij})$$
 has $42 \times 42 = 1764$ entries

Transition Model

$$P(X_{t+1} = j \mid X_t = i) = \boldsymbol{T}_{ij} = \begin{cases} 1/N(i) & \text{if } j \in \mathsf{NEIGHBORS}(i) \\ 0 & \text{otherwise} \end{cases}$$



$$S = 42$$

Matrix
$$T = (T_{ij})$$
 has $42 \times 42 = 1764$ entries

Assume a uniform distribution of the robot's starting location:

$$P(X_0 = i) = 1/S$$
 for $1 \le i \le S$

Sensor variable $E_t = NESW$ has four bits and $2^4 = 16$ possible values.

Sensor variable $E_t = NESW$ has four bits and $2^4 = 16$ possible values.

Assumptions:

• Each sensor (N, E, S, or W) has an error rate ε .

Sensor variable $E_t = NESW$ has four bits and $2^4 = 16$ possible values.

Assumptions:

- Each sensor (N, E, S, or W) has an error rate ε .
- Errors occur independently for the four sensors.

Sensor variable $E_t = NESW$ has four bits and $2^4 = 16$ possible values.

Assumptions:

- Each sensor (N, E, S, or W) has an error rate ε .
- Errors occur independently for the four sensors.

Probability of getting all four bits correct: $(1 - \varepsilon)^4$

Probability of getting all of them wrong: ε^4

Sensor variable $E_t = NESW$ has four bits and $2^4 = 16$ possible values.

Assumptions:

- Each sensor (N, E, S, or W) has an error rate ε .
- Errors occur independently for the four sensors.

Probability of getting all four bits correct: $(1 - \varepsilon)^4$ Probability of getting all of them wrong: ε^4

 $d_{it} = ext{\#bits that are different between the true values for square } i$ and actual reading e_t

Sensor variable $E_t = NESW$ has four bits and $2^4 = 16$ possible values.

Assumptions:

- Each sensor (N, E, S, or W) has an error rate ε .
- Errors occur independently for the four sensors.

Probability of getting all four bits correct: $(1 - \varepsilon)^4$ Probability of getting all of them wrong: ε^4

 $d_{it}=$ #bits that are different between the true values for square i and actual reading e_t

Probability that the robot in square i would receive a sensor reading e_t :

$$P(E_t = e_t \mid X_t = i) = (\mathbf{0}_t)_{ii} = (1 - \varepsilon)^{4 - d_{it}} \varepsilon^{d_{it}}$$
 diagonal observation matrix

Sensor variable $E_t = NESW$ has four bits and $2^4 = 16$ possible values.

Assumptions:

- Each sensor (N, E, S, or W) has an error rate ε .
- Errors occur independently for the four sensors.

Probability of getting all four bits correct: $(1 - \varepsilon)^4$ Probability of getting all of them wrong: ε^4

 $d_{it}=$ #bits that are different between the true values for square i and actual reading e_t

Probability that the robot in square i would receive a sensor reading e_t :

$$P(E_t = e_t \mid X_t = i) = (\mathbf{0}_t)_{ii} = (1 - \varepsilon)^{4 - d_{it}} \varepsilon^{d_{it}}$$
 diagonal observation matrix

A square with obstacles to the north and south would produce a sensor reading of 1110 with probability $(1 - \varepsilon)^3 \varepsilon^1$.


Localization

Posterior distribution over locations using the filtering equation:

$$P(X_{t+1} \mid \boldsymbol{e}_{1:t+1}) = \alpha \boldsymbol{O}_{t+1} \boldsymbol{T}^T P(X_t \mid \boldsymbol{e}_{1:t})$$


 $S \times 1$ column vector $\boldsymbol{f}_{1:t+1}$

 $\varepsilon = 0.2$




(a) Posterior distribution over robot location after $E_1 = 1011$

Perfect sensing




Localization (cont'd)






(b) Posterior distribution over robot location after $E_1 = 1011$, $E_2 = 1010$

Perfect sensing



Localization Error

Measured as the Manhattan distance from the true location.



The robot can also use smoothing to work out where it was at a given past time.

Viterbi Path Error

Error measured as the average Manhattan distance of states on the Viterbi path from corresponding states on the true path.

