

1. Explain how to insert, delete, and search a record
 - a. in heap file
 - b. in sorted file
2. Considering B+ tree with the following parameters
Size of one data entry = 20 bytes;
Page size=4096 bytes; 96 bytes are reserved for bit map
Total number of records = 100,000; record size = 40 bytes
 - a. If the B+ tree is dense and unclustered, what is the I/O cost for a range select with Reduction Factor = 0.1?
 - b. If the B+ tree is sparse, what is the I/O cost for a range select with Reduction Factor = 0.1?
 - c. If the B+ tree is dense and clustered, what is the I/O cost for a range select with Reduction Factor = 0.1?
3. Design pseudo code for
 - a. Block nested loop join
 - b. Grace hash join
 - c. Multi-way merge sort join
4. Consider the following relations: Technicians(SSN, name, address, phone_number), Tests(FAAid, name, max_score), Planes(Pid, model), and Examine(SSN, FAAid, Pid, date, score). For each of the following queries, write a relational algebraic expression and draw relational algebraic tree with selection and projection conducted as early as possible.
 - a. Find the names of the technicians who examines the same plane on 2/10/2019 and 2/11/2019
 - b. Find the date that at least one Boeing 747 plane got full scores in its tests
 - c. Find the name and ssn of the technicians who haven't conducted any test on any Boeing 747 plane before "2/10/2019"
5. How many left-deep plans are there for joining all four tables in question 4 without cross product? What are they? (hint: if two tables do not have a common attribute, then natural join is defined as cross product).