


Notes:(技术要求):

1. General tolerances for rubber parts meets ISO 3302-1 M3;
(一般橡胶件的尺寸公差满足 ISO 3302-1 M3级;)
2. Rubber material acc. to Q/JLY J7110371E-2022;
Spring characteristics take precedence over shore hardness;
Insert material acc. to PA66+GF35;
(橡胶参照Q/JLY J7110371E-2022《前、后稳定杆总成技术条件》标准,
产品性能要优先于材料硬度;骨架材料标准参照PA66+GF35;)
- 3.No part marking ; Marking for series part:Date clock,
ZD logo, Cavity number, >NR<,DC1E-A3-F,
(单模产品无刻字;复模产品刻字:时间钟,中鼎徽,型腔号,>NR<,DC1E-A3-F,φ28) ②
4. General Parting line max. 0.5mm thick and 1.0mm long permissible,
(通常飞边要求<0.5mm厚;<1mm长,)
- 5.See DVP&R for part test requirements;
(产品试验要求参见DVP&R;)
- 6.Prohibited/restricted substance acc. to Q/JL J160001-2024;
(禁限用物质要求参照Q/JL J160001-2024标准;)
7. Dimensions of delivery inspection marked ○ ;
(○ 为出厂检验尺寸;)

3	9010655-7/02-02 ©	塑料底座	2	PA66+GF35	C114220/02-02
2	9010655-7/02-01 ©	塑料插片	2	PA66+GF35	C114220/02-01
1		橡胶	1	R5604-H52 ㉔	
NO.	图号	名称	数量	材料	备注
投影法 第一画法 		比例 1:1	质量(g) 91.5g	材质 组件	产品号 C114220-CPSJ
热处理:表面处理				名称 前稳定杆衬套 (前稳定杆衬套)	
批准	标准化	审批	校对		
				夏明成 2025.12.11	稳定杆 系统
图样标记				图号 9010655-7 © (JS1037) ㉔	
S	A	B	共 1 张 第 1 张		㉔ 安徽中鼎密封件股份有限公司 A3