

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16							
A											来历	客户版本号	变更标记	区域	变更事项	中鼎版本号	年月日	变更者	A				
												04			首次下发图纸	A	2024.12.31	蒋子杰					
											SJ-250915	05	◎/2		变更产品图号	B	2025.3.19	蒋子杰					
B																			B				
	Variant	ZD SAP No.	Mubea proto. SAP No.	Mubea serial SAP No.		Mubea part No.	Rubber compound	Hardness (shore A)	Stab diameter (mm)	Bushing diameter (mm)	Insert outer radius (mm)	Insert inner radius (mm)	Insert thickness (mm)	Rubber thickness (mm)	Rubber thickness (mm)	Inner rubber thickness (mm)	Total weight (g)	Rubber volume 3 (cm)	Mubea part No. part 1	Material part 1	Material part 2		
			◎	without coating	with coating				ØA	ØE	RAR	RIR	B	T1A	T1B	T2							
A	C114284	91991220				TE-05-03-23-01-A	R5621	55±3	30.4-30.0	29.2	21.35	18.85	2.5	14.4	11.4	4.75	53	30.8	TE-05-03-23-02	GB/T 5754-H22	NR-BR, GS 93010 31 110-NR-55		
B	C114285	91991221				TE-05-03-23-01-B	R5621-H60	60±3	28.8	27.8				15.1	12.1	5.45	54	31.9			NR-BR, GS 93010 31 110-NR-60		
C																							C
D																							D
E																							E
F																							F
G																							G
H																							H
I																							I
J																							J
K																							K
L																							L
	DIN ISO 3302-1 M2 class																						
	>	≤	F(±)	C±																			
	0	4	0.10	0.15																			
	4	6.3	0.15	0.20																			
	6.3	10	0.20	0.25																			
	10	16	0.20	0.25																			
	16	25	0.25	0.35																			
	25	40	0.35	0.40																			
	40	63	0.40	0.50																			
	63	100	0.50	0.70																			
	100	160	0.70	0.80																			
	160		0.5%	0.7%																			
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16							

Mubea part number
Mubea图号

R28.5±0.3

R25.5±0.3

TE-05-03-23-01-A

ØE±0.3

27±0.3

(0.5)

42.6±0.3

38±0.3

A

Time clock
时间轴

51.98±0.3

54.96±0.3

ZD Logo

A

Variant letter
衬套字母

(0.5)

(RAR)

(RIR)

A - A

(B)

1

2

(33.39)

T2±0.3

T1B±0.3

T1A±0.3

B - B

Stabilizer diameter
(see table)
稳定杆杆径(如附表)

Ø30.4±0.0

B

B

01

Material code
材料代码

cavity No.
型腔号

Specification技术要求:

1.Nature rubber refer to the spec GS 93010 .
天然胶参照标准GS 93010 ;

2.No release agent containing Silicone material to be used.
不使用含硅材料的脱模剂;

3.General tolerance on rubber M2 as norm ISO 3302.1 .
橡胶尺寸公差参照ISO 3302.1 M2级 ;

4.The position and the present of the insert (rate plate) has to be 100% automatically controlled.
100%自动控制骨架的位置和存在 ;

5.The bonding between the rubber and the inserts needs to be stronger than >95% rubber break.
骨架与橡胶粘接面积应>95% ;

6.Emission reduced acc. To akt. GADSL and EU-directive 2000/53/EG.
节能减排参考akt. GADSL和EU-directive 2000/53/EG;

7.Mould misalignment max. 0.5 mm permissible.
模具偏差最大允许0.5毫米;

8.General parting line max. 0.5 mm thick and 1 mm long permissible. No parting line on the bonding surface to the stabilizer.
通常飞边要求≤0.5mm厚,≤1mm长,与稳定杆粘接面上不得有分型线;

9.◎ is marked for inspection dimensions.
◎为出厂检验尺寸。

Reference参考:

ISO 8015

DIN 1451

DIN 16742

DIN EN 1396

ISO 1817

ISO 3302

ISO 2768

VDA 260

GS 91002

GS 93008

GS 93010

GS 93016

QV 31075

WN 730007

ASTM D2000

BMW PR 945:21/07/2021

2	TE-05-03-23-02	铝骨架Al inlay	5754-H22	1	C114284/01-01	
1	/	橡胶Rubber	R5621	1		
序号	图号	名称	材料	数量	备注	
投影法	第一画法	比例	质量(g)	材质	产品号	
		1:1	见表格	组件	C114284-CPSJ	
热处理·表面处理	名称				稳定杆衬套 (后稳定杆衬套)	
批准	标准化	审批	校对	设计	项目组	
				蒋子杰	稳定杆系统	
图样标记	S	共 1 张 第 1 张			91991220 ◎ (WJK37)	
					安徽中鼎密封件股份有限公司	A3