

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16																																																																				
										来历	客户版本号	变更标记	区域	变更事项	中鼎版本号	年月日	变更者																																																																		
											04			首次下发图纸	A	2024.12.20	蒋子杰																																																																		
										SJ-250915	05	②/2		变更产品图号	B	2025.3.19	蒋子杰																																																																		
Variant	ZD SAP No.	Mubea proto. SAP No. ②	Mubea serial SAP No.		Mubea part No.	Hardness (shore A)	Stab diameter (mm)	Bushing diameter (mm)	Insert outer radius (mm)	Insert inner radius (mm)	Insert thickness (mm)	Rubber thickness (mm)	Inner rubber thickness (mm)	Total weight (g)	Rubber volume 3 (cm)	Mubea part No. part 1	Material part 1	Material part 2																																																																	
			without coating	with coating			ØA	ØE	RAR	RIR	B	T1	T2																																																																						
A	C114286	91993744			TE-06-03-23-01-A	55±3	31.0-30.6	29.8	20.7	19.5	1.2	15.1	5.35	62	33.1	TE-06-03-23-03	GB/T DC01	NR-BR, GS 93010 31 110-NR-55																																																																	
B	C114287	91991163			TE-06-03-23-01-B	55±3	30.0	29.0				15.5	5.75	63	33.7																																																																				
C	C114288	91991165			TE-06-03-23-01-C	60±3	29.0	28.0				16.0	6.25	64	34.6			NR-BR, GS 93010 31 110-NR-60																																																																	
Variant letter on both bushing sides 衬套两侧的字母 Upper part marking(line above lettering) on both sides; 上衬套两侧标识(线状) Mubea part number Mubea图号 Material code 材料代码 Stabilizer diameter(see table) 稳定杆杆径(如附表) Specification技术要求: 1.Nature rubber refer to the spec GS 93010 . 天然胶参照标准GS 93010 ; 2.No release agent containing Silicone material to be used. 不使用含硅材料的脱模剂; 3.General tolerance on rubber M2 as norm ISO 3302.1 . 橡胶尺寸公差参照ISO 3302.1 M2级 ; 4.The bonding between the rubber and the inserts needs to be stronger than >95% rubber break. 骨架与橡胶粘接面积应>95% ; 5.Emission reduced acc. To akt. GADSL and EU-directive 2000/53/EG. 节能减排需参考akt. GADSL和EU-directive 2000/53/EG; 6.Mould misalignment max. 0.5 mm permissible. 模具偏差最大允许0.5毫米; 7.General parting line max. 0.5 mm thick and 1 mm long permissible. No parting line on the bonding surface to the stabilizer. 通常飞边要求≤0.5mm厚,≤1mm长,与稳定杆粘接面上不得有分型线; 8.⊙ is marked for inspection dimensions. ⊙为出厂检验尺寸. Reference参考: ISO 8015 DIN 1451 DIN 16742 DIN EN 1396 ISO 1817 ISO 3302 ISO 2768 VDA 260 GS 91002 GS 93008 GS 93010 GS 93016 QV 31075 WN 730007 ASTN D2000 BMW PR 945:21/07/2021																																																																																			
<table><tr><td colspan="4">DIN ISO 3302-1 M2 class</td></tr><tr><td>></td><td>≤</td><td>F(±)</td><td>C±</td></tr><tr><td>0</td><td>4</td><td>0.10</td><td>0.15</td></tr><tr><td>4</td><td>6.3</td><td>0.15</td><td>0.20</td></tr><tr><td>6.3</td><td>10</td><td>0.20</td><td>0.25</td></tr><tr><td>10</td><td>16</td><td>0.20</td><td>0.25</td></tr><tr><td>16</td><td>25</td><td>0.25</td><td>0.35</td></tr><tr><td>25</td><td>40</td><td>0.35</td><td>0.40</td></tr><tr><td>40</td><td>63</td><td>0.40</td><td>0.50</td></tr><tr><td>63</td><td>100</td><td>0.50</td><td>0.70</td></tr><tr><td>100</td><td>160</td><td>0.70</td><td>0.80</td></tr><tr><td>160</td><td>-</td><td>0.5%</td><td>0.7%</td></tr></table>																		DIN ISO 3302-1 M2 class				>	≤	F(±)	C±	0	4	0.10	0.15	4	6.3	0.15	0.20	6.3	10	0.20	0.25	10	16	0.20	0.25	16	25	0.25	0.35	25	40	0.35	0.40	40	63	0.40	0.50	63	100	0.50	0.70	100	160	0.70	0.80	160	-	0.5%	0.7%																		
DIN ISO 3302-1 M2 class																																																																																			
>	≤	F(±)	C±																																																																																
0	4	0.10	0.15																																																																																
4	6.3	0.15	0.20																																																																																
6.3	10	0.20	0.25																																																																																
10	16	0.20	0.25																																																																																
16	25	0.25	0.35																																																																																
25	40	0.35	0.40																																																																																
40	63	0.40	0.50																																																																																
63	100	0.50	0.70																																																																																
100	160	0.70	0.80																																																																																
160	-	0.5%	0.7%																																																																																
<table><tr><td>2</td><td>TE-06-03-23-03</td><td>铁骨架</td><td>DC01</td><td>1</td><td>C114286/01-01</td></tr><tr><td>1</td><td></td><td>橡胶</td><td>R5621</td><td>1</td><td></td></tr><tr><td>序号</td><td>图号</td><td>名称</td><td>材料</td><td>数量</td><td>备注</td></tr><tr><td>投影法</td><td>第一画法</td><td>比例</td><td>质量(g)</td><td>材质</td><td>产品号</td></tr><tr><td></td><td></td><td>1:1</td><td>见表格</td><td>组件</td><td>C114286-CPSJ</td></tr><tr><td>热处理·表面处理</td><td colspan="3"></td><td>名称</td><td></td></tr><tr><td></td><td></td><td></td><td></td><td>稳定杆衬套 (前稳定杆衬套)</td><td></td></tr><tr><td>批准</td><td>标准化</td><td>审批</td><td>校对</td><td>设计</td><td>项目组</td></tr><tr><td></td><td></td><td></td><td></td><td>蒋子杰</td><td>稳定杆系统</td></tr><tr><td></td><td></td><td></td><td></td><td>2025.3.19</td><td></td></tr><tr><td>图样标记</td><td>S</td><td></td><td></td><td>共 2 张 第 2 张</td><td>Ⓜ 安徽中鼎密封件股份有限公司 A3</td></tr></table>																		2	TE-06-03-23-03	铁骨架	DC01	1	C114286/01-01	1		橡胶	R5621	1		序号	图号	名称	材料	数量	备注	投影法	第一画法	比例	质量(g)	材质	产品号			1:1	见表格	组件	C114286-CPSJ	热处理·表面处理				名称						稳定杆衬套 (前稳定杆衬套)		批准	标准化	审批	校对	设计	项目组					蒋子杰	稳定杆系统					2025.3.19		图样标记	S			共 2 张 第 2 张	Ⓜ 安徽中鼎密封件股份有限公司 A3
2	TE-06-03-23-03	铁骨架	DC01	1	C114286/01-01																																																																														
1		橡胶	R5621	1																																																																															
序号	图号	名称	材料	数量	备注																																																																														
投影法	第一画法	比例	质量(g)	材质	产品号																																																																														
		1:1	见表格	组件	C114286-CPSJ																																																																														
热处理·表面处理				名称																																																																															
				稳定杆衬套 (前稳定杆衬套)																																																																															
批准	标准化	审批	校对	设计	项目组																																																																														
				蒋子杰	稳定杆系统																																																																														
				2025.3.19																																																																															
图样标记	S			共 2 张 第 2 张	Ⓜ 安徽中鼎密封件股份有限公司 A3																																																																														
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16																																																																				