

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16			
A											来历	客户版本号	变更标记	区域	变更事项	中鼎版本号	年月日	变更者	A
												04			首次下发图纸	A	2024.12.20	蒋子杰	
											SJ-250915	05	◎/2		变更产品图号	B	2025.3.19	蒋子杰	
B																		B	
	Variant	ZD SAP No.	Mubea proto. SAP No.	Mubea serial SAP No.		Mubea part No.	Hardness (shore A)	Stab diameter (mm)	Bushing diameter (mm)	Insert outer radius (mm)	Insert inner radius (mm)	Insert thickness (mm)	Rubber thickness (mm)	Inner rubber thickness (mm)	Total weight (g)	Rubber volume 3 (cm³)	Mubea part No. part 1	Material part 1	Material part 2
			②	without coating	with coating			ØA	ØE	RAR	RIR	B	T1	T2					
C	A	C114286	91993744			TE-06-03-23-01-A	55±3	31.0-30.6	29.8				15.1	5.35	62	33.1	TE-06-03-23-03	GB/T DC01	NR-BR, GS 93010 31 110-NR-55
	B	C114287	91991163			TE-06-03-23-01-B	55±3	30.0	29.0	20.7	19.5	1.2	15.5	5.75	63	33.7			NR-BR, GS 93010 31 110-NR-60
	C	C114288	91991165			TE-06-03-23-01-C	60±3	29.0	28.0				16.0	6.25	64	34.6			
D																		D	
E																		E	
F																		F	
G																		G	
H																		H	
I																		I	
J																		J	
K																		K	
L																		L	

Variant letter on both bushing sides
衬套两侧的字母

Upper part marking(line above lettering) on both sides;
上衬套两侧标识(线状)

Mubea part number
Mubea图号

Material code
材料代码

Stabilizer diameter(see table)
稳定杆杆径(如附表)

Specification技术要求:
1.Nature rubber refer to the spec GS 93010 .
天然胶参照标准GS 93010 ;
2.No release agent containing Silicone material to be used.
不使用含硅材料的脱模剂;
3.General tolerance on rubber M2 as norm ISO 3302.1 .
橡胶尺寸公差参照ISO 3302.1 M2级 ;
4.The bonding between the rubber and the inserts needs to be stronger than >95% rubber break.
骨架与橡胶粘接面积应>95% ;
5.Emission reduced acc. To akt. GADSL and EU-directive 2000/53/EG.
节能减排需参考akt. GADSL和EU-directive 2000/53/EG;
6.Mould misalignment max. 0.5 mm permissible.
模具偏差最大允许0.5毫米;
7.General parting line max. 0.5 mm thick and 1 mm long permissible. No parting line on the bonding surface to the stabilizer.
通常飞边要求≤0.5mm厚,≤1mm长,与稳定杆粘接面上不得有分型线;
8.◎ is marked for inspection dimensions.
◎为出厂检验尺寸。

Reference参考:
ISO 8015
DIN 1451
DIN 16742
DIN EN 1396
ISO 1817
ISO 3302
ISO 2768
VDA 260
GS 91002
GS 93008
GS 93010
GS 93016
QV 31075
WN 730007
ASTN D2000
BMW PR 945:21/07/2021

DIN ISO 3302-1 M2 class

>	≤	F(±)	C±
0	4	0.10	0.15
4	6.3	0.15	0.20
6.3	10	0.20	0.25
10	16	0.20	0.25
16	25	0.25	0.35
25	40	0.35	0.40
40	63	0.40	0.50
63	100	0.50	0.70
100	160	0.70	0.80
160	-	0.5%	0.7%

Time clock and cavity No.
时间钟和型腔号

ZD Logo

投影法
第一画法

比例
1:1

质量(g)
见表格

材质
组件

产品号
C114287-CPSJ

名称
稳定杆衬套
(前稳定杆衬套)

图号
91991163 ◎
(WJK37)

批准
标准化
审批
校对
设计
项目组

蒋子杰
2025.3.19
稳定杆系统

图样标记
S

共 2 张 第 2 张

安徽中鼎密封件股份有限公司

A3