

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16					
A											来 历		客户版本号	变更标记	区域	变更事项	中鼎版本号	年 月 日	变更者	A	
													04			首次下发图纸	A	2024.12.20	蒋子杰		
											SJ-250915		05	@/2		变更产品图号	B	2025.3.19	蒋子杰		
B																					B
	Variant	ZD SAP No. ②	Mubea proto. SAP No.	Mubea serial SAP No. without coating with coating		Mubea part No.	Hardness (shore A)	Stab diameter (mm) ØA	Bushing diameter (mm) ØE	Insert outer radius (mm) RAR	Insert inner radius (mm) RIR	Insert thickness (mm) B	Rubber thickness (mm) T1	Inner rubber thickness (mm) T2	Total weight (g)	Rubber volume 3 (cm)	Mubea part No. part 1	Material part 1	Material part 2		
	A	C114289	91993745			TE-06-03-23-02-A	55±3	31.0-30.6	29.8				12.1	5.35	71	40.8			NR-BR, GS 93010 31 110-NR-55		
C	B	C114290	91991164			TE-06-03-23-02-B	55±3	30.0	29.0	20.7	19.5	1.2	12.5	5.75	72	41.5	TE-06-03-23-03	GB/T DC01			
	C	C114291	91991166			TE-06-03-23-02-C	60±3	29.0	28.0				13.0	6.25	73	42.4			NR-BR, GS 93010 31 110-NR-60		
D																					D
E																					E
F																					F
G																					G
H																					H
I																					I
J																					J
K																					K
L																					L
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16					

Material code
材料代码

Material code
材料代码

Variant letter on both bushing sides
衬套两侧的字母

Stabilizer diameter(see table)
稳定杆杆径(如附表)

Mubea part number
Mubea图号

Time clock and cavity No.
时间钟和型腔号

ZD Logo

Specification技术要求:
1.Nature rubber refer to the spec GS 93010 .
天然胶参照标准GS 93010 ;
2.No release agent containing Silicone material to be used.
不使用含硅材料的脱模剂;
3.General tolerance on rubber M2 as norm ISO 3302.1 .
橡胶尺寸公差参照ISO 3302.1 M2级 ;
4.The bonding between the rubber and the inserts needs to be stronger than >95% rubber break.
骨架与橡胶粘接面积应>95% ;
5.Emission reduced acc. To akt. GADSL and EU-directive 2000/53/EG.
节能减排需参考akt. GADSL和EU-directive 2000/53/EG;
6.Mould misalignment max. 0.5 mm permissible.
模具偏差最大允许0.5毫米;
7.General parting line max. 0.5 mm thick and 1 mm long permissible. No parting line on the bonding surface to the stabilizer.
通常飞边要求≤0.5mm厚,≤1mm长,与稳定杆粘接面上不得有分型线;
8.⊙ is marked for inspection dimensions.
⊙为出厂检验尺寸。

Reference参考:
ISO 8015
DIN 1451
DIN 16742
DIN EN 1396
ISO 1817
ISO 3302
ISO 2768
VDA 260
GS 91002
GS 93008
GS 93010
GS 93016
QV 31075
WN 730007
ASTN D2000
BMW PR 945:21/07/2021

2	TE-06-03-23-03	铁骨架	DC01	1	C114286/01-01
1		橡胶	R5621	1	
序号	图号	名称	材料	数量	备注
投影法	第一画法	比例	质量(g)	材质	产品号
		1:1	见表格	组件	C114290-CPSJ
热处理	表面处理	名称			
批准	标准化	审批	校对	设计	项目组
				蒋子杰	稳定杆系统
图样标记	S	共 1 张 第 1 张			91991164 ② (WJK37)
					安徽中鼎密封件股份有限公司

>	≤	F(±)	C±
0	4	0.10	0.15
4	6.3	0.15	0.20
6.3	10	0.20	0.25
10	16	0.20	0.25
16	25	0.25	0.35
25	40	0.35	0.40
40	63	0.40	0.50
63	100	0.50	0.70
100	160	0.70	0.80
160	-	0.5%	0.7%

DIN ISO 3302-1 M2 class