

																来 历		客 户 版 本 号		变 更 标 记		区 域		变 更 事 项		中 鼎 版 本 号		年 月 日		变 更 者	
																								首次下发产品图纸		A		2024.12.27		蒋子杰	
																SJ-251140				②/2				更新质量及材料标准		B		2025.4.25		蒋子杰	
																Total weight (g)		Rubber volume 3 (cm ³)		Mubea part No. part 1		Material part 1		Material part 2							
																⑥		③						⑧							
																23		16.1		TE-01-03-24-03				ASTM D2000 M4AA 514 A13 B13 F17							
																23.7		16.8						ASTM D2000 M4AA 614 A13 B13 F17							
																26.6		15.8		TE-01-03-24-04		GB/T 5754-H22		ASTM D2000 M4AA 614 A13 B13 F17							
																27.2		16.3						ASTM D2000 M4AA 614 A13 B13 F17							
																28.1		16.8						ASTM D2000 M4AA 614 A13 B13 F17							
																24.1		14.8		TE-01-03-24-05		PA66 GF30		ASTM D2000 M4AA 614 A13 B13 F17							
																24.6		15.3													

杆径标识、MUBEA图号

型号标识

A-A
1:1

B-B
1:1

中鼎徽、型腔号、时间钟

Specification技术要求:

1.Nature rubber refer to the spec ASTM D2000 .
天然胶参照标准ASTM D2000 ;
2.No release agent containing Silicone material to be used.
不使用含硅材料的脱模剂;
3.General tolerance on rubber M2 as norm ISO 3302.1 .
橡胶尺寸公差参照ISO 3302.1 M2级 ;
4.The bonding between the rubber and the inserts needs to be stronger than >95% rubber break.
骨架与橡胶粘接面积应>95% ;
5.Emission reduced acc. To akt. GADSL and EU-directive 2000/53/EG.
节能减排需参考akt. GADSL和EU-directive 2000/53/EG;
6.Mould misalignment max. 0.5 mm permissible.
模具偏差最大允许0.5毫米;
7.General parting line max. 0.5 mm thick and 1 mm long permissible.
No parting line on the bonding surface to the stabilizer.
通常飞边要求≤0.5mm厚,≤1mm长,与稳定杆粘接面上不得有分型线;
8.⑧ is marked for inspection dimensions.
⑥为出厂检验尺寸。

2	TE-01-03-24-03	铝骨架	5754-H22	1	C114304/01-01
1		橡胶	R5621-H60	1	
序号	图号	名称	材料	数量	备注
投影法 Projection method		比例Scale		质量Weight(g)	材质Material
第一画法First angle projection		1:1			产品号ZD production code
热处理·表面处理Heat Treatment·Surface Treatment				名称Part name	
批准	标准化	审批	校对	设计	项目组
Approval	Standards	Review	Check	Design	Team
蒋子杰 2025.4.25 稳定杆系统				图号Drawing No	
				91993248 (WDG06)	
标记SIGN	S	共 1 张 第 1 张			安徽中鼎密封件股份有限公司

Reference参考:

ISO 8015
DIN 1451
DIN EN 1396
ISO 1817
ISO 3302
ISO 2768
VDA 260
GADSL
Note-DPR-34184774

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16

Reference参考:
ISO 8015
DIN 1451
DIN EN 1396
ISO 1817
ISO 3302
ISO 2768
VDA 260
GADSL
Note-DPR-34184774