

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16																																																																	
									来历	客户版本号	变更标记	区域	变更事项		中鼎版本号	年月日	变更者	A																																																														
													首次下发		A	20250217	范康祺																																																															
技术要求: Specifications: 1.天然胶,硬度:60±3 shA,参照标准DBL 5558-45; Nature rubber according to DBL 5558-45. 2.耐臭氧实验参照标准ISO 1431-1 A法,参照标准DBL 5555 0级无裂纹; Ozone test according ISO 1431-1 operation mode A, grade 0 no cracking according DBL 5555. 3.自然老化参照标准DIN EN ISO 4892-2(850h,65±3℃,HR 60% min,61±2W/mm2/), 参照标准DBL 5555 0级无裂纹; Artificial weathering in accordance with DIN EN ISO 4892-2/ 850h/65±3℃/HR 60% min/61±2W/mm2/ ,grade 0 no cracking according DBL 5555 4.由索格菲完成粘接工序; The gluing is made by Sogefi. 5.粘接准备事项Bush status before for gluing on stab bar: •内表面需保持清洁,索格菲粘接前无需处理措施; •衬套出模后6个月可粘接; •采用脱模剂必须与索格菲粘接工艺兼容; •The internal surface of the bush must be clean and can receive the Sogefi glue without surface preparation. •The gluing operation can be made 6 months maximum after moulding. •The release agent used for bushes must be compatible with the Sogefi glue. 6.特殊性参照标准IGR-D-20/0: Special characteristics as IGR-D-20/0: 关键特性标识Critical: 重要特性标识Important: 橡胶尺寸公差参照NF/T47-001 M3级执行; General tolerances on rubber M3 as norm NF/T47.001. 7.追溯性标识:字高2.5mm,字深0.2mm; Traceability:characters height 2.5mm,characters deep 0.2mm. 8.刚度采用刚性夹具完成: 8-1.Z向静刚度:加载±5000N,速度:30mm/min,循环3次,计算±3000N时的刚度; 8-2.Z向动刚度:振幅±0.025mm,频率15到150Hz,增幅5Hz,计算100Hz时的刚度; 8-3.轴向刚度:加载±500N,速度:20mm/min,循环3次,计算±500N时的刚度; 8-4.扭转刚度:加载±25°,速度60°/min,循环3次,计算±3°时的刚度; Stiffness are checked with rigid blocks to meet the specification. 8-1.Radial static stiffness Kz:Load ±5000N for 3 cycles,speed:30mm/min,check at±3000N. 8-2.Radial dynamic stiffness Kdz:Amplitude ±0.025mm,frequency:15 to 150Hz,amplification:5Hz,check at 100Hz. 8-3.Axial stiffness:Load ±500N for 3 cycles,speed:20mm/min,check at±500N. 8-4.Torsional stiffness Kty:Load ±25° for 3 cycles,speed:60°/min,check at ±3°. 9.其他试验参照索格菲试验计划; The rest tests refer to Sogefi test plan. 10. 为工序、出厂检验尺寸。 is marked for inspection dimensions.																								B																																																								
																								C																																																								
																								D																																																								
																								E																																																								
																								F																																																								
																								G																																																								
																								H																																																								
																								I																																																								
									<table><tr><th colspan="9">NF/T 47-001 CLASS M3</th></tr><tr><th></th><th>≤6.3</th><th>≤10</th><th>≤16</th><th>≤25</th><th>≤40</th><th>≤63</th><th>≤100</th><th>≤160</th></tr><tr><td>F</td><td>±0.20</td><td>±0.20</td><td>±0.25</td><td>±0.35</td><td>±0.40</td><td>±0.50</td><td>±0.70</td><td>±0.80</td></tr><tr><td>C</td><td>±0.25</td><td>±0.35</td><td>±0.40</td><td>±0.50</td><td>±0.70</td><td>±0.80</td><td>±1.00</td><td>±1.30</td></tr></table>									NF/T 47-001 CLASS M3										≤6.3	≤10	≤16	≤25	≤40	≤63	≤100	≤160	F	±0.20	±0.20	±0.25	±0.35	±0.40	±0.50	±0.70	±0.80	C	±0.25	±0.35	±0.40	±0.50	±0.70	±0.80	±1.00	±1.30							J																				
NF/T 47-001 CLASS M3																																																																																
	≤6.3	≤10	≤16	≤25	≤40	≤63	≤100	≤160																																																																								
F	±0.20	±0.20	±0.25	±0.35	±0.40	±0.50	±0.70	±0.80																																																																								
C	±0.25	±0.35	±0.40	±0.50	±0.70	±0.80	±1.00	±1.30																																																																								
									<table><tr><td>投影法</td><td colspan="2">第一画法</td><td>比例</td><td colspan="2">1:1</td><td>质量(g)</td><td colspan="2">0.00g</td><td>材质</td><td colspan="2">30R7770-H60</td><td>产品号</td><td colspan="2">20C114428-CPSJ</td></tr><tr><td colspan="10">热处理:表面处理</td><td colspan="4">名称</td><td colspan="2">前稳定杆衬套 (前稳定杆衬套)</td></tr><tr><td>批准</td><td>标准化</td><td>审批</td><td>校对</td><td>设计</td><td>项目组</td><td colspan="7" rowspan="2">图号 18374-D27 (WFG58)</td></tr><tr><td colspan="6">图样标记</td><td>S</td><td colspan="2">共 1 张 第 1 张</td><td colspan="2">安徽中鼎密封件股份有限公司</td><td>A3</td></tr></table>									投影法	第一画法		比例	1:1		质量(g)	0.00g		材质	30R7770-H60		产品号	20C114428-CPSJ		热处理:表面处理										名称				前稳定杆衬套 (前稳定杆衬套)		批准	标准化	审批	校对	设计	项目组	图号 18374-D27 (WFG58)							图样标记						S	共 1 张 第 1 张		安徽中鼎密封件股份有限公司		A3							K
投影法	第一画法		比例	1:1		质量(g)	0.00g		材质	30R7770-H60		产品号	20C114428-CPSJ																																																																			
热处理:表面处理										名称				前稳定杆衬套 (前稳定杆衬套)																																																																		
批准	标准化	审批	校对	设计	项目组	图号 18374-D27 (WFG58)																																																																										
图样标记													S	共 1 张 第 1 张		安徽中鼎密封件股份有限公司		A3																																																														
									<table><tr><th colspan="2">索格菲杆径调教</th></tr><tr><th>杆径</th><th>ØA</th></tr><tr><td>32</td><td>31.5</td></tr><tr><td>29.5</td><td>29</td></tr><tr><td>27</td><td>26.5</td></tr></table>									索格菲杆径调教		杆径	ØA	32	31.5	29.5	29	27	26.5									L																																												
索格菲杆径调教																																																																																
杆径	ØA																																																																															
32	31.5																																																																															
29.5	29																																																																															
27	26.5																																																																															
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16																																																																	