

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16			
A										No.	客户版本号 (CUSTOMER VERSION)	No.	变更标记 (MARK CHANGE)	更改内容 (CHANGE CONTENT)		中鼎版本号 (ZD version)	日期 (DATE)	责任人 (RESPONSIBLE)	A
B														Initial Release (初始版本)		A	20250326	马传德	
C																			
D																			
E																			
F																			
G																			
H																			
I																			
J																			
K																			
L																			

技术要求: Specifications:

1. 天然胶, 硬度: 60±5 shore A, 参照标准RENAULT 30-00-118;
Nature rubber with 60±5 shore A, according to the spec. RENAULT 30-00-118.

2. 由索格菲完成粘接工序; The gluing is made by Sogefi.

3. 粘接准备事项 Bush status before for gluing on stab bar:
3.1 衬套内表面需保持清洁并进行活化, 索格菲粘接前无需额外的表面处理;
3.2 衬套出模后6个月可粘接;
3.3 采用脱模剂必须与索格菲粘接工艺兼容;
3.1 The internal surface of the bush must be clean and chemically activated, and can receive the Sogefi glue without additional surface preparation.
3.2 The gluing operation can be made 6 months maximum after moulding.
3.3 The release agent used for bushes must be compatible with the Sogefi glue.

4. 特殊特性参照标准 I-02-P-01-01: Special characteristics as I-02-P-01-01:
关键特性标识Critical: ▽
重要特性标识Important: ▽
橡胶尺寸公差参照 DIN ISO 3302-1 Class M3 级执行; General tolerances on rubber DIN ISO 3302-1 Class M3 .

5. 追溯性标识: 字高2.5mm, 字深0.2mm;
Traceability: characters height 2.5mm, characters deep 0.2mm.

6. 刚度采用卡箍和夹具完成 (见附表): Stiffness are checked with serial brackets and rigid blocks to meet the specification (see table).

7. 试验项目: 所有产品试验参照技术标准文件TSB28
Test item: For all tests refer to the technical specification TSB208

8. □ 为工序、出厂检验尺寸。
□ is marked for inspection dimensions.

DIN ISO 3302-1 Class M3										
	≤4	≤6.3	≤10	≤16	≤25	≤40	≤63	≤100	≤160	>160
F	±0.25	±0.25	±0.30	±0.40	±0.50	±0.60	±0.80	±1.00	±1.30	±0.8%
C	±0.40	±0.40	±0.50	±0.60	±0.80	±1.00	±1.30	±1.60	±2.0	±1.3%

CHARACTERISTICS TABLE				REQUEST	STATIC STIFFNESS			
PART NUMBER	ARA REFERENCE	STAB BAR DIAMETER ØD	INTERNAL BUSHING DIAMETER Ød*	DIRECTION	RADIAL Z	TORSION Y	RADIAL X	AXIAL Y
				LOAD SPEED	10mm/min	60° /min	10mm/min	10mm/min
				LOAD	±1mm	±16°	±1mm	±2mm
				CHECK SPEED	10mm/min	60° /min	10mm/min	10mm/min
				CHECK	±0.6mm	±9.6°	±0.6mm	±1.2mm
UNITS	N/mm	N. m/°	N/mm	N/mm				
drw-SAR-000002_08_A	TBD	24	23.5	ARA RIGID BLOCK	TBD	TBD	TBD	TBD
				SERIAL BRACKET	7900	1.2	7900	260

2	drw-SAR-00000208/01-01	Metal insert/金属骨架	1	DC01	C114490/01-01
1		Rubber/橡胶		R5604-H60	
No.	PN/代号	Composition/组成	Quantity/数量	Material/材料	Note/备注
第一角画法 (FIRST ANGLE PROJECTION)		比例 (SCALE) 1:1	重量 (WEIGHT) 48.1g	材料 (MATERIAL) NR+BR (R5604-H60)	产品号 (PRODUCT NO.) C114490-CPSJ
热处理·表面处理 (HEAT TREATMENT·SURFACE TREATMENT)				名称 (NAME) 稳定杆衬套 (前稳定杆衬套)	
批准 (APPROVAL)	标准化 (STD.)	审核 (AUDITOR)	校对 (CHECKER)	设计 (DESIGNER)	项目组 (PROJECT TEAM)
SIGN (标记)				图号 (PART NO.) drw-SAR-00000208 (WFG58)	
PAGES (共 1 张) OF (第 1 张)				ZHONGDING SEALING PARTS CO., LTD 中鼎密封件股份有限公司	