

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16																																																																																											
A	技术要求: Specifications: 1.天然胶, 硬度: 60±3 shA, 参照标准DBL 5558-45; Nature rubber according to DBL 5558-45. 2.由索格菲完成粘接工序; The gluing is made by Sogefi. 3.粘接准备事项Bush status before for gluing on stab bar: •内表面需保持清洁, 索格菲粘接前无需处理措施; •衬套出模后6个月可粘接; •采用脱模剂必须与索格菲粘接工艺兼容; •The internal surface of the bush must be clean and can receive the Sogefi glue without surface preparation. •The gluing operation can be made 6 months maximum after moulding. •The release agent used for bushes must be compatible with the Sogefi glue. 4.特殊特性参照标准IGR-D-20/0: Special characteristics as IGR-D-20/0: 关键特性标识Critical: 重要特性标识Important: 橡胶尺寸公差参照NF/T47-001 M3级执行; 橡胶尺寸公差参照 DIN ISO 3302-1 Class M3 级执行; General tolerances on rubber DIN ISO 3302-1 Class M3 . 5.追溯性标识: 字高2.5mm, 字深0.2mm; Traceability:characters height 2.5mm,characters deep 0.2mm. 6.刚度采用卡箍和夹具完成(见附表): Stiffness are checked with serial brackets and rigid blocks to meet the specification(see table). 7.其他试验参照索格菲试验计划; The rest tests refer to Sogefi test plan. 8.□为工序、出厂检验尺寸。 □ is marked for inspection dimensions.									No.	客户版本号 (CUSTOMER VERSION)	No.	变更标记 (MARK CHANGE)	更改内容 (CHANGE CONTENT)			中鼎版本号 (ZD version)	日期 (DATE)	责任人 (RESPONSIBLE)																																																																																								
B														Initial Release(初始版本)			A	20250616	马传德																																																																																								
C																																																																																																											
D																																																																																																											
E																																																																																																											
F										<table><tr><td>产品号</td><td>杆径</td><td>颜色标识</td></tr><tr><td>C114582</td><td>Ø26</td><td>白色</td></tr><tr><td>C114582</td><td>Ø25</td><td>绿色</td></tr></table>							产品号	杆径	颜色标识	C114582	Ø26	白色	C114582	Ø25	绿色																																																																																		
产品号										杆径	颜色标识																																																																																																
C114582										Ø26	白色																																																																																																
C114582										Ø25	绿色																																																																																																
G																																																																																																											
H																																																																																																											
I																																																																																																											
J	<table><tr><th colspan="4">CHARACTERTISTICS TABLE</th><th>REQUEST</th><th colspan="4">STATIC STIFFNESS</th></tr><tr><th rowspan="5">PART NUMBER</th><th rowspan="5">RUBBER HARDNESS</th><th rowspan="5">STAB BAR DIAMETER ØD</th><th rowspan="5">INTERNAL BUSHING DIAMETER ØA</th><th>DIRECTION</th><th>RADIAL Z</th><th>TORSION Y</th><th>RADIAL X</th><th>AXIAL Y</th></tr><tr><th>LOAD SPEED</th><td>10mm/min</td><td>60° /min</td><td>10mm/min</td><td>10mm/min</td></tr><tr><th>LOAD</th><td>±1mm</td><td>±16°</td><td>±1mm</td><td>±2mm</td></tr><tr><th>CHECK SPEED</th><td>10mm/min</td><td>60° /min</td><td>10mm/min</td><td>10mm/min</td></tr><tr><th>CHECK</th><td>±0.6mm</td><td>±9.6°</td><td>±0.6mm</td><td>±1.2mm</td></tr><tr><th colspan="4"></th><th>UNITS</th><th>N/mm</th><th>N. m/°</th><th>N/mm</th><th>N/mm</th></tr></table>									CHARACTERTISTICS TABLE				REQUEST	STATIC STIFFNESS				PART NUMBER	RUBBER HARDNESS	STAB BAR DIAMETER ØD	INTERNAL BUSHING DIAMETER ØA	DIRECTION	RADIAL Z	TORSION Y	RADIAL X	AXIAL Y	LOAD SPEED	10mm/min	60° /min	10mm/min	10mm/min	LOAD	±1mm	±16°	±1mm	±2mm	CHECK SPEED	10mm/min	60° /min	10mm/min	10mm/min	CHECK	±0.6mm	±9.6°	±0.6mm	±1.2mm					UNITS	N/mm	N. m/°	N/mm	N/mm	<table><tr><th colspan="11">DIN ISO 3302-1 Class M3</th></tr><tr><th></th><th>≤4</th><th>≤6.3</th><th>≤10</th><th>≤16</th><th>≤25</th><th>≤40</th><th>≤63</th><th>≤100</th><th>≤160</th><th>>160</th></tr><tr><td>F</td><td>±0.25</td><td>±0.25</td><td>±0.30</td><td>±0.40</td><td>±0.50</td><td>±0.60</td><td>±0.80</td><td>±1.00</td><td>±1.30</td><td>±0.8%</td></tr><tr><td>C</td><td>±0.40</td><td>±0.40</td><td>±0.50</td><td>±0.60</td><td>±0.80</td><td>±1.00</td><td>±1.30</td><td>±1.60</td><td>±2.0</td><td>±1.3%</td></tr></table>							DIN ISO 3302-1 Class M3												≤4	≤6.3	≤10	≤16	≤25	≤40	≤63	≤100	≤160	>160	F	±0.25	±0.25	±0.30	±0.40	±0.50	±0.60	±0.80	±1.00	±1.30	±0.8%	C	±0.40	±0.40	±0.50	±0.60	±0.80	±1.00	±1.30	±1.60	±2.0	±1.3%
CHARACTERTISTICS TABLE				REQUEST	STATIC STIFFNESS																																																																																																						
PART NUMBER	RUBBER HARDNESS	STAB BAR DIAMETER ØD	INTERNAL BUSHING DIAMETER ØA	DIRECTION	RADIAL Z	TORSION Y	RADIAL X	AXIAL Y																																																																																																			
				LOAD SPEED	10mm/min	60° /min	10mm/min	10mm/min																																																																																																			
				LOAD	±1mm	±16°	±1mm	±2mm																																																																																																			
				CHECK SPEED	10mm/min	60° /min	10mm/min	10mm/min																																																																																																			
				CHECK	±0.6mm	±9.6°	±0.6mm	±1.2mm																																																																																																			
				UNITS	N/mm	N. m/°	N/mm	N/mm																																																																																																			
DIN ISO 3302-1 Class M3																																																																																																											
	≤4	≤6.3	≤10	≤16	≤25	≤40	≤63	≤100	≤160	>160																																																																																																	
F	±0.25	±0.25	±0.30	±0.40	±0.50	±0.60	±0.80	±1.00	±1.30	±0.8%																																																																																																	
C	±0.40	±0.40	±0.50	±0.60	±0.80	±1.00	±1.30	±1.60	±2.0	±1.3%																																																																																																	
K	<table><tr><th rowspan="3">67091-PV</th><th rowspan="3">60 SHA</th><th rowspan="3">26</th><th rowspan="3">25.2</th><th>ARA RIGID BLOCK</th><td>TBD</td><td>TBD</td><td>TBD</td><td>TBD</td></tr><tr><th>SERIAL BRACKET</th><td>5500</td><td>2.0</td><td>TBD</td><td>TBD</td></tr><tr><th colspan="4"></th></tr></table>									67091-PV	60 SHA	26	25.2	ARA RIGID BLOCK	TBD	TBD	TBD	TBD	SERIAL BRACKET	5500	2.0	TBD	TBD					<table><tr><th colspan="6">第一角画法 (FIRST ANGLE PROJECTION)</th><th>比例 (SCALE) 1:1</th><th>重量 (WEIGHT) 48.1g</th><th>材料 (MATERIAL) NR+BR (R6938)</th><th>产品号 (PRODUCT NO.) C114582-CPSJ</th></tr><tr><th colspan="6">热处理 · 表面处理 (HEAT TREATMENT, SURFACE TREATMENT)</th><th colspan="5">名称 (NAME) 前稳定杆衬套 (前稳定杆衬套)</th></tr><tr><th>批准 (APPROVAL)</th><th>标准化 (STD.)</th><th>审核 (AUDITOR)</th><th>校对 (CHECKER)</th><th>设计 (DESIGNER)</th><th>项目组 (PROJECT TEAM)</th><th colspan="5">图号 (PART NO.) 67091-PV (WFG58)</th></tr><tr><td colspan="6"></td><td colspan="5">马传德</td><td></td></tr><tr><td colspan="6">SIGN(标记)</td><td>S</td><td colspan="3">PAGES (共 1 张) OF (第 1 张)</td><td colspan="2">ZHONGDING SEALING PARTS CO., LTD 中鼎密封件股份有限公司</td><td>A3</td></tr></table>							第一角画法 (FIRST ANGLE PROJECTION)						比例 (SCALE) 1:1	重量 (WEIGHT) 48.1g	材料 (MATERIAL) NR+BR (R6938)	产品号 (PRODUCT NO.) C114582-CPSJ	热处理 · 表面处理 (HEAT TREATMENT, SURFACE TREATMENT)						名称 (NAME) 前稳定杆衬套 (前稳定杆衬套)					批准 (APPROVAL)	标准化 (STD.)	审核 (AUDITOR)	校对 (CHECKER)	设计 (DESIGNER)	项目组 (PROJECT TEAM)	图号 (PART NO.) 67091-PV (WFG58)											马传德						SIGN(标记)						S	PAGES (共 1 张) OF (第 1 张)			ZHONGDING SEALING PARTS CO., LTD 中鼎密封件股份有限公司		A3																
67091-PV	60 SHA	26	25.2	ARA RIGID BLOCK	TBD	TBD	TBD	TBD																																																																																																			
				SERIAL BRACKET	5500	2.0	TBD	TBD																																																																																																			
第一角画法 (FIRST ANGLE PROJECTION)						比例 (SCALE) 1:1	重量 (WEIGHT) 48.1g	材料 (MATERIAL) NR+BR (R6938)	产品号 (PRODUCT NO.) C114582-CPSJ																																																																																																		
热处理 · 表面处理 (HEAT TREATMENT, SURFACE TREATMENT)						名称 (NAME) 前稳定杆衬套 (前稳定杆衬套)																																																																																																					
批准 (APPROVAL)	标准化 (STD.)	审核 (AUDITOR)	校对 (CHECKER)	设计 (DESIGNER)	项目组 (PROJECT TEAM)	图号 (PART NO.) 67091-PV (WFG58)																																																																																																					
						马传德																																																																																																					
SIGN(标记)						S	PAGES (共 1 张) OF (第 1 张)			ZHONGDING SEALING PARTS CO., LTD 中鼎密封件股份有限公司		A3																																																																																															
L	<table><tr><th rowspan="3">67091-PV</th><th rowspan="3">60 SHA</th><th rowspan="3">25</th><th rowspan="3">24.2</th><th>ARA RIGID BLOCK</th><td>TBD</td><td>TBD</td><td>TBD</td><td>TBD</td></tr><tr><th>SERIAL BRACKET</th><td>5500</td><td>2.0</td><td>TBD</td><td>TBD</td></tr><tr><th colspan="4"></th></tr></table>									67091-PV	60 SHA	25	24.2	ARA RIGID BLOCK	TBD	TBD	TBD	TBD	SERIAL BRACKET	5500	2.0	TBD	TBD																																																																																				
67091-PV	60 SHA	25	24.2	ARA RIGID BLOCK	TBD	TBD	TBD	TBD																																																																																																			
				SERIAL BRACKET	5500	2.0	TBD	TBD																																																																																																			