

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16					
A	技术要求: Specifications: 1.天然胶,硬度:60±5 shore A,参照标准RENAULT 30-00-118; Nature rubber with 60±5 shore A,according to the spec.RENAULT 30-00-118. 2.由索格菲完成粘接工序; The gluing is made by Sogefi. 3.粘接准备事项 Bush status before for gluing on stab bar: 3.1 内表面需保持清洁,索格菲粘接前无需处理措施 3.2 衬套出模后6个月可粘接; 3.3 采用脱模剂必须与索格菲粘接工艺兼容; 3.1 The internal surface of the bush must be clean and can receive the Sogefi glue without surface preparation. 3.2 The gluing operation can be made 6 months maximum after moulding. 3.3 The release agent used for bushes must be compatible with the Sogefi glue. 4.特殊特性参照标准 I-02-P-01-01:Special characteristics as I-02-P-01-01: 关键特性标识Critical: 重要特性标识Important: 橡胶尺寸公差参照 NF/T47-001 M3级执行; General tolerances on rubber M3 as norm NF/T47.001. 5.追溯性标识:字高2.5mm,字深0.2mm; Traceability:characters height 2.5mm,characters deep 0.2mm. 6.刚度采用卡箍和夹具完成(见附表): Stiffness are checked with serial brackets and rigid blocks to meet the specification(see table). 7.索格菲试验项目(Sogefi test); 7.1 噪音实验:在80℃*4周和120℃*24h环境下对3根老化前后产品分别做噪音实验,测试角度:9.4° &18.8° ,5种温度(-30℃,-20℃,-10℃,0℃,+10℃,+20℃),5次循环,不可察觉的噪音为合格; 7.2 拔脱实验:80%的粘接效果为合格(新件);70%的粘接效果为合格(疲劳件); 7.3 环境试验:在110℃环境下,扭转9.4° ,持续100小时,z&x向静刚度损失<10%,且粘接面积>70%为合格; 7.1 Noisy test:control before and after aging test on 3bars for 4 weeks at 80° c and 24h at 120° c,test angle(9.4° &18.8°),5 temperatures(-30℃,-20℃,-10℃,0℃,+10℃,+20℃),evaluation on 5 cycles,not noticeable noise=OK; 7.2 Destructive tests:80% rubber adhesion for new bush; 70% rubber adhesion after fatigue; 7.3 Ambient test: Preload bars as 9.4° angle for 100h at 110℃,the test is ok if the stiffness loss in z&x < 10% between before and after and peeling ok > 70%. 8.□为工序、出厂检验尺寸。 □is marked for inspection dimensions.									No. 客户版本号 (CUSTOMER VERSION)		No. 变更标记 (MARK CHANGE)		更改内容 (CHANGE CONTENT)		中鼎版本号 (ZD version)		日期 (DATE)		责任人 (RESPONSIBLE)	
B														Initial Release(初始版本)		A		20250902		马传德	
C																					
D																					
E										标识内容: 时间轴、厂家代码、材料标识、零件号、型腔号 Logo: Time clock Manufacture code, Material, Part No., Cavity No.		A-A 1:1									
F																					
G																					
H																					
I	CHARACTERISTICS TABLE									REQUEST		STATIC STIFFNESS				DYNAMIC STIFFNESS					
J	PART NUMBER	ARA REFERENCE	STAB BAR DIAMETER ØD	INTERNAL BUSHING DIAMETER Ød*	CODIFICATION	DIRECTION	RADIAL Z	TORSION Y	RADIAL X	AXIAL Y	RADIAL Z										
LOAD SPEED						10mm/min	60° /min	10mm/min	20mm/min	15 to 150Hz											
K	TBD	18652-227	22.7	22.2	AB	LOAD	±1mm	±16°	±1mm	±2mm	±0.01										
						CHECK	±0.6mm	±9°	±0.6mm	±1.2mm	100Hz										
						UNITS	N/mm	N.m/°	N/mm	N/mm	N/mm										
						ARA RIGID BLOCK	TBD	TBD	TBD	TBD	Kzdyn150/Kz stat<2										
L	TBD	18652-235	23.5	23.0	AC	SERIAL BRACKET	7000±15%	1.5±20%	TBD	TBD	Kzdyn150/Kz stat<2										
						ARA RIGID BLOCK	TBD	TBD	TBD	TBD	Kzdyn150/Kz stat<2										
						SERIAL BRACKET	7000±15%	1.5±20%	TBD	TBD	Kzdyn150/Kz stat<2										
						ARA RIGID BLOCK	TBD	TBD	TBD	TBD	Kzdyn150/Kz stat<2										
	TBD	18652-250	25.0	AD	SERIAL BRACKET	7000±15%	1.5±20%	TBD	TBD	Kzdyn150/Kz stat<2											
					ARA RIGID BLOCK	TBD	TBD	TBD	TBD	Kzdyn150/Kz stat<2											
					SERIAL BRACKET	7000±15%	1.5±20%	TBD	TBD	Kzdyn150/Kz stat<2											
					ARA RIGID BLOCK	TBD	TBD	TBD	TBD	Kzdyn150/Kz stat<2											
DIN ISO 3302-1 Class M3																					
		≤4	≤6.3	≤10	≤16	≤25	≤40	≤63	≤100	≤160	>160										
F		±0.25	±0.25	±0.30	±0.40	±0.50	±0.60	±0.80	±1.00	±1.30	±0.8%										
C		±0.40	±0.40	±0.50	±0.60	±0.80	±1.00	±1.30	±1.60	±2.0	±1.3%										
2 Z6012661/01-01 Plastic insert/塑料骨架 1 PA66+GF30 借用C114360/01-01																					
1 Rubber/橡胶 R5604-H60																					
No.		PN/代号		Composition/组成		Quantity/数量		Material/材料		Note/备注											
第一角画法 (FIRST ANGLE PROJECTION)		比例 (SCALE)		重量 (WEIGHT)		材料 (MATERIAL)		产品号 (PRODUCT NO.)													
		1:1		TBDg		NR+BR (R5604-H60)		C114715-CPSJ													
热处理·表面处理 (HEAT TREATMENT·SURFACE TREATMENT)																					
名称 (NAME)																					
前上稳定杆衬套 (前稳定杆衬套)																					
批准 (APPROVAL)		标准化 (STD.)		审核 (AUDITOR)		校对 (CHECKER)		设计 (DESIGNER)		项目组 (PROJECT TEAM)											
陈瑞		赵旭		钱琳		王伟		马传德		Stabilizer System 稳定杆系统											
2025.9.2																					
SIGN(标记)		PAGES(共 1 张)		OF(第 1 张)		ZHONGDING SEALING PARTS CO.,LTD		中鼎密封件股份有限公司		A3											