

☐ is marked for inspection dimensions.

CHARACTERISTICS TABLE						REQUEST	STATIC STIFFNESS			
PART NUMBER	ARA REFERENCE	STAB BARDIAMET ERØD	INTERNALB USHINGDIA METERØd*	RUBBER HARDNESS	CODIFICA TION	DIRECTION	RADIAL Z	TORSION Y	RADIAL X	AXIAL Y
						LOAD SPEED	30mm/min	120° /min	30mm/min	20mm/min
						LOAD	±5000N	±25°	±5000N	±500N
						CHECK SPEED	10mm/min	60° /min	10mm/min	20mm/min
		mm	mm			CHECK	±3000N	±3°	±3000N	±500N
						UNITS	N/mm	N. m/°	N/mm	N/mm
Jrw-SAR-0000 0442	/	26.5	26	50 SHA	TBD	ARA RIGID BLOCK	TBD	TBD	TBD	TBD
						SERIAL BRACKET	7750±15%	TBD	TBD	1.5±20%
	/	24.5	24	60 SHA	TBD	ARA RIGID BLOCK	TBD	TBD	TBD	TBD
						SERIAL BRACKET	7750±15%	TBD	TBD	1.5±20%
	/	23.5	23	62 SHA	TBD	ARA RIGID BLOCK	TBD	TBD	TBD	TBD
						SERIAL BRACKET	7750±15%	TBD	TBD	1.5±20%
	/	22.5	22	65 SHA	TBD	ARA RIGID BLOCK	TBD	TBD	TBD	TBD
						SERIAL BRACKET	7750±15%	TBD	TBD	1.5±20%