

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16																																																		
A	技术要求: 1、橡胶配方参照标准VW 2.8.1,其中94h*70℃老化及504h*55℃老化实验参照标准TL52716; 2、塑料骨架参照标准VW 50133; 3、未注尺寸公差参照DIN 3302-1 M3级; 4、产品刻字参照标准DIN 1451-(T4)H2; 5、产品性能实验测试方法和标准如表1; 6、通常飞边要求≤0.5mm厚,≤1mm长,模具偏差最大允许0.5毫米; 7、图中○为出厂检测尺寸。									来历	客户版本号	变更标记	区域	变更事项			中鼎版本号	年月日	变更者	A																																														
B														首次下发产品图纸			A	2025.11.12	毛伟	B																																														
C																				C																																														
D																				D																																														
E	表1:衬套性能实验 <table><tr><th>试验项目</th><th>试验方法</th><th>试验要求(±15%)</th></tr><tr><td rowspan="4">Z向刚度</td><td>1-预载±1mm,循环3次,速度100mm/min</td><td></td></tr><tr><td>1.1-加载±1mm,计算±0.6mm</td><td>6000N/mm</td></tr><tr><td>1.2-加载±0.5mm,计算±0.3mm</td><td>6500N/mm</td></tr><tr><td>1.3-加载±0.25mm,计算±0.15mm</td><td>7000N/mm</td></tr><tr><td rowspan="4">扭转刚度</td><td>2-预载±16°,循环3次,速度1.67°/sec</td><td></td></tr><tr><td>2.1-加载±16°,计算±9.6°</td><td>1.2Nm/deg</td></tr><tr><td>2.2-加载±8°,计算±4.8°</td><td>1.3Nm/deg</td></tr><tr><td>2.3-加载±4°,计算±2.4°</td><td>1.5Nm/deg</td></tr><tr><td>耐久实验</td><td>Z向加载±4932N,扭转±6.92°,频率1Hz,循环5万次</td><td>无异响、无裂纹</td></tr><tr><td>粘接实验</td><td>用∅A+3的套筒压脱短棒,检测压脱面积和力值</td><td>压脱力≥5000N,粘接面积≥90%</td></tr></table>									试验项目	试验方法	试验要求(±15%)	Z向刚度	1-预载±1mm,循环3次,速度100mm/min		1.1-加载±1mm,计算±0.6mm	6000N/mm	1.2-加载±0.5mm,计算±0.3mm	6500N/mm	1.3-加载±0.25mm,计算±0.15mm	7000N/mm	扭转刚度	2-预载±16°,循环3次,速度1.67°/sec		2.1-加载±16°,计算±9.6°	1.2Nm/deg	2.2-加载±8°,计算±4.8°	1.3Nm/deg	2.3-加载±4°,计算±2.4°	1.5Nm/deg	耐久实验	Z向加载±4932N,扭转±6.92°,频率1Hz,循环5万次	无异响、无裂纹	粘接实验	用∅A+3的套筒压脱短棒,检测压脱面积和力值	压脱力≥5000N,粘接面积≥90%			F																											
试验项目										试验方法	试验要求(±15%)																																																							
Z向刚度										1-预载±1mm,循环3次,速度100mm/min																																																								
										1.1-加载±1mm,计算±0.6mm	6000N/mm																																																							
	1.2-加载±0.5mm,计算±0.3mm	6500N/mm																																																																
	1.3-加载±0.25mm,计算±0.15mm	7000N/mm																																																																
扭转刚度	2-预载±16°,循环3次,速度1.67°/sec																																																																	
	2.1-加载±16°,计算±9.6°	1.2Nm/deg																																																																
	2.2-加载±8°,计算±4.8°	1.3Nm/deg																																																																
	2.3-加载±4°,计算±2.4°	1.5Nm/deg																																																																
耐久实验	Z向加载±4932N,扭转±6.92°,频率1Hz,循环5万次	无异响、无裂纹																																																																
粘接实验	用∅A+3的套筒压脱短棒,检测压脱面积和力值	压脱力≥5000N,粘接面积≥90%																																																																
G	表3:产品信息 <table><tr><th>项目代号</th><th>名称</th><th>客户图号</th><th>杆径</th><th>孔径</th><th>样块硬度</th><th>产品表面硬度</th></tr><tr><td>NCS</td><td>左(右)衬套</td><td>0321056A</td><td>∅19.6</td><td>∅18.6</td><td>60±3SHA</td><td>62±3SHA</td></tr></table>									项目代号	名称	客户图号	杆径	孔径	样块硬度	产品表面硬度	NCS	左(右)衬套	0321056A	∅19.6	∅18.6	60±3SHA	62±3SHA			G																																								
项目代号										名称	客户图号	杆径	孔径	样块硬度	产品表面硬度																																																			
NCS										左(右)衬套	0321056A	∅19.6	∅18.6	60±3SHA	62±3SHA																																																			
H										GB/T 3672.1-2002 M3 <table><tr><th>▷</th><th>≤</th><th>F(±)</th><th>C±</th></tr><tr><td>0</td><td>6.3</td><td>±0.2</td><td>±0.25</td></tr><tr><td>6.3</td><td>10</td><td>±0.2</td><td>±0.35</td></tr><tr><td>10</td><td>16</td><td>±0.25</td><td>±0.4</td></tr><tr><td>16</td><td>25</td><td>±0.35</td><td>±0.5</td></tr><tr><td>25</td><td>40</td><td>±0.4</td><td>±0.7</td></tr><tr><td>40</td><td>63</td><td>±0.5</td><td>±0.8</td></tr><tr><td>63</td><td>100</td><td>±0.7</td><td>±1</td></tr><tr><td>100</td><td>160</td><td>±0.8</td><td>±1.3</td></tr></table>									▷	≤	F(±)	C±	0	6.3	±0.2	±0.25	6.3	10	±0.2	±0.35	10	16	±0.25	±0.4	16	25	±0.35	±0.5	25	40	±0.4	±0.7	40	63	±0.5	±0.8	63	100	±0.7	±1	100	160	±0.8	±1.3	2 PT00505/01-01 塑料骨架 PA66+GF50 2 C904308/01-01 1 橡胶 R5516-H60 1 <table><tr><th>序号</th><th>图号</th><th>名称</th><th>材料</th><th>数量</th><th>备注</th></tr><tr><td>2</td><td>PT00505/01-01</td><td>塑料骨架</td><td>PA66+GF50</td><td>2</td><td>C904308/01-01</td></tr><tr><td>1</td><td></td><td>橡胶</td><td>R5516-H60</td><td>1</td><td></td></tr></table> 投影法 第一画法 比例 1:1 质量(g) 52.5g 材质 R5516-H60 产品号 C114775-CPSJ 热处理:表面处理 名称 后稳定杆衬套 (后稳定杆衬套) 批准 标准化 审批 校对 设计 项目组 毛伟 稳定杆系统 2025.11.12 图样标记 S 共 1 张 第 1 张 图号 0321056A (LN147) 安徽中鼎密封件股份有限公司 A3		序号	图号	名称	材料	数量	备注	2	PT00505/01-01	塑料骨架	PA66+GF50
▷	≤	F(±)	C±																																																															
0	6.3	±0.2	±0.25																																																															
6.3	10	±0.2	±0.35																																																															
10	16	±0.25	±0.4																																																															
16	25	±0.35	±0.5																																																															
25	40	±0.4	±0.7																																																															
40	63	±0.5	±0.8																																																															
63	100	±0.7	±1																																																															
100	160	±0.8	±1.3																																																															
序号	图号	名称	材料	数量	备注																																																													
2	PT00505/01-01	塑料骨架	PA66+GF50	2	C904308/01-01																																																													
1		橡胶	R5516-H60	1																																																														
I	MQB后杆调教表 <table><tr><th>杆径D</th><td>19</td><td>19.6</td><td>20.7</td><td>21.7</td></tr><tr><th>内径A</th><td>18</td><td>18.6</td><td>19.9</td><td>21</td></tr></table>									杆径D	19	19.6	20.7	21.7	内径A	18	18.6	19.9	21			I																																												
杆径D										19	19.6	20.7	21.7																																																					
内径A										18	18.6	19.9	21																																																					
J										表3:产品信息 <table><tr><th>项目代号</th><th>名称</th><th>客户图号</th><th>杆径</th><th>孔径</th><th>样块硬度</th><th>产品表面硬度</th></tr><tr><td>NCS</td><td>左(右)衬套</td><td>0321056A</td><td>∅19.6</td><td>∅18.6</td><td>60±3SHA</td><td>62±3SHA</td></tr></table>									项目代号	名称	客户图号	杆径	孔径	样块硬度	产品表面硬度	NCS	左(右)衬套	0321056A	∅19.6	∅18.6	60±3SHA	62±3SHA			J																															
项目代号	名称	客户图号	杆径	孔径	样块硬度	产品表面硬度																																																												
NCS	左(右)衬套	0321056A	∅19.6	∅18.6	60±3SHA	62±3SHA																																																												
K	GB/T 3672.1-2002 M3 <table><tr><th>▷</th><th>≤</th><th>F(±)</th><th>C±</th></tr><tr><td>0</td><td>6.3</td><td>±0.2</td><td>±0.25</td></tr><tr><td>6.3</td><td>10</td><td>±0.2</td><td>±0.35</td></tr><tr><td>10</td><td>16</td><td>±0.25</td><td>±0.4</td></tr><tr><td>16</td><td>25</td><td>±0.35</td><td>±0.5</td></tr><tr><td>25</td><td>40</td><td>±0.4</td><td>±0.7</td></tr><tr><td>40</td><td>63</td><td>±0.5</td><td>±0.8</td></tr><tr><td>63</td><td>100</td><td>±0.7</td><td>±1</td></tr><tr><td>100</td><td>160</td><td>±0.8</td><td>±1.3</td></tr></table>																		▷	≤	F(±)	C±	0	6.3	±0.2	±0.25	6.3	10	±0.2	±0.35	10	16	±0.25	±0.4	16	25	±0.35	±0.5	25	40	±0.4	±0.7	40	63	±0.5	±0.8	63	100	±0.7	±1	100	160	±0.8	±1.3			K									
▷										≤	F(±)	C±																																																						
0										6.3	±0.2	±0.25																																																						
6.3										10	±0.2	±0.35																																																						
10	16	±0.25	±0.4																																																															
16	25	±0.35	±0.5																																																															
25	40	±0.4	±0.7																																																															
40	63	±0.5	±0.8																																																															
63	100	±0.7	±1																																																															
100	160	±0.8	±1.3																																																															
L	MQB后杆调教表 <table><tr><th>杆径D</th><td>19</td><td>19.6</td><td>20.7</td><td>21.7</td></tr><tr><th>内径A</th><td>18</td><td>18.6</td><td>19.9</td><td>21</td></tr></table>									杆径D	19	19.6	20.7	21.7	内径A	18	18.6	19.9	21			L																																												
杆径D										19	19.6	20.7	21.7																																																					
内径A										18	18.6	19.9	21																																																					