

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				
A	完全代用品信息				Stiffness targets for all variants		Measurement range	Evaluation range	Precycles	来历	客户版本号	变更标记	区域	变更事项		中鼎版本号	年月日	变更者	A	
	代用品产品号	代用品客户代码	代用品零件号	代用品日期	签字	Radial Z stiffness	±6000N/mm	±5000N	±2500N	2				首次下发产品图纸		A	2025.8.19	蒋子杰		
B	C904641	WJK37		2025.8.19		Axial	>500N/mm	±1200N	±500N	2										
						Torsional	<1.5Nm/°	±20°	+5°~+10°	2										
C	Variant	ZD SAP No.	Mubea proto. SAP No.	Mubea serial SAP No.		Mubea part No.	Hardness (shore A)	Stab diameter (mm)	Bushing diameter (mm)	Insert outer radius (mm)	Insert inner radius (mm)	Insert thickness (mm)	Rubber thickness (mm)	Inner rubber thickness (mm)	Total weight (g)	Rubber volume 3 (cm³)	Mubea part No. part 1	Material part 1	Material part 2	
				without coating	with coating			ØA	ØE	RAR	RIR	B	T1	T2						
	B	C90464151	91963996	92405149		TE-05-09-21-01-B	65±3	23.8	22.8	19.2	17.2	2	18.3	6.8	51	34.1	TE-05-09-21-03	GB/T 5754-H16	GS 93010 31 110-NR-65	
D																				D
E																				E
F																				F
G																				G
H																				H
I																				I
J																				J
K																				K
L																				L
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16				

Mubea part number
Mubea图号

Material code
材料代码

R28.5±0.3

R23.75±0.3

(1.2)

TE-05-09-21-01-B >NR40K

ØE±0.3

Variant letter on both bushing sides
衬套两侧的字母

(0.5)

Upper part marking(line above lettering) on both sides;
上衬套两侧标识(线状)
Only for variant D and the following variants
仅D和后续系列

A-A

T2±0.3

T1±0.3

24.45±0.3

29.2±0.3

(RAR)

(RIR)

Stabilizer diameter(see table)
稳定杆杆径(如附表)

Time clock and cavity No.
时钟和型腔号

ZD Logo

47.5±0.3

56.99±0.3

40±0.3

Z

Y

X

Reference参考:

ISO 8015

DIN 1451

DIN 16742

DIN EN 1396

ISO 1817

ISO 3302

ISO 2768

VDA 260

GS 91002

GS 93008

GS 93010

GS 93016

QV 31075

WN 730007

ASTN D2000

BMW PR 945:21/07/2021

Specification技术要求:

1.Nature rubber refer to the spec GS 93010 .
天然胶参照标准GS 93010 ;

2.No release agent containing Silicone material to be used.
不使用含硅材料的脱模剂;

3.General tolerance on rubber M2 as norm ISO 3302.1 .
橡胶尺寸公差参照ISO 3302.1 M2级 ;

4.The bonding between the rubber and the inserts needs to be stronger than >95% rubber break.
骨架与橡胶粘接面积应>95% ;

5.Emission reduced acc. To akt. GADSL and EU-directive 2000/53/EG.
节能减排需参考akt. GADSL和EU-directive 2000/53/EG;

6.Mould misalignment max. 0.5 mm permissible.
模具偏差最大允许0.5毫米;

7.General parting line max. 0.5 mm thick and 1 mm long permissible. No parting line on the bonding surface to the stabilizer.
通常飞边要求≤0.5mm厚,≤1mm长,与稳定杆粘接面上不得有分型线;

8.○ is marked for inspection dimensions.
○为出厂检验尺寸。

2		橡胶	R6778-H65	1	
1	TE-05-09-21-03	铝骨架	5754 H16	1	C904640/01-01
序号	图号	名称	材料	数量	备注
投影法	第一画法	比例	质量(g)	材质	产品号
		1:1	见表格	组件	C90464151-CPSJ
热处理	表面处理	名称			
批准	标准化	审批	校对	设计	项目组
				蒋子杰	稳定杆系统
图样标记	S	共2张 第2张			
图号					92405149 (WZG332)
安徽中鼎密封件股份有限公司					A3

DIN ISO 3302-1 M2 class				Durability test			
>	≤	F(±)	C±	Test 6.4 A		Test 6.4 B	
0	4	0.10	0.15	Amplitude Fz		±7500N	
4	6.3	0.15	0.20	Frequency		2 Hz	
6.3	10	0.20	0.25	Angle amplitude		β_OL ±6° β_max ±20.7°	
10	16	0.20	0.25	Load cycles		100000 min.100000; after until break	
16	25	0.25	0.35	Pass requirement		Max.20% stiffness loss. No cracks until 100000 load cycles for block A and B	
25	40	0.35	0.40	T[°C]		23	
40	63	0.40	0.50	Radial and torsional load need to be applied in phase. Both tests need to be done on the same bushing.			
63	100	0.50	0.70				
100	160	0.70	0.80				
160	-	0.5%	0.7%				