

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16																																																
A	Durability test												来历	客户版本号	变更标记	区域	变更事项	中鼎版本号	年月日	变更者	A																																											
B	Test 6.4 A			Test 6.4 B									首次下发产品图纸						A	2025.4.1	蒋子杰																																											
	Amplitude Fz		±7500N		±500N																																																											
	Frequency		2 Hz																																																													
	Angle amplitude		β_OL		±6°		β_max		±20.7°																																																							
C	Load cycles		100000		min.100000; after until break		Stiffness targets for all variants		Measurement range		Evaluation range		Precycles																																																			
	Pass requirement		Max.20% stiffness loss. No cracks until 100000 load cycles for block A and B				Radial Z stiffness		±8000N/mm		±5000N		±2500N		2																																																	
	T[°C]		23				Axial		<500N/mm		±1200N		±500N		2																																																	
	Radial and torsional load need to be applied in phase. Both tests need to be done on the same bushing.						Torsional		<2.5Nm/°		±20°		+5°~+10°		2																																																	
D	Variant	ZD SAP No.	Mubea proto. SAP No.	Mubea serial SAP No.		Mubea part No.	Hardness (shore A)	Stab diameter (mm)	Bushing diameter (mm)	Insert outer radius (mm)	Insert inner radius (mm)	Insert thickness (mm)	Rubber thickness (mm)	Inner rubber thickness (mm)	Total weight (g)	Rubber volume 3 (cm³)	Mubea part No. part 1	Material part 1	Material part 2																																													
	E	C904643	91949565	91971783	91971785	TE-05-09-21-01-E	55±3	25.8-26.2	25.1	19.2	17.2	2	17.15	5.65	49	32.5	TE-05-09-21-03	GB/T 5754-H16	GS 93010 31 110-NR-55																																													
E	Mubea part number Mubea图号 R28.5±0.3 R23.75±0.3 (1.2) TE-05-09-21-01-E Material code 材料代码 (0.5) Variant letter on both bushing sides 衬套两侧的字母 ØE±0.3 Upper part marking(line above lettering) on both sides; 上衬套两侧标识(线状) Only for variant D and the following variants 仅D和后续系列 A-A T2±0.3 T1±0.3 24.45±0.3 29.2±0.3 (B) 2 1 (RAR) (RTR) Stabilizer diameter(see table) 稳定杆杆径(如附表) Ø25.8 Time clock and cavity No. 时间钟和型腔号 40±0.3 ZD Logo 47.5±0.3 56.99±0.3 Reference参考: ISO 8015 DIN 1451 DIN 16742 DIN EN 1396 ISO 1817 ISO 3302 ISO 2768 VDA 260 GS 91002 GS 93008 GS 93010 GS 93016 QV 31075 WN 730007 ASTN D2000 BMW PR 945:21/07/2021																																																															
F																																																																
G																																																																
H																																																																
I																																																																
J	本产品完全代用捷克慕贝尔(WJK37)产品,图号:91971783/产品号:C904643 <table><tr><td>2</td><td>橡胶</td><td>R6778-H55</td><td>1</td><td></td></tr><tr><td>1</td><td>TE-05-09-21-03</td><td>铝骨架</td><td>5754 H16</td><td>1</td></tr><tr><td>序号</td><td>图号</td><td>名称</td><td>材料</td><td>数量</td><td>备注</td></tr><tr><td>投影法</td><td>第一画法</td><td>比例</td><td>1:1</td><td>质量(g)</td><td>见表格</td></tr><tr><td>热处理·表面处理</td><td colspan="3"></td><td>材质</td><td>NR+5754 H16</td></tr><tr><td>批准</td><td>标准化</td><td>审批</td><td>校对</td><td>设计</td><td>项目组</td></tr><tr><td>图样标记</td><td>S</td><td colspan="3">共 1 张 第 1 张</td><td>④ 安徽中鼎密封件股份有限公司</td></tr></table>																				2	橡胶	R6778-H55	1		1	TE-05-09-21-03	铝骨架	5754 H16	1	序号	图号	名称	材料	数量	备注	投影法	第一画法	比例	1:1	质量(g)	见表格	热处理·表面处理				材质	NR+5754 H16	批准	标准化	审批	校对	设计	项目组	图样标记	S	共 1 张 第 1 张			④ 安徽中鼎密封件股份有限公司				
2	橡胶	R6778-H55	1																																																													
1	TE-05-09-21-03	铝骨架	5754 H16	1																																																												
序号	图号	名称	材料	数量	备注																																																											
投影法	第一画法	比例	1:1	质量(g)	见表格																																																											
热处理·表面处理				材质	NR+5754 H16																																																											
批准	标准化	审批	校对	设计	项目组																																																											
图样标记	S	共 1 张 第 1 张			④ 安徽中鼎密封件股份有限公司																																																											
K	DIN ISO 3302-1 M2 class <table><tr><td>></td><td>≤</td><td>F(±)</td><td>C±</td></tr><tr><td>0</td><td>4</td><td>0.10</td><td>0.15</td></tr><tr><td>4</td><td>6.3</td><td>0.15</td><td>0.20</td></tr><tr><td>6.3</td><td>10</td><td>0.20</td><td>0.25</td></tr><tr><td>10</td><td>16</td><td>0.20</td><td>0.25</td></tr><tr><td>16</td><td>25</td><td>0.25</td><td>0.35</td></tr><tr><td>25</td><td>40</td><td>0.35</td><td>0.40</td></tr><tr><td>40</td><td>63</td><td>0.40</td><td>0.50</td></tr><tr><td>63</td><td>100</td><td>0.50</td><td>0.70</td></tr><tr><td>100</td><td>160</td><td>0.70</td><td>0.80</td></tr><tr><td>160</td><td>-</td><td>0.5%</td><td>0.7%</td></tr></table>																				>	≤	F(±)	C±	0	4	0.10	0.15	4	6.3	0.15	0.20	6.3	10	0.20	0.25	10	16	0.20	0.25	16	25	0.25	0.35	25	40	0.35	0.40	40	63	0.40	0.50	63	100	0.50	0.70	100	160	0.70	0.80	160	-	0.5%	0.7%
>	≤	F(±)	C±																																																													
0	4	0.10	0.15																																																													
4	6.3	0.15	0.20																																																													
6.3	10	0.20	0.25																																																													
10	16	0.20	0.25																																																													
16	25	0.25	0.35																																																													
25	40	0.35	0.40																																																													
40	63	0.40	0.50																																																													
63	100	0.50	0.70																																																													
100	160	0.70	0.80																																																													
160	-	0.5%	0.7%																																																													
L	稳定杆衬套 (前稳定杆衬套) 图号 91971783 (WZG332) 蒋子杰 2025.4.1 稳定杆系统																																																															