

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16																					
A	Durability test				完全代用品信息					来历	客户版本号	变更标记	区域	变更事项		中鼎版本号	年 月 日	变更者	A																		
	Test 6.4 A		Test 6.4 B		代用品产品号	代用品客户代码	代用品零件号	代用日期	签字	首次下发产品图纸				A		2025.8.19		蒋子杰		B																	
B	Amplitude Fz	±7500N		±500N																																	
	Frequency	2 Hz																																			
	Angle amplitude	β_OL	±6°	β_max	±20.7°																																
	Load cycles	100000		min.100000; after until break																																	
C	Pass requirement	Max.20% stiffness loss. No cracks until 100000 load cycles for block A and B			Stiffness targets for all variants		Measurement range		Evaluation range		Precycles									C																	
	T[°C]	23			Radial Z stiffness	±6000N/mm	±5000N		±2500N		2																										
	Radial and torsional load need to be applied in phase. Both tests need to be done on the same bushing.				Axial	>500N/mm	±1200N		±500N		2																										
					Torsional	<1.5Nm/°	±20°		+5°~+10°		2																										
D	Variant	ZD SAP No.	Mubea proto. SAP No.	Mubea serial SAP No.		Mubea part No.	Hardness (shore A)	Stab diameter (mm)	Bushing diameter (mm)	Insert outer radius (mm)	Insert inner radius (mm)	Insert thickness (mm)	Rubber thickness (mm)	Inner rubber thickness (mm)	Total weight (g)	Rubber volume 3 (cm)	Mubea part No. part 1	Material part 1	Material part 2	D																	
				without coating	with coating			ØA	ØE	RAR	RIR	B	T1	T2																							
	B	C90464651	91963995	92405150		TE-05-09-21-02-B	65±3	23.8	22.8	19.2	17.2	2	15.4	6.8	62	43.9	TE-05-09-21-03	GB/T 5754-H16	GS 93010 31 110-NR-65																		
E	Time clock and cavity No. 时钟和型腔号				Specification技术要求: 1.Nature rubber refer to the spec GS 93010 . 天然胶参照标准GS 93010 ; 2.No release agent containing Silicone material to be used. 不使用含硅材料的脱模剂; 3.General tolerance on rubber M2 as norm ISO 3302.1 . 橡胶尺寸公差参照ISO 3302.1 M2级 ; 4.The bonding between the rubber and the inserts needs to be stronger than >95% rubber break. 骨架与橡胶粘接面积应>95% ; 5.Emission reduced acc. To akt. GADSL and EU-directive 2000/53/EG. 节能减排需参考akt. GADSL和EU-directive 2000/53/EG; 6.Mould misalignment max. 0.5 mm permissible. 模具偏差最大允许0.5毫米; 7.General parting line max. 0.5 mm thick and 1 mm long permissible. No parting line on the bonding surface to the stabilizer. 通常飞边要求≤0.5mm厚,≤1mm长,与稳定杆粘接面上不得有分型线; 8.⊙ is marked for inspection dimensions. ⊙为出厂检验尺寸。																E																
F																					F																
G																					G																
H																					H																
I																					I																
J																					J																
K																					K																
L																					L																
	DIN ISO 3302-1 M2 class																																				
	>	≤	F(±)		C±																																
	0	4	0.10		0.15																																
	4	6.3	0.15		0.20																																
	6.3	10	0.20		0.25																																
	10	16	0.20		0.25																																
	16	25	0.25		0.35																																
	25	40	0.35		0.40																																
	40	63	0.40		0.50																																
	63	100	0.50		0.70																																
	100	160	0.70		0.80																																
	160	-	0.5%		0.7%																																
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16																					