

|   |                                                                                                                                                                                                                      |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|---|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|----------------|-----------|---------|------------|------------|------------|----------|------------|----|---------------------------|-----------------|-------------------------------|----------------------|----|---------------------|------------|--------------|---|
|   | 1                                                                                                                                                                                                                    | 2     | 3              | 4         | 5       | 6          | 7          | 8          | 9        | 10         | 11 | 12                        | 13              | 14                            | 15                   | 16 |                     |            |              |   |
| A | 技术要求: Specifications:                                                                                                                                                                                                |       |                |           |         |            |            |            |          | 来历<br>From |    | 客户版本号<br>Customer Version | 变更标记<br>Marking | 区域<br>Position                | 变更事项<br>Modification |    | 中版版本号<br>ZD Version | 日期<br>Date | 责任人<br>Resp. | A |
| B | 1.天然胶,硬度:55±3 shore A,参照标准DBL 5558-45;<br>Nature rubber with 55±3 shore A,according to the spec.DBL 5558-45.                                                                                                         |       |                |           |         |            |            |            |          | 19388-E    |    |                           |                 | 初始图纸Initial drawing           |                      | A  | 20240928            | 范康祺        | B            |   |
| C | 2.由索格菲完成粘接工序; The gluing is made by Sogefi.                                                                                                                                                                          |       |                |           |         |            |            |            |          | 5J-246346  |    | 19388-E                   | @/2             | 增加产品刻字示意图;增加产品打点标识位置;更新噪音试验条件 |                      | B  | 20241129            | 范康祺        | C            |   |
| D | 3.粘接准备事项 Bush status before for gluing on stab bar:                                                                                                                                                                  |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              | D |
| E | 3.1 内表面需保持清洁,索格菲粘接前无需处理措施                                                                                                                                                                                            |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              | E |
| F | 3.2 衬套出模后6个月可粘接;                                                                                                                                                                                                     |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              | F |
| G | 3.3 采用脱模剂必须与索格菲粘接工艺兼容;                                                                                                                                                                                               |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              | G |
| H | 3.1 The internal surface of the bush must be clean and can receive the Sogefi glue without surface preparation.                                                                                                      |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              | H |
| I | 3.2 The gluing operation can be made 6 months maximum after moulding.                                                                                                                                                |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              | I |
| J | 3.3 The release agent used for bushes must be compatible with the Sogefi glue.                                                                                                                                       |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              | J |
| K | 4.特殊性参照标准 I-O2-P-01-01:Special characteristics as I-O2-P-01-01:                                                                                                                                                      |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              | K |
| L | 关键特性标识Critical:                                                                                                                                                                                                      |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              | L |
|   | 重要特性标识Important:                                                                                                                                                                                                     |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 橡胶尺寸公差参照 NF/T47-001 M3级执行; General tolerances on rubber M3 as norm NF/T47.001.                                                                                                                                       |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 5.追溯性标识:字高2.5mm,字深0.2mm;                                                                                                                                                                                             |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | Traceability:characters height 2.5mm,characters deep 0.2mm.                                                                                                                                                          |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 6.刚度采用卡箍和夹具完成(见附表): Stiffness are checked with serial brackets and rigid blocks to meet the specification(see table).                                                                                                |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 6.1.z&x向静刚度:加载±1mm,速度:10mm/min,循环4次,计算±0.5mm时的刚度;                                                                                                                                                                    |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 6.2.扭转刚度:加载±20°,速度:60°/min,循环4次,计算±5°时的刚度;                                                                                                                                                                           |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 6.1.Radial static stiffness Kz&x:Load ±1mm for 4 cycles, speed:10mm/min, check at ±0.5mm.                                                                                                                            |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 6.2.Torsional stiffness Kty:Load ±20° for 4 cycles,speed:60°/min,check at ±5°.                                                                                                                                       |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 7.索格菲试验项目(Sogefi test); @                                                                                                                                                                                            |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 7.1 噪音实验:在80℃*4周和120℃*24h环境下对3根老化前后产品分别做噪音实验,测试角度:9.4°&±23.5°,5种温度(-30℃,-20℃,-10℃,0℃,+10℃,+20℃),5次循环,不可察觉的噪音为合格;                                                                                                     |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 7.2 拔脱实验:80%的粘接效果为合格(新件);70%的粘接效果为合格(疲劳件);                                                                                                                                                                           |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 7.3 环境试验:在110℃环境下,扭转9.4°,持续100小时,z&x向静刚度损失<10%,且粘接面积>70%为合格;                                                                                                                                                         |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 7.1 Noisy test:control before and after aging test on 3bars for 4 weeks at 80°c and 24h at 120°c,test angle(9.4°&±23.5°),5 temperatures(-30℃,-20℃,-10℃,0℃,+10℃,+20℃),evaluation on 5 cycles,not noticeable noise=OK; |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 7.2 Destructive tests:80% rubber adhesion for new bush; 70% rubber adhesion after fatigue;                                                                                                                           |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 7.3 Ambient test: Preload bars as 9.4° angle for 100h at 110℃,the test is ok if the stiffness loss in z&x < 10% between before and after and peeling ok > 70%.                                                       |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 8.○为工序、出厂检验尺寸。                                                                                                                                                                                                       |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | ○is marked for inspection dimensions.                                                                                                                                                                                |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 标识内容:                                                                                                                                                                                                                |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 零件号:19388-238                                                                                                                                                                                                        |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 时间轴:24-25                                                                                                                                                                                                            |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 材料标识:>NR+BR<                                                                                                                                                                                                         |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 厂家代码:D200501                                                                                                                                                                                                         |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 型腔号:01-32                                                                                                                                                                                                            |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 打点标识:蓝色                                                                                                                                                                                                              |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   |                                                                                                                                                                                                                      |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | Upper bracket                                                                                                                                                                                                        |       |                |           |         |            |            |            |          | 19387      |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | Lower bracket                                                                                                                                                                                                        |       |                |           |         |            |            |            |          | 19385      |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | Stiffness requirement                                                                                                                                                                                                |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | Bar dia.                                                                                                                                                                                                             | ØID   | Identification | Color dot | Gauge   | Ks-Z(N/mm) | Ks-X(N/mm) | Ks-Y(N/mm) | Ty(Nm/°) |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | Ø23.8                                                                                                                                                                                                                | Ø23.3 | AB             | Blue      | Bracket | 3200±15%   | 2350±15%   | 550±15%    | 2max     |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | Block                                                                                                                                                                                                                |       |                |           |         |            |            |            |          |            |    |                           |                 |                               |                      |    |                     |            |              |   |
|   | 1                                                                                                                                                                                                                    | 2     | 3              | 4         | 5       | 6          | 7          | 8          | 9        | 10         | 11 | 12                        | 13              | 14                            | 15                   | 16 |                     |            |              |   |

3D Model Dimensions:

- Top View: (39.5±0.4), R19.75±0.35, (1.75), 21.5±0.35, 2-Ø23.3±0.2, 2-C7, 39.5±0.4, 21.5±0.35
- Side View: 30±0.4, 21.5±0.35, 30±0.4
- Bottom View: 2-R2, Ø2, 3
- Mould lower side: A, B, C, D
- Mould upper side: A, B, C, D

| NF/T 47-001 CLASS M3 |       |       |       |       |       |       |       |       |
|----------------------|-------|-------|-------|-------|-------|-------|-------|-------|
|                      | ≤6.3  | ≤10   | ≤16   | ≤25   | ≤40   | ≤63   | ≤100  | ≤160  |
| F                    | ±0.20 | ±0.20 | ±0.25 | ±0.35 | ±0.40 | ±0.50 | ±0.70 | ±0.80 |
| C                    | ±0.25 | ±0.35 | ±0.40 | ±0.50 | ±0.70 | ±0.80 | ±1.00 | ±1.30 |

|                                           |                             |           |          |              |          |               |           |                        |                |                                           |    |
|-------------------------------------------|-----------------------------|-----------|----------|--------------|----------|---------------|-----------|------------------------|----------------|-------------------------------------------|----|
| 投影法 Projection method                     | 第一画法 First angle projection | 比例 Scale  | 1:1      | 质量 Weight(g) | 34g      | 材质 Material   | R6938-H55 | 产品号 ZD production code | C90487851-CPSJ |                                           |    |
| 热处理·表面处理 Heat Treatment·Surface Treatment |                             |           |          |              |          | 名称 Part name  |           |                        |                | 稳定杆衬套<br>(后稳定杆衬套)<br>(Rear stab bar bush) |    |
| 批准 Approval                               | 标准化 Standards               | 审批 Review | 校对 Check | 设计 Design    | 项目组 Team | 图号 Drawing No |           |                        |                | 19388-238<br>(JS873)                      |    |
| 标记 SIGN                                   |                             |           |          |              |          | S             | A         | B                      | 共 1 张 第 1 张    | 安徽中鼎密封件股份有限公司                             | A3 |