NeuroSym-BD: A Neuro-Symbolic Framework for Violence Event Extraction and Escalation Modeling from Bangladeshi News

Anonymous Authors
Anonymous Institution
anonymised@institution.org

Abstract

We present **NeuroSym-BD**, an open, reproducible neuro-symbolic pipeline for automated extraction, coding, and reasoning over violence events from Bangladeshi news (The Daily Star). The system integrates: *(i)* an 8-stage NLP pipeline extracting CAMEO-coded event tuples; *(ii)* an RDF knowledge graph (BlazeGraph) capturing multi-relational conflict interactions, administrative hierarchies, and W3C PROV-O provenance; *(iii)* a neuro-symbolic reasoning layer combining PyKEEN relational embeddings (RotatE), BiLSTM sequence escalation modeling, and Description Logic ($\mathcal{ALC}$) constraint gates enforcing CAMEO ontological transitions; and *(iv)* natural language interfaces via Graph-RAG and NL2SPARQL.

Evaluated on a curated, held-out test partition ($n = 50$) of 100 gold-annotated Bangladeshi conflict events, our hybrid reasoner achieves high-violence ($HV \geq 18$) classification **F1 = 0.851** and **86.0% binary accuracy**, outperforming pure neural baselines by ΔF1 = +0.184 and jumping $+26.0\%$ in accuracy. Crucially, Description Logic constraint gating slashes the binary false positive rate from 63.0% down to 14.8% (a 76.5% relative false-alarm reduction) while maintaining 100% end-to-end PROV-O provenance traceability. Cross-source corroboration against GDELT 2.0 demonstrates 0.922 macro-group F1, while ACLED alignment yields 100% macro-group concordance across spatio-temporally matched events.

All code, annotated gold benchmarks, and evaluation scripts are released under the MIT License at [anonymisedforreview].

1 Introduction

Bangladesh experiences recurrent episodes of socio-political conflict— factional clashes between student political wings, hartal strikes, and security force operations—documented daily in its English-language press. Yet automated conflict monitoring in this region faces severe obstacles: low-resource linguistic variations, pervasive reporting ambiguities, and unconstrained neural classifiers that trigger catastrophic false-alarm rates due to lexical over-sensitization.

To address these challenges, **NeuroSym-BD** delivers three primary contributions:

1. **Localized CAMEO Event Extraction**: A hybrid NLP pipeline maps Bangladeshi news text to the CAMEO conflict coding taxonomy [Gerner et al., 2002, Schrodt, 2012], augmented with 6 Bangladesh-specific event sub-codes (hartal violence, party clashes, campus unrest).

2. **Description Logic Constraint Gating**: We formalize CAMEO escalation transitions and administrative hierarchies in $\mathcal{ALC}$ Description Logic axioms, implementing a hybrid inference engine that intercepts ungrounded neural logit predictions before acceptance.

3. **Auditable Provenance**: Every alert is grounded in RDF knowledge triples and source article sentences via PROV-O provenance links, eliminating hallucinated conflict attributions.




Figure 1: NeuroSym-BD system architecture: news ingestion → 8-stage NLP pipeline → RDF Knowledge Graph → hybrid neuro-symbolic reasoning with symbolic verification → analyst API layer.

2 Related Work

Event extraction for conflict analysis. Boschee et al. [2015] describe ICEWS, a large-scale event coding system using pattern matching. GDELT [Leetaru and Schrodt, 2013] extends this globally using CAMEO with neural re-ranking. Our work differs in its focus on a single underrepresented country and its integration of knowledge graph reasoning.

Neuro-symbolic AI for NLP. d'Avila Garcez and Lamb [2023] survey neuro-symbolic integration patterns. Yang et al. [2017] introduce Neural LP for rule learning over KGs. Zhang et al. [2022] propose hybrid systems for biomedical event extraction. We adapt this neuro-symbolic paradigm to low-resource South Asian conflict event coding.

Knowledge graph reasoning for events. Rossi et al. [2021] survey KG embedding methods including TransE [Bordes et al., 2013], ComplEx [Trouillon et al., 2016], and RotatE [Sun et al., 2019]. R-GCN [Schlichtkrull et al., 2018] and CompGCN [Vashishth et al., 2020] extend graph neural networks to relational graphs—our primary architectures.

Bangladesh conflict data. ACLED [Raleigh et al., 2010] provides ground-truth BD events from 2010 onward. To our knowledge, no prior NLP system specifically targets BD conflict event extraction.

3 System Architecture

Figure 1 shows the full NeuroSym-BD pipeline.

3.1 Data Layer

The Daily Star (`thedailystar.net`), Bangladesh's leading English-language daily, is polled via RSS every 15 minutes. Articles are crawled, rate-limited at 2 requests/second, and stored as JSON with schema $\{id, url, title, body, published_date, category, scraped_at\}$.

3.2 NLP Pipeline

The 8-stage pipeline (Figure 2) processes each article:
Violence relevance filter. Binary classifier using an 80-keyword lexicon with zero-shot BART-MNLI fallback [Yin et al., 2019] for borderline cases.
Named entity recognition. spaCy-transformers [Honnibal et al., 2020] extended with a Bangladesh-specific gazetteer for SECURITY_FORCE (RAB, BGB, Police), POLITICAL_PARTY (AL, BNP), and ARMED_GROUP entities.
CAMEO classification. Hybrid: (1) rule layer maps 40 violence trigger verbs to CAMEO codes directly; (2) if rule confidence < 0.6, zero-shot BART-MNLI classifies against CAMEO code label descriptions.




Figure 2: The 8-stage NLP extraction pipeline transforming unstructured text into grounded CAMEO event tuples.

Temporal and geospatial normalisation. Relative dates resolved to ISO 8601; locations resolved against a 64-district, 500+ upazila Bangladesh gazetteer with coordinates.

3.3 Knowledge Graph

Events are converted to RDF (Turtle) and ingested into BlazeGraph 2.1.6. The ontology extends CAMEO [Schrodt, 2012] with Bangladesh-specific sub-codes. Every event carries PROV-O [Groth and Moreau, 2013] provenance links to the source article URL and sentence offset.

3.4 Neuro-Symbolic Reasoning Layer

KG Embeddings (Task 4.2). We train TransE [Bordes et al., 2013] and RotatE [Sun et al., 2019] via PyKEEN [Ali et al., 2021] over the exported multi-relational knowledge graph $\mathcal{G} = (\mathcal{E}, \mathcal{R}, \mathcal{T})$ with 98 entities and 654 relational triples. RotatE achieves an MRR of 0.369 and Hits@10 of 64.1% (Table 4).

R-GCN Event Pattern Detection (Task 4.3). A two-layer Relational Graph Convolutional Network (R-GCN) with basis decomposition (4 bases) computes relation-specific message passing:

$$h_i^{(l+1)} = \sigma\left(\sum_{r\in\mathcal{R}}\sum_{j\in\mathcal{N}_r(i)}\frac{1}{c_{i,r}}W_r^{(l)}h_j^{(l)} + W_0^{(l)}h_i^{(l)}\right) \tag{1}$$

where $W_r^{(l)} = \sum_{b=1}^{B} a_{rb}^{(l)} V_b^{(l)}$ reduces parameters across multi-relational event interactions. Events with CAMEO code ≥ 17 provide the self-supervised high-violence signal.

Next-Step Escalation Modeling (Task 4.4). A Bidirectional LSTM ($h = 64$, 2 layers, dropout 0.2) is trained on historical district event sequences to model next-step CAMEO code transitions. Given an observed sequence of $N = 4$ preceding event categories $[e_{t-3}, \ldots, e_t]$ within a district, the model outputs candidate logits $P(e_{t+1} \mid e_{t-3:t})$.

Formal Description Logic Constraints (Task 4.9). Rather than relying solely on post-hoc heuristics, domain constraints are formalized as $\mathcal{ALC}$ Description Logic axioms governing the ontology $\mathcal{O}$. Let Assault, Fight, MassViolence, Coerce, Protest, and Sanction be primitive sub-concepts of CameoCategory:

$$\text{HighViolenceEvent} \equiv \text{Event} \sqcap \exists \text{hasCategory}.(\text{Assault} \sqcup \text{Fight} \sqcup \text{MassViolence}) \tag{2}$$

$$\text{TensionPrecursor} \equiv \text{Event} \sqcap \exists \text{hasCategory}.(\text{Protest} \sqcup \text{Sanction} \sqcup \text{Coerce}) \tag{3}$$

$$\text{ValidEscalation} \equiv \text{HighViolenceEvent} \sqcap \exists \text{precededBy}.\text{TensionPrecursor} \tag{4}$$

$$\text{UnprecedentedMassViolence} \equiv \text{Event} \sqcap \exists \text{hasCategory}.\text{MassViolence} \sqcap \neg\exists \text{precededBy}.(\text{Assault} \sqcup \text{Fight}) \tag{5}$$

$$\text{UnprecedentedMassViolence} \sqsubseteq \text{OntologicalViolation} \tag{6}$$

Predictions are evaluated against five formal constraint operators:

- **C-ONTO**: Concept violation satisfying OntologicalViolation (hard rejection; forces fallback to the nearest admissible CAMEO ancestor root).

- **C-ACTOR**: Role mismatch between actor capability and event predicate (e.g., civilian factions asserting military-exclusive actions; soft confidence penalty).
- **C-GEO**: Spatial administrative hierarchy mismatch (e.g., district not contained in reported division; soft penalty).
- **C-TEMP**: Chronological inversion $\text{Event}_t \prec \text{Event}_{t-1}$ (soft penalty).
- **C-CONF**: Confidence below calibrated operational threshold $\tau_{\text{conf}} = 0.60$ (soft penalty).

4 Experiments

4.1 Datasets and Benchmark Accounting

To eliminate evaluation ambiguity and potential data leakage, we establish a strict accounting protocol:

- **News Ingestion Corpus**: 135 full-text articles collected from *The Daily Star* (Politics, Crime & Justice) across 2024–2026.
- **Extracted Knowledge Graph**: 88 unique multi-actor conflict events represented as 1,973 RDF/Turtle triples with W3C PROV-O provenance in BlazeGraph.
- **Gold Benchmark Dataset**: 100 expert-curated conflict events spanning all 8 CAMEO intensity levels (13–20) with fine-grained actor roles, administrative locations, and source sentence offsets.
- **Partitioning Protocol**: The 100 gold benchmark events are partitioned via a deterministic 50/50 split (seed $= 42$) into 50 training/development examples (used for vocabulary and rule tuning) and 50 held-out test events. The held-out test bed contains 23 High-Violence events (CAMEO ≥ 18) and 27 Non-Violent/Low-Violence events (CAMEO < 18). All ablation and baseline comparisons in Tables 1 and 6 are evaluated strictly on this held-out 50-event set.
- **Explainability Audit Sample**: 100 system inferences traced end-to-end to PROV-O provenance sentences.

4.2 Evaluation Metrics

- **Binary Accuracy (BinAcc)**: $(TP + TN)/N$ for High-Violence detection ($HV \geq 18$).
- **Multi-Class Code Accuracy (MultiAcc)**: Exact-match rate for 8-class CAMEO root categories ($13 \ldots 20$).
- **P@HV, R@HV, F1@HV**: Precision, Recall, and $F_1 = 2PR/(P + R)$ for the High-Violence class.
- **Standard Binary FPR**: $FP/(FP + TN)$, the false positive rate over all true negative events.
- **False Alarm Rate (FAR)**: FP/N, the proportion of false alarms across the entire test set.
- **Detection Recall**: % of cross-source events corroborated between datasets.
- **Provenance Coverage**: % of predictions backed by ≥ 1 verified source article sentence.

Table 1: Ablation study and confusion matrix on held-out test events ($n = 50$, with 23 High-Violence and 27 Non-Violent gold events). TP, FP, TN, FN, BinAcc, P, R, and F1 evaluate the high-violence class (CAMEO $\geq$ 18). Std-FPR = $FP/(FP + TN)$. FAR = FP/N. Expl = end-to-end PROV-O provenance trace rate.

Condition	TP	FP	TN	FN	BinAcc	P@HV	R@HV	F1@HV	Std-FPR	Expl
Neural-Only	20	17	10	3	0.600	0.541	0.870	0.667	0.630	0.000
Symbolic-Only	21	16	11	2	0.640	0.568	**0.913**	0.700	0.593	**1.000**
Hybrid (Ours)	20	**4**	**23**	3	**0.860**	**0.833**	0.870	**0.851**	**0.148**	**1.000**

4.3 Ablation Study

Table 1 presents the ablation results alongside the complete confusion matrix over the 50 held-out test events.

The confusion matrix reveals the exact mechanism of neuro-symbolic synergy: Unconstrained neural sequence models suffer from extreme false-positive inflation ($FP = 17$ on 27 negative cases, Std-FPR $= 63.0\%$) due to high lexical tension in reporting. The hybrid Description Logic gates (C-ONTO, C-ACTOR, C-GEO) intercept 13 spurious high-violence predictions, slashing false positives from 17 down to 4 (Std-FPR $= 14.8\%$, a 76.5% relative false-alarm reduction; overall False Alarm Rate drops from 34.0% to 8.0%). Consequently, binary classification accuracy surges from 60.0% to **86.0%** ($+26.0\%$ absolute gain) and high-violence precision reaches $P@\text{HV} = 0.833$, yielding $F1@\text{HV} = \mathbf{0.851}$ (ΔF1 $= +0.184$ over neural-only) while preserving 100% provenance explainability. (Across all 8 fine-grained CAMEO root categories, exact multi-class root accuracy is 0.400 for all three conditions, confirming that the hybrid gain is concentrated precisely in separating lethal and physical violence from non-violent political action).

4.4 Cross-Source Benchmark Alignment

Table 2 summarises empirical alignment against GDELT 2.0 and ACLED benchmarks.

Table 2: Empirical cross-corroboration against GDELT 2.0 and ACLED benchmarks.

Benchmark	Detection Recall	Location Acc	CAMEO Group Acc	F1 Score
vs GDELT 2.0	0.922	—	0.922	0.922
vs ACLED	0.234	0.234	1.000	—

ACLED Crosswalk and Matching Denominators. Evaluating news event extraction against an external registry like ACLED requires careful accounting of taxonomical granularity. ACLED aggregates events into six broad event types. Table 3 details the explicit mapping crosswalk between ACLED event types and CAMEO 2-digit macro-groups.

Across 154 system-extracted events evaluated against 154 ACLED records for Bangladesh in the same time frame, candidate pairs are matched using a strict spatio-temporal boundary: temporal window $\Delta t \leq 3$ days and matching administrative district. This yields 36 confirmed matches ($36/154 = 23.4\%$ detection recall), reflecting the expected single-source bound of an English national daily (*The Daily Star*) compared to ACLED's multi-outlet rural field collection. Crucially, across all 36 spatio-temporally matched event pairs, system classifications achieve **100.0% macro-group concordance** ($36/36$) under the crosswalk mapping.

Table 3: Crosswalk mapping ACLED event types to CAMEO 2-digit macro-categories.

ACLED Event Type	Target CAMEO Group	Semantics
Battles	19 (FIGHT)	Armed clashes between organized armed or political factions
Violence against civilians	18 (ASSAULT)	Unilateral lethal or physical attacks on non-combatants
Riots	18 / 19 (ASSAULT / FIGHT)	Violent public disorder, mob violence, or clashes
Protests	14 (PROTEST)	Demonstrations, strikes (hartals), and non-violent rallies
Explosions / Remote	20 (MASS VIOLENCE)	Bomb blasts, IEDs, or mortar attacks
Strategic developments	16 / 17 (SANCTION / COERCE)	Arrests, section 144 curfews, or headquarters raids

4.5 Knowledge Graph Embedding Evaluation

We export the populated conflict knowledge graph (98 entities, 654 multi-relational triples) and evaluate relational link prediction using PyKEEN [Ali et al., 2021]. Triples are partitioned into an 80/10/10 train/validation/test split. Models are trained with filtered ranking protocol, embedding dimension $d = 64$, Adam optimizer (lr $= 0.001$), margin $\gamma = 9.0$, and 100 epochs under 5 random seeds (Table 4).

Table 4: Multi-relational KG embedding link prediction over held-out relational triples (filtered protocol).

Model	MRR	Hits@10	Hits@1
TransE	0.211	0.625	0.000
RotatE	**0.369**	**0.641**	**0.250**

4.6 Explainability and Provenance Grounding

We systematically traced 100 randomly sampled system inferences through the RDF-grounded provenance subgraph (Table 5). Provenance coverage measures the percentage of predictions directly citing an authenticated article URI and sentence offset. Sentence relevance measures whether the cited sentence contains verified conflict trigger tokens matching the predicted event category. The provenance grounding score calculates the harmonic mean between model confidence and trigger provenance verification.

Table 5: Explainability and provenance coverage evaluated across $n = 100$ predictions.

Metric	Value
Provenance coverage (PROV-O article cited)	97.0%
Rule coverage (symbolic rule fired)	100.0%
Sentence relevance (cited sentence $\ni$ trigger)	100.0%
Avg. graph neighbours cited	3.2
Avg. provenance grounding score	0.768
Avg. model confidence	0.783

4.7 Comparative Baseline Analysis

To isolate the contributions of symbolic constraint gating versus neural sequence representation, we compare NeuroSym-BD against three established architectural paradigms on the held-out conflict benchmark ($n = 50$):

1. **Keyword & Gazetteer Heuristic**: A deterministic trigger parser mapping regex and gazetteer entries directly to CAMEO categories without sequence context.
2. **Pure Neural Sequence Model (BiLSTM)**: A temporal sequence forecasting BiLSTM operating directly over historical event sequences without ontological constraints.
3. **Pure Symbolic CAMEO Reasoner**: The rule-based classifier incorporating Bangladesh-specific refinement patterns without neural sequence modeling.

Table 6: Comprehensive comparison against competitive architectural baselines on held-out test conflict events ($n = 50$). BinAcc = binary accuracy on high-violence ($HV \geq 18$). Std-FPR = standard false positive rate $FP/(FP + TN)$. Expl = end-to-end PROV-O provenance trace rate.

Architecture	BinAcc	Precision	Recall	F1@HV	Std-FPR	Expl Rate
Keyword & Gazetteer Heuristic	0.580	0.522	0.826	0.640	0.704	**1.000**
Pure Neural (BiLSTM)	0.600	0.541	0.870	0.667	0.630	0.000
Pure Symbolic (Rule Engine)	0.640	0.568	**0.913**	0.700	0.593	**1.000**
NeuroSym-BD (Hybrid Ours)	**0.860**	**0.833**	0.870	**0.851**	**0.148**	**1.000**

4.8 Qualitative Analysis and Case Studies

We present qualitative walkthroughs across representative Bangladesh conflict scenarios:

Case 1: University Campus Quota Clashes (Dhaka). *"Over a dozen student activists were injured yesterday when clashes broke out between rival factions outside the central library."* The neural pipeline identifies the trigger *"clashes broke out"* and candidate CAMEO code 182 (Physical Assault). The symbolic reasoner verifies that the student political entities possess valid conflict agency and checks the Description Logic axiom:

$$\text{ValidEscalation} \equiv \text{HighViolenceEvent} \sqcap \exists \text{precededBy}.\text{TensionPrecursor}$$

Because the event was chronologically preceded by demonstrations (CAMEO 14), the escalation is certified, and PROV-O links ground the inference to sentence offset 3 of the source article within 3 hops.

Case 2: Inter-Party Electoral Campaign Violence (Pabna). *"Awami League and BNP supporters hurled stones at each other during an election rally in Pabna."* The entity extractor resolves both rival party wings, triggering the reciprocal violence relation. CAMEO code 193 (Fight with Small Arms / Projectiles) is assigned with 94.8% neural confidence and passes all five symbolic constraints (C-CONF, C-ONTO, C-ACTOR, C-GEO, C-TEMP).

Case 3: Labor Unrest vs. Violent Assault Disambiguation (Savar). *"Hundreds of readymade garment workers blocked the Dhaka-Aricha highway demanding unpaid wages."* Unconstrained neural classifiers often misclassify highway blockades as violent assault (CAMEO 182) due to high lexical tension. Here, constraint **C-ONTO** intercepts the prediction: because no physical trauma or assault verbs are present, the rule engine forces reclassification to non-violent economic blockade (CAMEO 145), successfully preventing a high-severity false positive.

4.9 Error Taxonomy

To provide complete transparency for deployment by humanitarian agencies and conflict researchers, we conducted a systematic error audit over 100 examined predictions (50 held-out test events and 50 development events), categorizing errors into four mutually exclusive primary classes (Table 7).

Table 7: Systematic Error Taxonomy and hybrid architectural mitigations.

Error Class	Description & Root Cause	Freq	Hybrid Mitigation
ET-01: Transliteration	Inconsistent English transliterations of Bengali names and acronyms (e.g., BCL vs Chhatra League).	34.0%	Multi-alias gazetteer and RDF `owl:sameAs` resolution across 64 districts.
ET-02: Temporal Anchors	Relative clauses (e.g., *"late last night"*) where reporting timestamp conflicts with occurrence date.	28.0%	ISO 8601 temporal normalization anchoring relative time tokens to article publication metadata.
ET-03: Administrative Borders	Peri-urban jurisdictions overlapping district boundaries (e.g., Tongi, Savar, Keraniganj).	22.0%	Two-tier geospatial hierarchy with fallback administrative containment axioms.
ET-04: Passive Voice	Journalistic agent omission (e.g., *"three crude bombs were detonated"*).	16.0%	Typed wildcard insertion (`UNKNOWN_ACTOR`) preventing hallucinated actor linkage.

5 Discussion

Symbolic constraints as a quality gate. The C-ONTO hard constraint (invalid CAMEO code transition) accounts for 31% of rejected neural predictions in our test set. A common error was the neural model predicting "Mass Violence (20)" following a "Protest (14)" event with no intervening escalation signals— a sequence forbidden by the CAMEO ontology. This aligns with findings in neuro-symbolic NLP [d'Avila Garcez and Lamb, 2023] that symbolic constraints are most valuable for rare but catastrophic errors.

Provenance as trust infrastructure. The PROV-O provenance layer enables conflict analysts to verify any system output against its source article within seconds. In our explainability evaluation, 97.0% of predictions were backed by at least one cited article sentence, and 100.0% of those sentences contained at least one verified violence trigger keyword.

Limitations. (1) The system currently relies on English-language sources (The Daily Star); Bangla-language sources (Prothom Alo, etc.) are under development. (2) Coreference resolution for complex multi-party political entities remains challenging in dense reporting. (3) ACLED detection recall (23.4%) reflects strict administrative alignment filters between national English reporting and ACLED's multi-source rural collection. (4) Multi-party factional clashes with ambiguous passive voice require ongoing gazetteer expansion.

6 Conclusion

We presented NeuroSym-BD, an open neuro-symbolic pipeline for violence event extraction, ontological constraint validation, and escalation modeling from Bangladeshi news. By combining transformer-based NLP, RDF knowledge graphs, and formal Description Logic CAMEO ontology constraints, the system substantially outperforms competitive neural and symbolic baselines, achieving an 86.0% binary accuracy and reducing false-alarm rates by 76.5% while providing complete provenance traces grounded in W3C PROV-O standards.

The hybrid neuro-symbolic architecture demonstrates that formal Description Logic constraints provide an indispensable inductive bias for high-stakes conflict monitoring, preventing severe neural false

alarms without sacrificing recall.

Future work will extend coverage to Bangla-language sources, integrate satellite imagery for spatial verification, and explore causal reasoning over escalation chains.

References

Mehdi Ali, Max Berrendorf, Charles T. Hoyt, Laurent Vermue, Sahand Sharifzadeh, Volker Tresp, and Jens Lehmann. PyKEEN 1.0: A python library for training and evaluating knowledge graph embeddings. *Journal of Machine Learning Research*, 22(82):1–6, 2021.

Antoine Bordes, Nicolas Usunier, Alberto Garcia-Duran, Jason Weston, and Oksana Yakhnenko. Translating embeddings for modeling multi-relational data. *Advances in Neural Information Processing Systems*, 26, 2013.

Elizabeth Boschee, Jennifer Lautenschlager, Sean O'Brien, Steve Shellman, James Starz, and Michael Ward. ICEWS coded event data. *Harvard Dataverse*, 2015.

Artur d'Avila Garcez and Luís C. Lamb. Neurosymbolic AI: The 3rd wave. *Artificial Intelligence Review*, 56:12387–12406, 2023.

Deborah J. Gerner, Philip A. Schrodt, Ron Francisco, and Judith L. Weddle. The machine coding of political conflict: Opportunities and challenges in the post-Cold War world. In *Proceedings of the Annual Meeting of the American Political Science Association*, 2002.

Paul Groth and Luc Moreau. PROV-Overview: An overview of the PROV family of documents. *W3C Working Group Note*, 2013.

Matthew Honnibal, Ines Montani, Sofie Van Landeghem, and Adriane Boyd. spaCy: Industrial-strength natural language processing in python. *Zenodo*, 2020.

Kalev Leetaru and Philip A. Schrodt. GDELT: Global data on events, location, and tone, 1979–2012. *ISA Annual Convention*, 2(4):1–49, 2013.

Clionadh Raleigh, Andrew Linke, Håvard Hegre, and Joakim Karlsen. Introducing ACLED: An armed conflict location and event dataset. *Journal of Peace Research*, 47(5):651–660, 2010.

Andrea Rossi, Denilson Barbosa, Donatella Firmani, Antonio Matinata, and Paolo Merialdo. Knowledge graph embedding for link prediction: A comparative analysis. *ACM Transactions on Knowledge Discovery from Data*, 15(2):1–49, 2021.

Michael Schlichtkrull, Thomas N. Kipf, Peter Bloem, Rianne van den Berg, Ivan Titov, and Max Welling. Modeling relational data with graph convolutional networks. In *The Semantic Web: ESWC 2018*, pages 593–607, 2018.

Philip A. Schrodt. CAMEO: Conflict and mediation event observations codebook. *Version 1.1b3. Pennsylvania State University*, 2012.

Zhiqing Sun, Zhi-Hong Deng, Jian-Yun Nie, and Jian Tang. RotatE: Knowledge graph embedding by relational rotation in complex space. In *International Conference on Learning Representations*, 2019.

Théo Trouillon, Johannes Welbl, Sebastian Riedel, Éric Gaussier, and Guillaume Bouchard. Complex embeddings for simple link prediction. In *Proceedings of the 33rd International Conference on Machine Learning*, pages 2071–2080, 2016.

Shikhar Vashishth, Soumya Sanyal, Vikram Nitin, and Partha Talukdar. CompGCN: Composition-based multi-relational graph convolutional networks. In *International Conference on Learning Representations*, 2020.

Fan Yang, Zhilin Yang, and William W. Cohen. Differentiable learning of logical rules for knowledge base reasoning. In *Advances in Neural Information Processing Systems*, volume 30, 2017.

Wenpeng Yin, Jamaal Hay, and Dan Roth. Benchmarking zero-shot text classification: Datasets, evaluation and entailment approach. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*, pages 3914–3923, 2019.

Ning Zhang, Shumin Deng, Zhen Sun, Xi Chen, Wei Zhang, and Huajun Chen. Contrastive information extraction with generative transformer. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pages 11680–11688, 2022.

A Bangladesh CAMEO Extensions

Table 8 lists the Bangladesh-specific CAMEO codes added in `ontology/cameo_bd_extension.ttl`.

Table 8: Bangladesh CAMEO extensions.

Code	Label	Description
BD01	Harthal Violence	Violence during political general strike (harthal)
BD02	Political Clash	Direct confrontation between rival party activists
BD03	Student Protest Violence	Violence erupting from student-led protests
BD04	Security Force Operation	Targeted law enforcement action (RAB/Police)
BD05	Enforced Disappearance	Suspected state-led abduction of activists
BD06	Election Violence	Violence occurring in electoral context

B SPARQL Query Examples

Top 10 violence hotspot districts:

```
PREFIX cameo: <http://example.org/cameo/>
SELECT ?district (COUNT(?evt) AS ?count)
WHERE {
  ?evt a cameo:ViolenceEvent ;
       cameo:location ?loc .
  ?loc cameo:district ?district .
}
GROUP BY ?district
ORDER BY DESC(?count)
LIMIT 10
```

Escalation detection (district max code ≥ 18 in last 30 days):

```
PREFIX cameo: <http://example.org/cameo/>
SELECT ?district (MAX(?code) AS ?maxCode) (COUNT(?evt) AS ?n)
WHERE {
  ?evt a cameo:ViolenceEvent ;
       cameo:code ?code ;
       cameo:date ?date ;
       cameo:location ?loc .
  ?loc cameo:district ?district .
  FILTER (?date >= "2026-09-21"^^xsd:date && ?code >= 18)
```

```
}
GROUP BY ?district
ORDER BY DESC(?maxCode)
```