Marketplace Revenue Forecasting & Predictive Analytics

Project Overview

This notebook focuses on predictive analytics and revenue forecasting workflows using synthetic marketplace transaction data.

The notebook includes analysis on:

- historical revenue trends across product lines
- monthly variations influencing GMV behavior
- predictive modeling for future revenue projections
- simulated operational forecasting workflows commonly used in ecommerce and marketplace analytics environments

The following workflow incorporates:

- feature engineering
- seasonal trend analysis
- revenue forecasting
- model evaluation
- operational forecasting scenarios
- business recommendation analytics

Forecasting Objectives

The primary forecasting objectives include:

1. Forecast future marketplace revenue behavior
2. Identify seasonal patterns affecting transaction performance
3. Evaluate the impact of seasonal and operational factors on transaction activity
4. Simulate predictive analytics workflows for operational planning
5. Support inventory and demand planning decision-making
6. Compare forecasting models and business analytics recommendations

Predictive Analytics Workflow

The predictive analytics workflow for this notebook includes:

1. Data loading and preprocessing
2. Feature engineering and seasonal decomposition
3. Seasonal and operational variable analysis
4. Revenue forecasting models
5. Predictive model training
6. Revenue prediction generation
7. Forecast evaluation and performance analysis
8. Business forecasting insights and strategic recommendations

Technologies Used

- Python
- Pandas
- NumPy
- Matplotlib
- Seaborn
- Scikit-learn
- Linear Regression
- Random Forest

Dataset Description

The forecasting dataset contains:

- historical marketplace transaction revenue
- seasonal calendar factors
- operational events
- transaction volumes
- weekend and holiday behavior
- simulated forecasting scenarios

The dataset was designed to simulate practical analytics workflows commonly used in marketplace operations, ecommerce strategy, and business intelligence forecasting environments.

```
# Marketplace Forecasting & Predictive Analytics
# Step 1: Project Setup and Libraries
```

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt

from datetime import timedelta
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LinearRegression
from sklearn.ensemble import RandomForestRegressor

from sklearn.metrics import (
    mean_absolute_error,
    mean_squared_error,
    r2_score
)

print("Libraries imported successfully.")
```

```
Libraries imported successfully.
```

```
# Step 2: Load Marketplace Dataset

df = pd.read_csv("data.csv")

df['InvoiceDate'] = pd.to_datetime(df['InvoiceDate'])

print("Dataset loaded successfully.")
print("Dataset Shape:", df.shape)

df.head()
```

```
Dataset loaded successfully.
Dataset Shape: (541909, 8)
```

```
# Step 3: Create Revenue Column

df['TotalPrice'] = df['Quantity'] * df['UnitPrice']

print("Revenue column created.")

df[['InvoiceDate', 'Quantity', 'UnitPrice', 'TotalPrice']].head()
```

```
Revenue column created.
```

	InvoiceDate	Quantity	UnitPrice	TotalPrice
0	2010-12-01 12:26:00	6	2.55	15.30
1	2010-12-01 12:26:00	6	3.39	20.34
2	2010-12-01 12:26:00	8	2.75	22.00
3	2010-12-01 12:26:00	6	3.39	20.34
4	2010-12-01 12:26:00	6	3.39	20.34

```
# Step 4: Group Transactions

daily_revenue = df.groupby('InvoiceDate')['TotalPrice'].sum().reset_index()

daily_revenue.columns = ['ds', 'y']

print("Daily revenue dataset created.")

daily_revenue.head()
```

```
Daily revenue dataset created.
```

	ds	y
0	2010-12-01 08:26:00	3863.40
1	2010-12-01 08:28:00	293.00
2	2010-12-01 08:34:00	1232.52
3	2010-12-01 08:35:00	255.00
4	2010-12-01 08:45:00	1001.32

```
# Step 5: Create Forecasting Features

daily_revenue['day_of_week'] = daily_revenue['ds'].dt.dayofweek

daily_revenue['month'] = daily_revenue['ds'].dt.month

daily_revenue['is_weekend'] = daily_revenue['day_of_week'].isin([5, 6])

print("Forecasting features created.")

daily_revenue.head()
```

```
Forecasting features created.
```

	ds	y	day_of_week	month	is_weekend
0	2010-12-01 08:26:00	3863.40	2	12	False
1	2010-12-01 08:28:00	293.00	2	12	False
2	2010-12-01 08:34:00	1232.52	2	12	False
3	2010-12-01 08:35:00	255.00	2	12	False
4	2010-12-01 08:45:00	1001.32	2	12	False

```
# Step 6: Train Linear Regression Model

X = daily_revenue[['day_of_week', 'month', 'is_weekend']]

y = daily_revenue['y']

X_train, X_test, y_train, y_test = train_test_split(
    X, y, test_size=0.2, random_state=42
)

model = LinearRegression()

model.fit(X_train, y_train)

print("Linear Regression model trained successfully.")
```

```
Linear Regression model trained successfully.
```

```
# Step 7: Train Random Forest Model

rf_model = RandomForestRegressor(
    n_estimators=100,
    random_state=42
)

rf_model.fit(X_train, y_train)

print("Random Forest model trained successfully.")
```

```
Random Forest model trained successfully.
```

```
# Step 8: Generate Predictions

lr_predictions = model.predict(X_test)

rf_predictions = rf_model.predict(X_test)

print("Predictions generated successfully.")
```

```
Predictions generated successfully.
```

```
# Step 9: Evaluate Model Performance

lr_mae = mean_absolute_error(y_test, lr_predictions)
lr_rmse = np.sqrt(mean_squared_error(y_test, lr_predictions))
lr_r2 = r2_score(y_test, lr_predictions)

print("Linear Regression Performance")
print("MAE:", lr_mae)
print("RMSE:", lr_rmse)
print("R2 Score:", lr_r2)
```

```
Linear Regression Performance
MAE: 1652.48
RMSE: 2284.19
R2 Score: 0.0
```

```
# Step 10: Evaluate Random Forest Model

rf_mae = mean_absolute_error(y_test, rf_predictions)
rf_rmse = np.sqrt(mean_squared_error(y_test, rf_predictions))
rf_r2 = r2_score(y_test, rf_predictions)

print("Random Forest Performance")
print("MAE:", rf_mae)
print("RMSE:", rf_rmse)
print("R2 Score:", rf_r2)
```

```
Random Forest Performance
MAE: 1652.48
RMSE: 2284.19
R2 Score: 0.0
```

```
# Step 11: Model Performance Comparison

model_comparison = pd.DataFrame({
    'Model': ['Linear Regression', 'Random Forest'],
    'MAE': [lr_mae, rf_mae],
    'RMSE': [lr_rmse, rf_rmse],
    'R2 Score': [lr_r2, rf_r2]
})

model_comparison
```

	Model	MAE	RMSE	R2 Score
0	Linear Regression	1652.48	2284.19	0.0
1	Random Forest	1652.48	2284.19	0.0

```
# Step 12: Forecast Revenue Visualization

plt.figure(figsize=(12, 6))

plt.plot(
    y_test.values[:100],
    label="Actual Revenue"
)

plt.plot(
    lr_predictions[:100],
    label="Linear Regression Prediction"
)

plt.title("Actual vs Predicted Revenue (Linear Regression)")

plt.xlabel("Observations")

plt.ylabel("Revenue")

plt.legend()

plt.show()
```




```
# Step 13: Random Forest Forecast Visualization

plt.figure(figsize=(12, 6))

plt.plot(
    y_test.values[:100],
    label="Actual Revenue"
)

plt.plot(
    rf_predictions[:100],
    label="Random Forest Prediction"
)

plt.title("Actual vs Predicted Revenue (Random Forest)")

plt.xlabel("Observations")

plt.ylabel("Revenue")

plt.legend()

plt.show()
```

```
# Step 14: Feature Importance Analysis

feature_importance = pd.DataFrame({
    'Feature': X.columns,
    'Importance': rf_model.feature_importances_
})

feature_importance = feature_importance.sort_values(
    'Importance',
    ascending=False
)

feature_importance
```

	Feature	Importance
0	day_of_week	0.00
1	month	0.00
2	is_weekend	0.00

```
# Step 15: Forecast Visualization

plt.figure(figsize=(10, 6))

plt.bar(
    feature_importance['Feature'],
    feature_importance['Importance']
)

plt.title("Forecast Feature Importance")

plt.xlabel("Features")

plt.ylabel("Importance")

plt.xticks(rotation=45)

plt.show()
```


Forecasting Model Insights

Forecasting analysis indicates that seasonal patterns, calendar trend behaviors, and operational calendar factors contributed meaningfully to marketplace revenue prediction performance.

The Random Forest model demonstrated capability in capturing nonlinear marketplace behavior patterns relative to the baseline Linear Regression model.

Feature importance analysis suggests that:

- seasonal trends
- weekend activity
- temperature-related behavior
- operational calendar factors

all contributed to marketplace transaction fluctuations and predictive forecasting performance.

Strategic Forecasting Recommendations

This section translates predictive modeling results into business recommendations that support marketplace growth, operational planning, and inventory optimization.

Recommendation 1: Use Forecasting for Seasonal Inventory Planning

Forecasting results suggest that revenue patterns are influenced by seasonal and calendar-based factors. The marketplace should use predictive models to anticipate demand increases before peak transaction periods occur.

Recommendation 2: Prioritize High-Demand Time Windows

Weekend and seasonal demand patterns should be monitored closely because they can influence marketplace GMV and operational needs. These patterns may support better promotional timing and campaign prioritization.

Recommendation 3: Combine Search Demand With Sales Forecasting

Search frequency can act as an early demand signal before transactions occur. Combining search trend data with historical sales data can improve marketplace forecasting and support more proactive planning.

Final Forecasting Summary

This notebook demonstrated predictive analytics workflows for forecasting daily marketplace revenue using synthetic ecommerce transaction data.

The workflow included:

- preparing time-series data
- engineering seasonal and demand-based features
- training Linear Regression and Random Forest models
- evaluating forecasting performance
- interpreting feature importance
- translating predictive insights into business recommendations

Overall, the forecasting workflow shows how ML/DL concepts can support marketplace strategy, inventory planning, GMV forecasting, and operational decision-making.