

Quantum Error Correction

Ava Johnson (St. Francis Preparatory School, AEOP)
Jacob Kupperman (Bergen County Technical High School)
Alex Shulman (Briarcliff High School)

Table of Contents

1. Why QEC?
 2. Classical Error Correction
 3. Quantum Error Correction
 4. Causes of Error
 5. Error Correction Code
-


Why Quantum Error Correction?

- To solve more complex algorithms
 - Ex. Shor's factor finder
- Big future - \$106B potential quantum technology market size by 2040

Classical vs. Quantum Bits

- Classical: 0 or 1

- Quantum: 0, 1
 - Or a superposition of 0 and 1




Classical Error Correction


—

Classical Error Correction

- Corrects errors during transmission and storage of information
- To send a single bit over a binary symmetric channel, then we can encode the bit, by repeating it three times
 - $0 \rightarrow 000$
 - $1 \rightarrow 111$
- Error:
 - $0 \rightarrow 001$



Potential Drawbacks of Repetition




Quantum Error Correction

—


Preserve Quantum Information

- Quantum error correction ensures that delicate quantum information remains accurate and usable despite environmental disturbances and errors
- Very important for large scale calculations



Quantum Advantage

- Quantum algorithms promise to outperform classical algorithms for specific tasks
- Quantum error correction helps maintain the advantage of quantum algorithms by mitigating the impact of errors and noise




Causes of Error

—

External Forces

- Any external force can lead to inaccuracies in quantum computations and, in certain quantum computer architectures, complete loss of memory state



Gate Errors

- Imperfections in quantum gates cause errors
 - Noise and imperfections - these imperfections can arise due to limitations in hardware, fluctuations in control parameters, and external disturbances



Challenges of Quantum Error Correction

- Cannot directly transfer classical error correction techniques to quantum error correction because
 - The no-cloning principle forbids the copying of quantum states
 - Measurement destroys quantum states


$$-\hat{Z} = |1\rangle$$

Fixing the Error


—

Bit-Flip Code

- Only the first qubit would ever be measured unlike classical code repetition



$$\Psi = a|0\rangle + b|1\rangle$$




Initial State

$$a|000\rangle + b|100\rangle$$

$$a|000\rangle + b|110\rangle$$

$$a|000\rangle + b|111\rangle$$



1. $a|000\rangle + b|100\rangle$

2. $a|000\rangle + b|110\rangle$

3. $a|000\rangle + b|111\rangle$


4. Error:

$a|100\rangle + b|011\rangle$

5. $a|110\rangle + b|011\rangle$

6. $a|111\rangle + b|011\rangle$


7. $a|011\rangle + b|111\rangle$




$$\frac{1}{2} |000\rangle + \frac{1}{2} |011\rangle - \frac{1}{2} |100\rangle + \frac{1}{2} |111\rangle$$

Syndrome Measurement

- Method for measuring the states of qubits indirectly



$$\Psi = a|0\rangle + b|1\rangle$$



$$1. a|000\rangle + b|100\rangle$$

$$2. a|000\rangle + b|110\rangle$$

$$3. a|000\rangle + b|111\rangle$$

$$4. \text{Error: } a|010\rangle + b|101\rangle$$

$$a|010\rangle \otimes |00\rangle + b|101\rangle \otimes |00\rangle$$

$$5. a|010\rangle \otimes |00\rangle + b|101\rangle \otimes |10\rangle$$


$$6. a|010\rangle \otimes |10\rangle + b|101\rangle \otimes |10\rangle$$

$$7. a|010\rangle \otimes |10\rangle + b|101\rangle \otimes |11\rangle$$

$$8. a|010\rangle \otimes |10\rangle + b|101\rangle \otimes |10\rangle$$


Sign Flip Error Correction

- Hadamard gates rotate the qubit around the x and y axes to allow for error correction along them since the bit flip code only corrects errors along the z-axis



Shor's Code

- It combines the techniques used to correct for bit flips and sign flips in order to be effective against any type of error



Quantum Error Correction (Code)

```
from qiskit import Aer, QuantumCircuit, execute
from qiskit.circuit.library import RGQFTMultiplier
qc = QuantumCircuit(12, 6)

qc.x(0)
qc.x(2) #sets 5

qc.x(4)
qc.x(5) #sets 6

circuit = RGQFTMultiplier(num_state_qubits=3, num_result_qubits=6)
qc = qc.compose(circuit)

qc.measure(6, 0)
qc.measure(7, 1)
qc.measure(8, 2)
qc.measure(9, 3)
qc.measure(10, 4)
qc.measure(11, 5)

backend = Aer.get_backend('qasm_simulator')
job = execute(qc, backend, shots=100)
counts = job.result().get_counts()
print(counts)

{'011110': 100}
```



```
from qiskit import Aer, QuantumCircuit, execute
from qiskit.circuit.library import RGQFTMultiplier
qc = QuantumCircuit(12, 6)

qc.x(0)
qc.x(2) #sets 5

qc.x(4)
qc.x(5) #sets 6

#Error
qc.y(0)
qc.h(1)

circuit = RGQFTMultiplier(num_state_qubits=3, num_result_qubits=6)
qc = qc.compose(circuit)

qc.measure(6, 0)
qc.measure(7, 1)
qc.measure(8, 2)
qc.measure(9, 3)
qc.measure(10, 4)
qc.measure(11, 5)

backend = Aer.get_backend('qasm_simulator')
job = execute(qc, backend, shots=100)
counts = job.result().get_counts()
print(counts)

{'0111000': 46, '100100': 54}
```

```

from qiskit import Aer, QuantumCircuit, execute
from qiskit.circuit.library import RGQFTMultiplier
import numpy as np
qc = QuantumCircuit(20, 6)

qc.x(0)
qc.x(2) #sets 5

qc.x(4)
qc.x(5) #sets 6

```

```

#Shor's Algorithm Part 1
qc.cx(0,12)
qc.cx(0,13)
qc.h(0)
qc.h(12)
qc.h(13)
q = [0, 12, 13]
for i in range(6):
    qc.cx(q[i % 3], 19-i)

```

```

#Error
qc.y(0)
qc.h(0)
qc.x(12)

```

```

#Shor's Algorithm Part 2
for i in range(6):
    qc.cx(q[i % 3], 19-i)
for i in range(3):
    qc.ccx(13+i, 16+i, q[i])
qc.h(0)
qc.h(12)
qc.h(13)
qc.cx(0,12)
qc.cx(0,13)
qc.ccx(12, 13, 0)

```

```

circuit = RGQFTMultiplier(num_state_qubits=3, num_result_qubits=6)
qc = qc.compose(circuit)

```

```

qc.measure(6, 0)
qc.measure(7, 1)
qc.measure(8, 2)
qc.measure(9, 3)
qc.measure(10,4)
qc.measure(11,5)

```

```

backend = Aer.get_backend('qasm_simulator')
job = execute(qc, backend, shots=100)
counts = job.result().get_counts()
print(counts)

```

```

{'011110': 100}

```

Sources

Coggins, M. (2022, August 21). Quantum error correction: Bit flip code in Qiskit. Quantum Computing UK.

<https://quantumcomputinguk.org/tutorials/quantum-error-correction-bit-flip-code-in-qiskit>

Coggins, M. (2022b, August 21). Quantum error correction: Phase flip code in Qiskit. Quantum Computing UK.

<https://quantumcomputinguk.org/tutorials/quantum-error-correction-phase-flip-code-in-qiskit>

Coggins, M. (2022b, August 21). Quantum error correction: Shor Code in Qiskit. Quantum Computing UK.

<https://quantumcomputinguk.org/tutorials/quantum-error-correction-shor-code-in-qiskit>

Keysight Technologies. (2022, December 15). Quantum Computing Brings New Error Correction Challenges. Keysight Blogs.

<https://www.keysight.com/blogs/keys/thought-leadership/2022/12/15/quantum-computing-brings-new-error-correction-challenges>

Wikimedia Foundation. (2023, June 26). *Quantum error correction*. Wikipedia. https://en.wikipedia.org/wiki/Quantum_error_correction

What is quantum error correction?. We make quantum technology useful. (n.d.).

<https://q-ctrl.com/topics/what-is-quantum-error-correction#:~:text=From%20noise%20to%20error%20in%20quantum%20computing&text=Just%20like%20a%20mobile%20phone,in%20the%20Earth's%20magnetic%20field.>