170468

and Chemical

Date

30-Aug-2022

То

Quantity - 10,455 Kg

Our ref

Test # AE220396

PRODUCT INFORMATION

OK 48.08 2.5x350mm 1/2 VP	Lot: SBW0412061	Art No.	48082532G0
011 10100 21011000 11111 1/2 11			.000_00_0

CHEMICAL - WELD METAL COMPOSITION (%)

C(%)	Mn(%)	Si(%)	P(%)	S(%)	Ni(%)	Cr(%)	Mo(%)	V(%)	Cu(%)
0.05	1.25	0.46	0.014	0.007	0.83	0.1	0.09	0.02	0.1

MECHANICAL PROPERTIES OF THE WELD METAL As Welded

Rp0.2 (Mpa)	Rm (MPa)	EI (%)	Temp (°C)	Impact toughness					
519	613	29	-50	Energy (J)	102	148	154	Avg	135

Notes:

Radiographic examination acc. to ASME Sect II Part C SFA/AWS A5.5: : Acceptable result Schedule I C3 Tested as per Lot Class:

Made in Sweden Typical diffusible hydrogen value is less than 4ml/100g weld metal

REFERENCES

CLASSIFICATIONS Data Sheet: Reg No. EN009807 AWS/ASME SFA A5.5: E7018-G H4R

Report Number: 47302 Report No: D912164



ESAB Middle East FZE

Technical Department Rajesh Babu Quality & Product Specialist



ذات مسؤولية محدودة تأسست بموجب القانون رقم 9 لسنة 1992 Formed pursuant to law No. 9 of 1992 with limited liability

> إيساب الشرق الأوسط م ح **ESAB MIDDLE EAST FZE**