CODEASTRA 2.0 · CLOUD COMPUTING & DISTRIBUTED SYSTEMS

Geo-Distributed Disaster Data Replication with Graceful Degradation

A multi-region report service that keeps accepting data when the network breaks, merges safely when it returns, and tells operators exactly what is at risk.

3
replicas live on AWS (Mumbai, Hyderabad, Singapore)

68
automated tests passing

0%
edits silently lost, vs 42% for last-writer-wins (100 trials each)

<1 s
to converge after healing, across 3 AWS regions

Project report for judges and mentors · 12 October 2026
Status: engine complete and verified locally and on a three-region AWS deployment; baseline benchmark and dashboard in progress

1. Executive summary

During a disaster, the region that most needs to record reports is often the one that has lost its connection to everyone else. Most cloud databases force a bad choice: **refuse writes** until the network returns, or **accept writes and silently overwrite** whichever edit has the older timestamp.

We are building a replicated report service that takes a third path:

- **Always accept** a report locally, instantly, even when cut off.
- **Never silently lose** a write. Conflicts are kept in a visible ledger and resolved by clear rules or a human operator.
- **Tell the truth** about safety: every report is marked *local*, *replicated* or *confirmed*.
- **Prove history is intact.** Every event is hash-chained, so editing, deleting or forging a stored event is detectable, and a replica rejects forged events from a bad peer.
- **Prove it with numbers.** In 100 fault-injection trials per system, last-writer-wins silently lost 42.2% of acknowledged edits; our engine lost 0%.
- **Stay provider-independent.** No managed database service is used, so the same nodes can run on AWS and Google Cloud and survive a whole-provider failure.

> **One-sentence pitch.** Cloud providers move data between regions; we make that replication trustworthy and understandable during a disaster, by keeping every write, exposing every conflict, and showing what is still at risk.

Where we are today

The replication engine is built and verified: three nodes replicate, survive partitions, crashes and wrong clocks, and converge to identical state. It runs in Docker and is deployed as three servers on AWS (Mumbai, Hyderabad, Singapore), where the full partition, heal and crash-recovery scenario passes 12 of 12 checks. The comparison benchmark against a last-writer-wins baseline is complete (section 9). The operator dashboard and a run of the mixed AWS and Google Cloud deployment are the remaining work.

2. The problem we were given

Problem statement (Cloud Computing & Distributed Systems, #2): critical systems cannot assume a single region or network path is always available. During a disaster the system may need to keep accepting reports while disconnected from its primary service and later reconcile conflicting updates.

What the brief asks for	Our response
Two or more replicas, local writes, persistence	Three replicas, each its own process; every node writes to its own SQLite event log first
Replication protocol and recovery	Pull-based version-vector sync every 0.5 s, relaying through third nodes, catch-up after a heal or crash
Partition simulation	Per-link block, node pause (crash), clock skew and reset through an admin API
Defined conflict-resolution policy	Per-field merge rules plus a conflict ledger and operator decisions
Consistency-status API	`/status`, per-report durability, `/state-hash`
Operational dashboard	Web dashboard (in progress, built by a teammate)
"Explicitly choose and defend your consistency model"	Section 4

Disaster reports that survive a network failure


CodeAstra 2.0 · Cloud Computing & Distributed Systems · Geo-distributed replication with graceful degradation

1 Normal day: write locally first, copy in the background

Responder submits a disaster report → Nearest node saves it as an event, instantly → Background sync every 0.5 seconds → Other regions keep their own copy → **Status: CONFIRMED** held by every region

The user is never blocked waiting for the network. LOCAL · at risk | REPLICATED | CONFIRMED

2 Disaster: the network is cut, and both sides keep working



Mumbai keeps accepting reports
Its writes are marked LOCAL, so the operator can see they are at risk.

The same report gets edited on both sides
Mumbai: “road flooded” Hyderabad: “water knee high”

3 Recovery: reconnect and merge, with nothing silently lost

Network restored links reopen → Nodes exchange the missing events → Merge by field rules no clock needed → **Conflict ledger** keeps both versions → **All regions identical** proved by a state hash

Severity: highest wins | **Status**: most advanced wins | **Location**: latest, flag if >500 m | **Description**: keep both, operator picks

Verified: 68 automated tests · 100 fault trials: 0% of edits silently lost vs 42% for last-writer-wins · hash-chained history · converges in under 1 s across 3 AWS regions

Figure 1. End-to-end workflow: normal operation, disaster partition, recovery and merge.


3. How it works

3.1 Inside one node



- **Events, not rows.** Every create or edit is stored as an immutable event. A report's current state is *calculated* from its events. Nothing is edited or deleted, so nothing can be silently overwritten.
- **Hybrid logical clocks.** Each event carries a clock value that never goes backwards and is advanced by events received from other nodes, so a node with a wrong wall clock cannot corrupt ordering.
- **Version vectors.** Each event records what its author had already seen. This tells "one edit after another" apart from "two edits at the same time", which timestamps alone cannot do.
- **Pure merge function.** The merged result depends only on the *set* of events, not the order they arrived in, so any two nodes holding the same events compute the same state.

3.2 Replication



- Each node pulls from every peer every 0.5 s. A dead peer never delays the others (one thread per peer).
- Applying an event twice does nothing; events arriving out of order or with gaps are skipped and refetched.
- Nodes **relay** for each other: if Mumbai cannot reach Hyderabad but both reach Singapore, they still converge.
- Long outages catch up in batches of 500 events, always a gap-free prefix.
- **Reset epochs** stop a freshly wiped node from receiving old data back from a peer not yet wiped.

3.3 Merge rules (the consistency policy)

Field	Two edits at the same time	Why this rule
Severity (1-5)	Highest value wins; lowering needs an operator	In a disaster, under-reporting is more dangerous than over-reporting
Status	Most advanced wins (open < acknowledged < in progress < resolved); reopening needs an operator	Work already done should not be silently undone by a stale update
Location	Latest wins; if the two are more than 500 m apart, flag for an operator	Small corrections are safe; large jumps need a human
Description	Keep both versions and ask an operator	Free text cannot be merged safely by a rule
Type, reporter	Fixed at creation	Identity of a report must not drift

If a later edit was written by someone who had already seen both versions, it simply supersedes them. Every concurrent disagreement stays in the ledger as history, whether a rule or a person resolved it.

3.4 Durability: telling the truth about risk

Status	Meaning
local	Only this node holds the report. If this node is lost, the report is lost.
replicated	At least one other node is known to hold every event of the report.
confirmed	Every other node is known to hold it.

3.5 Verification built into the system

Each node exposes a hash of its merged state and the list of event ids it holds. Equal hashes mean two nodes hold the same events and merged them identically. An automated tester uses these to check, after every fault run, that nothing was lost and everything converged.

4. Consistency model and why we chose it

Our choice: available, eventually consistent

- Every node always accepts writes (availability under partition).
- All nodes converge to the same state once they exchange events (**strong eventual consistency**).
- No acknowledged write is ever discarded; disagreements are surfaced, not hidden.

Why not strong consistency?

- A strongly consistent system must refuse writes on the side without a majority.
- In a disaster that is exactly the side that needs to keep recording reports.
- Reports are mostly new facts that accumulate, so merging is practical and safe.

> **The honest limit.** A report saved in a region that is destroyed before it syncs is lost. No design removes this. We shrink the window to about half a second and show operators which reports are still *local*, so the risk is visible instead of hidden.

5. Existing approaches and where they fall short

Evidence level: **verified** means confirmed in documentation or papers during our research; **general knowledge** means widely known but not re-verified by us.

Approach	What it does	Where it falls short for this problem	Evidence
DynamoDB Global Tables, eventual mode	An isolated region keeps accepting writes and catches up when healthy	Conflicts resolved by **last writer wins**, so one edit is silently discarded; depends on clocks	**verified**
DynamoDB Global Tables, strong mode	A write is confirmed only after another region has it	Exactly 3 regions (or 2 plus a witness), no transactions, higher write latency; an isolated region cannot get confirmation (our inference)	**verified (partition behaviour inferred)**
AWS Amplify DataStore / AppSync	Offline-first client sync with Auto Merge, optimistic concurrency or a custom Lambda	Auto Merge prefers the server value for single fields; custom logic is left to the developer; syncs devices to one cloud endpoint; Gen 1 reaches end of life on 1 May 2027	**verified**
Consensus databases (Spanner, CockroachDB, etcd)	Strong consistency through majority agreement	The minority side of a partition cannot commit writes	**general knowledge**
Cassandra, Riak, CouchDB	Always-writable replicas	Typically timestamp-based or revision-based winners that can hide the losing version	**general knowledge**
CRDT libraries (e.g. Automerge)	Replicas converge automatically, peer to peer, with no central server	Built for collaborative documents; no domain rules (such as severity can only escalate), no operator workflow, no durability status	**verified (domain gap is our assessment)**
Real-world track record (Jepsen)	Independent fault-injection testing of databases	Found split-brain, lost acknowledged writes and lost updates in production systems, so "it replicates" is not proof	**verified**
Azure Cosmos DB, multi-region writes	Always-writable regions with a configurable conflict policy	Default is last-writer-wins on a timestamp; conflicts resolved that way do not appear in the conflict feed, and the policy cannot be changed after the container is created	**verified**
AWS QLDB (ledger database)	A managed, cryptographically verifiable ledger	Retired on 31 July 2025. The suggested replacement, Aurora PostgreSQL with audit logging, is reported to lack the cryptographic verifiability QLDB gave	**verified (secondary sources)**
Cross-cloud replication	Distributed SQL such as CockroachDB spans clouds; common practice is active-passive	No managed service offers active-active across AWS and Google Cloud that stays writable on the minority side of a partition; consensus systems need a majority	**search found no counter-example**

> **The gap we target:** AWS and others move the data. They do not decide what is true when two regions disagree, do not tell the operator which reports are at risk, and do not ship their own proof that nothing was lost.

6. What is different and innovative

We want to be clear about what is new. Event logs, hybrid clocks and version vectors are established techniques. Our contribution is combining them into a disaster-operations service with behaviour and verification that general-purpose tools do not provide.

Idea	What it gives the user
Domain-aware merge rules	Safe defaults for disaster reports: severity escalates, status advances, location jumps are flagged. Not a blanket "latest wins".
Visible conflict ledger	Every concurrent disagreement is stored with both versions and who decided. Nothing disappears silently.
Per-report durability	Operators see which individual reports are still at risk, not just a table-level latency number.
Causality, not clocks	Correct behaviour even when a node's clock is an hour wrong. We test this explicitly.
Built-in proof	A chaos tester runs random partitions, crashes and clock skew, then asserts convergence and zero lost writes, and compares against a last-writer-wins baseline.
Safe reset across nodes	Epoch numbers prevent old data reappearing after a cluster reset, a real operational trap.
Tamper-evident history	Each event is hash-chained to the previous one from the same node. Editing, deleting or forging a stored event is detectable by recomputing the chain, and a replica refuses forged events from a peer, then recovers from an honest one. AWS retired its ledger database, QLDB, in July 2025, so this fills a gap rather than repeating a product.
Independent of any one provider	Nothing depends on a managed database, so the same image runs on AWS and Google Cloud and a whole-provider outage cannot take all replicas down. Managed services cannot replicate across clouds, and consensus databases cannot write on the minority side of a partition.

7. Technology stack

Layer	Choice	Reason
Language	Python 3.13	Fast to build and test; strong ecosystem for fault-injection scripts
API server	FastAPI + Uvicorn	Typed requests, automatic interactive docs
Storage	SQLite (one file per node)	Durable across crashes, zero setup; fits the simulated-region scope
Node-to-node calls	httpx	Simple HTTP, easy to block and inspect in tests
Tests	pytest	Unit, multi-node and random-fault tests
Packaging	Docker and Compose	One command for teammates; same image locally and in the cloud
Cloud	AWS EC2 in three regions (deployed)	Real geographic separation. One small instance per region, created and removed by one script, all resources tagged for clean teardown
Access control	Shared-secret header on admin, sync and operator endpoints	Lets the nodes be reachable from any network while fault injection and operator decisions stay protected; reporting and reading stay open
Dashboard	Web single-page app	Shows regions, reports, conflicts and fault controls

We deliberately did not implement Raft or Paxos: this problem calls for an available design, and consensus would reintroduce the exact failure we are avoiding.

8. Progress so far

Component	Status	Evidence
Event log, logical clock, create and edit API	**Done**	Unit and API tests
Merge engine and per-field rules	**Done**	One test per rule, plus 40 random histories
Conflict ledger and operator resolve	**Done**	API and replication tests
Sync between nodes, relaying, batching	**Done**	Multi-node tests
Durability states, peer status, state hash	**Done**	Multi-node tests
Fault injection (block, pause, clock, reset)	**Done**	Admin API and tests
Local three-node cluster and smoke test	**Done**	12 of 12 checks over real HTTP
Docker packaging	**Done**	Image and compose file; data survives a hard kill and a full restart
Admin token on sensitive endpoints	**Done**	Tests for open, protected and wrong-token cases; verified live on AWS
AWS three-region deployment	**Done**	Mumbai, Hyderabad and Singapore; 12 of 12 checks across the real regions
Last-writer-wins baseline and chaos benchmark	**Done**	100 trials per system, 5 scenarios, results file and charts generated
Tamper-evident hash-chained log and audit endpoints	**Done**	10 tests; live tamper demo detects an edit made behind the app
Google Cloud deployment script	**Prepared**	Written and syntax-checked; not yet run against a real project
Operator dashboard	**In progress**	Assigned to a teammate; built against the API contract

Measured results

Check	Local cluster	Three AWS regions
Automated tests	68 passed	
Random fault runs (writes, partitions, crashes, clock skew)	25 seeds: always converged, no acknowledged write lost, identical ledgers	
End-to-end smoke test (replicate, partition, heal, crash)	12 of 12 passed	12 of 12 passed
Report appears in another region	0.3 to 0.5 s	0.17 s
Report reaches "confirmed" everywhere	about 0.5 s	0.29 s
Convergence after a partition heals	0.2 to 0.35 s	0.56 s
Crashed node catches up after resuming	0.1 to 0.3 s	0.40 s

Benchmark against a last-writer-wins baseline

100 trials per system (20 per scenario, seed 11), local clusters, identical randomised operations applied to both. Edits are made during partitions, pairwise cuts, flapping links, a crashed node and a fast clock. An edit is "silently lost" when its value is absent from the final report and from every conflict-ledger entry, and no warning was returned when it was accepted.

Measure	Our engine	Last-writer-wins baseline
Replicas converged	100%	100%
Acknowledged edits silently lost	**0.0% (0 of 199)**	**42.2%**
Acknowledged events missing from final state	**0.0%**	**24.5%**
Causally later edit overridden by a fast clock	**0 of 20**	**20 of 20**
Trials with no loss	**100 of 100**	**9 of 100**
Convergence after healing, p50 / p95	18 / 138 ms	8 / 119 ms

The baseline converges slightly faster, which is expected: it keeps no history to exchange. The scenarios are deliberately conflict-heavy stress tests, so these percentages show behaviour under failure, not the loss rate of a normal workload.

Timings are measured from a laptop that polls the nodes over HTTP, so they include the laptop's own network round trip and a 0.1 s polling step. Read them as upper bounds on the replication delay, from a single run each, not as a statistical benchmark.

9. How we will prove it to the judges

Method	What it shows
1. Live partition demo	Cut a region, edit the same report on both sides, restore, show the merge and ledger.
2. Side-by-side baseline	The same scenario on a last-writer-wins cluster: an edit disappears there, but not in ours.
3. Automated chaos benchmark	Hundreds of seeded random runs with a pass/fail table and charts.
4. Real multi-region deployment	Three AWS regions, with the partition triggered live.
5. Written model defense	This report, section 4: why availability, what is lost, and what is not.

Invariants checked after every fault run

ID	Invariant	How it is checked
I1	All nodes converge to the same state	Equal state hashes
I2	No acknowledged write is lost	Every acknowledged event id exists on every node
I3	No silent overwrite	Each concurrent disagreement is covered by a rule or a ledger entry
I4	Status never moves backwards without an operator	Compare final status with all writes
I5	Severity never decreases without an operator	Compare final severity with all writes
I6	Convergence time	Measured from heal to equal hashes (p50 and p95)

The headline figure is the **silent-overwrite rate**: in the benchmark of section 8, 42.2% of acknowledged edits vanished under last-writer-wins and none did in our engine. The baseline is our own implementation of item-level last-writer-wins, modelled on how DynamoDB Global Tables and Cosmos DB behave by default, not those products themselves. It replicates and converges correctly, and shares the engine's request validation, so the comparison is like for like.

Demo script (3 minutes)

1. Two regions show the same board. Create a report in Mumbai; it appears in Hyderabad and turns green.
2. Cut the link. The regions panel shows the break.
3. Edit the same report on both sides. Badges show "saved locally, at risk".
4. Restore the link. Banner changes from "out of sync" to "in sync".
5. Open the conflict ledger and show both versions and the policy.
6. Switch to side-by-side and show the baseline losing an edit.
7. Run the automated test and show it pass.

10. Plan from here

#	Task	Owner	Done when
1	Docker image and Compose for the three nodes	Engine / infra	**Done: smoke test passes against containers**
2	Connect baseline and dashboard to the engine	All	Dashboard drives the real cluster
3	Run the chaos benchmark on both clusters	Engine / infra	**Done: results file and charts produced**
4	Deploy three nodes to AWS regions	Engine / infra	**Done: partition and heal verified across regions**
5	Rehearse the demo twice, with a laptop-only fallback	All	Runs without venue Wi-Fi
6	Feature freeze, final report and slides	All	Submission ready

Stretch goals if time allows

- **Duplicate-report detection** (same place, time and type), filling the `possible_duplicates` field that is currently empty.
- **Signed node-to-node messages**, to show how the cybersecurity convergence from the brief would plug in.
- **Live updates** to the dashboard through server-sent events instead of polling.

11. Risks and limitations

Item	Mitigation or honest position
Data lost if a region is destroyed before syncing	Shown as *local* to operators; sync window about 0.5 s. Cannot be eliminated.
Integration of work from several people	Shared API contract, mock-first development, fixed integration checkpoints.
Cloud setup or venue network failure during the demo	Identical local cluster as a fallback.
Cost of running three cloud machines	Small instances, billing alarm already set, tagged resources and a one-command teardown.
Security is prototype-grade	Admin, sync and operator endpoints need a shared secret, but it travels over plain HTTP and anyone can create or read reports. HTTPS, per-user identity and signed messages are the production answer.
Not load tested	SQLite per node and three nodes only. The prototype proves behaviour under faults, not throughput.
The baseline is our model, not the products	It follows how DynamoDB Global Tables and Cosmos DB behave by default, but the real services were not benchmarked. The report says so wherever the numbers appear.
Tamper evidence is not tamper proofing	An administrator can still change a node's database. The change is detectable, but only by comparing against other replicas or an earlier head hash; the chain is not signed.
Google Cloud deployment not yet exercised	The script is written and checked for syntax; the mixed AWS and Google Cloud run is pending a Google Cloud project.
Urgent-first catch-up sync	Not built: it conflicts with the in-order rule that keeps conflict detection correct. We do not claim it.

12. Questions we expect, and our answers

Question	Answer
Why not just use DynamoDB Global Tables?	Its default mode resolves conflicts by latest timestamp, so an edit can vanish silently; its strong mode needs another region to confirm each write, which a cut-off region cannot get. We keep accepting writes and keep every version.
What if a region is destroyed?	Anything not yet synced is lost. We minimise that window, mark such reports as local, and say so openly.
Why not trust timestamps?	Devices in disaster zones often have wrong clocks, so we use causal information from version vectors and logical clocks.
Is this just a CRDT library?	No. We use similar convergence ideas but add disaster-specific rules, an operator ledger, durability status and a built-in verification harness.
How do you know it is correct?	Per-rule tests, random multi-node fault runs with invariants, and a comparison against a baseline.
Is your baseline fair?	It replicates and converges correctly and shares our request validation. It is our own implementation of item-level last-writer-wins, so we describe it as a model of how DynamoDB and Cosmos DB behave by default, not as those products.
What is new compared with a CRDT or AWS?	Disaster-specific merge rules with an operator ledger, per-report durability, a tamper-evident hash-chained history that replaces what AWS retired with QLDB, and a design with no managed service, so it runs across cloud providers.
Does it scale?	Not tested beyond three nodes and small data. The prototype proves the behaviour, not throughput.

Sources

- AWS: DynamoDB Global Tables — aws.amazon.com/dynamodb/global-tables
- AWS: Global tables overview (Prescriptive Guidance) — docs.aws.amazon.com/prescriptive-guidance/latest/dynamodb-global-tables/overview.html
- AWS News Blog: Multi-Region Strong Consistency in DynamoDB global tables
- AWS: Monitoring global tables (ReplicationLatency metric) — docs.aws.eu/amazondynamodb/latest/developerguide/globaltables_monitoring.html
- Amplify docs: DataStore conflict resolution — docs.amplify.aws/flutter/build-a-backend/more-features/datastore/conflict-resolution/
- Kleppmann, M. et al.: Automerge, real-time data sync between edge devices (MobiUK 2018)
- Kleppmann, M.: Local-first software — martin.kleppmann.com/2021/06/14/emergencity.html
- Jepsen: NATS 2.12.1 — jepsen.io/blog/2025-12-08-nats-2.12.1
- Jepsen: MariaDB Galera Cluster 12.1.2 — jepsen.io/blog/2026-03-16-mariadb-galera-cluster-12.1.2
- DZone: Conflict resolution using last-write-wins vs CRDTs
- InfoQ: AWS kills QLDB — infoq.com/news/2024/07/aws-kill-qldb (retired 31 July 2025)
- Microsoft Learn: Cosmos DB conflict types and resolution policies — learn.microsoft.com/en-us/azure/cosmos-db/conflict-resolution-policies
- Gigazine and Educative: analyses of the October 2025 AWS us-east-1 DynamoDB DNS outage (secondary sources)
- Pulse: multicloud database management — pulse.support/kb/multicloud-database-management

---

Technical claims about other products marked "general knowledge" were not re-verified during our research. Performance figures come from single runs measured from a laptop, on a local cluster and on three AWS regions as labelled.