

ELI V2.0 • REFERENCE

Commands & Installers

Every install path and every command in one place — copy-paste ready. This is the precise reference: the friendly walkthrough lives in the New User Install Guide; this is where you come to look up the exact flag.

Canonical version: 2.0.15 • **Best-tested:** Linux x86_64 + NVIDIA • **Author:** ShadowESC95

Windows, macOS and AMD are coded for and ship installers — expect rough edges off the daily-driver path. Run everything from inside the ELI folder unless noted.

1 • The one-click installer

The gentlest path. It does the whole job and opens ELI at the end. Safe to run more than once.

From a downloaded release (no git, no build)

Grab `ELI_v2-2.0.15-linux-portable.tar.gz` from [GitHub Releases](#), then:

```
tar -xzf ELI_v2-2.0.15-linux-portable.tar.gz
cd ELI_v2-2.0.15-linux-portable
chmod +x ELI_Setup.sh
./ELI_Setup.sh
```

`ELI_Setup.sh` runs the same 8-step setup as `scripts/eli_setup.sh`:

1. Welcome
2. Python check (needs Python 3.10+)
3. Python environment + dependencies (`install.sh --yes --auto-model`)
4. Starter model pack (GitHub asset restore, or a hardware-sized auto-download)
5. Local database
6. Memory embedder + voice models
7. App-menu icons (ELI v2.0, ELI Server, ELI Setup)
8. Opens the graphical setup wizard and launches ELI

From a git clone

```
git clone https://github.com/ShadowESC95/ELI_v2.0.git
cd ELI_v2.0
./scripts/eli_setup.sh
```

The absolute-easiest Linux path: the AppImage

```
chmod +x ELI_v2-2.0.15-x86_64.AppImage
./ELI_v2-2.0.15-x86_64.AppImage
```

First double-click installs ELI to `~/.local/share/ELI_v2` and runs setup once; every launch after opens ELI directly.

2 · Full install from source (developers)

Linux / macOS

```
git clone https://github.com/ShadowESC95/ELI_v2.0.git
cd ELI_v2.0
bash install.sh          # interactive: system report → plan → install → pick model
./scripts/eli_launch.sh # launch the desktop app
```

INSTALL.SH FLAGS (COMBINE AS NEEDED)

Flag	Effect
<code>--yes / -y</code>	No prompts — use detected defaults (CI / piped installs)
<code>--cpu-only</code>	Force the CPU build (ignore GPU)
<code>--gpu</code>	Force the GPU build even if none is auto-detected
<code>--install-cuda / --cuda</code>	Best-effort install the CUDA toolkit (nvcc), then rebuild llama-cpp with CUDA
<code>--auto-model</code>	Download one model sized to your VRAM after install
<code>--model=KEY</code>	Download a specific model (e.g. <code>--model=qwen2.5-7b</code>)
<code>--no-model</code>	Never download a model (also skips embedder/voice) — fully offline install
<code>--latest</code>	Use version ranges instead of the frozen reproducible lock
<code>--skip-torch</code>	Skip PyTorch (smaller install; disables self-training)

```
bash install.sh --yes --auto-model          # hands-off, with a model
bash install.sh --cpu-only --no-model        # minimal, no GPU, add a model later
bash install.sh --install-cuda --model=phi-4 # CUDA toolkit + a specific model
```

Windows

```
install.bat          :: normal — CUDA from the frozen lock + GPU verify
install.bat /cpu     :: CPU-only
install.bat /cuda    :: also auto-install the CUDA toolkit (winget) if missing
install.bat /latest  :: version ranges instead of the frozen lock
```

Or call PowerShell directly, then launch with `eli.bat` :

```
powershell -ExecutionPolicy Bypass -File install.ps1 [-CpuOnly] [-Gpu] `
  [-InstallCuda] [-Yes] [-AutoModel] [-NoModel] [-Model qwen2.5-7b] [-Latest]
```

Developer editable install (pip)

```
python3 -m venv .venv && . .venv/bin/activate
python -m pip install --upgrade pip setuptools wheel
python -m pip install -e ".[full]"
python -m eli                # GUI
python -m eli --headless     # terminal REPL
```

Android / Termux (headless — server + CLI, no GUI)

```
bash scripts/install_android.sh
```

3 • Launching ELI

```
./scripts/eli_launch.sh          # desktop app (GUI) – default
./scripts/eli_launch.sh gui      # same, explicit
./scripts/eli_launch.sh serve    # API + web-app server (this machine only)
./scripts/eli_launch.sh serve --lan # server exposed to your home network
./scripts/eli_launch.sh both --lan # server in background + desktop app
./eli.sh                         # shortcut for the desktop app
.venv/bin/python -m eli          # desktop app via module
.venv/bin/python -m eli --headless # text-only terminal REPL
```

Headless slash commands: `/status` • `/mode` • `/reset` • `/help` • `/quit`

THE WEB / PHONE SERVER DIRECTLY

```
./scripts/eli_serve.sh          # 127.0.0.1 only → http://127.0.0.1:8081/
./scripts/eli_serve.sh --lan     # home network → prints token URL + QR
./scripts/eli_serve.sh --lan --https # + HTTPS on :8443 (phone microphone)
./scripts/eli_serve.sh --port 9000 # custom port
./scripts/eli_serve.sh --lan --token MYSECRET # specific access token
```

4 • Models

```
.venv/bin/python -m eli.core.model_download --list # show the catalog
.venv/bin/python -m eli.core.model_download --auto # one best-fit for your VRAM
.venv/bin/python -m eli.core.model_download --choose # multi-select menu
.venv/bin/python -m eli.core.model_download --aux # just the memory embedder (~85 MB)
```

Bring your own: drop any chat/instruct `.gguf` into `models/` — ELI finds it and fits it to your hardware. Vision models also need their matching `mmproj` GGUF alongside.

VOICE WEIGHTS (IF NOT FETCHED DURING INSTALL)

```
.venv/bin/python -m eli.runtime.voice_assets
```

RESTORE THE MODEL/VOICE PACK FROM GITHUB (TAG LOCAL-ASSETS-V2.1, NEEDS GH)

```
gh auth login
./RUN_ELI.sh --with-github-assets
# or, without gh, after downloading assets manually:
python3 scripts/restore_github_asset_files.py --from-dir /path/to/assets
```

5 • Alternative & advanced paths

Path	Command	When
One-click run (portable)	<code>./RUN_ELI.sh</code>	Daily launch of a portable install
Classic portable install	<code>./INSTALL_ELI.sh</code> → <code>./RUN_ELI.sh</code>	Manual two-step
Safe Linux install	<code>bash scripts/safe_install_linux.sh</code>	Conservative, extra checks
Add the <code>eli</code> command	<code>bash scripts/install_eli_command.sh</code>	Get <code>eli</code> on <code>\$PATH</code>
App-menu icons only	<code>bash scripts/install_desktop_apps.sh</code>	Re-add launchers
Repo venv runner	<code>bash scripts/run_eli_repo_venv.sh</code>	Run against the repo's <code>.venv</code>
Purge a legacy install	<code>bash scripts/purge_legacy_eli.sh</code>	Clean an older ELI first

If your shell cached an old `eli` command after reinstalling: `hash -r`.

6 • Building release packages (maintainer)

```
bash scripts/build_v2_release.sh           # portable Linux tar.gz
bash scripts/build_v2_release.sh --with-assets # + bundled models (very large)
bash scripts/build_grandma_release.sh       # portable tar.gz + AppImage + checksums
bash packaging/linux/build-appimage.sh      # AppImage only
bash scripts/package_eli_release.sh         # wheel + sdist
SKIP_TESTS=1 bash build_packages.sh wheel appimage windows-lean # pick targets
```

Cross-platform builds

The Windows `Setup.exe` needs Inno Setup 6 on a Windows PC (`build-windows.ps1 -Version 2.0.15`); a signed macOS `.dmg` must be built on a Mac. The Linux portable, Applmage and Windows portable zip all build on Linux. Big model/voice binaries ship separately as Release assets (over Git's 100 MB blob limit). Full publish steps: `RELEASE.md` .

7 • Health checks & maintenance

```
bash run_tests.sh           # run the test suite
bash eli_diagnose.sh        # system diagnosis report
.venv/bin/python -m eli.tools.mic_diag # microphone diagnostics
.venv/bin/python -m eli.core.init_data # (re)build the local databases
```

From inside ELI you can also say "run a full runtime audit", "run the tests and tell me what to fix", or "upgrade yourself".

8 • Uninstall

ELI lives entirely inside its own folder — nothing spreads across your system:

```
rm -rf /path/to/ELI_v2.0
```

For an Applmage install, also remove `~/ .local/share/ELI_v2` . If you added app-menu icons, delete the `.desktop` files from `~/ .local/share/applications/` .

ELI v2.0 — source-available under the PolyForm Internal Use License 1.0.0. Contact: jaybridgeman0095@gmail.com • Issues: github.com/ShadowESC95/ELI_v2.0/issues