

# ELI — Commands and Installers

ELI v2.1.34

July 2026

## Contents

|                                                       |          |
|-------------------------------------------------------|----------|
| <b>ELI v2.0 — Commands &amp; Installers Reference</b> | <b>1</b> |
| 1. The one-click installer (recommended for everyone) | 1        |
| 2. Full install from source (developers)              | 2        |
| 3. Launching ELI                                      | 3        |
| 4. Models                                             | 3        |
| 5. Alternative & advanced install paths               | 4        |
| 6. Building release packages (maintainer)             | 4        |
| 7. Health checks & maintenance                        | 5        |
| 8. Uninstall                                          | 5        |

## ELI v2.0 — Commands & Installers Reference

**Updated for v2.1.30 (July 2026).** The primary way to install ELI is now the **prebuilt installers on GitHub Releases** — `ELI-Setup-<v>.exe` (Windows), the `.dmg` (macOS, Apple Silicon), the `.AppImage` (Linux). The Linux AppImage and Windows installer are built and launch-tested in CI; the macOS `.dmg` is built on a Mac and provided best-effort (not verified in CI). First launch offers GPU acceleration (NVIDIA CUDA / AMD Vulkan; Apple Metal is built in) and a starter model sized to your hardware. Data lives in a per-user `ELI_v2` folder and survives upgrades; `--fresh-start` resets it. Everything below remains valid for **source installs** (clone + `install.sh`) and the classic portable tarball.

*Every install path and command in one place. Copy-paste ready. Run everything from inside the ELI folder unless noted.*

Canonical version: **2.1.23**. Best-tested platform: **Linux x86\_64 + NVIDIA**. Windows, macOS, and AMD are coded for and ship installers, but expect rough edges.

---

### 1. The one-click installer (recommended for everyone)

This is the gentlest path — it does the whole job and opens ELI at the end. Safe to run more than once.

#### From a downloaded release (no git, no build)

Get `ELI_v2-2.1.30-linux-portable.tar.gz` from [GitHub Releases](#), then:

```
tar -xzf ELI_v2-2.1.30-linux-portable.tar.gz
cd ELI_v2-2.1.30-linux-portable
chmod +x ELI_Setup.sh
./ELI_Setup.sh
```

ELI\_Setup.sh runs the same 8-step one-click setup as scripts/eli\_setup.sh:

1. Welcome
2. Python check (needs Python 3.10+)
3. Python environment + dependencies (install.sh --yes --auto-model)
4. Starter model pack (GitHub asset restore, or a hardware-sized auto-download)
5. Local database
6. Memory embedder + voice models
7. App-menu icons (ELI v2.0, ELI Server, ELI Setup)
8. Opens the graphical setup wizard and launches ELI

### From a git clone

```
git clone https://github.com/ShadowESC95/ELI_v2.0.git
cd ELI_v2.0
./scripts/eli_setup.sh
```

### The absolute-easiest Linux path: the AppImage

Get ELI\_v2-2.1.30-x86\_64.AppImage from Releases:

```
chmod +x ELI_v2-2.1.30-x86_64.AppImage
./ELI_v2-2.1.30-x86_64.AppImage
```

First double-click installs ELI to ~/.local/share/ELI\_v2 and runs setup once; every launch after that opens ELI directly.

---

## 2. Full install from source (developers)

### Linux / macOS

```
git clone https://github.com/ShadowESC95/ELI_v2.0.git
cd ELI_v2.0
bash install.sh           # interactive: system report → plan → install → pick model
./scripts/eli_launch.sh   # launch the desktop app
```

**install.sh flags** (combine as needed):

| Flag                    | Effect                                                                        |
|-------------------------|-------------------------------------------------------------------------------|
| --yes / -y              | No prompts — use detected defaults (CI / piped installs)                      |
| --cpu-only              | Force the CPU build (ignore GPU)                                              |
| --gpu                   | Force the GPU build even if none is auto-detected                             |
| --install-cuda / --cuda | Best-effort install the CUDA toolkit (nvcc), then rebuild llama-cpp with CUDA |
| --auto-model            | Download one model sized to your VRAM after install                           |
| --model=KEY             | Download a specific model<br>(e.g. --model=qwen2.5-7b)                        |
| --no-model              | Never download a model (also skips embedder/voice) — fully offline install    |
| --latest                | Use version ranges instead of the frozen reproducible lock                    |
| --skip-torch            | Skip PyTorch (smaller install; disables self-training)                        |

## Examples:

```
bash install.sh --yes --auto-model           # hands-off, with a model
bash install.sh --cpu-only --no-model        # minimal, no GPU, add a model later
bash install.sh --install-cuda --model=phi-4 # CUDA toolkit + a specific model
```

## Windows

```
install.bat           :: normal – CUDA install from the frozen lock + GPU verify
install.bat /cpu      :: CPU-only
install.bat /cuda     :: also auto-install the CUDA toolkit (winget) if missing
install.bat /latest   :: version ranges instead of the frozen lock
```

Or call the PowerShell installer directly:

```
powershell -ExecutionPolicy Bypass -File install.ps1 [-CpuOnly] [-Gpu] `
  [-InstallCuda] [-Yes] [-AutoModel] [-NoModel] [-Model qwen2.5-7b] [-Latest]
```

Launch with eli.bat.

## Developer editable install (pip)

```
python3 -m venv .venv && . .venv/bin/activate
python -m pip install --upgrade pip setuptools wheel
python -m pip install -e ".[full]"
python -m eli                # GUI
python -m eli --headless     # terminal REPL
```

## Android / Termux (headless — server + CLI, no GUI)

```
bash scripts/install_android.sh
```

---

## 3. Launching ELI

```
./scripts/eli_launch.sh           # desktop app (GUI) – default
./scripts/eli_launch.sh gui       # same, explicit
./scripts/eli_launch.sh serve     # API + web-app server (this machine only)
./scripts/eli_launch.sh serve --lan # server exposed to your home network
./scripts/eli_launch.sh both --lan # server in background + desktop app
./eli.sh                          # shortcut for the desktop app
.venv/bin/python -m eli           # desktop app via module
.venv/bin/python -m eli --headless # text-only terminal REPL
```

**Headless slash commands:** /status · /mode · /reset · /help · /quit

### The web / phone server directly:

```
./scripts/eli_serve.sh           # 127.0.0.1 only → http://127.0.0.1:8081/
./scripts/eli_serve.sh --lan     # home network → prints a token-protected URL + QR
./scripts/eli_serve.sh --port 9000 # custom port
./scripts/eli_serve.sh --lan --token MYSECRET # use a specific access token
```

---

## 4. Models

```
.venv/bin/python -m eli.core.model_download --list # show the catalog
.venv/bin/python -m eli.core.model_download --auto # one best-fit for your VRAM
```

```
.venv/bin/python -m eli.core.model_download --choose # multi-select menu (pick any number)
.venv/bin/python -m eli.core.model_download --aux # just the memory embedder (~85 MB)
```

Bring your own: drop any chat/instruct .gguf into models/ — ELI finds it and fits it to your hardware. Vision models also need their matching mmpoj GGUF alongside.

**Voice weights** (if not fetched during install):

```
.venv/bin/python -m eli.runtime.voice_assets
```

**Restore the model/voice pack from GitHub** (tag local-assets-v2.1, needs gh):

```
gh auth login
./RUN_ELI.sh --with-github-assets
# or, without gh, after downloading assets manually:
python3 scripts/restore_github_asset_files.py --from-dir /path/to/downloaded/assets
```

## 5. Alternative & advanced install paths

| Path                         | Command                                 | When to use                                   |
|------------------------------|-----------------------------------------|-----------------------------------------------|
| One-click run (portable)     | ./RUN_ELI.sh                            | Daily launch of a portable install            |
| Classic portable install     | ./INSTALL_ELI.sh then<br>./RUN_ELI.sh   | Portable package, manual two-step             |
| Safe Linux install           | bash<br>scripts/safe_install_linux.sh   | Conservative install with extra checks        |
| Add the eli terminal command | bash<br>scripts/install_eli_command.sh  | Get eli on your \$PATH (~/.local/bin/eli)     |
| Install app-menu icons only  | bash<br>scripts/install_desktop_apps.sh | Re-add ELI / ELI Server / ELI Setup launchers |
| Repo venv runner             | bash<br>scripts/run_eli_repo_venv.sh    | Run against the repo's own .venv              |
| Purge a legacy install       | bash<br>scripts/purge_legacy_eli.sh     | Clean up an older ELI before reinstalling     |

If your shell cached an old eli command after reinstalling: hash -r.

## 6. Building release packages (maintainer)

```
bash scripts/build_v2_release.sh # portable Linux tar.gz
bash scripts/build_v2_release.sh --with-assets # + bundled models (very large)
bash scripts/build_grandma_release.sh # portable tar.gz + AppImage + checksums
bash packaging/linux/build-appimage.sh # AppImage only (from the portable build)
bash scripts/package_eli_release.sh # wheel + sdist
bash build_packages.sh wheel appimage windows-lean # pick targets
```

**Windows Setup.exe** (run on a Windows PC with Inno Setup 6):

```
bash build_packages.sh windows-lean
powershell -ExecutionPolicy Bypass -File packaging/windows/build-windows.ps1 -Version 2.1.23
```

A signed/notarized macOS .dmg must be built on a Mac. Large model/voice binaries ship separately as GitHub Release assets (over Git's 100 MB blob limit). Full publish steps: [RELEASE.md](#).

## 7. Health checks & maintenance

```
bash run_tests.sh           # run the test suite
bash eli_diagnose.sh        # system diagnosis report
.venv/bin/python -m eli.tools.mic_diag # microphone diagnostics (voice input)
.venv/bin/python -m eli.core.init_data # (re)build the local databases
```

---

## 8. Uninstall

ELI lives entirely inside its own folder — nothing spreads across your system:

```
rm -rf /path/to/ELI_v2.0
```

For an AppImage install, also remove `~/.local/share/ELI_v2`. If you added app-menu icons, delete the .desktop files from `~/.local/share/applications/`.

---

*ELI v2.0 — © 2026 Jason Fitzgibbon Bridgeman. Source-available under the PolyForm Internal Use License 1.0.0. Questions: [jaybridgeman0095@gmail.com](mailto:jaybridgeman0095@gmail.com)*