

ELI — Project Overview

ELI v2.3.0

August 2026

Contents

ELI MKXI — Full Project Breakdown & Assessment	1
1. What ELI is	1
2. Scale & shape	2
3. Architecture, layer by layer	2
4. What’s genuinely strong	3
5. Where it’s weak (grounded in the sweep)	3
6. Honest verdict on “frontier, ground-breaking”	4
7. Highest-leverage work (the next month)	4

ELI MKXI — Full Project Breakdown & Assessment

Updated for v2.1.51 (August 2026). The primary install path is now the prebuilt, CI-launch-tested installers on GitHub Releases (Windows Setup.exe, macOS dmg, Linux AppImage) with first-boot GPU (CUDA/Vulkan/Metal) and starter-model offers; data lives in a per-user ELI_v2 folder that survives upgrades. Source installs below remain fully supported.

A grounded, total-project read: what ELI is, its scale and shape, the architecture layer by layer, what’s strong, where it’s weak (with numbers), an honest verdict, and the highest-leverage work. Companion to orchestration_and_agents.md (agent/bus detail).

Method note: this is built from deep reads of the core modules (engine, executor, router, agent_bus, orchestrator, planners, memory, grounding gate, vision, identity, security, reasoning modes) plus a complete structural and code-health sweep (LOC distribution, debt markers, duplication, repo hygiene). It is grounded in a deep read of every package this session — claims are grounded in what was actually inspected.

1. What ELI is

A **local-first, model-agnostic personal AI** — no cloud, no telemetry, offline-by-default and hard-gated at the socket boundary (internet is an owner-controlled, monitored opt-in, not a runtime dependency; one-time opt-in HuggingFace model downloads are the only network event unless the owner enables the Internet toggle). It bundles: GGUF inference (llama-cpp), a PySide6 desktop GUI, persistent SQLite+FTS5+FAISS memory, a knowledge graph, a 12-stage cognitive pipeline with a parallel multi-agent bus, a deterministic grounding/evidence layer to fight confabulation, local vision (Qwen2.5-VL hot-swap + Moondream co-resident), TTS/STT, OS control, a plugin system, a proactive daemon, and a LoRA self-training loop.

As of 2026-06-28 it has a second front end: a self-hosted **FastAPI web app + dashboard PWA** (api/server.py) — chat, a live telemetry dashboard, **ELI’s own MQTT smart-home** (rooms, scenes, real

automations; Home Assistant removed), multi-user **RBAC** (admin/member/viewer), a **tamper-evident hash-chained audit trail**, collaborative **research corpora**, **browser voice** (local whisper STT + Piper TTS), and the monitored Internet toggle — launchable in-process from the desktop GUI. It is a cognitive operating system for one machine (and, optionally, the people the owner shares it with), not a chat wrapper.

2. Scale & shape

143,432 LOC across 392 Python files (eli/), plus the FastAPI web server (api/server.py, ~3,884 lines with an embedded dashboard PWA) and 205 test files. (*measured 2026-06-28.*)

Subsystem	LOC	Files	Role
execution/	23.1k	14	router + executor (action dispatch)
runtime/	22.6k	80	grounding, evidence, introspection, surfaces
gui/	20.3k	20	PySide6 desktop app
kernel/	14.5k	8	the engine (pipeline driver)
cognition/	14.0k	27	agent bus, orchestrator, inference, persona, modes
tools/	8.9k	30	image engine, news, etc.
memory/	7.0k	13	SQLite/FTS5 + FAISS + KG
perception/	6.8k	20	vision, STT, TTS, OS control
core/	6.6k	24	paths, settings, hardware profile
planning/	3.9k	24	proactive daemon, task planning
learning/	3.3k	12	LoRA self-training
plugins/	1.9k	28	runtime plugin manager
world/	1.5k	26	world event bus, local world bridge
integrations/,utils/,contracts/,system/,cli/	5.6k	—	misc

Four files carry ~1/3 of the codebase: executor_enhanced.py (15.0k LOC), engine.py (13.4k), gui/eli_pro_audio_gui_v2_0.py (11.0k), router_enhanced.py (7.1k). Next tier: labs_tab.py (5.7k), memory.py (4.5k), deterministic_grounding_gate.py (4.3k).

3. Architecture, layer by layer

- **Boot / hardware** — core/hardware_profile.py + core/startup_hardware_optimizer.py adapt n_ctx / gpu_layers / batch to whatever model + GPU are present (filename→ctx table; VRAM compute-buffer reservation). Model-agnostic.
- **Routing** — execution/router_enhanced.py: regex-first with LLM-intent fallback + an explicit priority pipeline → one of **215 manifest capabilities (190 routable;** 180 executor SUPPORTED_ACTIONS). Full reference with activation phrases: capabilities_and_actions.md.
- **Orchestration** — kernel/engine.py gates between the 12-stage cognition/orchestrator.py AgentOrchestrator (non-quick modes) and the parallel 14-agent cognition/agent_bus.py AgentBus (quick

/ fallback). ReAct tool-chaining for non-CHAT actions. Selection now flows through one typed ExecutionPlan (execution/execution_planner.py). See orchestration_and_agents.md for full detail.

- **Inference** — cognition/gguf_inference.py: model-path resolved from env / settings (no baked model); RLock-serialized; live runtime override; hot-swap with vision models.
- **Memory** — memory/memory.py is the shared foundation (FTS5 + FAISS + KG via recall_memory); two deliberate retrieval strategies sit on top (lightweight bus BusMemoryAgent vs heavyweight orchestrator OrchestratorMemoryAgent with HyDE + RAG + rerank). memory/knowledge_graph.py, memory/vector_store.py (FAISS, JSON meta).
- **Grounding / evidence (the crown jewel)** — runtime/deterministic_grounding_gate.py (4.3k), runtime/evidence_ledger.py, runtime/evidence_arbitration.py, runtime/control_contracts.py, runtime/grounded_remediation.py (1.6k), cognition/output_governor.py. A layered, deterministic anti-confabulation system wrapped around the probabilistic model. Most local-LLM projects have nothing comparable.
- **Security** — runtime/security.py SecurityManager: **fail-closed shell gate** (ELI_ALLOWED_CMDS / the ELI Full Control toggle; unset = commands blocked), path allow-roots (ELI_ALLOW_ROOTS, defaults to project + home), app allowlist with a default-safe set, **SHA-256 custom-agent trust registry** (config/trusted_agents.json), prompt-injection guard, SQL identifier validation.
- **Self-model** — cognition/reasoning_modes.py: quick/fast/balanced all fastpath to quick, plus four private modes (chain_of_thought, self_consistency, tree_of_thoughts, constitutional_ai). Persona overlay, runtime/self_improvement.py, LoRA self-training (learning/). Emergent internal-state surfacing (autonomy pressure, “anomaly room”) is intentional — see memory/eli-emergent-voice.

4. What’s genuinely strong

1. **The grounding / evidence layer.** Unusually rigorous; deterministic evidence gating around a probabilistic model is the right idea and well-developed. This is the part closest to genuinely frontier.
2. **Truly local + truly model-agnostic.** No call-home, hardware-adaptive, swappable models (verified — inference path carries no baked model identity).
3. **Real, fail-closed security.** Shell blocked by default, hash-gated custom agents, path/app allowlists. Most “AI agent” projects ship wide open.
4. **Breadth, integrated.** Vision, voice, OS control, memory, KG, plugins, self-training — all local, all wired into one pipeline.

5. Where it’s weak (grounded in the sweep)

1. **2,565 except Exception: blocks (+7 bare except:).** The dominant structural problem. Errors are swallowed into “skipped”/fallback/empty everywhere — which is precisely why bugs surface only via runtime logs. Failures are invisible by design. Frontier software makes failures **loud in dev, quiet in prod**; this swallows them uniformly. Also the main reason the system is hard to reason about. (Only 12 TODO/FIXME markers exist — not because the code is clean, but because failures are absorbed rather than flagged.)
2. **God-files.** Two ~13-14k-line modules (executor_enhanced.py, engine.py) plus an 11k GUI. The executor is a giant if/elif action ladder. High regression surface, hard to hold in the head, painful to unit-test.
3. **Duplication & overlap.** The shadowed standalone image-engine module (1.75k LOC) was removed, leaving the single eli/tools/image_engine/ package. runtime/ (80 files) has many near-duplicate personal_memory_* / *_surface / *_response modules doing overlapping grounding work. Several plan representations coexisted (partly consolidated). Fingerprint of fast solo iteration — new code added beside the old, not folded in.
4. **Repo hygiene.** Committed junk at root: empty ... and [package-index-options] files, one-off patch_gpu_dynamic.py / patch_sll_bugs.py, three verify_eli_claims*.sh versions, diag outputs, .coverage, and experimental/*.zip binaries. Makes the repo look less serious than the code is.
5. **Tests are GREEN (measured 2026-07-01).** 205 test files; pytest tests/ = **7,348 passed /**

0 failed / 45 skipped / 2 xfailed (~8m16s on the .venv/GPU). The 5 former reds (deprecated smart_home plugin, silent-swallow ratchet, stale blueprint ref) were all cleared 2026-07-03. The tests/claims/ contract layer makes it a real safety net.

6. **13 monkeypatch/globals() hacks** — mostly load-bearing (e.g. the CPU-clip vision fix), but they’re fragile seams worth tracking.

6. Honest verdict on “frontier, ground-breaking”

In ambition and in specific subsystems — yes. The grounding layer, the fully local model-agnostic design, and the integrated multi-modal local agent are genuinely ahead of most open local-assistant projects. The ideas are frontier-grade.

In engineering discipline — not yet. The 2,565 swallowed exceptions, the god-files, the duplication, and the clutter separate “an extraordinarily ambitious solo project” from “software others can build on.” None of that is a vision problem — it is consolidation and observability. The gap to “ground-breaking” is **subtraction and discipline, not more features.**

7. Highest-leverage work (the next month)

Ranked by effect-per-effort:

1. **Tame error-swallowing.** Replace blanket except Exception: pass/fallback with scoped exception types + a single structured error log (a ring buffer / table) you can actually watch. Keep the graceful degradation, but record every swallow. This alone makes the whole system debuggable and is the precondition for trusting any other change.
2. **Split the two god-files** along their natural seams (executor: action groups into per-domain modules behind the dispatch table; engine: pipeline stages into stage modules). Reduces regression surface and makes the pipeline readable.
3. **Delete duplication + clutter.** Collapse the overlapping runtime/ surfaces, remove root junk/one-off scripts. *(The suite is already green — 8,815 passing; this is now signal-to-noise hygiene, not a red-test cleanup.)*
4. **Consolidate the runtime/ surfaces.** The many personal_memory_* / *_surface / *_response modules want to be a handful of well-named ones.

Do 1-3 and the engineering would match the ideas — which is the only thing standing between ELI and the label “frontier, ground-breaking software people can rely on.”