

# ELI — Dag Orchestrator

ELI v2.1.97

August 2026

## Contents

|                                                                      |          |
|----------------------------------------------------------------------|----------|
| <b>DAG orchestrator — project-wide execution engine (2026-06-07)</b> | <b>1</b> |
| The orchestrator (eli/core/dag.py) . . . . .                         | 1        |
| Wired through the pipeline . . . . .                                 | 2        |
| Tests . . . . .                                                      | 2        |
| Test/project run → review (GUI + chat) . . . . .                     | 2        |
| Generative actions on the coding agent / planner DAG . . . . .       | 2        |
| SELF_IMPROVE routed through the coding agent . . . . .               | 2        |
| Multi-command + timed commands (2026-06-08) . . . . .                | 3        |

## DAG orchestrator — project-wide execution engine (2026-06-07)

eli/core/dag.py was a pure **scheduling** primitive (Kahn topological order, parallel layers, cycle detection, ancestors/descendants, critical-path). It was elevated into a full **execution orchestrator** and wired through the pipeline — additively, so every existing class/function and caller is unchanged.

### The orchestrator (eli/core/dag.py)

Orchestrator / run\_graph(tasks) execute a set of Tasks on their dependency DAG:

- **Parallel intra-layer execution** — independent nodes in a topological layer run concurrently (threads); max\_workers=1 ⇒ deterministic sequential.
- **Dependency result-passing** — each node fn gets a NodeContext with results (completed upstream outputs) + a shared mutable shared bag.
- **Conditional nodes** — when(ctx) -> bool skips a branch dynamically.
- **Retries + backoff** — per-node retries with exponential retry\_backoff.
- **Fallback** — a fallback fn runs if all attempts fail.
- **Per-node timeout** — total node budget (best-effort; enforced via a worker future).
- **Memoisation** — pluggable cache keyed by cache\_key (status cached).
- **Priority scheduling** — higher-priority nodes first within a ready layer.
- **Fail-fast + global time budget** — stop scheduling after a failure / budget.
- **Auto-skip** — a node whose upstream didn't complete is skipped with a reason.
- **critical semantics** — a non-critical node's failure doesn't fail the run.
- **Deterministic RunReport** — per-node status/attempts/timing + order + layers + critical path + failed/skipped lists + to\_dict() for observability.

Pure stdlib; the orchestrator does no LLM/IO — the node callables do.

## Wired through the pipeline

- **Agents (cognition):** the agent bus runs the 15 agents on the orchestrator (`_run_agents_orchestrated`, default `ELI_AGENT_ORCHESTRATOR=1`, falls back to the layered then flat paths). Dependency-ordered, intra-layer parallel, per-agent timeouts (mode + model-tier scaled), upstream results passed downstream, and a `RunReport` captured per dispatch. Behaviour-preserving: agent fns never raise out (errors → `ok=False`), so edges only order + pass upstream, never gate.
- **Router → executor (observability):** `ORCHESTRATION_STATUS` action (“orchestration status” / “show your agent dag”) returns the live engine, execution layers, dependencies, critical path, and last-run telemetry — so ELI can explain its own orchestration honestly.
- **Evidence gathering:** `evidence_planner.gather()` now runs its channels (code / web / memory / runtime) **in parallel on the orchestrator** — each channel isolated (non-critical: one failing yields no evidence, never blocks others), results merged in deterministic `KNOWN_CHANNELS` order, with a sequential fallback. `memory/runtime` (no model calls) genuinely overlap; model-using channels serialise safely on the global `_LLM_CALL_LOCK`.
- **report\_pipeline — deliberately NOT parallelised.** All model calls serialise on `_LLM_CALL_LOCK`, so parallel section drafting gives zero speedup (model-bound + globally locked) while adding risk. It stays sequential with its own retries.
- **GUI:** a read-only **Orchestration** sub-tab in Labs (and the `ORCHESTRATION_STATUS` chat action) surface the live layers/deps/critical-path + the last dispatch’s per-node `RunReport`.
- Also on the DAG: the coding planner (`coding/plan_graph.py`) and the LoRA pipeline.

## Tests

`tests/test_dag_orchestrator.py` (14) cover every feature; existing dag/coding/agent tests + the full suite stay green. Flags: `ELI_AGENT_ORCHESTRATOR`, `ELI_AGENT_DAG`.

## Test/project run → review (GUI + chat)

`eli/runtime/test_review.py::run_and_review()` runs the suite (or a subset), **backs up the prior report, writes a timestamped errors file** capturing failing tests (possible errors) under `artifacts/test_reports/`, and returns a **results-driven options menu** (each option carries a chat command routing to examine/propose/ generate/eval). Surfaced two ways: - **GUI:** a “Test & Review” Labs sub-tab — run the full suite in the background, see totals + failures + backup/error paths, get **ELI’s natural-language summary**, and click result-driven option buttons that hand off to ELI in chat. - **Chat:** the `TEST_REVIEW` action (“test review” / “run the tests and tell me what to fix”) returns the grounded report (LLM-summarised) + the options menu. - **Option buttons stream into the main chat** (`MainWindow.send_to_chat`) — clicking an option continues the conversation in the Chat tab, not the panel.

## Generative actions on the coding agent / planner DAG

- **GENERATE\_PROJECT** → `CodeAgent.solve(use_dag=True)`: decompose into a subtask DAG (`plan_graph` over `eli/core/dag`), solve nodes in order, **VERIFY** the composed module; saves to `artifacts/projects/`. Single-pass chat fallback (`ELI_PROJECT_DAG=0`).
- **GENERATE\_SCRIPT / CREATE\_SCRIPT / WRITE\_SCRIPT** → already routed through the verified coding agent (`plan` → DAG/tree-search → execute → repair → bug-memory).

## SELF\_IMPROVE routed through the coding agent

`SelfImprovementEngine.propose_via_agent()` (mode propose, or auto-detected from “propose/verified fix/fix the failing”) turns each recent failure into a coding task and runs the **CodeAgent** (decompose→solve→**verify** via tree-search + execution gate) over them **in parallel on run\_graph**, returning **verified, propose-only** fixes (gated; nothing applied until “apply self-improvement patch”). This is the delegation pattern realised: `SELF_IMPROVE` composes the existing coding agent + orchestrator rather than reinventing repair. The Test & Review “Propose verified fixes” option routes here.

Artifact-dir resolution is now consistent — `run_test_report.py` and the `confest` report hook both honour `ELI_ARTIFACTS_DIR` (no real-folder pollution in tests).

## Multi-command + timed commands (2026-06-08)

- **Multi-command chaining** (`eli/runtime/command_splitter.py` + router `multi_command_prepass` → `MULTI_COMMAND`): one utterance chaining imperative commands is split (the “plan”), then the executor routes & runs each segment in order and combines results — the planning step that lets the agents/executor handle several actions from one sentence. Sequential today; `run_graph` is ready for parallel fan-out of independent (“and”-joined) commands.
- **Timed commands** → background workers: any imperative + a future time defers to the durable scheduler (see `runtime_planning_world.md`).