

ELI — Orchestration And Agents

ELI v2.1.97

August 2026

Contents

ELI Orchestration & Agents — Full Topology	1
Two agent stacks (this is the key thing to understand)	1
Planning artifacts — 4 of them, only 1 drives execution	2
Where it is actually weak (corrected)	3
Recommended fixes (prioritized)	3
Update — 2026-06-09	4

ELI Orchestration & Agents — Full Topology

Supersedes the earlier `agent_bus.md`, which only documented the parallel specialist bus and missed the real `AgentOrchestrator`. Read-only reference; nothing here changes behaviour.

Source files: - `eli/cognition/orchestrator.py` — the real orchestrator (12-stage pipeline) - `eli/cognition/agent_bus.py` — the parallel 14-specialist bus - `eli/kernel/engine.py` — wiring / dispatch gate - `eli/execution/execution_planner.py` — declarative plan model (UNUSED) - `eli/planning/task_planner.py` — planner shim (stub)

Two agent stacks (this is the key thing to understand)

ELI does **not** have one agent system. It has two, selected by reasoning mode and action type:

1. `AgentOrchestrator` — the real orchestrator (`orchestrator.py`)

The 12-stage cognitive pipeline. The engine calls it via `_run_internal_orchestrator` (`engine.py`:7265, 8982). Components:

- **PlannerAgent.plan_retrieval()** (`orchestrator.py`:53) — produces a **mode-aware retrieval plan**:
 - fast: keyword only, no FAISS/RAG, KG only if identity, 1 ReAct iter, skip HyDE
 - balanced (default): keyword + semantic + KG, RAG if doc query, 3 ReAct iters
 - deep: everything, large budgets, full HyDE, 3 ReAct iters
- **OrchestratorMemoryAgent** (`orchestrator.py`:131) — performs the retrieval: HyDE expansion → keyword/FTS5 + FAISS semantic + document RAG + KG → `hybrid_merge` → `rerank`. **Sequential** by design — the `llama_cpp` embedder is not thread-safe and segfaults under concurrent daemon-thread calls.
- **ExecutorAgent** (`orchestrator.py`:119) — thin wrapper over `executor_enhanced.execute`.

Flow inside `AgentOrchestrator.run()`: - **Non-CHAT actions** (`orchestrator.py`:539-740): dispatches the **AgentBus** for specialist evidence (line 561), then runs a **ReAct observation loop** (598-644): runs the executor, asks the loaded LLM ANSWER or TOOL: <action> <args>, and **chains to the next tool**, accumulating observations. 1 iter in fast mode, up to 3 otherwise. For “grounded synthesis” actions the observations are assembled into context and passed to the LLM; for direct actions the executor result is returned as-is. - **CHAT** (`orchestrator.py`:742-897): Stage 3 HyDE → Stage 4 planner → Stage 5/6/7 retrieval →

Stage 8 merge → Stage 9 rerank → Stage 10 context assembly → Stage 10.5 persona handoff → Stage 11 generation. Private reasoning modes (chain_of_thought, self_consistency, tree_of_thoughts, constitutional_ai) hand off to engine._run_chat_reasoning_loop so the mode-specific algorithm runs. **Note: the AgentBus is NOT called on the CHAT path** — the orchestrator uses its own OrchestratorMemoryAgent retrieval instead.

2. AgentBus — the parallel 14-specialist fan-out (agent_bus.py)

15 agents in _ALL_AGENTS (agent_bus.py:3071), each a _BaseAgent subclass with name + timeout_s:

#	name	timeout_s	accesses
1	memory	5.0	SQLite + FTS5 + FAISS; self-gates (_eli_memory_should_run)
2	system	8.0	direct action execution (SYSTEM_ACTIONS)
3	habit	3.0	user_patterns / habit tables
4	self_improvement	3.0	LoRA / self-tuning introspection
5	proactive	3.0	suggestion / anticipation
6	frontier	5.0	frontier / awareness model
7	plugin	6.0	plugin registry (PLUGIN_ACTIONS)
8	capability	6.0	capability manifest
9	voice	5.0	TTS / voice subsystem
10	orchestrator	3.0	bus-level planner — emits a plan dict only
11	file_code	4.0	source tree / code introspection
12	reflection	4.0	reflection log / insights
13	introspection	4.0	runtime / cognition self-inspection
14	knowledge_graph	3.0	entity / relation graph

Execution (AgentBus.dispatch, agent_bus.py:1533): - **Selective fan-out**: tiny filler chat → {memory, orchestrator}; non-chat → _select_agents_for_intent minimal set (keyword/action ladder, line 470); plain CHAT → broad fan-out across all _enabled agents. - **Parallel**: ThreadPoolExecutor, one thread per agent (or runtime_policy.budget("agent_workers", floor=4, ceiling=32)). - **Per-agent hard timeout**: future.result(timeout=agent.timeout_s) (1585); timeout/exception → failed AgentResult, never blocks the response. - **Aggregation** (_aggregate_confidence, 1248): per-agent contribution = evidence_quality × evidence_density × learned per-(agent,action) calibration; single-agent cap; empty-bus ceiling; corroboration bonus at ≥3 contributors. This part is genuinely solid.

When each runs (engine gate _eli_orch_should_run, engine.py:8962)

Situation	Path
Quick-mode CHAT, or phatic	AgentBus directly (engine.py:8994)
Balanced/deep CHAT	AgentOrchestrator — own retrieval; bus <i>not</i> used
Non-CHAT action (any mode)	AgentOrchestrator → calls bus + ReAct loop
Orchestrator returns None / raises	Falls back to AgentBus directly

Planning artifacts — 4 of them, only 1 drives execution

1. **ReAct loop** (orchestrator.py:598) — the *only* planner that actually sequences execution (tool → observe → decide → next tool).
2. **PlannerAgent.plan_retrieval** (orchestrator.py:53) — plans *retrieval* budgets, not actions. Used every CHAT turn.

3. **Bus OrchestratorAgent plan** (`agent_bus.py:1336`) — emits an `orchestrator_plan` dict stored in `trace["orchestrator_plan"]` (`engine.py:9026`) for display / persona handoff / status. **Never executed.**
4. **execution_planner.build_execution_plan** (`ExecutionPlan/PlanStep`) — now **wired in** as the canonical typed plan. `AgentBus.dispatch` builds it each turn, injecting the proven `_select_agents_for_intent` result as `agent_profile`, and drives active_agents *through* `plan.agent_profile` (selection result unchanged). The plan is surfaced on `DispatchResult.execution_plan`. `EXECUTE_GOAL` also builds a real plan via it.
5. **task_planner.TaskPlanner** — no longer a hardcoded shim; it now delegates to `execution_planner.build_execution_plan` so there is a single real plan representation across the codebase.

Where it is actually weak (corrected)

1. **Two retrieval strategies — but NOT a real weakness (corrected).** Earlier framed as duplicate engines; on proper reading both bottom out on the *same* `eli/memory/memory.py` primitives (`recall_memory:1722`, `search_conversations:2533`). The bus's `BusMemoryAgent` is a thin wrapper over the all-in-one `recall_memory` (lightweight, for quick/parallel); the orchestrator's `OrchestratorMemoryAgent` decomposes the same primitives (`keyword_only=True`) + adds RAG + rerank (heavyweight, for deep). A core retrieval bug is fixed once in `memory.py` for both. The fast/deep split is deliberate; forcibly unifying would collapse it for no gain. Left as-is.
2. **The bus is still a single isolated round.** Within one dispatch, the 14 agents cannot consume each other's output. The ReAct loop chains *executor tool actions*, not bus agents — so a bus-level dependency (e.g. KG seeded by memory's entities) still cannot be expressed.
3. **Planning partially consolidated (improved).** `execution_planner` is now the canonical typed plan and drives bus selection; `task_planner` delegates to it. Remaining overlap: the engine's `_build_runtime_orchestrator_plan` (rich stage dict) and the bus `OrchestratorAgent` plan still co-exist with the typed `ExecutionPlan`. The ReAct loop remains the only planner that actually *executes* a sequence. A future pass could fold the stage dict into `ExecutionPlan.steps` so there is one plan type end-to-end.
4. **ReAct loop fragility — FIXED.** Now validates the proposed `T00L:<action>` against `SUPPORTED_ACTIONS` (143 registered actions) and stops the loop on an unknown/hallucinated action instead of switching to it; merges `intent["args"]` (preserving originals) instead of overwriting. (`orchestrator.py` ReAct block.)
5. **Custom-agent timeout override — FIXED.** The override is now `_apply_runtime_policy_timeouts()`, applied to built-ins and **re-applied after `_load_custom_agents()`**, so custom agents get hardware-adapted timeouts too.
6. **Timeouts don't cancel work.** `future.result(timeout)` only stops waiting; a timed-out write-capable agent (`memory/habit`) can still land a late DB write.
7. **Confidence coupled to a fixed evidence-key schema.** `_evidence_density` only counts known keys; a custom agent returning useful prose under an unknown key contributes 0.0 to grounding.
8. **No early-exit for direct actions; failures debug-only.** Bus waits on the slowest selected agent even when a direct `action_result` is already in hand; timeouts/exceptions log at `log.debug` with no health surface (despite the `agent_metrics` table existing).

Recommended fixes (prioritized)

Priority	Fix	Why
High	Unify retrieval: have the bus <code>BusMemoryAgent/KnowledgeGraphAgent</code> and the orchestrator's <code>OrchestratorMemoryAgent</code> call one shared retrieval module.	Kills the dual-stack divergence (#1) — the single biggest source of mode-dependent bugs.

Priority	Fix	Why
High	Move <code>_load_custom_agents()</code> above the runtime-policy timeout loop (or re-apply the override after loading).	One-line fix for the redistribution timeout gap (#5).
High	Harden the ReAct loop: validate <code><action></code> against the known action set before chaining; merge (not overwrite) <code>intent["args"]</code> ; cap/parse defensively.	Closes silent-break + arg-loss (#4).
Med	Make the bus optionally two-round for dependent agents (round-1 results passed into round-2 <code>run()</code>), gated by a real plan.	Enables KG-seeded-by-memory etc. (#2).
Med	Either wire <code>execution_planner.ExecutionPlan</code> in as the bus's selection/sequencing source, or delete it + the shim <code>task_planner</code> to cut dead surface.	Resolves the 5-planner fragmentation (#3).
Med	Generic evidence-density floor: count any non-empty payload at low weight so unknown-key/custom agents aren't zeroed.	Makes custom agents first-class to confidence (#7).
Med	Cooperative-cancel token checked before write-capable agents commit.	Closes the late-write hole (#6).
Low	Early-return once a direct <code>action_result</code> exists; surface agent health (timeout rate, p95) from <code>agent_metrics</code> in <code>RUNTIME_STATUS</code> .	Latency + observability (#8).

Highest leverage: **#1 (unify the two retrieval stacks)** and **#4 (harden the ReAct loop)** — those are where correctness actually drifts today. The bus's confidence math and timeout enforcement are already good and don't need work.

Update — 2026-06-09

- **HabitAgent ↔ proactive disconnect fixed.** The bus `HabitAgent` used to read only `get_habit_rules()` (the usually-empty `habit_rules` table), so the chat path was blind to the behaviour the proactive daemon detects into the habits table. It now also reads `get_detected_habits()` and emits a summary + `detected_habits`; `AgentResult.has_evidence` recognises the new keys (it was judging the agent "no evidence" → dropped), and `DispatchResult.to_context_block` renders the habit summary into the chat context. Habit data is now consistent across the chat agent, `HABIT_STATUS`, and the persona overlay.
- **Goal autogenesis** (`planning/goal_autogenesis.py`) feeds the autonomy/goal-tick stack from ELI's own signals — see `runtime_planning_world.md`.