

# ELI — Learning

ELI v2.1.67

August 2026

## Contents

|                                                   |          |
|---------------------------------------------------|----------|
| <b>ELI Learning — LoRA Self-Training Pipeline</b> | <b>1</b> |
| Files & the pipeline . . . . .                    | 1        |
| What it is — and isn't . . . . .                  | 2        |
| Honest assessment . . . . .                       | 2        |

## ELI Learning — LoRA Self-Training Pipeline

eli/learning/ — 3.3k LOC, 12 files. ELI's self-improvement-via-fine-tuning path. **Important framing:** this is a *curated, human-gated, operator-invoked* training pipeline — **not** an autonomous self-modifying loop, and it targets a **separate trainable base (Phi-3)**, not the inference GGUF.

### Files & the pipeline

The stages, roughly in order:

| File                        | LOC | Stage                                                        |
|-----------------------------|-----|--------------------------------------------------------------|
| dataset_builder.py          | 558 | turn ELI's logged turns/corrections into supervised examples |
| dataset_filters.py          | 154 | quality gates (is_bad_response, row_is_reviewed)             |
| export_trainable_dataset.py | 168 | export reviewed rows → trainable JSONL                       |
| merge_reviewed_datasets.py  | 135 | merge reviewed dataset shards                                |
| bootstrap_phi3_base.py      | 245 | one-time download of the trainable HF Phi-3 base             |
| base_model_resolver.py      | 185 | locate/validate the trainable base (vs an adapter)           |
| training_preflight.py       | 142 | check peft/transformers/datasets present + target ready      |
| lora_trainer_guard.py       | 571 | TrainerTarget plans (paths, base_family) + guard checks      |
| lora_trainer.py             | 656 |                                                              |
| lora_eval.py                | 491 | eval harness (score vs expected/forbidden, inspect adapter)  |

## Flow

1. **Build** (`dataset_builder.py`): mines ELI's own conversation/correction history into `SupervisedExamples`. Crucially includes `clean_text` + **redact\_text (PII redaction)** and an exclusion set so sensitive/garbage content never becomes a training example. Writes `training/datasets/eli_supervised_v0.jsonl` + a report.
2. **Gate** (`dataset_filters.py`): `is_bad_response` and `row_is_reviewed` enforce quality + a **human review flag**.
3. **Export / merge**: reviewed rows → `*.trainable.jsonl`.
4. **Preflight** (`training_preflight.py`): refuses to proceed unless the HF training stack is installed and the target/base resolve.
5. **Train** (`lora_trainer.py`): `_dataset_report` **refuses to train** on a dataset with unreviewed rows, wrong-target rows, or bad-response rows — i.e. it will not learn from un-vetted data. Loads Phi-3 through native transformers (with a RoPE-scaling compat shim), trains the LoRA adapter.
6. **Eval** (`lora_eval.py`): `score_response` against expected/forbidden, plus `inspect_adapter` / `inspect_eval_suite`.

## Targets (`lora_trainer_guard.py`)

`TrainerTargets` define adapter/dataset/output paths for `phi3` and `phi3-ultra` variants under `models/lora/adapters/`. `base_family` is parameterised (`phi3/mistral/qwen`), so the trainer isn't hard-locked to one family even though Phi-3 is the default trainable base.

## What it is — and isn't

- It **is**: a responsible, reproducible fine-tuning pipeline with PII redaction, human review gating, preflight, and an eval harness. The dataset comes from ELI's real interactions (corrections, failures, conversations).
- It **isn't**: (a) automatic — no runtime trigger wires it in; it's run via `CLI/main()` entrypoints (`bootstrap_phi3_base`, `training_preflight`, `lora_trainer`). (b) connected to the live inference model — it trains a Phi-3 adapter, while inference typically runs a different GGUF. So a trained improvement does **not** flow into the running assistant unless you also run the Phi-3 base + adapter as the inference model.

## Honest assessment

- **Strong (and unusually responsible)**: PII redaction, refusing to train on unreviewed/bad rows, a preflight, and an eval suite are exactly what a serious fine-tuning loop needs and what most hobby projects skip. The base-vs-adapter validation prevents the classic "trained on an adapter" mistake.
- **Weak / watch**:
  1. **Base/inference disconnect** — training improves Phi-3, but the assistant usually runs another GGUF, so the self-improvement doesn't reach the live model. The loop is only closed if you actually serve the trained model.
  2. **Manual** — "self-training" is operator-driven, not autonomous. That's safe, but it means it improves only when you run it. (Arguably the right trade-off, but worth stating plainly rather than implying autonomy.)
  3. **Heavy deps** — needs the full HF/peft/transformers stack present; the preflight handles absence gracefully, but it's a large optional surface.
  4. **Phi-3 default** — intentional and parameterised, but the canned `TrainerTargets` and several resolver candidates are Phi-3-named, so adding a new base family is more than a config change.