



# ELI — Commands and Installers

ELI v2.4.67

September 2026

## Contents

|                                                                 |          |
|-----------------------------------------------------------------|----------|
| <b>ELI v2.0 — Commands &amp; Installers Reference</b>           | <b>1</b> |
| 1. The one-click installer (recommended for everyone) . . . . . | 1        |
| 2. Full install from source (developers) . . . . .              | 2        |
| 3. Launching ELI . . . . .                                      | 3        |
| 4. Models . . . . .                                             | 3        |
| 5. Alternative & advanced install paths . . . . .               | 4        |
| 6. Building release packages (maintainer) . . . . .             | 4        |
| 7. Health checks & maintenance . . . . .                        | 5        |
| 8. Uninstall . . . . .                                          | 5        |
| CLI-reachable surfaces . . . . .                                | 5        |

## ELI v2.0 — Commands & Installers Reference

**Updated for v2.4.67 (September 2026).** One hardware-aware GUI wizard. Prebuilt installers on [GitHub Releases](#). Full beginner map: first time Installation/INSTALLATION\_GUIDE.md.

*Every install path and command in one place. Copy-paste ready. Run everything from inside the ELI folder unless noted.*

Canonical version: **2.4.67**. Best-tested platform: **Linux x86\_64 + NVIDIA**. Windows, macOS, AMD, Intel Arc, and Apple Silicon ship supported paths; Iris Xe / ≤8 GB use CPU policy.

---

### 1. The one-click installer (recommended for everyone)

#### From a downloaded portable release

```
tar -xzf ELI_v2-2.4.67-linux-portable.tar.gz
cd ELI_v2-2.4.67-linux-portable
chmod +x ELI_Setup.sh
./ELI_Setup.sh
```

ELI\_Setup.sh → scripts/eli\_setup.sh:

1. Minimal .venv + PySide6 (when a display is available)
2. **eli.setup.hardware\_policy** decides CPU vs GPU

3. **Unified Install Wizard** streams `install.sh / install.ps1` **once**
4. Hard-fail stages until nomic + voice + chat model succeed

Terminal fallback (headless / no Qt): `install.sh --yes [--cpu-only] --auto-model`, then `--run-remaining`.

### From a git clone

```
git clone https://github.com/ShadowESC95/ELI_v2.0.git
cd ELI_v2.0
./scripts/eli_setup.sh
```

### Linux AppImage

```
chmod +x ELI_v2-2.4.67-x86_64.AppImage
./ELI_v2-2.4.67-x86_64.AppImage
```

### Compatibility aliases (not separate installers)

`scripts/eli_one_click_setup.sh` and `scripts/install_eli.sh` **only redirect** to `eli_setup.sh`.

## 2. Full install from source (developers)

### Linux / macOS

```
git clone https://github.com/ShadowESC95/ELI_v2.0.git
cd ELI_v2.0
bash install.sh           # interactive: system report → plan → install → pick model
./scripts/eli_launch.sh   # launch the desktop app
```

On Iris Xe / ≤8 GB prefer `./scripts/eli_setup.sh` or `bash install.sh --yes --cpu-only --auto-model`.

**install.sh flags** (combine as needed):

| Flag                                 | Effect                                                                        |
|--------------------------------------|-------------------------------------------------------------------------------|
| <code>--yes / -y</code>              | No prompts — use detected defaults (CI / piped installs)                      |
| <code>--cpu-only</code>              | Force the CPU build (ignore GPU)                                              |
| <code>--gpu</code>                   | Force the GPU build even if none is auto-detected                             |
| <code>--install-cuda / --cuda</code> | Best-effort install the CUDA toolkit (nvcc), then rebuild llama-cpp with CUDA |
| <code>--auto-model</code>            | Download one model sized to your VRAM after install                           |
| <code>--model=KEY</code>             | Download a specific model<br>(e.g. <code>--model=qwen2.5-7b</code> )          |
| <code>--no-model</code>              | Never download a model (also skips embedder/voice) — fully offline install    |
| <code>--latest</code>                | Use version ranges instead of the frozen reproducible lock                    |
| <code>--skip-torch</code>            | Skip PyTorch (smaller install; disables self-training)                        |

### Examples:

```

bash install.sh --yes --auto-model           # hands-off, with a model
bash install.sh --cpu-only --no-model        # minimal, no GPU, add a model later
bash install.sh --install-cuda --model=phi-4 # CUDA toolkit + a specific model

```

## Windows

```

install.bat           :: normal – CUDA install from the frozen lock + GPU verify
install.bat /cpu      :: CPU-only
install.bat /cuda      :: also auto-install the CUDA toolkit (winget) if missing
install.bat /latest    :: version ranges instead of the frozen lock

```

Or call the PowerShell installer directly:

```

powershell -ExecutionPolicy Bypass -File install.ps1 [-CpuOnly] [-Gpu] `
  [-InstallCuda] [-Yes] [-AutoModel] [-NoModel] [-Model qwen2.5-7b] [-Latest]

```

Launch with eli.bat.

## Developer editable install (pip)

```

python3 -m venv .venv && . .venv/bin/activate
python -m pip install --upgrade pip setuptools wheel
python -m pip install -e ".[full]"
python -m eli           # GUI
python -m eli --headless # terminal REPL

```

## Android / Termux (headless — server + CLI, no GUI)

```

bash scripts/install_android.sh

```

---

## 3. Launching ELI

```

./scripts/eli_launch.sh           # desktop app (GUI) – default
./scripts/eli_launch.sh gui       # same, explicit
./scripts/eli_launch.sh serve     # API + web-app server (this machine only)
./scripts/eli_launch.sh serve --lan # server exposed to your home network
./scripts/eli_launch.sh both --lan # server in background + desktop app
./eli.sh                          # shortcut for the desktop app
./venv/bin/python -m eli          # desktop app via module
./venv/bin/python -m eli --headless # text-only terminal REPL

```

**Headless slash commands:** /status · /mode · /reset · /help · /quit

**The web / phone server directly:**

```

./scripts/eli_serve.sh           # 127.0.0.1 only → http://127.0.0.1:8081/
./scripts/eli_serve.sh --lan      # home network → prints a token-protected URL + QR
./scripts/eli_serve.sh --port 9000 # custom port
./scripts/eli_serve.sh --lan --token MYSECRET # use a specific access token

```

---

## 4. Models

```

./venv/bin/python -m eli.core.model_download --list # show the catalog
./venv/bin/python -m eli.core.model_download --auto # one best-fit for your VRAM
./venv/bin/python -m eli.core.model_download --choose # multi-select menu (pick any number)
./venv/bin/python -m eli.core.model_download --aux # just the memory embedder (~85 MB)

```

Bring your own: drop any chat/instruct .gguf into models/ — ELI finds it and fits it to your hardware. Vision models also need their matching mmproj GGUF alongside.

**Voice weights** (if not fetched during install):

```
.venv/bin/python -m eli.runtime.voice_assets
```

**Restore the model/voice pack from GitHub** (tag local-assets-v2.1, needs gh):

```
gh auth login
./RUN_ELI.sh --with-github-assets
# or, without gh, after downloading assets manually:
python3 scripts/restore_github_asset_files.py --from-dir /path/to/downloaded/assets
```

---

## 5. Alternative & advanced install paths

| Path                         | Command                                                           | When to use                                   |
|------------------------------|-------------------------------------------------------------------|-----------------------------------------------|
| One-click run (portable)     | <code>./RUN_ELI.sh</code>                                         | Daily launch of a portable install            |
| Classic portable install     | <code>./INSTALL_ELI.sh</code> then <code>./RUN_ELI.sh</code>      | Portable package, manual two-step             |
| Safe Linux install           | <code>bash</code><br><code>scripts/safe_install_linux.sh</code>   | Conservative install with extra checks        |
| Add the eli terminal command | <code>bash</code><br><code>scripts/install_eli_command.sh</code>  | Get eli on your \$PATH (~/.local/bin/eli)     |
| Install app-menu icons only  | <code>bash</code><br><code>scripts/install_desktop_apps.sh</code> | Re-add ELI / ELI Server / ELI Setup launchers |
| Repo venv runner             | <code>bash</code><br><code>scripts/run_eli_repo_venv.sh</code>    | Run against the repo's own .venv              |
| Purge a legacy install       | <code>bash</code><br><code>scripts/purge_legacy_eli.sh</code>     | Clean up an older ELI before reinstalling     |

If your shell cached an old eli command after reinstalling: `hash -r`.

---

## 6. Building release packages (maintainer)

```
bash scripts/build_v2_release.sh           # portable Linux tar.gz
bash scripts/build_v2_release.sh --with-assets # + bundled models (very large)
bash scripts/build_grandma_release.sh       # portable tar.gz + AppImage + checksums
bash packaging/linux/build-appimage.sh      # AppImage only (from the portable build)
bash scripts/package_eli_release.sh         # wheel + sdist
bash build_packages.sh wheel appimage windows-lean # pick targets
```

**Windows Setup.exe** (run on a Windows PC with Inno Setup 6):

```
bash build_packages.sh windows-lean
powershell -ExecutionPolicy Bypass -File packaging/windows/build-windows.ps1 -Version 2.4.67
```

A signed/notarized macOS .dmg must be built on a Mac. Large model/voice binaries ship separately as GitHub Release assets (over Git's 100 MB blob limit). Full publish steps: [RELEASE.md](#).

### Installer branding

The setup wizard carries the ELI icon on every page. Three separate slots feed from the one source icon, and they are not interchangeable:

| Slot                 | File                                 | Where it shows                 |
|----------------------|--------------------------------------|--------------------------------|
| SetupIconFile        | packaging/desktop/Eli_Icon.ico       | the Setup.exe file icon itself |
| WizardImageFile      | packaging/desktop/wizard_large*.tiff | the welcome and finish pages   |
| WizardSmallImageFile | packaging/desktop/wizard_small*.tiff | the header of every other page |

Inno Setup accepts **only 24-bit BMP** for the two wizard slots — it rejects .png and .ico, and mis-renders a BMP that carries an alpha channel — so they cannot simply be the app icon and are generated from it instead:

```
python3 packaging/desktop/generate_wizard_images.py # regenerate after changing the icon
```

The second file in each installer.iss list is the high-DPI variant; Inno picks by the user's display scaling. Desktop and Start-menu shortcuts take their icon from the executable, which PyInstaller embeds via ELI.spec, so they need no separate entry.

The blueprint PDFs in this directory carry the same mark on their title page, applied by scripts/generate\_blueprint\_pdf

---

## 7. Health checks & maintenance

```
bash run_tests.sh # run the test suite
bash eli_diagnose.sh # system diagnosis report
.venv/bin/python -m eli.tools.mic_diag # microphone diagnostics (voice input)
.venv/bin/python -m eli.core.init_data # (re)build the local databases
```

### Reading the licence

ELI is **source-available**, not open-source: PolyForm Noncommercial License 1.0.0. Run, modify, and distribute it for any noncommercial purpose; you may not use it, or a modified version, for a commercial purpose. The terms are reachable identically from every download — installed app, portable folder, AppImage or .app:

```
eli --license # source install / portable tarball
./ELI_v2-*.AppImage --license
ELI.exe --license # Windows (the Setup.exe also shows it during install)
```

The files ship alongside the app too: LICENSE, NOTICE, THIRD\_PARTY\_NOTICES.md (dependency licences, incl. the PySide6 LGPL note) and models/MODEL\_LICENSES.md (model and voice terms).

---

## 8. Uninstall

ELI lives entirely inside its own folder — nothing spreads across your system:

```
rm -rf /path/to/ELI_v2.0
```

For an AppImage install, also remove ~/.local/share/ELI\_v2. If you added app-menu icons, delete the .desktop files from ~/.local/share/applications/.

---

ELI v2.0 — © 2026 Jason Fitzgibbon Bridgeman. Source-available under the PolyForm Noncommercial License 1.0.0. Questions: jaybridgeman0095@gmail.com

## CLI-reachable surfaces

| Module                                    | python -m entry                           | What it does                                                 |
|-------------------------------------------|-------------------------------------------|--------------------------------------------------------------|
| <code>eli.learning.target_registry</code> | —                                         | declare/list/delete LoRA training targets                    |
| <code>eli.learning.review_queue</code>    | —                                         | mine + review training candidates                            |
| <code>eli.plugins.security_scan</code>    | —                                         | <code>scan_file(path)</code> — 11-engine malware scan        |
| <code>eli.plugins.mcp</code>              | —                                         | <code>doctor()</code> — diagnose every configured MCP server |
| <code>eli.cognition.agent_trust</code>    | —                                         | <code>grant / revoke / inspect</code> custom agent code      |
| <code>tools/eval/run_eval.py</code>       | <code>--target router\ engine\ all</code> | eval board; now delegates to <code>run_board()</code>        |

`tools/eval/run_eval.py` output is unchanged — `main()` now calls `run_board()` and does the printing, so the CLI behaves exactly as before while the GUI can drive the same code in-process.

## Requirements

`requirements.txt` gained `peft`, `datasets` and (non-macOS) `bitsandbytes`. See `installation.md`.