



ELI — Portable Scripts Guide

ELI v2.4.78

September 2026

Contents

Which script do I run? — ELI v2.0 portable	1
The short answer	1
Pick your path (decision table)	2
Important: ELI needs an AI model	2
Every file, explained	2
After it's running — everyday use	4
If something goes wrong	4

Which script do I run? — ELI v2.0 portable

Updated for v2.4.72 (September 2026). The primary way to install ELI is now the **prebuilt installers on GitHub Releases** — ELI-Setup-<v>.exe (Windows), the .dmg (macOS, Apple Silicon), the .AppImage (Linux). The Linux AppImage and Windows installer are built and launch-tested in CI; the macOS .dmg is built on a Mac and provided best-effort (not verified in CI). First launch offers GPU acceleration (NVIDIA CUDA / AMD Vulkan; Apple Metal is built in) and a starter model sized to your hardware. Data lives in a per-user ELI_v2 folder and survives upgrades; --fresh-start resets it. Everything below remains valid for **source installs** (clone + install.sh) and the classic portable tarball.

You have just extracted **ELI_v2-2.4.72-linux-portable** and you are looking at a folder full of scripts. This guide explains **every launcher in plain language**: what it is, when to use it, the exact command to type, and what it actually does under the hood. No prior knowledge assumed.

The short answer

After a fresh extract, open a terminal in this folder and run:

```
chmod +x ELI_Setup.sh
./ELI_Setup.sh
```

That one command installs everything, sets ELI up, and launches it. If you only ever read one line of this document, that is the line.

chmod +x means “mark this file as runnable” — you only need it once. The ./ in front means “run the script that is right here in this folder.”

Everything else in this folder is either **(a)** something `ELI_Setup.sh` calls for you, **(b)** an alternative for people who want more control, or **(c)** a tool for developers that you should ignore.

Pick your path (decision table)

Your situation	Run this
"Just make it work." <code>ELI_Setup.sh</code> says Please install PySide6	<code>./ELI_Setup.sh</code> <code>bash install.sh --yes --auto-model</code> then <code>./RUN_ELI.sh</code>
I want to install now and launch later, separately	<code>./INSTALL_ELI.sh</code> then <code>./RUN_ELI.sh</code>
My computer has no NVIDIA graphics card	<code>./INSTALL_ELI.sh --cpu-only</code> then <code>./RUN_ELI.sh</code>
I want ELI's AI model + voices too (big download)	<code>./RUN_ELI.sh --with-github-assets</code>
I want to use ELI from my phone or tablet	<code>./scripts/eli_serve.sh --lan --https</code>
I'm on Windows	<code>install.bat</code> (or the <code>Setup.exe</code> from GitHub Releases)
I'm a developer building release packages	<code>build_packages.sh</code> — <i>not for normal use</i>

Important: ELI needs an AI model

A fresh portable ships **without** the large AI model file (to keep the download small). The `models/` folder starts empty. ELI will not think until a model is present. Two ways to get one:

- **Bundled convenience pack** (model + voices), pulled from the project's GitHub Release:

```
gh auth login                # one-time: log in to GitHub
./RUN_ELI.sh --with-github-assets # downloads the model/voice pack, then launches
```

- **Automatic model download** (guided), if you prefer just the model:

```
.venv/bin/python -m eli.core.model_download --auto
```

`ELI_Setup.sh` offers to do the asset step for you, so most people never type these by hand.

Every file, explained

`ELI_Setup.sh` — the recommended one-click

What it is: the friendly “grandparent setup.” A double-click-friendly name that hands off to `scripts/eli_setup.sh`. **When to use:** first time, and whenever you want the easy path. **Command:** `./ELI_Setup.sh` **What it does:** runs an 8-step first-run sequence — creates the private Python environment (`.venv`), installs all dependencies, sets up the databases, optionally fetches the model/voice pack, installs the `eli` terminal command and a desktop icon, opens a small graphical wizard (using pop-up dialogs if your system has them), and finally launches ELI. **To you:** the “do everything for me” button.

`INSTALL_ELI.sh` — same as `ELI_Setup.sh` (legacy name)

What it is: a thin wrapper around `scripts/eli_setup.sh` (identical to `ELI_Setup.sh`). **When to use:** same as `ELI_Setup.sh`; name kept for older docs. **Command:** `./INSTALL_ELI.sh` **What it does:** opens the unified GUI installer when possible; otherwise runs `install.sh --yes --auto-model`. It does **not** open ELI — that's what `RUN_ELI.sh` is for. **Useful options:** `--cpu-only` (no graphics card), `--skip-torch` (don't

install the heavy PyTorch library), `--with-github-assets` (also grab the model/voice pack). **To you:** “get it ready, but don’t open it yet.”

`RUN_ELI.sh` — launch ELI (your daily button)

What it is: a wrapper around `scripts/eli_startup.sh`. **When to use:** every day, to start ELI. Safe to run even if you haven’t installed yet — it will install first if needed. **Command:** `./RUN_ELI.sh` **What it does:** checks that ELI is installed (installs if not), optionally restores the model/voice assets, then launches the app. **Useful options:** `--with-github-assets` (fetch the model/voice pack before launching), `--safe-mode` (turn off proactive/experimental startup features if something misbehaves), `--trace` (verbose logs for troubleshooting), `--no-setup` (skip the install check). **To you:** the “open ELI” button.

`install.sh` — the full Linux/macOS installer (advanced)

What it is: the low-level installer that the one-click scripts wrap. This is the real engine that builds the environment. **When to use:** you want direct control over the installation, or you’re comfortable in a terminal. **Command:** `bash install.sh` **What it does:** creates the `.venv`, installs the **exact, frozen** set of tested dependencies (reproducible), verifies GPU offload works, and initialises data folders and databases. It does **not** set up the friendly `eli` command, the wizard, or launch ELI — the one-click scripts add those niceties on top. **Useful options:** `--cpu-only` (no GPU), `--skip-torch` (skip PyTorch), `--latest` (newest dependency versions instead of the frozen lock), `--install-cuda` (best-effort install of the NVIDIA CUDA toolkit). **To you:** “the manual installer” — most people should use `ELI_Setup.sh` instead.

`install.bat` and `install.ps1` — Windows installers

What they are: the Windows equivalent of `install.sh`. `install.bat` is the double-click file; it simply launches the more capable `install.ps1` (PowerShell). **When to use:** you’re on Windows. **Command (in the folder):** `install.bat` — or `install.bat /cpu` for no GPU. **What they do:** same idea as `install.sh` — build the environment, verify the GPU, initialise databases. **Useful options:** `/cpu` (CPU-only), `/cuda` (also install the CUDA toolkit via winget), `/latest` (newest versions instead of the frozen lock). **To you:** “the Windows installer.” Non-technical Windows users may prefer the `Setup.exe` from the GitHub Releases page instead.

`eli.sh` — the bare launcher (low-level)

What it is: the minimal launcher. It points the environment variables at this folder and runs `python -m eli` inside the `.venv`. **When to use:** rarely — only if you’ve already installed and want the most direct start. **Command:** `./eli.sh` **What it does:** exactly one thing — starts ELI from the already-built `.venv`. If the environment isn’t there yet, it tells you to run the installer first. `RUN_ELI.sh` is the friendlier version of this. **To you:** the “engine start” with none of the conveniences.

`eli` — the terminal command (created during setup)

What it is: a shortcut installed into `~/.local/bin/eli` by the setup scripts. **When to use:** after installing, from **any** folder. **Command:** `eli` **What it does:** launches ELI without needing to be inside this folder. **Tip:** if typing `eli` runs an old version, run `hash -r` once to refresh your shell.

`eli-v2.0.desktop` — the desktop / menu shortcut

What it is: a Linux application-menu entry (the clickable icon). **When to use:** you don’t run it directly — the setup installs it so ELI appears in your applications menu with its icon, launchable by mouse. **What it contains:** the app name, icon, and the command to run (`scripts/eli_launch.sh gui`). The `__REPO_ROOT__` placeholders inside are filled in with this folder’s real path when the launcher is installed (via `./packaging/desktop/install_desktop_launcher.sh`). **To you:** the “ELI icon” in your menu once setup has run.

build_packages.sh — developer tool (not for end users)

What it is: the script that **builds** the distributable packages (Python wheel, Linux AppImage, Windows portable zip, macOS bundle, etc.). **When to use:** only if you are packaging ELI for release. **What it does:** assembles installable artifacts under dist/. It does **not** run or install ELI for use. **To you:** ignore this one — it's for whoever ships ELI, not for using it.

scripts/eli_serve.sh — use ELI from your phone / tablet

What it is: starts ELI's built-in web server so a browser on another device can reach it. **Command:** ./scripts/eli_serve.sh --lan --https **What it does:** binds to your local network (--lan) with an access token, and enables HTTPS (--https) which browsers require before they'll allow the **microphone**. It prints a URL (and a QR code is available in the app's *Connect a phone* tab) to open on the phone. Everything still runs on **this** machine — nothing goes to any cloud. **To you:** the “talk to ELI from my couch on my phone” button.

README_INSTALL.txt

What it is: the short plain-text quick-start that ships in the folder. This PDF is the expanded, friendly version of it.

After it's running — everyday use

- **Start ELI:** ./RUN_ELI.sh (or just type eli, or click the menu icon)
- **Phone access:** ./scripts/eli_serve.sh --lan --https
- **Your data lives here** (created automatically on first run): artifacts/db/ (memories & conversations), artifacts/runtime/, and config/. Because this is a *portable* copy, everything stays inside this folder — you can move or back up the whole ELI_v2-2.4.72-linux-portable folder and nothing is lost.

If something goes wrong

- **“Virtual environment not found”:** you launched before installing — run ./ELI_Setup.sh (or ./INSTALL_ELI.sh) first.
- **No NVIDIA GPU / install fails on GPU bits:** reinstall with ./INSTALL_ELI.sh --cpu-only.
- **ELI has no model / won't answer:** fetch one with ./RUN_ELI.sh --with-github-assets (after gh auth login) or .venv/bin/python -m eli.core.model_download --auto.
- **Odd behaviour at startup:** try ./RUN_ELI.sh --safe-mode, or --trace for detailed logs written under artifacts/startup/logs/.

*ELI runs entirely on your own hardware. It is offline by default — turn on the **Net** toggle in the app only when you want it to reach the internet.*