

ELI — Architecture Ascii

ELI v2.4.79

September 2026

Contents


Blueprint — ELI Full Architecture (ASCII)	1
A. Full system — layered block diagram	1
B. The 15 agents	3
C. Module tree (LOC · key files · role)	3
D. On-disk data layout	5
E. The flow in one line	5


Blueprint — ELI Full Architecture (ASCII)

Updated for v2.4.72. All CHAT modes → gradient orchestrator; bus composed at S06.

The entire system in one drawing, plus the module tree and data layout. Grounded in the real source (see `architecture.md` for prose, `diagrams.md` for the pipeline/memory/gating close-ups). Every layer and box maps to a real path.

A. Full system — layered block diagram





- └─ media_runtime.py
- └─ portable_intent_contract.py
- cognition/ 20.8k — think
 - └─ agent_bus.py 3.5k 15 agents + dispatch
 - └─ orchestrator.py 12-stage deep retrieval
 - └─ gguf_inference.py 3.2k · inference_broker.py model-agnostic inference
 - └─ reasoning_modes.py · hyde.py · reranker.py · llm_intent.py
 - └─ persona.py/_updater/_values/_status/_hygiene (+ persona.txt, persona.auto.txt)
 - └─ context_synthesiser.py · working_memory.py
 - └─ output_governor.py · response_governance.py · response_sanitizer.py
 - └─ grounded_status.py · introspection_agent.py · tone_analyzer.py
- runtime/ 35.4k — grounding spine + daemons (95 files)
 - └─ deterministic_grounding_gate.py 3.4k · grounding_escalation.py
 - └─ evidence_ledger/arbitration.py
 - └─ persistence_gate.py · truth_report.py · control_contracts.py
 - └─ response_contracts/packets/policy.py · final_response_assembly/provider.py
 - └─ user_visible_response_surface.py · personal_memory*.py · reflection.py
 - └─ background_tasks.py · self_improvement.py · code_monitor.py
 - └─ capability_sync.py · pending_proposal.py · runtime_policy.py
- memory/ 8.8k — remember (11 files)
 - └─ memory.py 5.7k Memory · SQLite + FTS5 · storage policy in policy.py
 - └─ vector_store.py FAISS index
- perception/ 10.2k — sense (23 files)
 - └─ vision.py · analyze_image/csv/pdfs/mesh.py · ambient_vision.py
 - └─ audio_stt.py · local_whisper_stt.py · voice_worker_streaming.py
 - └─ tts_router.py · os_controller.py · screen_locator.py · gaze_engine.py
- planning/ 4.0k — proactivity (19 files)
 - └─ proactive_daemon.py · habits_scheduler.py · habits.py · jobqueue_cli.py
- coding/ 2.1k — CodeAgent (plan→search→verify→repair, 12 files)
- learning/ 4.3k — LoRA self-training (14 files)
 - └─ lora_trainer/eval/guard.py · dataset_builder/filters.py
 - └─ bootstrap_phi3_base.py · base_model_resolver.py · training_preflight.py
- plugins/ 5.9k — manager + bundled plugins (34 files)
 - └─ calendar · document_reader · media · notes · pomodoro · weather · system_stats · tts · web · web_automation
- world/ 1.8k — EliWorld (world_event_bus, local_world_bridge)
- core/ 11.2k — infra
 - └─ netguard.py offline failsafe + allow_network()
 - └─ paths.py · portable_paths.py · legacy_paths.py · db_paths.py
 - └─ runtime_settings.py · config.py · grounding.py
 - └─ hardware_profile.py · startup_hardware_optimizer.py · dynamic_runtime_budget.py
 - └─ model_download.py
- gui/ 27.4k — PySide6 desktop
 - └─ eli_pro_audio_gui_v2_0.py 13.1k · app.py · labs_tab.py 5.7k

```

├─ panels/ (startup.py: model picker + FirstBootWizard, HardwareTuningDock)
├─ tools/ 7.6k — image_engine · news · document tools
├─ contracts/ 0.8k · cli/ 0.1k · system/ 1.2k · utils/ 1.8k · setup/ 1.9k · onboarding/ 0.7k

```

D. On-disk data layout

```

artifacts/
├─ db/
│   ├── user.sqlite3      memories · memories_archive · memory_meta · semantic ·
│   │                     conversation_turns · conversations · session_summaries ·
│   │                     kg_entities · kg_relations · recall_log · runtime_events ·
│   │                     learning_replay · observations · habits/habit_events/habit_rules ·
│   │                     user_patterns · user_model · eli_stances · belief_revisions ·
│   │                     news_articles · news_reflections (+ FTS5 indexes)
│   ├── agent.sqlite3     agent_dispatches · agent_metrics · improvements · failures ·
│   │                     corrections · capability_proposals · error_tracking
│   ├── system_index.sqlite3 OS index
│   └─ coding_memory.sqlite3 coding_bug_fixes
├─ vectors/index.faiss    semantic index (embedder: nomic-embed-...Q4_K_M.gguf)
├─ conversations/
├─ runtime/ · runtime_snapshot.json      live model/runtime truth
├─ world/{snapshots,ledger,journal}/
├─ documents/ · scripts/ · analyze_image_*/
├─ config/ settings.json (gitignored) · templates/settings.template.json ·
│           settings.example.json · plugins_state.json
└─ models/ <your>.gguf · embeddings/ · whisper/ · image/      tts_piper/ Piper voices

```

E. The flow in one line

```

INPUT → ROUTER → ENGINE ─┬─ FAST-PATH ───────────────────→ OUTPUT (verbatim)
                        │
                        └─ ORCHESTRATOR (all CHAT modes, gradient)
                              ├── retrieve_for_turn() → MEMORY
                              ├── dispatch_specialists() → 15-agent BUS
                              └─ broker.infer() → finalize_turn() (S12)
GATES: netguard · persistence · grounding · escalation · governor
INFERENCE (broker → gguf, model-agnostic) → OUTPUT → TTS/GUI
BACKGROUND: proactive · self-improve · habits · learning(LoRA) · world · scheduler

Companion docs: architecture.md (prose, every subsystem) · diagrams.md (pipeline / memory
/ gating close-ups) · tools/eval/README.md (the measurement layer). “”

```