

File Header Anomaly Detector: how it is put together



sketched from the filesk

File Header Anomaly Detector: the run, step by step



If a step fails, the honest run says so and stops.

traced, not guessed. GK

Product map: what File Header Anomaly Detector is for

WHAT IT IS

A small project in Python, Markdown, Text. The README and the files are the whole claim.

WHAT GOES IN

The files at the top of the tree: main.py, README.md, banner.png.

WHAT COMES OUT


What the top files produce when they run or get read. Nothing else is promised.

WHERE IT STOPS

No service behind it, no account, no upload. If a path is untested, VISUAL.md says so.

mapped by hand, GK

File Header Anomaly Detector: data flow, in one direction




One direction. Anything the code does not do is not drawn.

second sheet, OK

File Header Anomaly Detector in numbers, counted 2026-10-30

Counted from the local snapshot of this repo. Method for every number: VISUAL.md.



5 files in the tree.

6 commits, first 2025-06-07, last 2026-10-30, from the local git log.

No test files by name in this snapshot.

counted and drawn, CK

File Header Anomaly Detector: schematic of the apparatus


the system as a machine: parts, flow, and measurements

construction lines left in, as drawn

parts list

1. main.py
2. README.md
3. banner.png
4. logo.png

in flow order, first to last



base plate: the repo itself, sectioned

span: 5 files, 124 lines counted

turns of the crank so far: 6 commits, 2025-06-07 to 2026-10-30

measured and sketched, GK