

Nginx配置二级域名



一双鞋两双 [关注](#)

2019.03.26 17:47:21 字数 524 阅读 961

一、找到系统Nginx的配置文件

```
find / -name nginx.conf
```

我的电脑是在: /etc/nginx/nginx.conf

```
[root@izbp12q9h36kv8v25s1x4hz conf.d]# find / -name nginx.conf
/etc/nginx/nginx.conf
[root@izbp12q9h36kv8v25s1x4hz conf.d]#
```

nginx.conf

二、在/etc/nginx目录的conf.d文件夹创建一个default.conf文件

```
[root@izbp12q9h36kv8v25s1x4hz nginx]# cd conf.d/
[root@izbp12q9h36kv8v25s1x4hz conf.d]# ll
total 8
-rw-r--r-- 1 root root 7164 Mar 26 17:24 default.conf
[root@izbp12q9h36kv8v25s1x4hz conf.d]#
```

conf.d

解释: 因为在nginx.conf文件的最后面有这么一段代码: include /etc/nginx/conf.d/*.conf; 引入conf.d下所有的.conf文件。

三、在conf.d/default.conf文件内添加一下内容:

```
server {

    listen    80;

    server_name celue.bgsm888.com;    // -----(需要更改) 监听的域名

    #charset koi8-r;

    #access_log logs/host.access.log main;

    location / {

        root /home/www/celue;    // -----(需要更改) 项目地址

        index index.php index.html index.htm;

        # example

        #ModSecurityEnabled on;

        #ModSecurityConfig /etc/nginx/modsecurity.conf;

    }

    error_page 404    /404.html;

    location = /404.html {

        root /usr/share/nginx/html;

    }

    location ~* \.(eot|otf|ttf|woff|svg)$ {

        root /home/www/celue;    // -----(需要更改) 项目地址

        add_header Access-Control-Allow-Origin *;

    }

    # redirect server error pages to the static page /50x.html

    #
```

```

error_page 500 502 503 504 /50x.html;

location = /50x.html {

    root /usr/share/nginx/html;

}

# proxy the PHP scripts to Apache listening on 127.0.0.1:80
#

#location ~ /\.php$ {

#    proxy_pass http://127.0.0.1;

#}

# pass the PHP scripts to FastCGI server listening on 127.0.0.1:9000
#

location ~ /\.php {

    root /home/www/celue; // -----(需要更改) 项目地址

    fastcgi_param SCRIPT_FILENAME $document_root$fastcgi_script_name;

    fastcgi_index index.php;

    fastcgi_split_path_info ^(.+\.php)(/.+)$;

    fastcgi_param PATH_INFO $fastcgi_path_info;

    fastcgi_param PATH_TRANSLATED $document_root$fastcgi_path_info;

    include fastcgi_params;

    fastcgi_pass 127.0.0.1:9000;

    fastcgi_connect_timeout 600;

    fastcgi_send_timeout 600;

    fastcgi_read_timeout 600;

    fastcgi_buffer_size 256k;

    fastcgi_buffers 16 256k;

    fastcgi_busy_buffers_size 512k;

    fastcgi_temp_file_write_size 512k;

}

# deny access to .htaccess files, if Apache's document root

# concurs with nginx's one

#

#location ~ /\.ht {

#    deny all;

#}

}

```

四、重启nginx（查询自己的sbin/nginx目录替换）

```

/usr/local/nginx/sbin/nginx -t

/usr/local/nginx/sbin/nginx -s reload

```

五、遇到的问题

在配置完成之后，访问出现了403。

5.1 首先看看是否有index文件

检查后发现都有，应该不是这个原因。

5.2 再检查是否是文件夹的权限问题

```
chmod -R 777
```

使用上面的命令后还是不行。

5.3 检查启动用户和nginx工作用户是否一致

修改nginx.conf的第一行，改成下面这样

```
user root;
```

重启nginx，访问正常。

参考地址：1、[CSDN使用nginx配置二级域名](#)

2、[Nginx配置文件详细说明](#)

 0人点赞 >



 服务器



"小礼物走一走，来简书关注我"

赞赏支持

还没有人赞赏，支持一下




一双鞋两双

编写行云流水般的代码农民

总资产0.274 (约0.03元) 共写了5927字 获得3个赞 共0个粉丝

关注



写下你的评论...

全部评论 0

只看作者

按时间倒序

按时间正序

