UC-01

Trip Leader

Create Trip

Short-Description / Goal	Allows Trip Leader to create a new trip including destination, dates, and members
Preconditions	1. User is logged in 2. User is Trip Leader
Postconditions	Trip is created with initial details and stored in system
Error Situations – System State in the Event of an Error	1. Missing required fields → trip not created 2. Invalid dates → system rejects input
Actor(s) / Initiator(s)	Trip Leader
Trigger	User clicks 'Create Trip'
Standard Process (Main Success Scenario)	1. User opens create trip page 2. User enters destination, dates, and description 3. User optionally adds members 4. User submits form 5. System validates data 6. System stores trip information 7. System confirms creation
Alternative Processes (Alternative/Other Scenarios)	Invalid data → system shows error and asks for correction

UC-02

Trip Leader

Delete Trip

Short-Description / Goal	Allows Trip Leader to permanently delete an existing trip
Preconditions	1. User is logged in 2. User is Trip Leader 3. Trip exists
Postconditions	Trip and all associated data are removed from the system
Error Situations – System State in the Event of an Error	1. Trip not found → error shown 2. User lacks permission → action denied
Actor(s) / Initiator(s)	Trip Leader
Trigger	User clicks 'Delete Trip'
Standard Process (Main Success Scenario)	1. User opens trip settings 2. User clicks delete trip 3. System asks for confirmation 4. User confirms deletion 5. System deletes trip and all related data 6. System redirects to home page
Alternative Processes (Alternative/Other Scenarios)	User cancels → trip is not deleted

UC-03

Trip Leader

Update Trip

Short-Description / Goal	Allows Trip Leader to update trip information such as dates or destination
Preconditions	1. User is logged in 2. User is Trip Leader 3. Trip exists
Postconditions	Trip details are updated and saved
Error Situations – System State in the Event of an Error	1. Invalid data → system rejects and shows error 2. Network error → changes not saved
Actor(s) / Initiator(s)	Trip Leader
Trigger	User edits trip details
Standard Process (Main Success Scenario)	1. User opens trip settings 2. User edits desired fields 3. User submits changes 4. System validates updated data 5. System saves changes 6. System confirms update
Alternative Processes (Alternative/Other Scenarios)	Invalid input → system highlights errors

UC-04

Trip Member

Add/Modify Activity

Short-Description / Goal	Allows a trip member to add a new activity or modify an existing one in the trip itinerary
Preconditions	1. User is logged in 2. User is a member of the trip
Postconditions	Activity is added or updated in the trip itinerary
Error Situations – System State in the Event of an Error	1. Missing required fields → activity not saved 2. Scheduling conflict detected → system notifies user
Actor(s) / Initiator(s)	Trip Member
Trigger	User selects 'Add Activity' or edits existing one
Standard Process (Main Success Scenario)	1. User opens trip itinerary 2. User clicks 'Add Activity' or selects existing activity 3. User fills in activity details 4. System checks for scheduling conflicts 5. System identifies conflicting timezones if needed 6. User submits 7. System saves activity
Alternative Processes (Alternative/Other Scenarios)	Conflict detected → user is prompted to resolve

UC-05

Trip Member

Propose Activity (Draft)

Short-Description / Goal	Allows a trip member to propose an activity as a draft for group consideration
Preconditions	1. User is logged in 2. User is a member of the trip
Postconditions	Draft activity is submitted and visible to other members
Error Situations – System State in the Event of an Error	1. Incomplete proposal → draft not submitted
Actor(s) / Initiator(s)	Trip Member
Trigger	User submits a draft proposal
Standard Process (Main Success Scenario)	1. User opens proposal form 2. User fills activity details as draft 3. User submits draft 4. System saves draft and notifies members
Alternative Processes (Alternative/Other Scenarios)	User saves without submitting → stays as local draft

UC-06

Trip Member

Opt-in/Out of Activity

Short-Description / Goal	Allows a trip member to opt in or out of a specific activity
Preconditions	1. User is logged in 2. Activity exists in the itinerary
Postconditions	User's participation status is updated
Error Situations – System State in the Event of an Error	1. Activity already started → opt-out not allowed
Actor(s) / Initiator(s)	Trip Member
Trigger	User toggles participation in an activity
Standard Process (Main Success Scenario)	1. User views activity 2. User clicks 'Join' or 'Leave' 3. System updates participation list 4. System notifies trip leader if needed
Alternative Processes (Alternative/Other Scenarios)	Activity is mandatory → opt-out is disabled

UC-07

Trip Member

Add Expenses

Short-Description / Goal	Allows trip members to log expenses related to the trip
Preconditions	1. User is logged in 2. User is a member of the trip
Postconditions	Expense is recorded; budget is updated; currency converted if needed
Error Situations – System State in the Event of an Error	1. Invalid amount → expense not saved 2. Budget exceeded → notification sent
Actor(s) / Initiator(s)	Trip Member
Trigger	User clicks 'Add Expense'
Standard Process (Main Success Scenario)	1. User opens expenses section 2. User enters expense details and amount 3. System converts currency if needed 4. System saves expense 5. System updates trip budget 6. System monitors budget threshold 7. System notifies if budget exceeded
Alternative Processes (Alternative/Other Scenarios)	Invalid input → error shown, expense not recorded

UC-08

Trip Member

Vote on Activities

Short-Description / Goal	Allows trip members to vote on proposed activities
Preconditions	1. User is logged in 2. User is a member of the trip 3. Voting is active for an activity
Postconditions	Vote is recorded and tally updated
Error Situations – System State in the Event of an Error	1. Voting period has ended → vote not accepted 2. User already voted → duplicate prevented
Actor(s) / Initiator(s)	Trip Member
Trigger	Voting is opened for an activity
Standard Process (Main Success Scenario)	1. User opens voting section 2. User views activity details 3. User casts vote 4. System records vote 5. System updates vote tally 6. Voting auto-closes when deadline reached
Alternative Processes (Alternative/Other Scenarios)	Activity is sensitive → anonymous voting is triggered

UC-09

Trip Member

Participate in Discussions

Short-Description / Goal	Allows trip members to communicate and discuss trip plans
Preconditions	1. User is logged in 2. User is a member of the trip
Postconditions	Message is posted and visible to all members
Error Situations – System State in the Event of an Error	1. Empty message → not posted 2. User muted → cannot post
Actor(s) / Initiator(s)	Trip Member
Trigger	User opens discussion board
Standard Process (Main Success Scenario)	1. User opens discussion section 2. User types message 3. User submits message 4. System validates and posts message 5. Other members receive notification
Alternative Processes (Alternative/Other Scenarios)	User edits or deletes message → system updates thread

UC-10

Trip Member

Submit Trip Rating

Short-Description / Goal	Allows members to rate the overall trip experience
Preconditions	1. User is logged in 2. Trip is completed
Postconditions	Rating is submitted and stored
Error Situations – System State in the Event of an Error	1. Rating already submitted → duplicate prevented
Actor(s) / Initiator(s)	Trip Member
Trigger	Trip is marked as completed
Standard Process (Main Success Scenario)	1. System prompts user to rate trip 2. User selects rating score 3. User optionally adds comment 4. System saves rating 5. System updates trip rating average
Alternative Processes (Alternative/Other Scenarios)	User skips → no rating submitted

UC-11

Trip Member

Approve Final Settlement

Short-Description / Goal	Allows members to review and approve the final expense settlement
Preconditions	1. User is logged in 2. Trip has ended 3. All expenses are logged
Postconditions	Settlement is approved and finalized
Error Situations – System State in the Event of an Error	1. Member disputes amount → settlement flagged for review
Actor(s) / Initiator(s)	Trip Member
Trigger	Settlement is presented at end of trip
Standard Process (Main Success Scenario)	1. System calculates final settlement 2. System presents each member's share 3. User reviews settlement 4. User approves or disputes 5. If approved by all → settlement finalized 6. System sends confirmation to all members
Alternative Processes (Alternative/Other Scenarios)	Member disputes → admin or leader reviews

UC-12

System (included in Add/Modify Activity)

Identify Conflicts

Short-Description / Goal	System automatically detects scheduling conflicts between activities
Preconditions	1. At least two activities exist in the itinerary
Postconditions	Conflicts are identified and user is notified
Error Situations – System State in the Event of an Error	1. System fails to retrieve schedule → conflict check skipped
Actor(s) / Initiator(s)	System (included in Add/Modify Activity)
Trigger	Triggered automatically when activity is added or modified
Standard Process (Main Success Scenario)	1. User adds or modifies activity 2. System compares new activity time with existing ones 3. System detects any overlap 4. System notifies user of conflict 5. User resolves conflict manually
Alternative Processes (Alternative/Other Scenarios)	No conflict found → activity saved normally

UC-13

System (included in Add/Modify Activity)

Convert Timezones

Short-Description / Goal	System converts activity times to correct local timezones for all members
Preconditions	1. Activity has a time and destination set 2. Members are in different timezones
Postconditions	Activity times are displayed in each member's local timezone
Error Situations – System State in the Event of an Error	1. Timezone data unavailable → UTC displayed as fallback
Actor(s) / Initiator(s)	System (included in Add/Modify Activity)
Trigger	Triggered when activity spans multiple timezones
Standard Process (Main Success Scenario)	1. System detects destination timezone 2. System retrieves each member's local timezone 3. System converts activity time accordingly 4. System displays localized times to each member
Alternative Processes (Alternative/Other Scenarios)	Member sets manual timezone → system uses that instead

UC-14

Trip Member

Categorize Priority

Short-Description / Goal	Allows members to tag activities with a priority level to aid planning
Preconditions	1. User is logged in 2. Activity exists in itinerary
Postconditions	Activity is tagged with selected priority level
Error Situations – System State in the Event of an Error	1. Activity not found → tagging fails
Actor(s) / Initiator(s)	Trip Member
Trigger	Member tags activity as must-have or nice-to-have
Standard Process (Main Success Scenario)	1. User opens activity 2. User selects priority tag (must-have / nice-to-have) 3. System saves tag 4. System updates activity display with priority badge
Alternative Processes (Alternative/Other Scenarios)	User removes tag → activity returns to untagged state

UC-15

Trip Member

Invite New Users

Short-Description / Goal	Allows trip members to invite new users to join the trip
Preconditions	1. User is logged in 2. User is a member of the trip
Postconditions	Invitation is sent to the new user
Error Situations – System State in the Event of an Error	1. Invalid email → invitation not sent 2. User already in trip → duplicate prevented
Actor(s) / Initiator(s)	Trip Member
Trigger	User clicks 'Invite'
Standard Process (Main Success Scenario)	1. User opens invite section 2. User enters email of invitee 3. System validates email 4. System sends invitation 5. Invitee receives email and joins
Alternative Processes (Alternative/Other Scenarios)	Invitee ignores → invitation expires after set time

UC-16

System (included in Upload Documents)

Encrypt Document

Short-Description / Goal	System encrypts uploaded documents to ensure secure storage
Preconditions	1. Document has been uploaded by user
Postconditions	Document is encrypted and stored securely
Error Situations – System State in the Event of an Error	1. Encryption fails → document not stored, user notified
Actor(s) / Initiator(s)	System (included in Upload Documents)
Trigger	Triggered automatically when document is uploaded
Standard Process (Main Success Scenario)	1. User uploads document 2. System receives file 3. System encrypts document using secure algorithm 4. System stores encrypted file 5. System logs encryption event
Alternative Processes (Alternative/Other Scenarios)	Encryption service unavailable → upload aborted

UC-17

System (extends Monitor Budget Threshold)

Notify Budget Exceeded

Short-Description / Goal	System automatically notifies members when the trip budget is exceeded
Preconditions	1. Budget threshold is set 2. Expenses have been added
Postconditions	Notification is sent to all relevant members
Error Situations – System State in the Event of an Error	1. Notification service down → alert logged but not sent
Actor(s) / Initiator(s)	System (extends Monitor Budget Threshold)
Trigger	Total expenses exceed the defined budget threshold
Standard Process (Main Success Scenario)	1. System monitors total expenses after each addition 2. System compares total to budget threshold 3. If threshold exceeded → system triggers alert 4. System sends notification to trip leader and members
Alternative Processes (Alternative/Other Scenarios)	Budget updated to higher limit → alert cleared

UC-18

System (extends Vote on Activities)

Anonymous Voting

Short-Description / Goal	Ensures that votes on sensitive activities are cast anonymously
Preconditions	1. Activity is marked as sensitive 2. Voting is active
Postconditions	Votes are recorded without revealing voter identity
Error Situations – System State in the Event of an Error	1. Anonymization fails → voting paused
Actor(s) / Initiator(s)	System (extends Vote on Activities)
Trigger	Activity is marked as sensitive
Standard Process (Main Success Scenario)	1. System detects activity is marked sensitive 2. System enables anonymous mode for voting 3. Members cast votes without names attached 4. System tallies votes 5. System reveals result only, not individual votes
Alternative Processes (Alternative/Other Scenarios)	Activity unmarked as sensitive → normal voting resumes

UC-19

Trip Member / Trip Leader

Exercise Weighted Voting

Short-Description / Goal	Allows certain members to have more voting weight based on role or setting
Preconditions	1. Weighted voting is enabled 2. Voting is active
Postconditions	Votes are tallied using assigned weights
Error Situations – System State in the Event of an Error	1. Weight values invalid → system uses default equal weights
Actor(s) / Initiator(s)	Trip Member / Trip Leader
Trigger	Trip leader enables weighted voting
Standard Process (Main Success Scenario)	1. Trip leader enables weighted voting 2. System assigns weight values to members 3. Members cast votes 4. System multiplies votes by assigned weights 5. System tallies weighted results 6. System displays outcome
Alternative Processes (Alternative/Other Scenarios)	Tie occurs → trip leader exercises tiebreaking authority

UC-20

System (extends Vote on Activities)

Auto Close Voting

Short-Description / Goal	System automatically closes voting when the deadline is reached
Preconditions	1. Voting is active 2. A deadline has been set
Postconditions	Voting is closed and final tally is recorded
Error Situations – System State in the Event of an Error	1. System clock error → voting remains open until manual close
Actor(s) / Initiator(s)	System (extends Vote on Activities)
Trigger	Voting deadline is reached
Standard Process (Main Success Scenario)	1. System monitors voting deadline 2. Deadline is reached 3. System closes voting automatically 4. System records final tally 5. System notifies all members of result
Alternative Processes (Alternative/Other Scenarios)	All members vote early → voting closes before deadline

UC-21

Trip Member

Upload Documents

Short-Description / Goal	Allows trip members to upload trip-related documents such as visas and tickets
Preconditions	1. User is logged in 2. User is a member of the trip
Postconditions	Document is uploaded, encrypted, and accessible to authorized members
Error Situations – System State in the Event of an Error	1. Unsupported file type → upload rejected 2. File too large → upload rejected
Actor(s) / Initiator(s)	Trip Member
Trigger	User clicks 'Upload Document'
Standard Process (Main Success Scenario)	1. User opens documents section 2. User selects file to upload 3. System validates file 4. System encrypts document 5. System stores document 6. System grants access based on permissions
Alternative Processes (Alternative/Other Scenarios)	Encryption fails → upload aborted

UC-22

System (included in Approve Final Settlement)

Split Expenses Unevenly

Short-Description / Goal	System supports splitting expenses unevenly among trip members
Preconditions	1. Expenses have been logged 2. Members agree to custom split
Postconditions	Expenses are split according to custom percentages or amounts
Error Situations – System State in the Event of an Error	1. Split percentages do not total 100% → error shown
Actor(s) / Initiator(s)	System (included in Approve Final Settlement)
Trigger	Members agree to uneven expense split
Standard Process (Main Success Scenario)	1. User opens settlement settings 2. User selects uneven split option 3. User enters custom share for each member 4. System validates total 5. System applies custom split 6. System displays updated shares
Alternative Processes (Alternative/Other Scenarios)	Member rejects split → negotiation continues

UC-23

System (included in Add Expenses)

Convert Currency

Short-Description / Goal	System automatically converts foreign currency expenses to the trip's base currency
Preconditions	1. Exchange rates are up to date 2. Expense has a currency specified
Postconditions	Expense is converted and stored in base currency
Error Situations – System State in the Event of an Error	1. Exchange rate unavailable → user prompted to enter manually
Actor(s) / Initiator(s)	System (included in Add Expenses)
Trigger	Expense is entered in a foreign currency
Standard Process (Main Success Scenario)	1. User enters expense in foreign currency 2. System detects currency mismatch 3. System fetches current exchange rate 4. System converts amount 5. System stores converted expense
Alternative Processes (Alternative/Other Scenarios)	Rate outdated → system flags and prompts admin to update

UC-24

System (included in Add Expenses)

Monitor Budget Threshold

Short-Description / Goal	System continuously monitors total expenses against the defined budget threshold
Preconditions	1. Budget is set for the trip 2. Expenses are being added
Postconditions	Budget status is updated; alert triggered if threshold exceeded
Error Situations – System State in the Event of an Error	1. Budget not set → monitoring skipped
Actor(s) / Initiator(s)	System (included in Add Expenses)
Trigger	Expense is added to the trip
Standard Process (Main Success Scenario)	1. System retrieves current total expenses 2. System compares total to budget threshold 3. If below threshold → no action 4. If threshold reached or exceeded → notify budget exceeded use case triggered
Alternative Processes (Alternative/Other Scenarios)	Budget threshold changed → system recalculates immediately

UC-25

Trip Member

Manage Health Info

Short-Description / Goal	Allows members to manage their sensitive health information for trip planning
Preconditions	1. User is logged in
Postconditions	Health info is saved securely
Error Situations – System State in the Event of an Error	1. Incomplete form → not saved
Actor(s) / Initiator(s)	Trip Member
Trigger	User opens health info settings
Standard Process (Main Success Scenario)	1. User opens health settings 2. User enters or updates health details 3. System saves data securely 4. System marks data as sensitive
Alternative Processes (Alternative/Other Scenarios)	User cancels → no changes saved

UC-26

Trip Member

View Trip

Short-Description / Goal	Allows members to view all trip details including itinerary and members
Preconditions	1. User is logged in 2. User is a member of the trip
Postconditions	Trip details are displayed
Error Situations – System State in the Event of an Error	1. Trip not found → error shown
Actor(s) / Initiator(s)	Trip Member
Trigger	User opens trip page
Standard Process (Main Success Scenario)	1. User clicks on trip 2. System retrieves trip data 3. System displays itinerary, members, activities, and expenses
Alternative Processes (Alternative/Other Scenarios)	Trip is private → access denied for non-members

UC-27

Trip Member / Trip Leader

Assign Responsibilities

Short-Description / Goal	Allows leaders or members to assign specific tasks to trip members
Preconditions	1. User is logged in 2. Trip exists
Postconditions	Responsibility is assigned and member is notified
Error Situations – System State in the Event of an Error	1. Member not found → assignment fails
Actor(s) / Initiator(s)	Trip Member / Trip Leader
Trigger	User opens responsibilities section
Standard Process (Main Success Scenario)	1. User opens responsibilities section 2. User selects task 3. User assigns task to a member 4. System saves assignment 5. System notifies assigned member
Alternative Processes (Alternative/Other Scenarios)	Member declines → task returned to unassigned

UC-28

External System

Optimize Route

Short-Description / Goal	External system provides optimized travel routes for the trip itinerary
Preconditions	1. Trip has multiple destinations
Postconditions	Optimized route is returned and displayed
Error Situations – System State in the Event of an Error	1. External system unavailable → fallback message shown
Actor(s) / Initiator(s)	External System
Trigger	System requests route optimization
Standard Process (Main Success Scenario)	1. System sends destinations to external API 2. External system calculates optimal route 3. System receives route data 4. System displays route on map
Alternative Processes (Alternative/Other Scenarios)	No optimal route → multiple options presented

UC-29

External System

Check Visa Requirements

Short-Description / Goal	External system provides visa requirement info based on nationality and destination
Preconditions	1. User is logged in 2. Destination is set
Postconditions	Visa requirements are displayed
Error Situations – System State in the Event of an Error	1. External API error → cached data shown or error message
Actor(s) / Initiator(s)	External System
Trigger	User requests visa info for destination
Standard Process (Main Success Scenario)	1. User requests visa info 2. System sends request to external API 3. API returns visa requirements 4. System displays results to user
Alternative Processes (Alternative/Other Scenarios)	Country not found → user prompted to check manually

UC-30

External System

Recommend Activity

Short-Description / Goal	External system recommends activities based on destination and user preferences
Preconditions	1. Trip has a destination set
Postconditions	Activity recommendations are displayed
Error Situations – System State in the Event of an Error	1. API unavailable → no recommendations shown
Actor(s) / Initiator(s)	External System
Trigger	System requests activity suggestions
Standard Process (Main Success Scenario)	1. System sends destination to external recommendation API 2. API returns suggested activities 3. System displays recommendations to members
Alternative Processes (Alternative/Other Scenarios)	No recommendations → system shows generic popular activities

UC-31

System (included in Add/Modify Activity)

Calculate Travel Time

Short-Description / Goal	System calculates estimated travel time between activity locations
Preconditions	1. At least two activity locations exist 2. External mapping service is available
Postconditions	Travel time is calculated and displayed between activities
Error Situations – System State in the Event of an Error	1. Mapping service unavailable → travel time not shown
Actor(s) / Initiator(s)	System (included in Add/Modify Activity)
Trigger	Activity with travel is added to itinerary
Standard Process (Main Success Scenario)	1. User adds activity with a location 2. System retrieves previous activity location 3. System requests travel time from mapping service 4. System receives estimated duration 5. System displays travel time between activities
Alternative Processes (Alternative/Other Scenarios)	No route found → user notified to verify manually

UC-32

Trip Leader

Confirm/Reject Proposed Activities

Short-Description / Goal	Allows Trip Leader to approve or reject activities proposed by members
Preconditions	1. User is logged in 2. User is Trip Leader 3. At least one activity proposal exists
Postconditions	Activity is confirmed or rejected; members are notified
Error Situations – System State in the Event of an Error	1. No proposals exist → nothing to review
Actor(s) / Initiator(s)	Trip Leader
Trigger	Trip leader reviews proposed activities
Standard Process (Main Success Scenario)	1. Trip Leader opens proposals list 2. Trip Leader reviews each proposed activity 3. Trip Leader clicks confirm or reject 4. System updates activity status 5. System notifies relevant members
Alternative Processes (Alternative/Other Scenarios)	Leader leaves without action → proposals remain pending

UC-33

Trip Leader

Revert Itinerary Version

Short-Description / Goal	Allows the trip leader to revert the trip itinerary to a previous version
Preconditions	1. User is logged in 2. User is Trip Leader 3. Change history exists
Postconditions	Itinerary is reverted to the selected previous version
Error Situations – System State in the Event of an Error	1. No previous version available → revert not possible
Actor(s) / Initiator(s)	Trip Leader
Trigger	Trip leader decides to undo changes
Standard Process (Main Success Scenario)	1. Trip Leader opens change history 2. Trip Leader selects a previous version 3. Trip Leader clicks revert 4. System asks for confirmation 5. System restores selected version 6. System notifies all members of the revert
Alternative Processes (Alternative/Other Scenarios)	Leader cancels → current version remains unchanged

UC-34

Trip Leader

Manage Member Permissions

Short-Description / Goal	Allows trip leader to control what actions each member can perform
Preconditions	1. User is logged in 2. User is Trip Leader
Postconditions	Permissions are updated and applied
Error Situations – System State in the Event of an Error	1. Invalid permission level → not applied
Actor(s) / Initiator(s)	Trip Leader
Trigger	User opens member settings
Standard Process (Main Success Scenario)	1. User opens member management 2. User selects member 3. User assigns or removes permissions 4. System saves changes 5. System applies new access rules
Alternative Processes (Alternative/Other Scenarios)	Leader removes self → system prevents action

UC-35

Trip Leader

View Change History

Short-Description / Goal	Allows the trip leader to view a log of all changes made to the trip
Preconditions	1. User is logged in 2. User is Trip Leader
Postconditions	Change history is displayed
Error Situations – System State in the Event of an Error	1. No changes recorded → empty log shown
Actor(s) / Initiator(s)	Trip Leader
Trigger	User opens change history log
Standard Process (Main Success Scenario)	1. User opens change history 2. System retrieves log 3. System displays list of changes with timestamps and authors
Alternative Processes (Alternative/Other Scenarios)	Leader reverts change → itinerary rolled back

UC-36

Trip Leader

Access Control for Doc

Short-Description / Goal	Allows the trip leader to control who can view or edit uploaded documents
Preconditions	1. User is logged in 2. User is Trip Leader 3. Documents exist in the trip
Postconditions	Access permissions are applied to the selected document
Error Situations – System State in the Event of an Error	1. Permission conflict → system applies most restrictive rule
Actor(s) / Initiator(s)	Trip Leader
Trigger	Leader sets document access permissions
Standard Process (Main Success Scenario)	1. Trip Leader opens documents section 2. Trip Leader selects a document 3. Trip Leader sets access permissions per member 4. System saves and applies permissions 5. Members see only documents they are authorized to view
Alternative Processes (Alternative/Other Scenarios)	Leader grants full access → all members can view and edit

UC-37

Emergency Contact

Receive Trip Itinerary

Short-Description / Goal	Allows an emergency contact to receive a copy of the trip itinerary
Preconditions	1. Trip itinerary is finalized 2. Emergency contact info is provided
Postconditions	Emergency contact receives the trip itinerary
Error Situations – System State in the Event of an Error	1. Invalid contact info → itinerary not delivered
Actor(s) / Initiator(s)	Emergency Contact
Trigger	Trip leader shares itinerary with emergency contact
Standard Process (Main Success Scenario)	1. Trip Leader triggers share to emergency contact 2. System retrieves finalized itinerary 3. System sends itinerary to emergency contact via email 4. Emergency contact receives itinerary
Alternative Processes (Alternative/Other Scenarios)	Contact unreachable → system retries or notifies leader

UC-38

Trip Member

Share Itinerary Member

Short-Description / Goal	Allows members to share the trip itinerary with an emergency contact
Preconditions	1. User is logged in 2. Trip itinerary exists
Postconditions	Itinerary is shared with the emergency contact
Error Situations – System State in the Event of an Error	1. Sharing fails → member notified
Actor(s) / Initiator(s)	Trip Member
Trigger	Member shares itinerary with emergency contact
Standard Process (Main Success Scenario)	1. User opens itinerary 2. User clicks share 3. User enters emergency contact details 4. System sends itinerary copy 5. System confirms delivery
Alternative Processes (Alternative/Other Scenarios)	Contact email invalid → user prompted to re-enter

UC-39

Emergency Contact

Receive Emergency Alert

Short-Description / Goal	Emergency contact receives an alert when an emergency is reported during the trip
Preconditions	1. Emergency contact info is registered 2. An emergency is reported by a member
Postconditions	Emergency contact is notified with trip and member details
Error Situations – System State in the Event of an Error	1. Contact unreachable → alert logged and retried
Actor(s) / Initiator(s)	Emergency Contact
Trigger	Emergency alert is triggered during the trip
Standard Process (Main Success Scenario)	1. Member or system triggers emergency alert 2. System retrieves emergency contact info 3. System sends alert with member and trip details 4. Emergency contact receives notification 5. System logs alert event
Alternative Processes (Alternative/Other Scenarios)	No emergency contact set → alert sent to system admin

UC-40

User (abstract)

Login

Short-Description / Goal	Allows any user to authenticate and access the system
Preconditions	1. User has an account
Postconditions	User is authenticated and redirected to dashboard
Error Situations – System State in the Event of an Error	1. Wrong credentials → access denied 2. Account locked → user notified
Actor(s) / Initiator(s)	User (abstract)
Trigger	User opens login page
Standard Process (Main Success Scenario)	1. User opens login page 2. User enters email and password 3. System validates credentials 4. System grants access 5. System redirects to dashboard
Alternative Processes (Alternative/Other Scenarios)	Forgot password → user redirected to reset flow

UC-41

User (abstract)

Logout

Short-Description / Goal	Allows user to securely end their session
Preconditions	1. User is logged in
Postconditions	Session is terminated
Error Situations – System State in the Event of an Error	1. Session already expired → handled gracefully
Actor(s) / Initiator(s)	User (abstract)
Trigger	User clicks 'Logout'
Standard Process (Main Success Scenario)	1. User clicks logout 2. System ends user session 3. System redirects to login page
Alternative Processes (Alternative/Other Scenarios)	Session timeout → auto logout

UC-42

User (abstract)

Manage Profile

Short-Description / Goal	Allows users to view and edit their personal profile information
Preconditions	1. User is logged in
Postconditions	Profile is updated
Error Situations – System State in the Event of an Error	1. Invalid data → not saved
Actor(s) / Initiator(s)	User (abstract)
Trigger	User opens profile settings
Standard Process (Main Success Scenario)	1. User opens profile page 2. User edits personal info 3. User saves changes 4. System validates and saves
Alternative Processes (Alternative/Other Scenarios)	User cancels → no changes applied

UC-43

User (abstract)

Change Password

Short-Description / Goal	Allows users to update their account password
Preconditions	1. User is logged in
Postconditions	Password is changed successfully
Error Situations – System State in the Event of an Error	1. Old password incorrect → rejected 2. New password too weak → rejected
Actor(s) / Initiator(s)	User (abstract)
Trigger	User requests password change
Standard Process (Main Success Scenario)	1. User opens security settings 2. User enters old password 3. User enters new password 4. System validates 5. System updates password 6. System confirms change
Alternative Processes (Alternative/Other Scenarios)	Forgot password → email reset link sent

UC-44

System Admin

Manager User Accounts

Short-Description / Goal	Allows system admin to create, edit, suspend, or delete user accounts
Preconditions	1. Admin is logged in
Postconditions	User account changes are saved
Error Situations – System State in the Event of an Error	1. User not found → error shown 2. Cannot delete active admin → prevented
Actor(s) / Initiator(s)	System Admin
Trigger	Admin opens user management panel
Standard Process (Main Success Scenario)	1. Admin opens user management 2. Admin searches for user 3. Admin selects action (edit/suspend/delete) 4. System performs action 5. System logs the operation
Alternative Processes (Alternative/Other Scenarios)	Invalid action → error message shown

UC-45

System Admin

Monitor System Health

Short-Description / Goal	Allows admin to monitor server status, uptime, and performance metrics
Preconditions	1. Admin is logged in
Postconditions	System health status is displayed
Error Situations – System State in the Event of an Error	1. Monitoring service down → fallback message shown
Actor(s) / Initiator(s)	System Admin
Trigger	Admin opens system dashboard
Standard Process (Main Success Scenario)	1. Admin opens system health panel 2. System retrieves health metrics 3. System displays uptime, load, and alerts
Alternative Processes (Alternative/Other Scenarios)	Alert triggered → admin receives notification

UC-46

System Admin

Update Exchange Rates

Short-Description / Goal	Allows admin to update currency exchange rates used across the system
Preconditions	1. Admin is logged in
Postconditions	Exchange rates are updated system-wide
Error Situations – System State in the Event of an Error	1. Invalid rate data → not applied
Actor(s) / Initiator(s)	System Admin
Trigger	Admin triggers rate update
Standard Process (Main Success Scenario)	1. Admin opens exchange rate settings 2. Admin inputs or fetches new rates 3. System validates rates 4. System saves and applies rates
Alternative Processes (Alternative/Other Scenarios)	Fetch fails → admin enters rates manually

UC-47

System Admin

View Global Statistics

Short-Description / Goal	Allows admin to view aggregated system usage and trip statistics
Preconditions	1. Admin is logged in
Postconditions	Statistics are displayed
Error Situations – System State in the Event of an Error	1. No data available → empty state shown
Actor(s) / Initiator(s)	System Admin
Trigger	Admin opens statistics panel
Standard Process (Main Success Scenario)	1. Admin opens statistics panel 2. System aggregates data 3. System displays charts and metrics
Alternative Processes (Alternative/Other Scenarios)	Filter applied → data refreshed by criteria