

Transfer Demo Database ERD

PostgreSQL database: hlrms_transfer

transfer_profiles		
Key	Column	Type
PK UQ UQ	id	UUID
	user_id	UUID
	transfer_id	VARCHAR(16)
	email	VARCHAR(320)
	display_name	VARCHAR(200)
	created_at	TIMESTAMPTZ
	updated_at	TIMESTAMPTZ
Constraints • UNIQUE (user_id) • UNIQUE (transfer_id)		

Participant Identity References
sender_user_id / recipient_user_id
(No Physical FK)

wallet_balances		
Key	Column	Type
PK FK	id	BIGSERIAL
	user_id	UUID
	currency	VARCHAR(3)
	balance	NUMERIC(20, 2)
	version	BIGINT
	created_at	TIMESTAMPTZ
	updated_at	TIMESTAMPTZ
Constraints • FOREIGN KEY (user_id) REFERENCES transfer_profiles(user_id) ON DELETE CASCADE • UNIQUE (user_id, currency) • CHECK (balance >= 0) • CHECK (currency IN ('USD', 'EUR', 'TRY', 'SYP'))		

transfer_transactions		
Key	Column	Type
PK UQ	id	UUID
	request_id	UUID
	sender_user_id	UUID
	recipient_user_id	UUID
	sender_transfer_id	VARCHAR(16)
	recipient_transfer_id	VARCHAR(16)
	sender_display_name	VARCHAR(200)
	recipient_display_name	VARCHAR(200)
	amount	NUMERIC(20, 2)
	currency	VARCHAR(3)
	created_at	TIMESTAMPTZ
	Constraints • UNIQUE (request_id) • CHECK (amount > 0) • CHECK (sender_user_id <> recipient_user_id)	

Legend

— Physical Foreign Key

- - - Logical Reference (No Physical FK)

PK = Primary Key

FK = Foreign Key

UQ = Unique Constraint

Notes

- transfer_profiles.user_id is a logical identity from the Auth domain.
- transfer_transactions.request_id logically references HLRMS requests.id.
- sender_user_id and recipient_user_id are logical participant identities; no database FK is declared.
- All timestamp columns use PostgreSQL TIMESTAMPTZ.