

ST7000

**SMALL TETRA RADIO** 

The ST7000 small TETRA radio combines a small and discreet form, simple user interface and clear audio. With a hybrid internal and external antenna system, the ST7000 fits easily in a pocket. The touch sensitive buttons, integrated Bluetooth® 4.1 wireless technology, reversible USB-C connector for charging, and 3.5mm audio connector make the ST7000 a flexible, modern TETRA radio.



# **KEY FEATURES**

- Small and discreet design
- Simple and intuitive user interface
- Vibrate alert and haptic feedback for discreet use
- White OLED screen with touch UI for easy navigation
- Loud and clear audio
- 3.5 mm audio connector for maximum accessory compatibility
- Reversible USB-C connector for flexible charging and programming
- Enhanced coverage with 1.8W transmit power
- Durable with IP54 and MIL-STD 810 F/G rating
- Long-life battery with up to 20 hours of use
- Integrated Bluetooth 4.1 wireless technology
- GPS and GLONASS for location services













# **ST7000 SPECIFICATIONS**

GENERAL	
Dimensions H x W x D	107 x 60 x 19mm
Weight Including Battery and Antenna	173g
Battery	Removable 2300 mAh IMPRES Li-lon
Battery Performance -	Duty Cycle 5/5/90 > 20 Hours (380-430MHz) / > 19 Hours (800MHz)
	Duty Cycle 5/35/60 > 17 Hours
Audio	Speech Loudness at 30cm: 94 Phon
	Audio Output Power at Rated / Max: 0.9 W
	Audio Distortion at Rated: 1.0 %
RF SPECIFICATIONS	
Frequency Bands	380-430 MHz, 800 MHz
Transmitter RF	Power Class 3L (1.8W) & Class 4 (1W)
Receiver Class	A and B
Rx Static Sensitivity (UHF)	UHF: -116dBm (min); -118dBm (typical) 800 MHz: -114dBm (min); -116dBm (typical)
Rx Dynamic Sensitivity	UHF: -107 dBm (min); -109 dBm (typical) 800 MHz: -105 dBm (min); -107 dBm (typical)
ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature °C	-20 to +55
Storage Temperature °C	-30 to +85
Humidity	ETS 300-019-1-7 Class 7.3E, MIL STD 810 F, G
Dust and Water Ingress Protection —	IP54 (All Connectors are IP67 Rated)
	Dust, Driving Rain Protection
Shock, Drop and Vibration	ETS 300-019 1-7 class 5M3; MIL-STD 810 F/G
MAIN VOICE SERVICES	
Full Duplex TMO Private, PABX, PSTN, Emergency	
Half Duplex TMO Private, Group, Emergency	
Half Duplex DMO Private, Group, Emergency	
Inter-MNI, Gateway, Repeater Compatible	
PTT Double Push	
Adaptive Audio Control (AGC)	
Emergency Call Management	
Tactical Emergency Group Call to ATTACHED Talkgroup	
Non-Tactical Emergency Group Call to DEDICATED Talkgroup	
HOT MIC Emergency - Hands Free in Moments That Matter	
Emergency Status Msg Sent to Dispatch Console	
Preemptive Priority Calls	
DMO Repeater and Gateway Services	
Works with DMO Repeaters and Gateways*	
BLUETOOTH AUDIO & DATA SERVICES	
Bluetooth Versions Supported	Bluetooth 2.1 +EDR, Bluetooth 4.1, Bluetooth Smart (BTLE)
Bluetooth Security	Bluetooth 2.1 Introduces Mandatory Encryption with Secure Simple Pairing (SSP), Easier Pairing and Preventing Sniffing / Hacking
Bluetooth Audio	HeadSet Profile, Fast PTT with Motorola Solutions Accessories
Bluetooth Data Services	Serial Port Profile, Dial Up Networking Profile, Discovery Mode, Generic Access Profile, Generic Attributes Profile (GATT), Heart Rate Profile, Battery Service Profile, Devices Info Profile.
LOCATION SERVICES	
Constellations Supported	GPS and GLONASS
Simultaneous Satellites —	12
	Integrated Internal Antenna
Tracking Sensitivity	-163 dBm
Accuracy	< 5metre (50% probable) @ -130 dBm
Protocols	ETSI LIP, LRRP

<sup>\*</sup> Does not work as a DMO repeater.



# **ST7000 SPECIFICATIONS**

## **USER INTERFACE**

# **Hard Keys**

High Tactility PTT

Power / Wakeup Button

Talkgroup Change Rocker Switch

Volume up / down

2 Configurable One Touch Buttons, Extensive List of Functions

#### **Touch User Interface**

Touch sensitive menu icons usable with gloves or in the rain

Simplified user interface

Menu editor, simplify and tailor to user needs

#### **Display**

PMOLED 128 x 64 pixels, white

#### **Simplified User Interface**

Favourite Talkgroups

Favourite Contacts

Bluetooth

Radio Settings

My Info

Language Options

#### **Advanced User Interface**

Talkgroups – TMO Folders: 256, TMO Unique: 10,000

Talkgroups – DMO Folders: 128, DMO Groups: 2,000

Talkgroups – Extended Folders: 330, Mixed TMO/DMO Groups: up to 15 groups per folder

Scan Lists - 40 lists of up to 20 groups

Contacts - up to 1000 with 6 numbers per contact (max 2000 unique numbers)

Fast/Flexible Call Set Up / Answer

Multiple Ring Tones possible

## **Text & Status Messaging**

Status Messages sent from programmable button\*\*

#### **SECURITY OPTIONS**

Enhanced Security - OTAR/DMO SCK

Authentication (Mutual)

Air Interface Encryption (ETSI / SFPG TEA Algorithms)

Security Class 1, 2, 3 and 3G support

End to End Encryption: Motorola CRYPTR micro Hardware Module

BOS Smart Card support

Permanent Disable (ETSI, V2-Customer Restore)

Temporary Disable (Stun)

### **DATA & MESSAGING SERVICES**

Secondary Control Channel

ETSI and Enhanced AT Commands (including Voice Control and Short Data)

TNP1 - Support simultaneous Packet Data and Short Data Services over PEI

iTM Fleet Management (Remote Programming)



<sup>\*\*</sup> SDS messaging, Call-out and Object-call features currently not supported.



For more information, please visit: www.motorolasolutions.com/ST7000

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2019 Motorola Solutions, Inc. All rights reserved. (05-2019)



