Envelope Encryption and Key Provider

P01_S05 · 2026-11-13 · Encrypts every stored secret under its own data key, wrapped by a pluggable key provider, with a master-key rotation that never touches ciphertext.


What it does

- Connectors (P01_S07) will store API keys and passwords through `SecretService`. Each value is encrypted with AES-256-GCM under a fresh 32-byte data key (DEK), bound to its workspace and secret id.
- The DEK is wrapped by a master key (KEK) from a local keyring in `MASTER_KEYS` or `MASTER_KEYS_FILE`. The database holds only ciphertext, a wrapped DEK and the id of the key that wrapped it.
- The API refuses to start with a missing or weak keyring: the all-zero placeholder, a base64 passphrase, or anything other than 32 random bytes.
- `flowbuilder keys rotate` re-wraps every DEK under a new master key, in every workspace. Reruns are safe, and an interrupted run picks up where it stopped.

How it works

1. **Put.** The caller opens a `workspace_transaction` and calls `SecretService.put`. It generates the secret id and a fresh DEK, then seals the value with associated data `workspace_id.bytes + secret_id.bytes`.
2. **Wrap.** `LocalKeyProvider.wrap` encrypts the DEK with AES-GCM under the first keyring key, with the same workspace and secret context. The row is inserted with `ciphertext`, `nonce`, `wrapped_dek`, `key_id` and `last4`, where `last4` is filled only for values of 12+ characters.
3. **Get.** `SecretService.get` reads the row, unwraps the DEK with the row's `key_id`, and opens the ciphertext. Moving or swapping any column between rows or workspaces fails with `SecretDecryptionError` instead of returning another secret.
4. **Rotate a value.** `SecretService.rotate` stores a new value under the same id, with a new DEK and nonce, so connectors keep their `secret_ref`.
5. **Rotate the master key.** An operator puts the new key first in the keyring. `rewrap_data_keys` connects as the schema owner and works in batches of 100, locking rows with `FOR UPDATE`. It unwraps each old DEK and wraps it under the active key, and changes only `wrapped_dek` and `key_id`.
6. **Report.** The CLI prints `rewrapped N data keys to <key_id>; M remain under other keys`. It exits 1 while rows remain, or on an unreadable row or a provider that breaks its contract.

Visual



The rotation only ever reads and writes the key columns:

```
SELECT id, workspace_id, wrapped_dek, key_id FROM secrets
 WHERE key_id <> :active_key_id ORDER BY id LIMIT :batch_size FOR UPDATE;
UPDATE secrets SET wrapped_dek = :wrapped_dek, key_id = :key_id WHERE id = :id;
```

Code map

File path	Class / Function	Role
`backend/src/app/crypto/envelope.py`	`seal`, `open_sealed`, `new_data_key`, `secret_aad`, `last4`	AES-256-GCM for one value; associated data and `last4` rules
`backend/src/app/crypto/key_provider.py`	`KeyProvider`	Protocol: `active_key_id`, `wrap(dek, context)`, `unwrap(wrapped, key_id, context)`
`backend/src/app/crypto/key_provider.py`	`LocalKeyProvider`	Wraps under the first keyring key, unwraps under any
`backend/src/app/crypto/key_provider.py`	`parse_master_keys`, `load_local_key_provider`	Read and validate the keyring; refuse weak keys
`backend/src/app/crypto/key_provider.py`	`local_key_id`	Key id: `local:` + 16 hex chars of HMAC-SHA256
`backend/src/app/crypto/key_provider.py`	`KeyringError`, `UnknownKeyIdError`, `KeyUnwrapError`	Errors that name sources and key ids, never keys
`backend/src/app/crypto/service.py`	`SecretService.put` / `get` / `rotate`	Store, read and replace a secret in the caller's transaction
`backend/src/app/crypto/service.py`	`SecretNotFoundError`, `SecretDecryptionError`	Errors naming the workspace and secret only

File path	Class / Function	Role
`backend/src/app/crypto/rotation.py`	`rewrap_data_keys`, `RewrapReport`	Batched re-wrap of every DEK under the active key
`backend/src/app/crypto/rotation.py`	`DataKeyRewrapError`, `KeyProviderContractError`	Stop on an unreadable row or a misbehaving provider
`backend/src/app/cli.py`	`main`, `build_parser`, `rotate_keys`	The `flowbuilder keys rotate` command and its exit codes
`backend/src/app/config.py`	`KeyringSettings`	Exactly one of `MASTER_KEYS` and `MASTER_KEYS_FILE`
`backend/src/app/main.py`	`create_app_from_environment`	Loads the keyring at startup, so a weak key stops the API
`backend/migrations/versions/0006_secrets_key_rotation_policies.py`	`upgrade`, `downgrade`	Owner SELECT and UPDATE policies on `secrets`
`infra/docker-compose.yml`	`api`, `rotate-keys`	`MASTER_KEYS` for the API; one-shot rotation (profile `maintenance`)
`backend/tests/crypto/`	`test_envelope`, `test_key_provider`, `test_service`, `test_rotation`	Property, AAD, rotation, resume and lock-race tests

Notes

- **Configuration:** `MASTER_KEYS` (the compose stack uses this) or `MASTER_KEYS_FILE`. Generate a key with `openssl rand -base64 32`. The API and `rotate-keys` hold the keys; the worker does not.
- **Running a rotation:** `docker compose --env-file .env -f infra/docker-compose.yml run --build --rm rotate-keys`. Follow the two-phase rollout in `docs/key-providers.md` before running it.
- **API:** no endpoints yet. P01_S07 adds the connector routes that call `SecretService`.
- **Limitations:**
  - The owner policies guard against mistakes; they are not a security boundary against the owner role.
  - One row whose key is missing from the keyring stops every rotation until it is resolved.
  - A random wrap nonce limits one master key to about 2^32 wraps.
  - Vault and AWS KMS providers are designed in `docs/key-providers.md`, not built (P06_S09).