ShelfSense: AI-Based Retail Merchandising Audit

Progress brief, Sprints 1–4

CSE499A, Section 10, Group 1
Syed Ashfaq Shafin, Sadid Mehal Habib, Shafil Ahmed, Rutaba Adiba Rahman
North South University, 18 October 2026

Summary

ShelfSense turns a merchandiser's phone video of store shelves into an audit report backed by evidence. Sprints 1–3 are complete. In Sprint 4 we recorded 111 supermarket videos, trained a product detector that reaches **mAP50 0.913** on SKU-110K, and showed that asking the vision-language model (VLM) about one detected product at a time **doubles the brands it finds** (recall 0.30 → 0.63) compared with asking about the whole frame.

Problem and approach

Brand companies (Coca-Cola, Pepsi/Transcom, Akij, …) pay shops for branded fridges and prime shelf placement, and send field auditors to check compliance. Auditors can be bribed and report false results. ShelfSense replaces the auditor's word with *verifiable evidence*: every finding points to a keyframe and timestamp a person can check. Because a false "competitor in your fridge" accuses an honest shopkeeper, the system favours *precision over recall* for violations. Key KPIs: cooler purity, paid placement, out-of-stock and share of shelf.

VLMs cannot count densely packed products, so the pipeline is hybrid: **(1)** extract sharp, non-duplicate keyframes → **(2)** a YOLO nano detector finds every product → **(3)** a small VLM (Qwen2-VL-2B) reads the brand of each product crop → **(4)** rules compute the KPIs and write the report. Everything runs on student hardware: laptops and free Kaggle GPUs.

Progress by sprint

Sprint	Focus	Status	Main result
1	Setup and problem definition	Done	Scope, KPIs, repository, six-sprint plan
2	Data and keyframe extraction	Done	Extractor with blur and duplicate filters; Crete blur score replaced Laplacian variance, which failed on real video
3	Baseline VLM (zero-shot)	Done	Prompts fixed the answer format but not perception: invented brands (precision 0.13–0.30), every count "10"
4	Product detection	Mostly done	Detector mAP50 0.913; crop-based brand reading doubles recall; mAP on our own frames pending corrected labels
5	Integration and rule engine	Next	End-to-end JSON audit report
6	Evaluation and demo	Planned	Metrics against manual counts, demo app

Latest update (Sprint 4)

New footage

111 own shelf videos from a Bangladeshi supermarket (about 22 minutes; duplicates found by SHA-256 and stock clips removed). Split into 82 train and 29 test videos by blocks of neighbouring clips, so the same shelf never appears in both sets. Keyframe extraction kept 4,491 of 5,069 sampled frames; the videos gave the first real test of the blur filter.

Product detector

YOLOv8n, one class *product*, trained on 2,000 SKU-110K shelf photos (30 epochs, 2.7 hours on a 4 GB laptop GPU) and evaluated on 500 held-out photos.

Setting	mAP50	mAP50-95	Precision	Recall
1,024 px, up to 1,000 boxes per image (chosen)	**0.913**	**0.564**	0.897	0.844
1,024 px, up to 299 boxes	0.889	0.549	0.897	0.833
640 px (default), up to 1,000 boxes	0.866	0.510	0.875	0.792

Dense shelves need both settings: one photo holds 718 products. On all 4,558 keyframes (our videos plus 67 from the stock clips) the detector found 151,279 products (median 29 per frame). It works on packed shelves seen from a normal distance but misses large products close to the camera (Fig. 1).



Figure 1: Detector on our test videos. Left: large close-up cartons are missed. Right: packed shelves, where nearly every product is found.

Brand reading: product crops vs whole frames

On 12 frames from six drinks-shelf test videos we asked the same Qwen2-VL-2B model to list the brands in the whole frame, and to name the brand of 120 single-product crops cut by the detector.

Method	Usable answers	Brand precision	Brand recall
Whole frame, “list the brands”	6 of 12	1.00 (6 frames)	0.30
Detector crops, “which brand is this?”	12 of 12	0.94	**0.63**

Half of the whole-frame answers got stuck repeating words and gave no list. On crops, 48 of 67 readable products were named correctly. Wrong brands were rare (2 of 120) but both were “Coca-Cola”, so a person must still check the evidence before a violation is reported (Fig. 2). Brand labels for this test are drafts awaiting a team check; answers were matched to the list of 24 expected brands, so the numbers are an upper bound.




Figure 2: Single-product crops with the true brand and the VLM's answer.

Limitations

- The new videos show open shelves, not branded fridges, so cooler purity is not yet tested.
- Detector accuracy on our own frames is not measured yet; it needs corrected labels.
- Results on 6–29 videos show patterns, not statistical significance.

Next steps

1. Correct the detector's pre-labels on 222 of our keyframes (including empty gaps), fine-tune the detector on them and report mAP and counting error on our test frames.
2. Record branded beverage fridges, including some with competitor products, to test cooler purity.
3. Sprint 5: connect all stages into one pipeline that writes a JSON audit report with evidence (keyframe, timestamp, box) for every finding.