

# Lab: What's Wrong with the Network?

In this lab, you will learn the basics of Linux networking. You will also learn how to check network connectivity between two hosts, and gain a practical understanding of how DNS works and much more!

## Testing network connectivity

An easy way to check whether you have internet access on your Linux machine is by trying to reach any remote host (server) on the internet. This can be done by using the [ping] command.

To test whether you can reach [google.com], you can run the following command:

```
root@ubuntu-linux:~# ping google.com
PING google.com (172.217.1.14) 56(84) bytes of data.
64 bytes from iad23s25-in-f14.1e100.net (172.217.1.14): icmp_seq=1 ttl=55 time=38.7 ms
64 bytes from iad23s25-in-f14.1e100.net (172.217.1.14): icmp_seq=2 ttl=55 time=38.7 ms
64 bytes from iad23s25-in-f14.1e100.net (172.217.1.14): icmp_seq=3 ttl=55 time=40.4 ms
64 bytes from iad23s25-in-f14.1e100.net (172.217.1.14): icmp_seq=4 ttl=55 time=36.6 ms
64 bytes from iad23s25-in-f14.1e100.net (172.217.1.14): icmp_seq=5 ttl=55 time=40.8 ms
64 bytes from iad23s25-in-f14.1e100.net (172.217.1.14): icmp_seq=6 ttl=55 time=38.6 ms
64 bytes from iad23s25-in-f14.1e100.net (172.217.1.14): icmp_seq=7 ttl=55 time=38.9 ms
64 bytes from iad23s25-in-f14.1e100.net (172.217.1.14): icmp_seq=8 ttl=55 time=37.1 ms
^C
--- google.com ping statistics ---
8 packets transmitted, 8 received, 0% packet loss, time 66ms
rtt min/avg/max/mdev = 36.555/38.724/40.821/1.344 ms
```

Notice that without any options, the [ping] command keeps sending packets continuously, and it won't stop until you hit *Ctrl + C*.

You can use the [-c] option to specify the number of packets you want to send to a host. For example, to only send three packets to [google.com], you can run the following command:

```
root@ubuntu-linux:~# ping -c 3 google.com
PING google.com (172.217.1.14) 56(84) bytes of data.

64 bytes from iad23s25-in-f14.1e100.net (172.217.1.14): icmp_seq=1 ttl=55 time=39.3 ms
64 bytes from iad23s25-in-f14.1e100.net (172.217.1.14): icmp_seq=2 ttl=55 time=49.7 ms
64 bytes from iad23s25-in-f14.1e100.net (172.217.1.14): icmp_seq=3 ttl=55 time=40.8 ms

--- google.com ping statistics ---
3 packets transmitted, 3 received, 0% packet loss, time 59ms rtt min/avg/max/mdev =
39.323/43.267/49.708/4.595 ms
```

## Listing your network interfaces

You can list the available network interfaces on your system by viewing the contents of the [/sys/class/net] directory:

```
root@ubuntu-linux:~# ls /sys/class/net

eth0 lo
```

We have two network interfaces on my system:

1. [eth0]: The Ethernet interface
2. [lo]: The loopback interface

Notice that, depending on your computer's hardware, you may get different names for your network interfaces.

## The ip command

You can also use the [ip link show] command to view the available network interfaces on your system:

```
root@ubuntu-linux:~# ip link show
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN mode DEFAULT group
default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
2: eth0: <NO-CARRIER,BROADCAST,MULTICAST,UP> mtu 1500 qdisc pfifo_fast state DOWN mode
DEFAULT group default qlen 1000
    link/ether f0:de:f1:d3:e1:e1 brd ff:ff:ff:ff:ff:ff
3: wlan0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc mq state UP mode DORMANT
group default qlen 1000
    link/ether 10:0b:a9:6c:89:a0 brd ff:ff:ff:ff:ff:ff
```

## Checking your IP address

Without a cell phone number, you can't call any of your friends; similarly, your computer needs an IP address to connect to the internet. There are many different ways you can use to check your machine's IP address. You can use the old-school (yet still popular) [ifconfig] command followed by the name of your network interface that is connected to the internet:

```
root@ubuntu-linux:~# ifconfig eth0

eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST>  mtu 1500
    inet 172.17.0.2  netmask 255.255.0.0  broadcast 172.17.255.255
    ether 02:42:ac:11:00:02  txqueuelen 0  (Ethernet)
    RX packets 94183  bytes 100304746 (100.3 MB)
    RX errors 0  dropped 0  overruns 0  frame 0
    TX packets 146553  bytes 117106569 (117.1 MB)
    TX errors 0  dropped 0 overruns 0  carrier 0  collisions 0
```

You can also use the [-a] option to list all network interfaces:

```
root@ubuntu-linux:~# ifconfig -a

eth0: flags=4099<UP,BROADCAST,MULTICAST> mtu 1500
    ether f0:de:f1:d3:e1:e1 txqueuelen 1000 (Ethernet)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 0 bytes 0 (0.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
    device interrupt 20 memory 0xf2500000-f2520000

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
```

```

    inet6 ::1 prefixlen 128 scopeid 0x10<host>
    loop txqueuelen 1000 (Local Loopback)
    RX packets 4 bytes 156 (156.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 4 bytes 156 (156.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

wlan0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 172.16.1.73 netmask 255.255.255.0 broadcast 172.16.1.255
    inet6 fe80::3101:321b:5ec3:cf9 prefixlen 64 scopeid 0x20<link>
    ether 10:0b:a9:6c:89:a0 txqueuelen 1000 (Ethernet)
    RX packets 482 bytes 45500 (44.4 KiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 299 bytes 57788 (56.4 KiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

```

You can see from the output that I am only connected to the internet through my Wi-Fi interface ([wlan0]), and my IP address is [172.16.1.73].

You can also use the newer [ip] command to check your machine's IP address. For example, you can run the [ip address show] command to list and show the status of all your network interfaces:

```

root@ubuntu-linux:~# ip address show
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host
        valid_lft forever preferred_lft forever
2: eth0: <NO-CARRIER,BROADCAST,MULTICAST,UP> mtu 1500 qdisc pfifo_fast state
    DOWN link/ether f0:de:f1:d3:e1:e1 brd ff:ff:ff:ff:ff:ff
3: wlan0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc mq state
    UP link/ether 10:0b:a9:6c:89:a0 brd ff:ff:ff:ff:ff:ff
    inet 172.16.1.73/24 brd 172.16.1.255 scope global dynamic
        noprefixroute wlan0 valid_lft 85684sec preferred_lft 85684sec
    inet6 fe80::3101:321b:5ec3:cf9/64 scope link noprefixroute
        valid_lft forever preferred_lft forever

```

## Checking your gateway address

Your computer grabs an IP address from a **router**; this router is also referred to as the **default gateway** as it connects you to the outside world (internet). Those routers are everywhere; they are at your house, coffee shops, schools, hospitals, and so on.

You can check the IP address of your default gateway by running any of the following commands:

- [route -n]
- [netstat -rn]
- [ip route]

Let's start with the first command, [route -n]:

```
root@ubuntu-linux:~# route -n
```

Kernel IP routing table

Destination	Gateway	Genmask	Flags	Metric	Ref	Use	Iface
0.0.0.0	172.16.1.254	0.0.0.0	UG	600	0	0	wlan0
172.16.1.0	0.0.0.0	255.255.255.0	U	600	0	0	wlan0

You can see from the output that my default gateway IP address is [172.16.1.254]. Now let's try the second command, [netstat -rn]:

```
root@ubuntu-linux:~# netstat -rn
```

Kernel IP routing table

Destination	Gateway	Genmask	Flags	MSS	Window	irtt	Iface
0.0.0.0	172.17.0.1	0.0.0.0	UG	0	0	0	eth0
172.17.0.0	0.0.0.0	255.255.0.0	U	0	0	0	eth0

The output almost looks identical. Now the output differs a little bit with the third command, [ip route]:

```
root@ubuntu-linux:~# ip route
```

```
default via 172.16.1.254 dev wlan0 proto dhcp metric 600
172.16.1.0/24 dev wlan0 proto kernel scope link src 172.16.1.73 metric 600
```

The default gateway IP address is displayed on the first line: default via [172.16.1.254]. You should also be able to ping your default gateway:

```
root@ubuntu-linux:~# ping -c 2 ADD_YOUR_GATEWAY_ID_HERE
```

```
PING 172.16.1.254 (172.16.1.254) 56(84) bytes of data.
64 bytes from 172.16.1.254: icmp_seq=1 ttl=64 time=1.38 ms
64 bytes from 172.16.1.254: icmp_seq=2 ttl=64 time=1.62 ms
```

```
--- 172.16.1.254 ping statistics ---
```

```
2 packets transmitted, 2 received, 0% packet loss, time 3ms rtt min/avg/max/mdev =
1.379/1.501/1.624/0.128 ms
```

## Flying with traceroute

You can use the [traceroute] command to trace the route to any destination. The general syntax of the [traceroute] command is as follows:

```
traceroute destination
```

For example, you can trace the route from your machine to [google.com] by running the following command:

```
root@ubuntu-linux:~# traceroute google.com
```

```
traceroute to google.com (172.217.1.14), 30 hops max, 60 byte packets
```

```
1 172.16.1.254 (172.16.1.254) 15.180 ms 15.187 ms 15.169 ms
2 207-47-195-169.ngai.static.sasknet.sk.ca (207.47.195.169) 24.059 ms
3 142.165.0.110 (142.165.0.110) 50.060 ms 54.305 ms 54.903 ms
```

```
4 72.14.203.189 (72.14.203.189) 53.720 ms 53.997 ms 53.948 ms
5 108.170.250.241 (108.170.250.241) 54.185 ms 35.506 ms 108.170.250.225
6 216.239.35.233 (216.239.35.233) 37.005 ms 35.729 ms 38.655 ms
7 yyz10s14-in-f14.1e100.net (172.217.1.14) 41.739 ms 41.667 ms 41.581 ms
```

As you can see, my machine took seven trips (hops) to reach my final destination, [google.com]. Notice the first hop is my default gateway, and the last hop is the destination.

The [traceroute] command comes in handy when you are troubleshooting connectivity issues. For example, it may take you a very long time to reach a specific destination; in this case, [traceroute] can help you detect any points of failure on the path to your destination.

## Breaking your DNS

Every time you enter a domain name on your browser, the DNS translates (resolves) the domain name to its corresponding IP address. The IP address of your DNS server is stored in the file [/etc/resolv.conf]:

```
root@ubuntu-linux:~# cat /etc/resolv.conf
```

I am using the DNS server [142.165.200.5], which is provided by my **Internet Service Provider (ISP)**. You can use the [nslookup] command to see DNS in action. The general syntax of the [nslookup] command is as follows:

```
nslookup domain_name
```

The [nslookup] command uses DNS to obtain the IP address of a domain name. For example, to get the IP address of [facebook.com], you can run the following command:

```
root@ubuntu-linux:~# nslookup facebook.com
Server: 142.165.200.5
Address: 142.165.200.5#53

Non-authoritative answer:
Name: facebook.com
Address: 157.240.3.35
Name: facebook.com
Address: 2a03:2880:f101:83:face:b00c:0:25de
```

Notice it displayed the IP address of my DNS server in the first line of the output. You can also see the IP address [157.240.3.35] of [facebook.com].

You can also ping [facebook.com]:

```
root@ubuntu-linux:~# ping -c 2 facebook.com
PING facebook.com (157.240.3.35) 56(84) bytes of data.
64 bytes from edge-star-mini-shv-01-seal.facebook.com (157.240.3.35):
icmp_seq=1 ttl=55 time=34.6 ms
64 bytes from edge-star-mini-shv-01-seal.facebook.com (157.240.3.35):
icmp_seq=2 ttl=55 time=33.3 ms

--- facebook.com ping statistics ---

2 packets transmitted, 2 received, 0% packet loss, time 2ms
rtt min/avg/max/mdev = 33.316/33.963/34.611/0.673 ms
```

Now let's break things! My mum once told me that I have to break things so I can understand how they work. Let's see what life is without DNS by emptying the file [/etc/resolv.conf]:

```
root@ubuntu-linux:~# cp /etc/resolv.conf /etc/resolv.conf_backup
root@ubuntu-linux:~# echo > /etc/resolv.conf
root@ubuntu-linux:~# cat /etc/resolv.conf

root@ubuntu-linux:~#
```

Now let's do [nslookup] on [facebook.com]:

```
root@ubuntu-linux:~# nslookup facebook.com
```

You will see that it hangs as it is unable to resolve domain names anymore. Now let's try to ping [facebook.com]:

```
root@ubuntu-linux:~# ping facebook.com

ping: facebook.com: Temporary failure in name resolution
```

You get the error message [Temporary failure in name resolution], which is a fancy way of saying that your DNS is broken! However, you can still ping [facebook.com] by using its IP address:

```
root@ubuntu-linux:~# ping -c 2 157.240.3.35
PING 157.240.3.35 (157.240.3.35) 56(84) bytes of data.
64 bytes from 157.240.3.35: icmp_seq=1 ttl=55 time=134 ms
64 bytes from 157.240.3.35: icmp_seq=2 ttl=55 time=34.4 ms

--- 157.240.3.35 ping statistics ---
2 packets transmitted, 2 received, 0% packet loss, time 2ms
rtt min/avg/max/mdev = 34.429/84.150/133.872/49.722 ms
```

Let's fix our DNS, but this time we will not use the DNS server of our ISP; instead, we will use Google's public DNS server [8.8.8.8]:

```
root@ubuntu-linux:~# echo "nameserver 8.8.8.8" > /etc/resolv.conf
root@ubuntu-linux:~# cat /etc/resolv.conf
nameserver 8.8.8.8
```

Now let's do an [nslookup] on [facebook.com] again:

```
root@ubuntu-linux:~# nslookup facebook.com

Server: 8.8.8.8
Address: 8.8.8.8#53

Non-authoritative answer:
Name: facebook.com
Address: 31.13.80.36
Name: facebook.com
Address: 2a03:2880:f10e:83:face:b00c:0:25de
```

Notice that my active DNS is now changed to [8.8.8.8]. I also got a different IP address for [facebook.com], and that's because Facebook is running on many different servers located in various regions of the world.

# Your hostname

Every website has a domain name that uniquely identifies it over the internet; similarly, a computer has a hostname that uniquely identifies it over a network.

Your computer's hostname is stored in the file [/etc/hostname]:

```
root@ubuntu-linux:~# cat /etc/hostname
ubuntu-linux
```

Now it's time to test your understanding of Linux networking with a knowledge-check exercise.

## Knowledge check

For the following exercises, open up your Terminal and try to solve the following tasks:

1. Change your hostname to [darkarmy].
2. Display the IP address of your default gateway.
3. Trace the route from your machine to [www.ubuntu.com](http://www.ubuntu.com).
4. Display the IP address of your DNS.
5. Display the IP address of [www.distrowatch.com](http://www.distrowatch.com).
6. Bring down your Ethernet interface.
7. Bring your Ethernet interface back up.